

# Exercises: Functional Programming

This document defines the exercises for ["Java Advanced" course @ Software University](#). Please submit your solutions (source code) of all below described problems in [Judge](#).

## 1. Consumer Print

Write a program that **reads** a collection of **strings**, separated by one or **more** whitespaces, from the console and then prints them onto the console. Each string should be printed on a new line. Use a **Consumer<T>**.

### Examples

Input	Output
Pesho Gosho Adasha	Pesho Gosho Adasha

## 2. Knights of Honor

Write a program that **reads a collection of names** as strings from the console and then **appends "Sir"** in front of every name and prints it back onto the console. Use a **Consumer<T>**.

### Examples

Input	Output
Pesho Gosho Adasha StanleyRoyce	Sir Pesho Sir Gosho Sir Adasha Sir StanleyRoyce

## 3. Custom Min Function

Write a simple program that **reads a set of numbers** from the console and finds the **smallest** of the **numbers** using a simple **Function<Integer[], Integer>**.

### Examples

Input	Output
1 4 3 2 1 7 13	1

## 4. Applied Arithmetic

On the first line you are given a **list of numbers**. On the next lines you are passed different **commands** that you need to apply to all numbers in the list: **"add"** -> adds 1; **"multiply"** -> multiplies by 2; **"subtract"** -> subtracts 1; **"print"** -> prints all numbers on a **new line**. The input will end with an **"end"** command, after which you need to print the result.

## Examples

Input	Output
1 2 3 4 5 add add print end	3 4 5 6 7

Input	Output
5 10 multiply subtract print end	9 19

## 5. Reverse and Exclude

Write a program that **reverses** a collection and **removes** elements that are **divisible** by a given integer **n**.

### Examples

Input	Output
1 2 3 4 5 6 2	5 3 1
20 10 40 30 60 50 3	50 40 10 20

## 6. Predicate for names

Write a **predicate**. Its goal is to **check** a name for its length and to return **true** if the names length is **less or equal** the passed **integer**. You will be given an **integer** that represents the length you have to use. On the second line you will be given a **string** array with some names. Print the names, passing the **condition** in the predicate.

### Examples

Input	Output
4 Kurnelia Qnaki Geo Muk Ivan	Geo Muk Ivan
4 Karaman Asen Kiril Yordan	Asen

## 7. Find the smallest element

Write a program which is using a custom **function** (written by you) to find the **smallest** integer in a **sequence** of **integers**. The input could have more than one space. Your task is to **collect** the integers from the console, find the **smallest one** and print its **index** (if **more** than one such elements exist, print the index of the **rightmost** one).

### Hints

- Use a **Function<List<Integer>, Integer>** or something similar.

### Examples

Input	Output
1 2 3 0 4 5 6	3
123 10 11 3	3



## 8. Custom Comparator

Write a custom **comparator** that **sorts** all even numbers before all **odd** ones in **ascending order**. Pass it to an **Arrays.sort()** function and print the result.

### Examples

Input	Output
1 2 3 4 5 6	2 4 6 1 3 5
-3 2	2 -3

## 9. List of Predicates

Find all **numbers** in the range **1..N** that are **divisible** by the numbers of a given sequence. Use **predicates**.

### Examples

Input	Output
10 1 1 1 2	2 4 6 8 10
100 2 5 10 20	20 40 60 80 100

## 10. Predicate Party!

The Wire's parents are on a vacation for the holidays and he is planning an epic party at home. Unfortunately, his organizational skills are next to non-existent so you are given the task to help him with the reservations.

On the first line you get a **list** with all the **people** that are coming. On the next lines, until you get the **"Party!"** command, you may be asked to **double** or **remove** all the people that apply to **given criteria**. There are three different options:

- Everyone that has a name **starting** with a given string;
- Everyone that has a name **ending** with a given string;
- Everyone that has a name with a given **length**.

When you print the guests that are coming to the party, you have to print them in **ascending** order. If nobody is going, print **"Nobody is going to the party!"**. See the examples below:

### Examples

Input	Output
Pesho Misho Stefan Remove StartsWith P Double Length 5 Party!	Misho, Misho, Stefan are going to the party!
Pesho Double StartsWith Pesh Double EndsWith esho Party!	Pesho, Pesho, Pesho, Pesho are going to the party!



Pesho Remove StartsWith P Party!	Nobody is going to the party!
--	-------------------------------

## 11. \* The Party Reservation Filter Module

You are a young and talented **developer**. The first task you need to do is to implement a **filtering module** to a party reservation software. First, The Party Reservation Filter Module (**TPRF** Module for short) is passed a **list** with invitations. Next the **TPRF** receives a sequence of **commands** that specify if you need to add or remove a given filter.

**TPRF** Commands are in the given format **{command;filter type;filter parameter}**

You can receive the following **TPRF** commands: **"Add filter"**, **"Remove filter"** or **"Print"**. The possible **TPRF** filter types are: **"Starts with"**, **"Ends with"**, **"Length"** and **"Contains"**. All **TPRF** filter parameters will be a string (or an integer for the length filter).

The input will end with a **"Print"** command. See the examples below:

### Examples

Input	Output
Pesho Misho Slav Add filter;Starts with;P Add filter;Starts with;M Print	Slav
Pesho Misho Jica Add filter;Starts with;P Add filter;Starts with;M Remove filter;Starts with;M Print	Misho Jica

