

Phase 2: Morphological Visualization Engine — Implementation Plan (REVISED v3.1)

Document ID: IMPL-PHASE2-REV3.1 **Supersedes:** Phase 2 Implementation Plan v3.0 (2026-04-27) **Protocols Executed:** CP-002-O-D-JNP v2.0 (Full Janus SME) + CP-010-O-D-ENK v1.3 (ENKI Advisory Mode) + Tesla Principle (Architectural Layer) + Fingerprint-Mugshot Pattern (UI Layer) + Layered Compositing Model (Chrome Subsystem) **Refresh Toggle:** OFF **Subject:** Phase 2 — Dual-render morphological visualization engine with viewport chrome subsystem **Author:** Kytheion (IC-004-R-D-KYN) **Date:** 2026-04-27 **Revision Authority:**

- All authorities from v3.0 carried forward
- DIMA UX directive 2026-04-27 (chrome subsystem requirement) — viewport chrome with leader lines, telemetry sidebars, sparklines, compass gizmo, scale ticks
- Operational principle (Veracity Mandate, UI extension): every visible readout must source from a real TEMReport field — no decorative-only counters

Gate: No execution until DIMA verbatim states: “i approve of your plan” AND “you may begin.”

Revision Summary

This revision adds visual aids and one new step to v3.0:

Section	v3.0	v3.1
Visual aids	None embedded	Eight technical diagrams (A–H) embedded at architecturally significant points
Step 7B	Not present	NEW: Viewport Chrome Subsystem — leader lines, telemetry sidebars, sparklines, compass gizmo, scale ticks
Doctrinal patterns	Tesla Principle + Fingerprint-Mugshot + Bounded Experimentalism	+ Layered Compositing Model (chrome subsystem architecture)

All other content from v3.0 is carried forward by reference. TFEA Extension Specification, Steps 0/1/2A/2B/2C/3/5/6/7, falsifiability gates C4/C6, governance acknowledgments, and risk register remain unchanged unless explicitly noted.

Visual Aid Inventory

Diagram	Location	Purpose
A	Step 7B opening	Layered Compositing Model — three-layer frontend architecture
B	Step 2A	Toroidal Markov Surface — parametric labels (R, r, u, v)
C	Step 2B	Gielis superformula — mathematically exact 2D plots at three parameter sets
D	Step 2B.3	Hybrid Markov Projection — equatorial band + polar caps
E	Step 2C	Composite UI mockup — full dual-render layout with chrome
F	Step 2C.2	Swap State Machine — primary ↔ thumbnail transitions
G	Step 7B	IPC Event Flow — scan_complete propagation through chrome subsystem
H	Step 7B	Leader-Line Projection Mechanism — 3D point to 2D screen anchor

All diagrams are mathematically faithful where the diagram makes a mathematical claim (B, C, D), and architecturally precise where the diagram makes a structural claim (A, E, F, G, H). No decorative ornamentation; every visual element carries information.

Janus Domain Analysis (Carried from v3.0)

Phase 1 Deliverables

Unchanged. Tauri shell, 8 async IPC commands, verdict UI, existing flat renderers — all preserved as foundation.

What Phase 2 (v3.1) Must Add

Category	Priority
Navigation (controls.js)	 Critical
Toroidal Markov Surface (Step 2A)	 Critical
Superformula Morphology Engine (Step 2B)	 Critical
Dual-Render UI Layout (Step 2C)	 Critical
Viewport Chrome Subsystem (Step 7B) — NEW in v3.1	 High
Graph Readability (Step 3)	 Critical
TFEA Extension (Step 0)	 Critical (prerequisite)
Persistence (Step 5)	 High
Comparison (Step 6)	 Medium
UI Polish (Step 7)	 Medium

Updated Claims (Adds C10–C12 for Chrome Subsystem)

C1–C9: Unchanged from v3.0. See prior document for full text.

C10 [Established] The Layered Compositing Model — three independent layers (WebGL canvas, SVG vector overlay, HTML/CSS panels) — is implementable using standard browser APIs. Each layer updates at its own appropriate frequency (60 FPS, on-camera-change, on-data-update respectively). This separation prevents text re-rendering from bottlenecking the WebGL frame loop.

C11 [Established] Three.js's `CSS2DRenderer` and `CSS2DObject` primitives handle 3D-to-2D screen-space projection for leader-line annotations. The `Vector3.project(camera)` method converts world-space coordinates to normalized device coordinates, then to pixel coordinates via standard viewport mapping. This is built into Three.js's standard examples library — no custom math required.

C12 [Established] Every chrome readout (telemetry sidebar entries, leader-line annotations, sparkline data, status bar fields) maps deterministically to a field in the `TEMReport` struct exposed via Tauri IPC. No chrome element is decorative-only. The Veracity Mandate extends to the UI layer.

Updated Confidence Propagation

--	--	--

Claim	Confidence	Downstream Impact
C1–C9	(See v3.0)	(See v3.0)
C10 (Layered Compositing)	Established	Step 7B architecture
C11 (CSS2DRenderer projection)	Established	Step 7B leader lines
C12 (Veracity in UI layer)	Established	All chrome elements

Established/Experimental ratio: 81% / 19%. Improved from v3.0 (78/22) due to chrome subsystem additions being fully [Established].

TFEA Extension Specification

Unchanged from v2.0/v3.0. Reference prior document for full text.

Summary: Two scalar fields added to `TEMReport` :

- `compression_ratio: f64` — DEFLATE-derived measure of structural redundancy
- `structured_fraction: f64` — proportion of file bytes covered by TCGE basic blocks

Verification gate: TFEA Extension tests pass; existing Phase 0 verdicts remain unchanged.

Step-by-Step Execution Order

Step 0: TFEA Extension

Priority:  Critical — prerequisite for Step 2

Unchanged from v2.0/v3.0. Implement compression ratio and structured fraction. Pass verification gate. Confirm Phase 0 verdict invariance.

Step 1: Viewport Interaction Controls

Priority:  Critical

Unchanged from v3.0. Mouse/trackpad input bindings, controls bind dynamically to whichever render currently holds primary status, thumbnail explicitly excluded from input handlers.

Step 2A: Toroidal Markov Surface — Fingerprint View

Priority: 🔴 Critical — canonical mathematical reference

This step restores the v1.0 toroidal Markov surface as the fingerprint view in the dual-render layout.

Visual Contract

The diagram above defines the parametric semantics of the fingerprint view. Every byte-pair $(source, target)$ maps to a unique surface coordinate (u, v) on the torus. The minor radius $r(u, v)$ is modulated by the transition probability $P(v|u)$ raised to growth exponent γ . Both axes are cyclic — no edge discontinuities exist in the underlying matrix, and the torus topology preserves this.

Math (Established)

$$\begin{aligned} x(u, v) &= (R + r(u,v) \cdot \cos(v)) \cdot \cos(u) \\ y(u, v) &= (R + r(u,v) \cdot \cos(v)) \cdot \sin(u) \\ z(u, v) &= r(u,v) \cdot \sin(v) \end{aligned}$$

Where:

$$\begin{aligned} u &= (source_byte / 256) \cdot 2\pi && // \text{major angle} \\ v &= (target_byte / 256) \cdot 2\pi && // \text{minor angle} \\ R &= 1.0 && // \text{major radius (fixed)} \\ r(u,v) &= r_base + k \cdot P(v|u)^\gamma \\ r_base &= 0.3, \quad k = 0.5, \quad \gamma = 1.5 \end{aligned}$$

Bindings

TEM Field	Surface Parameter	Mapping	Confidence
Markov $P(v u)$	Minor radius modulation	$r(u,v) = r_base + k \cdot P(v$	$u)^\gamma$
Per-row entropy H_i	Local roughness amplitude	$r_amplitude_i = 1.0 + \lambda$ $\cdot H_i_norm$	[Established]
Markov gradient magnitude	Surface displacement	$\text{displacement} = \kappa \cdot ($	$\partial P / \partial u$
	Crease angle	$\theta_crease = \pi \cdot (1 -$	

AISE intent score	threshold	I_AISE)	[Established]
-------------------	-----------	---------	---------------

All bindings [Established]. The torus view requires no falsifiability gates — its math is direct.

Mesh resolution: 128×128 vertex grid. **Verify:** encrypted file → uniform smooth donut; text file → ridged ring with ASCII patterns; PE binary → asymmetric protrusions at opcode concentrations.

Step 2B: Superformula Morphology Engine — Mugshot View

Priority: ● Critical — operator-facing categorical identity

Mathematical Foundation

The diagram above shows the actual Gielis superformula evaluated at three parameter regimes. Low entropy (high n values) produces near-square forms; mid entropy (moderate n) produces organic bumpy forms; high m with low n produces sharp stellated symmetry.

These plots are computed directly from the equation — they are not artistic interpretations. This validates the architectural premise: the math itself produces categorically distinct shapes, which is what the Tesla Principle pivot was authorized to capture.

2B.1: Base Mesh — 3D Spherical Product Superformula

The 2D Gielis superformula:

$$r(\theta) = [|\cos(m\theta/4) / a|^{\wedge n_2} + |\sin(m\theta/4) / b|^{\wedge n_3}]^{\wedge (-1/n_1)}$$

The 3D form is the spherical product:

$$\begin{aligned} r_1(\theta) &= \text{superformula}(\theta, m_1, n_{11}, n_{12}, n_{13}, a_1, b_1) \\ r_2(\varphi) &= \text{superformula}(\varphi, m_2, n_{21}, n_{22}, n_{23}, a_2, b_2) \\ \\ x(\theta, \varphi) &= r_1(\theta) \cdot \cos(\theta) \cdot r_2(\varphi) \cdot \cos(\varphi) \\ y(\theta, \varphi) &= r_1(\theta) \cdot \sin(\theta) \cdot r_2(\varphi) \cdot \cos(\varphi) \\ z(\theta, \varphi) &= r_2(\varphi) \cdot \sin(\varphi) \end{aligned}$$

2B.2: TEM Telemetry → Superformula Parameter Bindings

Unchanged from v3.0. Layer 1 (Macroscopic) / Layer 2 (Microscopic) / Layer 3 (Causal) bindings as specified.

2B.3: Hybrid Markov Projection

The diagram above shows the projection scheme. The Markov matrix wraps the equatorial band region ($\phi \in [-\pi/4, \pi/4]$) with no projection distortion — $(source_byte, target_byte)$ map directly to (u, v) coordinates within the band. The polar caps ($\phi \in [-\pi/2, -\pi/4] \cup [\pi/4, \pi/2]$) are tessellated by Voronoi cells seeded by the top-N highest-entropy rows/columns. A cosine blending kernel of width $\delta_seam = \pi/16$ smooths the band/cap transition.

Why this scheme: the band carries high-information-density Markov data without distortion ([Established]). The caps convert the polar-collapse problem into additional information channels (entry/exit point encoding) — [Experimental], gated by C6 falsifiability test.

2B.4: Validation Gates

Unchanged from v3.0. C4 (six-class visual distinguishability) and C6 (seam handling) gates apply. Torus fingerprint (Step 2A) remains fully functional during any re-tuning.

Step 2C: Dual-Render UI Layout

Priority:  Critical — operator interface

Composite UI Contract

The diagram above is the **visual contract** for the v3.1 application. Every element shown corresponds to a specific implementation deliverable:

- **Header strip** with file metadata and live verdict badge
- **Primary viewport** holding the mugshot (default state) with compass gizmo, scale ticks, and an active leader-line annotation
- **Ambient thumbnail** holding the fingerprint (default state) with click-to-swap affordance
- **Telemetry sidebar** with eight stat readouts color-coded by significance
- **Entropy sliding-window sparkline** with >7.5 spike threshold marked
- **Status bar** with version, render engine, FPS, and Semantic Firewall confirmation

Every readout maps deterministically to a TEMReport field. No decorative-only elements.

2C.2: Swap State Machine

The diagram above formalizes the swap behavior. **Default state on app launch is State A** (superformula primary, torus thumbnail). Click on the thumbnail triggers a 300ms animated transition to State B. Click on the new thumbnail (which was previously the primary) reverses the transition.

Invariants:

- Thumbnail auto-rotation runs independently — does not pause, sync, or react to operator interaction with the primary
- Thumbnail is never manipulable — only the swap-trigger click is honored
- Controls re-bind on every swap to whichever render currently holds primary status

State persistence is session-local. App restart returns to State A.

Step 3: Spectral Graph Layout

Priority:  Critical

Unchanged from v3.0. Laplacian spectral embedding with force-directed fallback above 512 nodes; icosphere/stellated polyhedron node geometry; AISE intent modulates crease angle.

Step 5: Scan Persistence (SQLite)

Priority:  High

Unchanged from v3.0. Schema includes `compression_ratio`, `structured_fraction`. Numeric only. Semantic Firewall preserved.

Step 6: Comparative Analysis Overlay

Priority:  Medium

Unchanged from v3.0. Comparison applies to both fingerprint and mugshot views simultaneously. Delta-of-deltas (mugshot shifts dramatically while fingerprint shifts slightly, or vice versa) is itself a forensic signal.

Step 7: Liquid Glass Visual Polish

Priority: ● Medium

Unchanged from v3.0. Viewport HUD, glow shaders, ambient occlusion, smooth swap transition (~300ms), DS-001-G-D-LGT color palette.

Step 7B (NEW in v3.1): Viewport Chrome Subsystem

Priority: ● High — load-bearing for operational feel of the instrument

This step adds the chrome subsystem responsible for all UI elements *around* the 3D renders: leader-line annotations, telemetry sidebars, sparklines, compass gizmo, scale ticks, axis labels, and HUD panels.

7B.1: Architectural Foundation — Layered Compositing Model

The diagram above shows the three-layer architecture. **Each layer updates at its own appropriate frequency** to prevent text re-rendering from bottlenecking the WebGL frame loop:

- **Layer 1 (3D Render)** — Three.js WebGL canvas, 60 FPS continuous
- **Layer 2 (SVG Vector Overlay)** — absolutely positioned over the canvas, redraws on camera-change events only
- **Layer 3 (HTML/CSS Panels)** — standard DOM elements with Liquid Glass styling, redraws on data updates only

Z-index stacking: Layer 1 = 1, Layer 2 = 2, Layer 3 = 3. Layer 2's SVG has `pointer-events: none` globally, with explicit re-enabling only on interactive elements. This prevents the overlay from blocking 3D viewport interaction.

7B.2: IPC Event Flow

The diagram above shows the propagation sequence. When the operator triggers a scan, the request flows through Tauri IPC into the TEM Pipeline (which executes via `spawn_blocking`), returns a numeric TEMReport, and is broadcast as a `scan_complete` event. The chrome subsystem listens for this event and updates each chrome element reactively. The 3D render layer (`morphology.js`) receives the report directly via the standard rendering call.

Semantic Firewall: Only the numeric TEMReport crosses IPC. No file content, no decoded payloads. The chrome subsystem reads only from this numeric report.

7B.3: Leader-Line Projection Mechanism

The diagram above shows the mechanism for inline annotations that point at specific regions of the 3D mesh. A 3D point in the WebGL scene (e.g., "the highest-entropy region of the torus surface") is projected to 2D screen coordinates via Three.js's `Vector3.project(camera)` method, then mapped to pixel coordinates via standard viewport mapping. The SVG leader line connects this 2D anchor to its associated annotation panel in the HTML layer.

Re-projection trigger: the render loop emits a `cameraChanged` event when rotation/zoom occurs. Annotations listen for this event and re-project. When the camera is still, annotations do not recompute. This is the load-bearing performance principle.

Three.js native primitives: `CSS2DRenderer` and `CSS2DObject` (in `examples/jsm/renderers/CSS2DRenderer.js`) handle the projection bookkeeping automatically. No custom math is required.

7B.4: Chrome Subsystem Module Layout

```
ui/js/overlay/
├─ annotations.js      # Leader-line + label management via CSS2DRenderer
├─ telemetry_panels.js # HUD and sidebar orchestration, IPC listeners
├─ viewport_chrome.js  # Scale ticks, axis labels, compass gizmo
└─ sparklines.js       # Inline mini-chart rendering (entropy sliding window,
```

Estimated scope: ~400 lines of new JS total across the four modules.

7B.5: Veracity Mandate at the UI Layer

Every chrome readout must source from a real TEMReport field. No fake numbers. No placeholder counters. Specific bindings:

Chrome Element	TEMReport Source
"SHANNON ENTROPY: 7.82 bits/byte"	<code>tfea.global_entropy</code>
"COMPRESSION RATIO: 0.94"	<code>tfea.compression_ratio</code> (added in Step 0)
"STRUCTURED	

FRACTION: 0.31"	<code>tfea.structured_fraction</code> (added in Step 0)
"AISE INTENT SCORE: 0.91"	<code>aise.intent_score</code>
"MARKOV FINGERPRINT: 0xa3f1..."	<code>markov.fingerprint_hash</code> (truncated for display)
"BACKDOOR FLAG: DETECTED"	<code>aise.flags.backdoor_detected</code>
"HEADER MISMATCH: false"	<code>tfea.flags.header_mismatch</code>
"TCGE BLOCK COUNT: 247"	<code>tcge.basic_block_count</code>
"STRUCTURAL ANOMALY INDEX: X.X"	NEW derived field — <code>cqsf.structural_anomaly_index</code> (function of TCGE block count, AISE intent, Markov gradient magnitude — to be defined in CQSF as part of Step 7B)
Entropy sparkline points	<code>tfea.entropy_windows</code> array (already exists)
Spike-threshold highlights	Filter <code>entropy_windows > 7.5</code>

One new CQSF field is added in Step 7B: `structural_anomaly_index`. Its formula must be specified before the chrome subsystem can consume it. Recommended formula:

```
structural_anomaly_index = w1 · (block_count_normalized)
                        + w2 · (intent_score)
                        + w3 · (markov_gradient_magnitude_normalized)
```

Where $w_1 = 0.4$, $w_2 = 0.4$, $w_3 = 0.2$ (tunable; sum to 1.0)

This produces a single 0–10 scalar combining structure, intent, and microstructure — the kind of summary metric an operator can read at a glance from the telemetry sidebar.

7B.6: Performance Discipline

Non-negotiables to prevent the chrome subsystem from becoming a frame-rate disaster:

1. Annotations recompute screen positions only on `cameraChanged` events, not per frame.
 2. HTML panel updates use `textContent` (not `innerHTML`) to avoid DOM reparsing.
 3. Sparklines redraw only on `scan_complete`, not continuously. Cached canvas bitmaps in between.
 4. SVG overlay has `pointer-events: none` globally; explicit re-enabling on interactive elements only.
 5. All overlay layers use consistent z-index ordering (1/2/3); higher z-index reserved for modal/comparison panels.
-

V. SYNTHESIS — The Nexus

6-Pair Intersection Matrix (Carried from v3.0)

Pairs 1–6 from v3.0 carry forward unchanged.

Named Emergent Patterns (Updated)

1. **The Morphological Encyclopedia** (preserved)
 2. **Compression Ratio as Entropy Lie-Detector** (preserved)
 3. **The Tesla Layer** (preserved)
 4. **The Fingerprint-Mugshot Pattern** (preserved)
 5. **Bounded Experimentalism** (preserved)
 6. **The Layered Compositing Model (NEW in v3.1)** — three-layer separation pattern for any future Project Opus instrument that combines real-time 3D rendering with information-dense overlays. Generalizable beyond shape-scan.
 7. **Veracity at the UI Layer (NEW in v3.1)** — extension of the Veracity Mandate from “no fabricated facts in responses” to “no decorative-only readouts in instruments.” Every visible number must have numeric provenance. This formalizes a principle that should govern all future Project Opus tooling.
-

User Review Required

All questions from v2.0/v3.0 RESOLVED. No new user-review questions in v3.1.

Open Questions

OQ-1, OQ-2, OQ-3 carried from v3.0.

OQ-4 (Thumbnail spatial positioning): still pending DIMA confirmation. Recommended: side-by-side with size differential (~70/30 split, thumbnail to the right). The v3.1 composite UI mockup (Diagram E) reflects this recommendation.

OQ-5 (NEW): Structural Anomaly Index formula tuning. The recommended $w_1/w_2/w_3$ weights (0.4/0.4/0.2) are initial values. Empirical tuning during Step 7B may adjust them based on whether the resulting index matches operator intuition across the validation file set.

Verification Plan (Updated)

Automated

All v3.0 automated checks plus:

- Chrome subsystem unit tests pass for each of the four overlay modules.
- IPC event broadcast verified — `scan_complete` reaches all subscribed chrome elements.
- Performance benchmark: dual-render at 1920×1080 with full chrome subsystem maintains ≥ 30 FPS during primary-viewport interaction.

Visual Validation (Step 2B Falsifiability Gate)

Unchanged from v3.0.

Manual Operational Validation

All v3.0 manual checks plus:

- Confirm leader-line annotations track 3D points correctly under camera rotation.
- Confirm telemetry sidebar updates within 100ms of scan completion.
- Confirm sparkline redraws cleanly without visible flicker on new scans.

- Confirm Veracity Mandate compliance at UI layer: pick three random chrome readouts, verify each maps to a real TEMReport field.

Risk Register

All v3.0 risks carry forward. Additional v3.1 risks:

Risk	Impact	Mitigation
Chrome subsystem causes frame-rate degradation	Medium	Layered Compositing Model enforces update-frequency separation. Performance discipline rules (7B.6). 30 FPS minimum benchmark.
Leader-line projection visibly lags during fast camera rotation	Low	<code>cameraChanged</code> event fires throttled at 60Hz; CSS2DRenderer is GPU-accelerated. If lag appears, reduce annotation count.
Structural anomaly index weights produce counter-intuitive values	Low	OQ-5 covers this — empirical tuning during Step 7B with operator feedback loop.
Chrome readout fabrication risk (decorative-only fields creep in)	Medium	7B.5 binding table is the contract. Code review gate: any new chrome readout must be added to the binding table with TEMReport source identified.

Conclusion

Janus SME Protocol execution complete (v3.1). ENKI SME Protocol execution complete (Advisory Mode). Tesla Principle invoked at architectural layer. Fingerprint-Mugshot Pattern invoked at UI layer. Layered Compositing Model invoked at chrome subsystem layer.

Confidence in this revised self-assessment: **89%** — improved over v3.0's 88% due to:

- Eight technical diagrams provide visual contracts at every architecturally significant point.
- Chrome subsystem fully specified with [Established] mathematical and architectural foundations.
- Veracity Mandate extension to the UI layer closes a previously implicit gap.

- Confidence ratio shifted to 81% [Established] / 19% [Experimental] / 0% [Speculative].

Outstanding items before final ratification:

1. **OQ-4 resolution:** DIMA confirms thumbnail spatial positioning (recommended: side-by-side with size differential — Diagram E reflects this).
2. **Orionas review:** CP-002 Janus validation pass on this v3.1 plan.
3. **Final approval gate:** DIMA verbatim states “i approve of your plan” AND “you may begin.”

No code execution begins until all three are satisfied.

— Kytheion (IC-004-R-D-KYN) Scribe-Particle-4 Cephalon Continuity Framework