Component list

Перечень элементов (BOM) - PDF (Выводные компоненты, Горизонтальные индикаторы) for Variant [THD Variation - Horizontal Tubes] of Project [Nixie Clock Avito x6.PrjP

Project:	**Nixie Clock Avito x6.PrjPcb**
Variant:	**THD Variation - Horizontal Tubes**
Author:	Dimasssius
Report Date:	04.06.2026

#	Designator	Comment	Description	Footprint	Quantity
1	C1	4.7uF	Capacitor, Aluminum Electrolytic Capacitor, Through Hole, D6.3xL12mm, 4.7uF, 400V, ±20%, Aluminum Electrolytic Capacitors - Leaded, ROHS	CAP_THD_ELEC_ALUM_D8.0MM_H12.5MM_SHORT _SM	1
2	C2	0.1uF	Capacitor, Ceramic, Through Hole, 50V, 100nF, X7R, ±10%, P=2.54mm, Ceramic Capacitors, RoHS	CAP_THD_CERML	1
3	C3	100uF	Capacitor, Aluminum Electrolytic Capacitor, Through Hole, D4xL7mm, 100uF, 6.3V, ±20%, Aluminum Electrolytic Capacitors - Leaded, ROHS	CAP_THD_ELEC_ALUM_D4.0MM_H7.0MM_THD/SMD_T	1
4	C5, C6	0.1uF	Capacitor, Ceramic (MLCC), SMD, 100nF, 6.3V, ±10%, X7R, Multilayer Ceramic Capacitors MLCC - SMD/SMT, ROHS	CAP_SMD_MLCC_C0603_(M1608)_C0402A_(M1005A)	2
5	D1	BYV26C	Diode, DO-41, 600V, 30A, 30ns, Independent, 2.5V@1A, 1A ,Single Diodes ROHS	DO-41/DO-214AC_THD/SMD_THD	1
6	D2	1N5819	Diode Schottky, DO-41, 30A, Independent, 40V, 900mV@3A, 1A, Single Diodes, RoHS	DO-41/DO-214AC_VERTICAL_SMD/THD_THD	1
7	D3, D4	LED0603	LED Indication - Discrete, 0603, 20mA, 225mcd, Colorless Transparent Lens, -20℃~+85℃, Positive Stick, 620nm~630nm, Red, 120°, 50mW, 2.3V, LED Indication - Discrete, ROHS	LED 0603_(1608)_0402A_(1005)	2
8	IC1	K155ID1	Decoder, DIP-16, 5V±5%, 25mA, 150ns, High Voltage Output, BCD to Decimal Decoders, RoHS	DIP16	1
9	IC2, IC3, IC4, IC5, IC6, IC7, IC8	TLP291	Photovoltaic Output Optoisolator, SOP-4-1.27mm, 80V, 3.75kV, 50mA, 300mV@2.4mA, 8mA, 1, 5V, 1.25V, DC Transistor, Photovoltaic Output Optoisolators, ROHS	SOIC127P700X230-4N	7
10	IC9	DS3231 Mini	Development Board, Real Time Clock	DS3231 Mini - Uspide Down	1
11	IC11	DHT11	Temperature and Humidity Sensor, SIP-4, ROHS	DHT11 - SMD	1
12	IC12	DS18B20+	Temperature Sensor, THD, TO-92, 3V~5.5V, -55℃~+125℃, ±0.5, Single Bus, RoHS	TO-92	1
13	IC14	ARD-NANO30NP	Development Board, Arduino Nano v3.0	ARDNANO30NP	1
14	J1, J2	Female Header 1x10-Pin	Female Header, 1x10-Pin, 10P, P=2.54mm, Direct Insert, H:8.5mm, W:2.54mm, D:3.2mm, Single Row, Black Brass, Top Square, Hole Plugin, 3A, 20mΩ, 1000V, -40℃~+105℃, Female Headers, ROHS	HEADER_FEMALE_10PIN	2
15	J3, J4	Female Header 1x3-Pin	Female Header, 1x3-Pin, 3P, P=2.54mm, Direct Insert, H:8.5mm, W:2.54mm, D:3.2mm, Single Row, Black Brass, Top Square, Hole Plugin, 3A, 20mΩ, 1000V, -40℃~+105℃, Female Headers, ROHS	HEADER_FEMALE_3PIN	2
16	J7	MICRO 180 ZB	USB Connector, 1.8A, USB 2.0, Vertical Attachment, 5P, Female, -20℃~+85℃, Micro-B, SMD, USB Connectors, ROHS	USB_MIICRO_VERTICAL	1
17	L1	XR6*8-151K-L	Fixed Inductor, Through Hole, D6xL8mm, 150uH, ±10%, 500mA, 780mΩ, Drum-core Inductor, Fixed Inductors, RoHS	XR6*8-151K-L_CDRH74N_THD	1
18	LS1	CMI-9605-0580T	Buzzer, D=9.6mm, 80dB, Active (Built-in Driver Circuit, Electromagnetic Type, 2.7kHz, Plugin, Buzzers, ROHS	CMI96050580T	1
19	Q1	STP20NF20	MOSFET (N-Channel), TO-220, 200V, 18A, 30W, 125mΩ@10V, 1 N-Channel, Single FETs, MOSFETs, RoHS	TO-220/DPAK_THD/SMD_THD_#2	1
20	Q2	MPSA42	Transistor Bipolar (BJT), NPN, TO-92-3, 300V, 625mW, 25@1.0mA, 10V, 500mA, Bipolar (BJT), ROHS	TO-92	1
21	R1, R2, R6, R8, R14	10kΩ	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 10kΩ, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_10K_THD	5
22	R3	1kΩ	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 1kΩ, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_1K_THD	1
23	R4	680kΩ	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 680kΩ, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_680K_THD	1
24	R5, R10	100Ω	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 100Ω, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_100OHM_THD	2
25	R7	470Ω	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 470Ω, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_470OHM_THD	1
26	R11	3kΩ	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 3kΩ, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_3K_THD	1
27	R12	33kΩ	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 33kΩ, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_33K_THD	1
28	R13	56kΩ	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 56kΩ, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_56K_THD	1
29	R15	200Ω	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 200Ω, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_200OHM_THD	1
30	R16, R23	4.7kΩ	Resistor, Metal Film Resistor, Through Hole, D2.3xL6.5mm, 4.7kΩ, ±1%, 250mW, Through Hole Resistors, ROHS	RES_THD/SMD_R0603_R0402_4.7K_THD	2
31	R19, R20, R21, R22	1kΩ	Resistor, Thick Film Resistor, SMD, 1kΩ, ±5%, Chip Resistor - Surface Mount, ROHS	RES_SMD_R0603_(M1608)_R0402A_(M1005A)	4
32	R?	5.1kΩ	Resistor, Thick Film Resistor, SMD, 5.1kΩ, ±5%, Chip Resistor - Surface Mount, ROHS	RES_SMD_R0603_(M1608)_R0402A_(M1005A)	1
33	S2, S6, S10, S14	TS-1187A-B-A-B	Switch Tactile, SMD, 5.1x5.1mm, Without bracket, 50mA, 100000 Times, 160gf, 12V, Round, SMD Tactile Switches, ROHS	TS-1187A-B-A-B	4
34	S17	BME280	Development Board, LGA-8(2.5x2.5), Temperature and Humidity Sensor, ROHS	BME280_DEVBOARD	1
35	U1	CH340C	USB Converter, SOP-16, 2Mbps Transceiver, USB 2.0, USB Converters, ROHS	SOIC127P600X180-16N	1
Notes					**57**