

Technical specification elastic cord PE /polyethylene

| ITEM | 6mm PE / polyethylene | 8mm PE / polyethylene |
|--|------------------------|------------------------|
| Diameter | 6MM | 8mm |
| Color | Black,White,Grey,other | Black,White,Grey,other |
| Meters Per Spool | 100 | 100 |
| Carriers | 16 | 16 |
| Yarn | Polyethylene | Polyethylene |
| Yarn Denier | 0.3mm x 3 Ply | 0.3mm x 3 Ply |
| Rubber Gauage | 32 | 32 |
| Rubber ends | 50 | 80 |
| Stitches/inch | 32 | 29 |
| Weight / Meter | 24,816 | 41,25 |
| Modulus of Elongation in Kgs / Weight required for elongation in Kgs | | |
| Percentage | Kg | Kg |
| 25% | 1,8 | 2,1 |
| 50% | 2,5 | 3 |
| 75% | 3,2 | 3,8 |
| 100% | 3,9 | 4,7 |
| 125% | 4,5 | 6 |
| Safe working Load | 60Kg | 75Kg |
| Nett Weight / Spool | 2.5 Kg | 4.1 Kg |
| | | |

Elastic cord is supplied without joints / breaks .

Elastic cord is UV stable and has very high abrasion resistance.

IN-TEN Family S.R.O. Tel.: +420-725-368-707

EMAIL: <u>info@in-ten.cz</u>
WEB: <u>www.in-ten.cz</u>