


# Stockage







# Storage

- What storage is ?
  - Architecture
  - Storage types
  - Protocols
- Fundamentals
  - Hardware
  - Logical
  - Resiliency
  - Storage Efficiency

# Storage



# Storage



# Talking about Zettabyte

80% unstructured data


50% in data centers and private clouds – 50% in public clouds

4.8 billion internet users in 2022 (up from 3.4 bn in 2017)

In 2020, every person generated 1.7 megabytes/sec of data

90% of all data have been created in the last 2 years


200+ bn devices have been generating data in 2020



1 Yottabyte = 1024 Zettabytes = 1024 Exabytes = 1024 Petabytes = 1024 Terabytes = 1024 Gigabyte = 1024 Megabyte = 1024 Kilobyte = 1024 Byte

# Storage



## Block



### Block storage

'Parking lot' metaphor—  
data stored in rigidly  
defined blocks—access  
by specific 'space' location


## File



### File storage

'Parking garage' metaphor—  
data arranged in  
hierarchical levels—  
retrace path to access

## Object



### Object storage

'Valet parking' metaphor—  
no need to worry about  
storage details—easy to  
store and access data



# Storage

File Class = Image


- Enable apps and users to store their unique metadata separately from one another

## System Metadata

- Filename: NZ219983.JPG
- Created: January 4, 2012
- Last modified: January 4, 2012

## Custom Metadata Annotation 1

- Subject: Tibia fracture
- Place Taken: ABC Hospital
- Department: Emergency Room
- Patient ID: 547968840



File + Metadata = Object



## Custom Metadata Annotation 2

- Subject: Physical Therapy Consult
- Place Accessed: XYZ Therapy
- Insurance: PDQ #13342
- Patient ID: 547968840

# Storage

## Data Archives

Long access latency tolerance  
Long retention periods  
Erasure coding

## Media Repository



Large object sizes (+250MB)  
Distributed repositories  
High data rates for redistribution  
Time to first byte latency < 50ms

## Web Data Repository



Small object (~KB)  
performance  
Searchable, scalable metadata  
High object counts



# Storage

Architecture	Storage	Protocol
DAS	Block storage	SCSI
SAN	Block storage	FCP / iSCSI
NAS	File storage	NFS => Linux SMB => Windows
NAS	Object storage	S3 => Amazon Web Service (AWS) Blob => Azure

# Storage

Media	Interface	Form factor	Capacity (e.g. 2022)	Price
HDD	SATA	3.5" / 2.5"	30 TB	\$
HDD	SAS	3.5" / 2.5"	4 TB	\$\$
SSD	SAS	2.5" / mSATA	8 TB	\$\$\$\$
SSD	NVMe	M.2	2 TB	\$\$\$\$\$

## Physical Storage Performance Tiers

Tier	Type	Rotational speed	Connection Type	Expected IOPS
1	Offline			
2	HDD	7200	SATA	75-100
3	HDD	10k	SAS	125-150
4	HDD	15k	SAS	175-210
5	Hybrid		SAS	200-500
6	SSD		SAS	>5k
7	SSD		NVMe	>10k



# Knowledge check

- Raid 0/1/3/5

# Storage




# Storage enclosure


HA Pair

Controller 1

Controller 2




# Storage enclosure






# Storage enclosure



## MetroCluster




# Storage



# Storage



100%



The screenshot shows the Windows File Explorer interface. The top navigation bar includes 'File', 'Computer', 'View', and 'Manage' tabs. The address bar shows 'This PC'. The left sidebar has 'Favorites' (Desktop, Downloads, Recent places) and 'This PC'. The main pane displays 'Folders (6)' and 'Devices and drives (14)'. The 'Devices and drives' section lists several drives, with 'C:\LUNs\LogS\DBM09 (X:)' selected and highlighted in blue.



# Lab

- Create RAID 1 via Storage Space Windows
- Create share SMB with default values

Same exercise via Powershell :

- Create RAID 1 with 2 disks
- Create SMB share
- Set share permissions Full Control for gs\_all
- Set NTFS ACLs Full control for gs\_admins
- Set NTFS ACLs read only for gs\_standard
- Remove all others NTFS ACLs




# Knowledge check

- Team 1 : Block storage
- Team 2 : File storage
- Team 3 : Object storage




# Disk Management tools

- Disk Management snap-in:
  - GUI
  - Manage disks and volumes, both basic and dynamic, locally or on remote computers
  - Simple partition creation
- DiskPart:
  - Scriptable command-line tool
  - Create scripts to automate disk-related tasks
  - Always runs locally
- Windows PowerShell:
  - Has native disk management commands
  - Can be used to script disk-related tasks



Use DiskPart or Windows PowerShell to convert partition styles



# MBR

MBR (Master Boot Record) is the name of the first sector of the hard disk drive (512 bytes)  
It contains the partition table (4 primary partitions maximum) and is responsible to launch the bootloader to start the operating system if it exists on the disk.

## MBR

Master Boot Record						Extended Partition		
Partition table								
Master Boot Code	1st Partition Table Entry	2nd Partition Table Entry	3rd Partition Table Entry	4th Partition Table Entry	0x55 AA	Primary Partition (C:)	Primary Partition (E:)	Primary Partition (F:)
						Logical Drive (G:)	Logical Drive (H:)	Logical Drive <i>n</i>

# GPT


GUID Partition Table (GPT) is the new standard for the layout of partition tables, replacing MBR. Like MBR, GPTs use logical block addressing (LBA) in place of the historical cylinder-head-sector (CHS) addressing.

The protective MBR is stored at LBA 0, and the GPT header is in LBA 1. The GPT header has a pointer to the partition table (Partition Entry Array), which is typically at LBA 2. Each entry on the partition table has a size of 128 bytes, meaning each disk can support 128 partitions.

GPT uses 64 bits for logical block addresses, allowing a maximum disk size of 264 sectors. For disks with 512-byte sectors, the maximum size is 8 ZiB ( $264 \times 512$ -bytes) or 9.44 ZB ( $9.44 \times 10^{21}$  bytes).

Partition header is redundant to provide better resiliency, a second partition table is stored at the end of the disk.

## GUID Partition Table Scheme



# MBR and GPT

## MBR

BIOS

Windows XP / Vista / 7 / 8 / 10

32 bits

64 bits

4 partitions max

2 TB per partition max

## GPT

BIOS / UEFI

Windows 7 / 8 / 10


64 bits

128 partitions max


9,4 ZB per partition max

# Simple volumes


- Simple volume that encompasses available free space from a single, basic, or dynamic hard disk drive

 <b>Disk 2</b> Basic 31.88 GB Online	<b>Simple1 (F:)</b> 4.98 GB NTFS Healthy (Primary Partition)	26.89 GB Unallocated
--	--	-------------------------

- Can be extended if contiguous space is free on the same disk

 <b>Disk 2</b> Basic 31.88 GB Online	<b>Simple1 (F:)</b> 6.94 GB NTFS Healthy (Primary Partition)	24.94 GB Unallocated
--	--	-------------------------

- If extending into noncontiguous space, the disk will be converted to dynamic if it is a basic disk

 <b>Disk 2</b> Dynamic 31.88 GB Online	<b>Simple1 (F:)</b> 6.94 GB NTFS Healthy	<b>Simple2 (G:)</b> 200 MB NTFS Healthy	<b>Simple1 (F:)</b> 1.95 GB NTFS Healthy	22.79 GB Unallocated
--	--	---	--	-------------------------

# Dynamic disks












- Consists of multidisk volumes:
  - Spanned
  - Striped
  - Mirrored
- Can contain up to 1024 volumes
- Can convert from basic disk without data loss
- Requires all volumes to be deleted when converting to basic disk
- Can be managed by using DiskPart or Disk Management:
  - There are no Windows PowerShell cmdlets for managing dynamic disks



# Mirrored, spanned, and striped volumes

Join areas of unallocated space on disks into a single logical disk

- **MIRRORED:**
  - Disk space is allocated once and used simultaneously
- **SPANNED:**
  - Disk space is added and used sequentially
- **STRIPED:**
  - Disk space is allocated once and used equally across every physical disk in the striped set

 <b>Disk 2</b> Dynamic 32.00 GB Online	 <b>Mirrored (F:)</b> 9.77 GB NTFS Healthy	 <b>Spanned (G:)</b> 1.95 GB NTFS Healthy	 <b>Striped</b> 1.95 GB NTFS Healthy	18.33 GB Unallocated
 <b>Disk 3</b> Dynamic 32.00 GB Online	 <b>Mirrored (F:)</b> 9.77 GB NTFS Healthy	 <b>Spanned (G:)</b> 1.46 GB NTFS Healthy	 <b>Striped</b> 1.95 GB NTFS Healthy	18.81 GB Unallocated
 <b>Disk 4</b> Dynamic 32.00 GB Online	 <b>Spanned (G:)</b> 3.91 GB NTFS Healthy		 <b>Striped</b> 1.95 GB NTFS Healthy	26.14 GB Unallocated

# Managing existing volumes

- Resize a volume to create additional, unallocated space to use for data or apps on a new volume.
- Before shrinking:
  - Defragment the disk
  - Ensure that the volume you want to shrink does not contain any page files

# Monitoring storage usage

- Presents an overview of storage usage by:
  - Drive (internal, external, and OneDrive)
  - 13 categories including System, Apps, Music, and Pictures
- Enables you to choose the drive to which you want to save new files, such as:
  - Apps
  - Music
  - Documents
  - Videos
  - Pictures
- Storage Sense can automatically free up space

## Apps & games

### Installing apps

Choose where you can get apps from. Installing only apps from the Store helps protect your PC and keep it running smoothly.

Allow apps from anywhere 

### Apps & features




#### [Manage optional features](#)

Search, sort, and filter by drive. If you would like to uninstall or move an app, select it from the list.

Search this list 


Sort by: Name 

Filter by: This PC (C:) 

	Alarms & Clock Microsoft Corporation	16.0 KB 10/20/2017
	App Installer Microsoft Corporation	8.00 KB 10/20/2017
	Calculator Microsoft Corporation	8.00 KB 10/20/2017

# Storage Spaces Overview

- Use Storage Spaces to add physical disks of any type and size to a storage pool, and then create highly available virtual disks from the storage pool
- To create a storage space, you need the following:
  - One or more physical disks
  - Storage pool that includes the disks
  - Storage space that is created with disks from the storage pool
  - Disk drives that are based on storage spaces



# Features of Storage Spaces

Feature	Options
Storage layout	<ul style="list-style-type: none"><li>• Simple</li><li>• Two-way or three-way mirror</li><li>• Parity</li></ul>
Provisioning schemes	<ul style="list-style-type: none"><li>• Thin vs. fixed provisioning</li></ul>

## Manage Storage Spaces

Use Storage Spaces to save files to two or more drives to help protect you from a drive failure. Storage Spaces also lets you easily add more drives if you run low on capacity. If you don't see task links, click Change settings.

[Change settings](#)


Storage pool

OK


Using 3.50 GB of 27.7 GB pool capacity


[Create a storage space](#)  
[Add drives](#)  
[Rename pool](#)


Storage spaces

Storage space (E:) OK  
Parity  
17.5 GB  
Using 2.25 GB pool capacity  
[View files](#)  
[Change](#)  
[Delete](#)

Physical drives

Microsoft Virtual Disk OK  
Attached via SAS  
13.5 % used  
Providing 9.25 GB pool capacity  
[Rename](#)

Microsoft Virtual Disk OK  
Attached via SAS  
10.8 % used  
Providing 9.25 GB pool capacity  
[Rename](#)

Microsoft Virtual Disk OK  
Attached via SAS  
[Rename](#)

# The FAT file system

- Supported by most operating systems
- For small volumes with simple folder structure
- Often used for removable media
- Windows supports FAT, FAT32, and exFAT:
  - Maximum volume size, cluster size, and number of files
- No support for security and other NTFS features




# The NTFS file system

Default file system in Windows


Supports many features not available with FAT:

- Security and auditing
- Large volumes
- Quotas
- Compression
- Encryption
- Reliability
- Other advanced features




# The ReFS file system

- Provides the highest level of resiliency and scalability
- Can be used only on mirrored storage spaces:
  - Automatically detects and corrects errors
  - Two-way or three-way mirror
- Supports security and auditing
- Does not support:
  - Compression
  - Quotas
  - Encryption
  - Volume shrinking




# Tools Used for Managing Files and Folders

- Command prompt:
  - **cd** or **chdir** to change the parent directory
  - **del**, **md**, **move**, and other commands to manage files and folders
  - **icacls** to displays and modifies permissions
- Windows PowerShell:
  - **Set-Location**, **Remove-Item**, and other cmdlets
  - Same aliases as command prompt commands
  - **Set-ACL** to manage file permissions



# File and Folder Permissions

- Control access on NTFS and ReFS file system
- Can be added for groups, users, and computers:
  - Cumulative for group members
- Can be assigned to:
  - Files
  - Folders
  - Volumes (root folder)
- Permissions can be:
  - Allow
  - Deny (takes precedence)
- Basic and advanced



# Overview of Permission Inheritance



Permissions for Adam Barr

	Allow	Deny
Modify	<input type="checkbox"/>	<input type="checkbox"/>
Read & execute	<input checked="" type="checkbox"/>	<input type="checkbox"/>
List folder contents	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Read	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Write	<input type="checkbox"/>	<input type="checkbox"/>




Permission entries:


Type	Principal	Access	Inherited from
Allow	Adam Barr (Adam@adatum.com)	Read & execute	C:\Folder1\
Allow	Administrators (LON-CL2\Administrators)	Full control	C:\
Allow	SYSTEM	Full control	C:\
Allow	Users (LON-CL2\Users)	Read & execute	C:\
Allow	Authenticated Users	Modify	C:\



# Implementing Conditions to Limit File and Folder Access




# Effective Access Feature



# Copying and moving files

- When you copy files and folders, they always inherit the permissions of the destination folder
- When you move files and folders within the same volume, they keep their explicit permissions
- When you move files and folders to a different volume, they inherit the permissions of the destination folder






# What are Shared Folders?


- Shared Folders are accessible over a network
- You can share only volumes and folders
- Share permissions control access over a network:
  - They do not apply if users access the content locally
- You must have Administrative permissions to create a share
- There are many ways to view shared folders:
  - File Explorer
  - The Shared Folders snap-in
  - **Net view**\\*computername* /*all*
  - The **Get-SmbShare** cmdlet
- You can access a shared folder by using UNC

# Shared Folder Properties



# Distributed File System

DFS groups shared folders located on different servers into one or more logically structured namespaces. This makes it possible to give users a virtual view of shared folders, where a single path leads to files located on multiple servers, as shown in the following figure:






# Labs

- Exercise 1 : Compare Share permissions **VS** NTFS rights
- Exercise 2 : Use of robocopy
- Exercise 3 : DFS
  - Install DFS replication role on 2 servers
  - Create 1 Folder with 2x targets (different locations)
  - Enable DFS Replication on the DFS Folder
  - Monitor replication (via powershell)
- Exercise 4 : Mount NFS share to linux client

# Disk optimization


- Defragmentation not needed on SSDs.
  - Windows Auto-Detects Disk Type
  - Optimize will run TRIM on SSDs
- Disk fragmentation on HDDs can:
  - Consist of both fragmented files and fragmented free space
  - Lead to poor performance of a disk subsystem
- Default settings are usually sufficient.



# Storage compression

## Compression


Reduce data storage cost by transparently compressing the data on disk using standard compression algorithms.



# Storage deduplication

## Deduplication

Data deduplication is a process that eliminates excessive copies of data and significantly decreases storage capacity requirements.




Scenario	Content	Typical space savings
User documents	Office documents, photos, music, videos, etc.	30-50%
Deployment shares	Software binaries, cab files, symbols, etc.	70-80%
Virtualization libraries	ISOs, virtual hard disk files, etc.	80-95%
General file share	All the above	50-60%

# File and folder compression

The NTFS file system uses NTFS file compression to compress files, folders, and volumes:

- Uses compression to save disk space
- Does not use compression for system files and folders
- Compression is configured as an NTFS attribute
- NTFS calculates disk space based on uncompressed file size
- Applications that open a compressed file only see the uncompressed data






# Storage compaction

## Compaction

Space saving technology called Inline Adaptive Data Compaction that places multiple logical data blocks in a single 4KB block on storage, thereby multiplying compression savings.



# Storage allocation space

## Thin provisioning


Space saving technology which storage is not reserved in advance.

Instead, storage is allocated dynamically, as it is needed.

Free space is released back to the storage system when data in the volume or LUN is deleted.

## Pros & Cons:

- + Easier storage growth
- + Add disks when the need arises
- Monitor carefully



# Storage snapshots

## Snapshot

Snapshot copy is a read-only, point-in-time image of a volume. The image consumes minimal storage space and incurs negligible performance overhead because it records only changes to files since the last Snapshot copy was made.




Figure 1a




Figure 1b




Figure 1c

A snapshot is taken in 1a. In 1b, changed data is written to a new block and the pointer is updated, but the snapshot pointer still points to the old block, giving you a live view of the data and an historical view. Another snapshot is taken in 1c and you now have access to 3 generations of your data without taking up the disk space that 3 unique copies would require; live, snapshot 2 and snapshot 1 in order of age.

# Storage tiering


## Tiering / Auto-tiering

Identify and classify data based on their access rate.

Usually classified in two categories :

- Hot data are active data => Need to be stored in the high-performance storage
- Cold data are not access for some time => Should be stored in low-cost storage.

Depending on the technology, tiering and auto-tiering can be done at file level or block level. Different policies can be applied.




# File storage threats

- Corruption
- Manual / Accidental deletion
- Data steal
- Virus / Malware
- Cyber-Attack



- Firewall
- WORM storage (specific use case)
- Encryption
  - At rest => protect against hardware stolen
  - In transit => protect against man in the middle
- Set strict ACL / Share permissions
- Security awareness
- Use MFA where possible
- Antivirus
- Antiransomware
- Backup
- Auditing
- Don't use vulnerable technologies SMB v1 / Windows file servers (Previous version can be removed by attackers)

# File storage threats



# Lab

## Block Storage

- Start “iSCSI initiator” on Clt1
- Collect iQN from Clt1
- Install iSCSI Target server & iSCSI Target storage Provider roles on SrvFS1
- Create iSCSI disk on SrvFS1 based on the Storage Space (raid1) created in Lab 1
- Present the iSCSI disk to Clt1 iQN
- Discover iSCSI target on Clt1 and connect SrvFS1
- Mount the disk in Clt1 via “iSCSI initiator”
- Initiate the disk + mount on letter E:\
- Write some data + dismount + offline the disk
- Start “iSCSI initiator” on SrvDC1
- Collect iQN from SrvDC1
- Change the iSCSI disk targets in SrvFS1 to present the disk to SrvDC1
- Discover iSCSI target on SrvDC1 and connect SrvFS1 with multipath
- Mount the disk in SrvDC1 via “iSCSI initiator”
- Where is it mounted ? And Why ?
- Check if data written from Clt1 are there ?
- What is MPIO / ALUA ?



# Lab

## Object Storage

### Exercise 1

- Install S3 browser on your BYOD
- Configure access with S3 Keys
- Create your own bucket + enable versioning
- Upload a word document
- Add custom tags + check properties to verify if tag is applied
- Delete the document in the bucket
- Check the version history

### Exercise 2

- Install AWS Tools for Windows
- Create bucket and upload data via PowerShell
- Create a static website