



Delivering Excellence in Software Engineering



Software Testing

Introduction to Cucumber

© 2008. EPAM Systems. All rights reserved.


Agenda

- **About BDD**
- **About Cucumber**
- **Gherkin**
- **Practices**

2 © 2008. EPAM Systems. All rights reserved.



About BDD



3 © 2008. EPAM Systems. All rights reserved.




About BDD

• What is BDD?

- BDD is an evolution in the thinking behind Test Driven Development and Acceptance Test Driven Planning.
- Unit test: „Build the thing right.“
- Acceptance test: „Build the right thing.“
- BDD aims to help focus development on the delivery of prioritised, verifiable business value by providing a common vocabulary (Ubiquitous Language) that spans the divide between Business and Technology.

„A language structured around the domain model and used by all team members to connect all the activities of the team with the software.“



4 © 2008. EPAM Systems. All rights reserved.



Behaviour Driven Development practices

- Establishing the goals of different stakeholders required for a vision to be implemented
- Drawing out features which will achieve those goals using feature injection
- Involving stakeholders in the implementation process(acceptance criteria, features)
- Using examples to describe the behaviour of the application, or of units of code
- Automating those examples to provide quick feedback and regression testing

5 © 2008. EPAM Systems. All rights reserved.



About Cucumber

- Cucumber is a BDD tool that for running acceptance tests
- Reads plain text descriptions of application features with example scenarios which can be converted into automation.
- Takes big effort to ensure the tests can be read and written by stakeholders themselves



6 © 2008. EPAM Systems. All rights reserved.



About Cucumber

- Lines are called Steps
- Good steps are easy to understand and as obvious as it can be
- The text is written in a business readable domain language, known as Gherkin.

Feature: Sign up

Scenario: Successful sign up

Given I am on the homepage

When I follow the sign up link

And I fill out the form with valid details

Then I should receive a confirmation email

And I should see a personalized greeting message

Gherkin – Ubiquitous Language for BDD

Given-When-Then format is popular because:

- it enables us to express our requirements in plain English
- it forces us to express each scenario clearly in terms of interactions with the system

(prerequisite) GIVEN a registered user 'bob'
(action) WHEN a user navigates to the Sign In page
(action) AND the user signs in as 'bob'
(result) THEN the profile page for 'bob' will be displayed

Feature: Adding movies to the queue

value proposition



In order to keep of track movies that I want to see
As a NetFlix customer
I can add movies to a queue



feature

Sets up the initial state for the scenario we are testing:

- ✓ may interact with the system
- ✓ should be expressed as a pre-existing condition
- ❖ should NOT perform interactions relevant to the scenario
- ❖ should NOT be expressed like an action

Gherkin – When keyword

Describes the things that the user (or some other actor) does to the system:

- ✓ should describe what the user does
- ❖ should NOT describe things that the system does

11 © 2008. EPAM Systems. All rights reserved.



Gherkin – Then keyword

Describes the things that the system is expected to do (in response to something done in a When clause):

- ✓ should describe what the system should do
- ❖ should NOT describe things that the user does

12 © 2008. EPAM Systems. All rights reserved.



Gherkin - incorrect examples

GIVEN a registered user 'bob'
THEN a user navigates to the Sign In page
THEN the user signs in as 'bob'
THEN the profile page for 'bob' is displayed

GIVEN a user registers as 'bob'
WHEN a user navigates to the Sign In page
AND the user signs in as 'bob'
THEN the profile page for 'bob' will be displayed


GIVEN a registered user 'bob'
THEN a user navigates to the Sign In page
AND the user signs in as 'bob'
THEN the profile page for 'bob' will be displayed

13 © 2008. EPAM Systems. All rights reserved.



Step definitions

- To execute Steps we need automation code
- Steps are matched via Regular Expressions
- Step definitions are pure ruby codes
- `Given` I have \$100 in my account
- `Given` /I have \\$100 in my Account/ `do`
 #TODO: code that puts \$100 into Account
`end`



14 © 2008. EPAM Systems. All rights reserved.



Cucumber folder structure

Example of Cucumber Project Directory Structure:

- Cucumber
 - /config folder
 - /features
 - /step_definitons folder
 - my_step.rb file -- step definitions (ruby)
 - ...
 - /support folder
 - ...
 - my_feature.feature file -- Gherkin scenarios
 - ...



Delivering Excellence in Software Engineering

Practices



Cucumber configuration

- Cucumber is a Ruby gem
- It can be installed via the following command:
gem install cucumber
- Step to configure cucumber:
 - Install ruby
 - Install cucumber gem
 - Install ansicon(optional)

17 © 2008. EPAM Systems. All rights reserved.



Practice I – Calculator

- Requirement: create and test a calculator which is able to add two numbers and print out the result

Feature: Adding

Scenario: Add two numbers

Given the input 2+2

When the calculator is run

Then the output should be 4

18 © 2008. EPAM Systems. All rights reserved.



Practice I – Calculator

```
require "Open3"
require 'test/unit'
include Test::Unit::Assertions

Given /^the input (.*)$/ do |input|
  File.open('input.txt', 'w') do |file|
    file.puts(input)
  end
end

When /^the calculator is run$/ do
  command = "ruby calculator.rb input.txt"
  Open3.popen3(command) do |stdin, stdout, stderr|
    error_message = stderr.read
    raise(error_message) unless error_message.empty?
    @output = stdout.read
  end
end

Then /^the output should be (\d)$/ do |expected_output|
  assert_equal(expected_output, @output, "The output was not what was expected")
end
```

19 © 2008. EPAM Systems. All rights reserved.



Example tables

- Running the same scenario for different parameters
- Use Scenario Outline with Example tables

```
Feature: Adding
  Scenario Outline: Add two numbers
    Given the input <input>
    When the calculator is run
    Then the output should be <result>
  Examples:
    |input|result|
    | 2+2 | 4      |
    | 3+4 | 7      |
```

20 © 2008. EPAM Systems. All rights reserved.



Tags

- Tags are used to help organize test case running
- Usage: cucumber -t @my_feature

```
@my_feature
Feature: Adding
  Scenario Outline: Add two numbers
    Given the input <input>
    When the calculator is run
    Then the output should be <result>
  Examples:
    |input|result|
    | 2+2 |  4   |
    | 3+4 |  7   |
```

Tags

- It is possible to tag Example tables

```
Feature: Adding
  Scenario Outline: Add two numbers
    Given the input <input>
    When the calculator is run
    Then the output should be <result>
  @first_addition
  Examples:
    |input|result|
    | 2+2 |  4   |
  @second_addition
  Examples:
    |input|result|
    | 3+4 |  7   |
```

Q & A

23

© 2008. EPAM Systems. All rights reserved.



- **Helpful links:**

[Ruby 1.9.3 API](#)

[Watir 1.6.5 API](#)

[Watir WebDriver](#)

[Regex tutorial](#)

[Cucumber](#)

[Cuke Ninja](#)

24 © 2008. EPAM Systems. All rights reserved.





Delivering Excellence in Software Engineering

Introduction to Cucumber



For more information, please contact:

András Füge
Software Test Automation Engineer
EPAM Systems, Inc.
Futó utca 47-53
H-1082 Budapest, Hungary
Phone: +36 1 327 7400 # 54999
Email: andras_fuge@epam.com
<http://www.epam.com>

© 2008. EPAM Systems. All rights reserved.