

Dinero Install Scripts (macOS, Linux, Windows)

Drop these files into your repo under `scripts/`. They create **user-level** services that auto-start `dinerod` with the correct datadir and cookie path. All scripts use **localhost-only RPC** by default.

Defaults: - **RPC**: `127.0.0.1:20998` - **P2P**: `20999` - **Data dir**: OS-specific (see each script) -
Config: `<DATADIR>/dinerod.conf` (created if missing)

1) macOS — launchd (user agent)

File: `scripts/install-macos.sh`

```
#!/usr/bin/env bash
set -euo pipefail

LABEL="org.dinero.dinerod"
APP_DIR="/Applications/Dinero"           # adjust if different
BIN="$APP_DIR/dinerod"
DATADIR="$HOME/Library/Application Support/DineroCoin"
PLIST="$HOME/Library/LaunchAgents/$LABEL.plist"

mkdir -p "$DATADIR" "$HOME/Library/LaunchAgents"

CONF="$DATADIR/dinerod.conf"
if [[ ! -f "$CONF" ]]; then
    cat >"$CONF" <<EOF
server=1
rpcbind=127.0.0.1
rpcallowip=127.0.0.1
rpcport=20998
port=20999
rpccookiefile=$DATADIR/.cookie
EOF
    echo "Wrote $CONF"
fi

cat >"$PLIST" <<PLIST
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE plist PUBLIC "-//Apple//DTD PLIST 1.0//EN" "http://www.apple.com/DTDs/PropertyList-1.0.dtd">
<plist version="1.0">
  <dict>
    <key>Label</key><string>$LABEL</string>
```

```

    <key>ProgramArguments</key>
    <array>
      <string>$BIN</string>
      <string>-datadir</string><string>$DATADIR</string>
    </array>
    <key>RunAtLoad</key><true/>
    <key>KeepAlive</key><true/>
    <key>StandardOutPath</key><string>$DATADIR/dinerod.out.log</string>
    <key>StandardErrorPath</key><string>$DATADIR/dinerod.err.log</string>
  </dict>
</plist>
PLIST

echo "Loading launch agent $LABEL"
launchctl unload "$PLIST" 2>/dev/null || true
launchctl load "$PLIST"
launchctl start "$LABEL"

echo "Installed and started dinerod as launchd user agent. Logs in $DATADIR/."

```

File: `scripts/uninstall-macos.sh`

```

#!/usr/bin/env bash
set -euo pipefail
LABEL="org.dinero.dinerod"
PLIST="$HOME/Library/LaunchAgents/$LABEL.plist"
launchctl stop "$LABEL" 2>/dev/null || true
launchctl unload "$PLIST" 2>/dev/null || true
rm -f "$PLIST"
echo "Removed launch agent $LABEL"

```

2) Linux — systemd user service

File: `scripts/install-linux.sh`

```

#!/usr/bin/env bash
set -euo pipefail

BIN="/usr/local/bin/dinerod" # adjust if different
DATADIR="$HOME/.local/share/DineroCoin"
UNIT_DIR="$HOME/.config/systemd/user"
UNIT_FILE="$UNIT_DIR/dinerod.service"

```

```

mkdir -p "$DATADIR" "$UNIT_DIR"

CONF="$DATADIR/dinero.conf"
if [[ ! -f "$CONF" ]]; then
    cat >"$CONF" <<EOF
server=1
rpcbind=127.0.0.1
rpcallowip=127.0.0.1
rpcport=20998
port=20999
rpccookiefile=$DATADIR/.cookie
EOF
    echo "Wrote $CONF"
fi

cat >"$UNIT_FILE" <<UNIT
[Unit]
Description=Dinero daemon
After=network-online.target
Wants=network-online.target

[Service]
ExecStart=$BIN -datadir=$DATADIR
Restart=always
RestartSec=2
# Hardening (optional)
NoNewPrivileges=true
PrivateTmp=true
ProtectSystem=full
ProtectHome=true

[Install]
WantedBy=default.target
UNIT

systemctl --user daemon-reload
systemctl --user enable --now dinerod

echo "Installed and started dinerod as systemd --user service. Logs via
journalctl --user -u dinerod"

```

File: `scripts/uninstall-linux.sh`

```

#!/usr/bin/env bash
set -euo pipefail
systemctl --user stop dinerod 2>/dev/null || true

```

```
systemctl --user disable dinerod 2>/dev/null || true
rm -f "$HOME/.config/systemd/user/dinerod.service"
systemctl --user daemon-reload
echo "Removed dinerod systemd user service."
```

Note: To run even when no user is logged in, enable lingering once: `loginctl enable-linger "$USER"` (requires systemd-logind).

3) Windows — Service (PowerShell)

File: `scripts/install-windows.ps1`

```
[CmdletBinding()] param(
    [string]$Exe = "$env:ProgramFiles\Dinero\dinerod.exe",
    [string]$DataDir = "$env:APPDATA\DineroCoin",
    [string]$ServiceName = "DineroD",
    [string]$DisplayName = "Dinero Daemon"
)
$ErrorActionPreference = 'Stop'

# Ensure admin for service creation
$principal = New-Object
Security.Principal.WindowsPrincipal([Security.Principal.WindowsIdentity]::GetCurrent())
if (-not
    $principal.IsInRole([Security.Principal.WindowsBuiltInRole]::Administrator)) {
    Write-Error "Please run PowerShell as Administrator."
}

New-Item -ItemType Directory -Path $DataDir -Force | Out-Null
$conf = Join-Path $DataDir 'dinerod.conf'
if (-not (Test-Path $conf)) {
    @"
server=1
rpcbind=127.0.0.1
rpcallowip=127.0.0.1
rpcport=20998
port=20999
rpccookiefile={DATADIR}\.cookie
"@ -replace '{DATADIR}', $DataDir | Set-Content -Path $conf -Encoding ascii
    Write-Host "Wrote $conf"
}

# Proper quoting for binPath
$binPath = '"{0}" -datadir="{1}"' -f $Exe, $DataDir
```

```
# Create or update service
$exists = (Get-Service -Name $ServiceName -ErrorAction SilentlyContinue)
if ($null -eq $exists) {
    sc.exe create $ServiceName binPath= $binPath start= auto | Out-Null
    sc.exe description $ServiceName "$DisplayName" | Out-Null
    sc.exe failure $ServiceName reset= 0 actions= restart/1000 | Out-Null
} else {
    sc.exe config $ServiceName binPath= $binPath start= auto | Out-Null
}

Start-Service $ServiceName
Write-Host "Installed and started service '$ServiceName'"
```

File: `scripts/uninstall-windows.ps1`

```
[CmdletBinding()] param(
    [string]$ServiceName = "DineroD"
)
$ErrorActionPreference = 'Stop'
$svc = Get-Service -Name $ServiceName -ErrorAction SilentlyContinue
if ($svc) {
    if ($svc.Status -ne 'Stopped') { Stop-Service $ServiceName -Force -ErrorAction
    SilentlyContinue }
    sc.exe delete $ServiceName | Out-Null
    Write-Host "Removed service '$ServiceName'"
} else {
    Write-Host "Service '$ServiceName' not found"
}
```

4) Optional: Health Dashboards (bundle-friendly)

File: `scripts/dnr-health.sh` (POSIX)

```
#!/usr/bin/env bash
set -euo pipefail
RPC_URL="${RPC:-http://127.0.0.1:20998}"
COOKIE_FILE="${COOKIE_FILE:-$HOME/Library/Application Support/
DineroCoin/.cookie}"

get_auth() {
    local tok; tok=$(tr -d '\r\n' <"$COOKIE_FILE")
    if [[ "$tok" != *.* ]]; then tok="__cookie__:$tok"; fi
```

```

    printf 'Authorization: Basic %s' "$($(printf '%s' "$tok" | base64))"
}

while ;; do
    hdrs=( -H "$(get_auth)" -H 'content-type: application/json' )
    body='{"jsonrpc":"2.0","id":1,"method":"getmininginfo","params":[]}'
    resp=$(curl -s --fail "${RPC_URL}" "${hdrs[@]}" --data "$body" || true)
    clear
    if [[ -z "$resp" ]]; then echo "RPC unreachable"; sleep 2; continue; fi
    echo "$resp" | jq .
    sleep 2
done

```

File: `scripts/health.ps1` (Windows)

```

param(
    [string]$Rpc = "http://127.0.0.1:20998",
    [string]$CookieFile = "$env:APPDATA\DineroCoin\cookie"
)
function Get-AuthHeader {
    $tok = (Get-Content -Raw -Path $CookieFile).Trim()
    if ($tok -notmatch ':') { $tok = "__cookie__$tok" }
    $b64 = [Convert]::ToBase64String([Text.Encoding]::UTF8.GetBytes($tok))
    @{ Authorization = "Basic $b64"; 'Content-Type' = 'application/json' }
}
while ($true) {
    try {
        $body = @{ jsonrpc='2.0'; id=1; method='getmininginfo'; params=@() } |
        ConvertTo-Json -Compress
        $r = Invoke-RestMethod -Uri $Rpc -Method Post -Headers (Get-AuthHeader) -
        Body $body
        Clear-Host
        $r.result | Format-List
    } catch { "RPC unreachable: $_" }
    Start-Sleep -Seconds 2
}

```

Notes

- Adjust binary paths if your installer places `dinerod` elsewhere.
- Datadirs are **per-user**; services run in the user session (enable `loginctl enable-linger` on Linux to run headless).
- Security: RPC bound to `127.0.0.1`, cookie auth enabled; do **not** expose RPC publicly.