

Question 1  
Correct  
Marked out of 3.00  
Flag question

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.  
The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size \* size. Print a Print W for white spaces and B for black spaces.

Input:

2  
3  
5

Output:

WBW  
BWB  
WBW  
WBWBW  
BWBWB  
WBWBW  
BWBWB  
WBWBW

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int r,c;
5     scanf("%d",&r);
6     for(int i=1;i<=r;i++)
7     {
8         scanf("%d",&c);
9         for(int i=1;i<=c;i++)
10        {
11            for(int j=1;j<=c;j++)
12            {
13                if((i+j)%2==0)
14                    printf("W");
15                else
16                    printf("B");
17            }
18            printf("\n");
19        }
20    }
21    return 0;
22 }
```

|   | Input | Expected | Got   |   |
|---|-------|----------|-------|---|
| ✓ | 2     | WBW      | WBW   | ✓ |
|   | 3     | BWB      | BWB   |   |
|   | 5     | WBW      | WBW   |   |
|   |       | WBWBW    | WBWBW |   |
|   |       | BWBWB    | BWBWB |   |
|   |       | WBWBW    | WBWBW |   |
|   |       | BWBWB    | BWBWB |   |
|   |       | WBWBW    | WBWBW |   |

Passed all tests! ✓

Question **2**  
 Correct  
 Marked out of 5.00  
 Flag question

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:

2  
 2 W  
 3 B

Output:

WB  
 BW  
 BWB  
 WBW  
 BWB

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int main()
3 {
4     int n,b;
5     char c;
6     scanf("%d",&n);
7     for(int x=1;x<=n;x++)
8     {
9         scanf("%d %c",&b,&c);
10        for(int i=1;i<=b;i++)
11        {
12            for(int j=1;j<=b;j++)
13            {
14                if((i+j)%2==0)
15                    printf("%c",c);
16                else if(c=='W')
17                    printf("B");
18                else
19                    printf("W");
20            }
21            printf("\n");
22        }
23    }
24    return 0;
25 }
```

|   | Input | Expected | Got |   |
|---|-------|----------|-----|---|
| ✓ | 2     | WB       | WB  | ✓ |
|   | 2 W   | BW       | BW  |   |
|   | 3 B   | BWB      | BWB |   |
|   |       | WBW      | WBW |   |
|   |       | BWB      | BWB |   |

Passed all tests! ✓

Question **3**  
Correct  
Marked out of  
7.00  
Flag question

Decode the logic and print the Pattern that corresponds to given input.

If N= 3

then pattern will be :

10203010011012

\*\*4050809

\*\*\*\*607

If N= 4, then pattern will be:

1020304017018019020

\*\*50607014015016

\*\*\*\*809012013

\*\*\*\*\*10011

Constraints

2 <= N <= 100

Input Format

First line contains T, the number of test cases

Each test case contains a single integer N

Output

First line print Case #i where i is the test case number

In the subsequent line, print the pattern

Test Case 1

3

3

4

5

Output

Case #1

10203010011012

\*\*4050809

\*\*\*\*607

Case #2

1020304017018019020

\*\*50607014015016

\*\*\*\*809012013

\*\*\*\*\*10011

Case #3

102030405026027028029030

\*\*6070809022023024025

\*\*\*\*10011012019020021

\*\*\*\*\*13014017018

\*\*\*\*\*15016

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int main()
3  {
4      int n,v,p3,c,in,i,i1,i2,t,ti;
5      scanf("%d",&t);
6      for(ti=0;ti<t;ti++)
7      {
8          v=0;
9          scanf("%d",&n);
10         printf("Case #\n",ti+1);
11         for(i=0;i<n;i++)
12         {
13             c=0;
14             if(i>0)
15             {
16                 for(i1=0;i1<i;i1++)
17                 {
18                     printf("***");
19                 }
20             }
21             for(i1=i;i1<n;i1++)
22             {
23                 if(i>0)
24                 {
25                     c++;
26                 }
27                 printf("%d0",++v);
28             }
29             if(i==0)
30             {
31                 p3=v+(v*(v-1))+1;
32                 in=p3;
33             }
34             in=in-c;
35             p3=in;
36             for(i2=i;i2<n;i2++)
37             {
38                 printf("%d",p3++);
39                 if(i2!=n-1)
40                 {
41                     printf("0");
42                 }
43             }printf("\n");
44         }
45     }
46     return 0;
47 }

```

|   | Input | Expected                 | Got                      |   |
|---|-------|--------------------------|--------------------------|---|
| ✓ | 3     | Case #1                  | Case #1                  | ✓ |
|   | 3     | 10203010011012           | 10203010011012           |   |
|   | 4     | **4050809                | **4050809                |   |
|   | 5     | ****607                  | ****607                  |   |
|   |       | Case #2                  | Case #2                  |   |
|   |       | 1020304017018019020      | 1020304017018019020      |   |
|   |       | **50607014015016         | **50607014015016         |   |
|   |       | ****809012013            | ****809012013            |   |
|   |       | *****10011               | *****10011               |   |
|   |       | Case #3                  | Case #3                  |   |
|   |       | 102030405026027028029030 | 102030405026027028029030 |   |
|   |       | **6070809022023024025    | **6070809022023024025    |   |
|   |       | ****10011012019020021    | ****10011012019020021    |   |
|   |       | *****13014017018         | *****13014017018         |   |
|   |       | *****15016               | *****15016               |   |

Passed all tests! ✓

P.DINESH KUMAR  
240801069  
ECE-B

Question 1  
Correct  
Marked out of  
3.00  
[Flag question](#)

The k-digit number N is an Armstrong number if and only if the k-th power of each digit sums to N.

Given a positive integer N, return true if and only if it is an Armstrong number.

Example 1:

Input:

153

Output:

true

Explanation:

153 is a 3-digit number, and  $153 = 1^3 + 5^3 + 3^3$ .

Example 2:

Input:

123

Output:

false

Explanation:

123 is a 3-digit number, and  $123 \neq 1^3 + 2^3 + 3^3 = 36$ .

Example 3:

Input:

1634

Output:

true

Note:

$1 \leq N \leq 10^8$

**Answer:** (penalty regime: 0 %)

P.DINESH KUMAR  
240801069  
ECE-B

```

1 #include <stdio.h>
2 #include <math.h>
3 int main()
4 {
5     int num,n,a=0,d=0,b=0,s;
6     scanf("%d",&num);
7     n=num;
8     b=num;
9     while(n!=0)
10    {
11        n=n/10;
12        d++;
13    }
14    while(b!=0)
15    {
16        for(int i=1;i<=d;i++)
17        {
18            s=b%10;
19            b=b/10;
20            a=a+(pow(s,d));
21        }
22    }
23    if(num==a)
24        printf("true");
25    else
26        printf("false");
27    return 0;
28 }

```

|   | Input | Expected | Got   |   |
|---|-------|----------|-------|---|
| ✓ | 153   | true     | true  | ✓ |
| ✓ | 123   | false    | false | ✓ |

Passed all tests! ✓

Question **2**

Correct

Marked out of 5.00

Flag question

Take a number, reverse it and add it to the original number until the obtained number is a palindrome. Constraints  $1 \leq \text{num} \leq 99999999$   
Sample Input 1 32 Sample Output 1 55 Sample Input 2 789 Sample Output 2 66066

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int main()
3 {
4     int n,nt=0,t=0,rn;
5     scanf("%d",&n);
6     do
7     {
8         nt=n;
9         rn=0;
10        while(n!=0)
11        {
12            rn=rn*10+n%10;
13            n=n/10;
14        }
15        n=nt+rn;
16        t++;
17    }while(rn!=nt || t==1);
18    printf("%d",rn);
19    return 0;
20 }

```

|   | Input | Expected | Got   |   |
|---|-------|----------|-------|---|
| ✓ | 32    | 55       | 55    | ✓ |
| ✓ | 789   | 66066    | 66066 | ✓ |

Passed all tests! ✓

P.DINESH KUMAR  
240801069  
ECE-B

Question **3**  
 Correct  
 Marked out of 7.00  
 Flag question

A number is considered lucky if it contains either 3 or 4 or 3 and 4 both in it. Write a program to print the nth lucky number. Example, 1st lucky number is 3, and 2nd lucky number is 4 and 3rd lucky number is 33 and 4th lucky number is 34 and so on. Note that 13, 40 etc., are not lucky as they have other numbers in it.

The program should accept a number 'n' as input and display the nth lucky number as output.

Sample Input 1:

3

Sample Output 1:

33

Explanation:

Here the lucky numbers are 3, 4, 33, 34, and the 3rd lucky number is 33.

Sample Input 2:

34

Sample Output 2:

33344

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int main()
3 {
4     int n=1,i=0,nt,co=0,e;
5     scanf("%d",&e);
6     while(i<e)
7     {
8         nt=n;
9         while(nt!=0)
10        {
11            co=0;
12            if((nt%10)!=3 && (nt%10)!=4)
13            {
14                co=1;
15                break;
16            }
17            nt=nt/10;
18        }
19        if(co==0)
20        {
21            i++;
22        }
23        n++;
24    }
25    printf("%d",--n);
26    return 0;
27 }
```

|   | Input | Expected | Got   |   |
|---|-------|----------|-------|---|
| ✓ | 34    | 33344    | 33344 | ✓ |

Passed all tests! ✓