BIG O

-> BIG O in layman language

a tool to analyze the performance of your code or algorithm

let's take a step back to understand from where big O notation is coming

-> Asymptotic analysis

- defining the mathematical boundation of any algorithm to define its run-time performance.
- helps in concluding the best case, average case, and worst case scenario of an algorithm.
- bound to input which means if there is no input, algo will work in constant time.

-> need of doing this analysis?

- define performance of a system.
- take example of an assembly line for a soft drink bottle.
    - Say first step is to clean the bottle

BIG O

- second is to fill bottle
- third is to seal it
- fourth is to print the logo
- let's say each of the step takes 1 second per bottle except filling which takes 5 sec.
- the overall performance of the system will be 5 sec.

- similarly for software systems knowing the performance of different blocks or different algorithms helps identify the overall performance of the software system

-> Asymptotic Notations

- Big oh Notation (?)
- Omega Notation (Ω)
- Theta Notation (θ)

Big oh is mostly used and considered. So let's begin :)

BIG O

-> Dive in Big O notation

- express the upper boundary of an algorithm running time.
- say f(n) and g(n) are functions for positive integers
- then, $f(n) = O(g(n))$
- $f(n) \leqslant cg(n)$ for all $n \geqslant n0$



f(n) is big oh of g(n)



BIG O

-> Finding the Big O complexity

- analyze input
- figure out the different operations in the algorithms
- figure out the operations with the higher complexities. These operations define the Big O complexity of your code of your code



BIG O

-> Algos and their time complexity

- Logarithmic algorithm - O(logn) - Binary Search.
- Linear algorithm - O(n) - Linear Search.
- Superlinear algorithm - O(nlogn) - Heap Sort, Merge Sort.
- Polynomial algorithm - O(n^c) - Bubble Sort, Selection Sort, Insertion Sort
- Exponential algorithm - O(c^n) - Tower of Hanoi.
- Factorial algorithm - O(n!) - Traveling Salesman, and other backtracking problems.

-> Space complexity

- identifying memory footprint or space complexity is as important as time complexity
- analyze the input and identify how much space it occupies

BIG O

- look at pieces of the program responsible for memory usage. For example, recursive implementation as it reserves memory for recursion stack

-> Quick references

Data Structure	Time Complexity								Space Complexity
	Average				Worst				Worst
	Access	Search	Insertion	Deletion	Access	Search	Insertion	Deletion	
Array	Θ(1)	Θ(n)	Θ(n)	Θ(n)	O(1)	O(n)	O(n)	O(n)	O(n)
Stack	Θ(n)	Θ(n)	Θ(1)	Θ(1)	O(n)	O(n)	O(1)	O(1)	O(n)
Queue	Θ(n)	Θ(n)	Θ(1)	Θ(1)	O(n)	O(n)	O(1)	O(1)	O(n)
Singly-Linked List	Θ(n)	Θ(n)	Θ(1)	Θ(1)	O(n)	O(n)	O(1)	O(1)	O(n)
Doubly-Linked List	Θ(n)	Θ(n)	Θ(1)	Θ(1)	O(n)	O(n)	O(1)	O(1)	O(n)
Skip List	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(n)	O(n)	O(n)	O(n)	O(n log(n))
Hash Table	N/A	Θ(1)	Θ(1)	Θ(1)	N/A	O(n)	O(n)	O(n)	O(n)
Binary Search Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(n)	O(n)	O(n)	O(n)	O(n)
Cartesian Tree	N/A	Θ(log(n))	Θ(log(n))	Θ(log(n))	N/A	O(n)	O(n)	O(n)	O(n)
B-Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(log(n))	O(log(n))	O(log(n))	O(log(n))	O(n)
Red-Black Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(log(n))	O(log(n))	O(log(n))	O(log(n))	O(n)
Splay Tree	N/A	Θ(log(n))	Θ(log(n))	Θ(log(n))	N/A	O(log(n))	O(log(n))	O(log(n))	O(n)
AVL Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(log(n))	O(log(n))	O(log(n))	O(log(n))	O(n)
KD Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(n)	O(n)	O(n)	O(n)	O(n)

credits: https://www.bigocheatsheet.com/

ANKIT PANGASA

BIG O

-> Quick references

Array Sorting Algorithms

Algorithm	Time Complexity			Space Complexity
	Best	Average	Worst	Worst
Quicksort	Ω(n log(n))	Θ(n log(n))	O(n^2)	O(log(n))
Mergesort	Ω(n log(n))	Θ(n log(n))	O(n log(n))	O(n)
Timsort	Ω(n)	Θ(n log(n))	O(n log(n))	O(n)
Heapsort	Ω(n log(n))	Θ(n log(n))	O(n log(n))	O(1)
Bubble Sort	Ω(n)	Θ(n^2)	O(n^2)	O(1)
Insertion Sort	Ω(n)	Θ(n^2)	O(n^2)	O(1)
Selection Sort	Ω(n^2)	Θ(n^2)	O(n^2)	O(1)
Tree Sort	Ω(n log(n))	Θ(n log(n))	O(n^2)	O(n)
Shell Sort	Ω(n log(n))	Θ(n(log(n))^2)	O(n(log(n))^2)	O(1)
Bucket Sort	Ω(n+k)	Θ(n+k)	O(n^2)	O(n)
Radix Sort	Ω(nk)	Θ(nk)	O(nk)	O(n+k)
Counting Sort	Ω(n+k)	Θ(n+k)	O(n+k)	O(k)
Cubesort	Ω(n)	Θ(n log(n))	O(n log(n))	O(n)

credits: https://www.bigocheatsheet.com/

hope you found it useful

do like, share, comment
and save!

follow Ankit Pangasa for
more such useful content!

BIG O

- look at pieces of the program responsible for memory usage. For example, recursive implementation as it reserves memory for recursion stack

-> Quick references

Data Structure	Time Complexity								Space Complexity
	Average				Worst				Worst
	Access	Search	Insertion	Deletion	Access	Search	Insertion	Deletion	
Array	Θ(1)	Θ(n)	Θ(n)	Θ(n)	O(1)	O(n)	O(n)	O(n)	O(n)
Stack	Θ(n)	Θ(n)	Θ(1)	Θ(1)	O(n)	O(n)	O(1)	O(1)	O(n)
Queue	Θ(n)	Θ(n)	Θ(1)	Θ(1)	O(n)	O(n)	O(1)	O(1)	O(n)
Singly-Linked List	Θ(n)	Θ(n)	Θ(1)	Θ(1)	O(n)	O(n)	O(1)	O(1)	O(n)
Doubly-Linked List	Θ(n)	Θ(n)	Θ(1)	Θ(1)	O(n)	O(n)	O(1)	O(1)	O(n)
Skip List	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(n)	O(n)	O(n)	O(n)	O(n log(n))
Hash Table	N/A	Θ(1)	Θ(1)	Θ(1)	N/A	O(n)	O(n)	O(n)	O(n)
Binary Search Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(n)	O(n)	O(n)	O(n)	O(n)
Cartesian Tree	N/A	Θ(log(n))	Θ(log(n))	Θ(log(n))	N/A	O(n)	O(n)	O(n)	O(n)
B-Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(log(n))	O(log(n))	O(log(n))	O(log(n))	O(n)
Red-Black Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(log(n))	O(log(n))	O(log(n))	O(log(n))	O(n)
Splay Tree	N/A	Θ(log(n))	Θ(log(n))	Θ(log(n))	N/A	O(log(n))	O(log(n))	O(log(n))	O(n)
AVL Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(log(n))	O(log(n))	O(log(n))	O(log(n))	O(n)
KD Tree	Θ(log(n))	Θ(log(n))	Θ(log(n))	Θ(log(n))	O(n)	O(n)	O(n)	O(n)	O(n)

credits: https://www.bigocheatsheet.com/