

```
C:\Windows\System32\cmd.e x + v
Microsoft Windows [Version 10.0.26200.8875]
(c) Microsoft Corporation. All rights reserved.

C:\Users\DINESH VS\Desktop\CD PRACTICAL\exp29>flex exp29.l
C:\Users\DINESH VS\Desktop\CD PRACTICAL\exp29>gcc lex.yy.c
C:\Users\DINESH VS\Desktop\CD PRACTICAL\exp29>a sample.l
Enter C code snippet (Press Ctrl+D when finished):

#include <stdio.h>
[HEADER FILE]      : #include <stdio.h>

int main() {
[KEYWORD]          : int
[IDENTIFIER]       : main
[DELIMITER/PUNCT] : (
[DELIMITER/PUNCT] : )
[DELIMITER/PUNCT] : {
    int count = 10;
[KEYWORD]          : int
[IDENTIFIER]       : count
[OPERATOR]         : =
[INTEGER CONSTANT] : 10
[DELIMITER/PUNCT] : ;
    // Print statement
    if (count > 5) {
[KEYWORD]          : if
[DELIMITER/PUNCT] : (
[IDENTIFIER]       : count
[IDENTIFIER]       : count
```

```
C:\Windows\System32\cmd.e x + v

[DELIMITER/PUNCT] : )
[DELIMITER/PUNCT] : {
    int count = 10;
[KEYWORD]          : int
[IDENTIFIER]       : count
[OPERATOR]         : =
[INTEGER CONSTANT] : 10
[DELIMITER/PUNCT] : ;
    // Print statement
    if (count > 5) {
[KEYWORD]          : if
[DELIMITER/PUNCT] : (
[IDENTIFIER]       : count
[OPERATOR]         : >
[INTEGER CONSTANT] : 5
[DELIMITER/PUNCT] : )
[DELIMITER/PUNCT] : {
    printf("Hello World");
[IDENTIFIER]       : printf
[DELIMITER/PUNCT] : (
[STRING LITERAL]  : "Hello World"
[DELIMITER/PUNCT] : )
[DELIMITER/PUNCT] : ;
    }
[DELIMITER/PUNCT] : }
    return 0;
[KEYWORD]          : return
[INTEGER CONSTANT] : 0
[DELIMITER/PUNCT] : ;
}
```