

DATA COLLECTION

```
In [1]: # import libraries
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

```
In [2]: # To Import Dataset
sd=pd.read_csv(r"c:\Users\user\Downloads\\fit1.csv")
sd
```

```
Out[2]:
```

	Row Labels	Sum of Jan	Sum of Feb	Sum of Mar	Sum of Total Sales
0	A	0.06	0.08	0.06	75
1	B	0.04	0.17	0.19	160
2	C	0.10	0.12	0.05	101
3	D	0.03	0.22	0.08	127
4	E	0.25	0.11	0.12	179
5	F	0.08	0.16	0.18	167
6	G	0.19	0.09	0.17	171
7	H	0.26	0.06	0.14	170
8	Grand Total	1.00	1.00	1.00	1150

```
In [3]: # to display top 10 rows
sd.head(10)
```

```
Out[3]:
```

	Row Labels	Sum of Jan	Sum of Feb	Sum of Mar	Sum of Total Sales
0	A	0.06	0.08	0.06	75
1	B	0.04	0.17	0.19	160
2	C	0.10	0.12	0.05	101
3	D	0.03	0.22	0.08	127
4	E	0.25	0.11	0.12	179
5	F	0.08	0.16	0.18	167
6	G	0.19	0.09	0.17	171
7	H	0.26	0.06	0.14	170
8	Grand Total	1.00	1.00	1.00	1150

DATA CLEANING AND PRE_PROCESSING

```
In [4]: sd.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 9 entries, 0 to 8
Data columns (total 5 columns):
#   Column                Non-Null Count  Dtype
---  -
0   Row Labels            9 non-null     object
1   Sum of Jan             9 non-null     float64
2   Sum of Feb             9 non-null     float64
3   Sum of Mar             9 non-null     float64
4   Sum of Total Sales     9 non-null     int64
dtypes: float64(3), int64(1), object(1)
memory usage: 488.0+ bytes
```

```
In [5]: # to display summary of statistics
sd.describe()
```

```
Out[5]:
```

	Sum of Jan	Sum of Feb	Sum of Mar	Sum of Total Sales
count	9.000000	9.000000	9.000000	9.000000
mean	0.223333	0.223333	0.221111	255.555556
std	0.304097	0.295508	0.296625	337.332963
min	0.030000	0.060000	0.050000	75.000000
25%	0.060000	0.090000	0.080000	127.000000
50%	0.100000	0.120000	0.140000	167.000000
75%	0.250000	0.170000	0.180000	171.000000
max	1.000000	1.000000	1.000000	1150.000000


```
In [6]: #to display colums heading
sd.columns
```

```
Out[6]: Index(['Row Labels', 'Sum of Jan', 'Sum of Feb', 'Sum of Mar',
              'Sum of Total Sales'],
              dtype='object')
```

EDA and visualization

```
In [7]: sns.pairplot(sd)
```

```
Out[7]: <seaborn.axisgrid.PairGrid at 0x281660d7a00>
```




```
In [8]: sns.distplot(sd['Sum of Total Sales'])
```

C:\ProgramData\Anaconda3\lib\site-packages\seaborn\distributions.py:2557: FutureWarning: `distplot` is a deprecated function and will be removed in a future version. Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `histplot` (an axes-level function for histograms).

```
warnings.warn(msg, FutureWarning)
```


```
Out[8]: <AxesSubplot:xlabel='Sum of Total Sales', ylabel='Density'>
```



```
In [9]: sd1=sd[['Row Labels', 'Sum of Jan', 'Sum of Feb', 'Sum of Mar',  
               'Sum of Total Sales']]
```

```
In [10]: sns.heatmap(sd1.corr())
```

```
Out[10]: <AxesSubplot:>
```



TO TRAIN THE MODEL _MODEL BUILDING

we are going to train Linear Regression model; we need to split out the data into two variables x and y where x is independent on x (output) and y is dependent on x(output) address column as it is not required our model

```
In [11]: x= sd1[['Sum of Jan', 'Sum of Feb', 'Sum of Mar']]
y=sd1['Sum of Total Sales']
```

```
In [12]: # To split my dataset into training data and test data
from sklearn .model_selection import train_test_split
x_train,x_test,y_train,y_test=train_test_split(x,y,test_size=0.4)
```

```
In [13]: from sklearn.linear_model import LinearRegression

lr=LinearRegression()
lr.fit(x_train,y_train)
```

Out[13]: LinearRegression()

```
In [14]: print(lr.intercept_)
```

-4.876270497816279


```
In [15]: coeff= pd.DataFrame(lr.coef_,x.columns,columns=['Co-efficient'])
coeff
```

Out[15]:

	Co-efficient
Sum of Jan	343.746826
Sum of Feb	416.830781
Sum of Mar	431.020574

```
In [16]: prediction = lr.predict(x_test)
plt.scatter(y_test,prediction)
```

```
Out[16]: <matplotlib.collections.PathCollection at 0x28168c6db50>
```



```
In [17]: print(lr.score(x_test,y_test))
0.998153586676438
```

```
In [18]: lr.score(x_train,y_train)
```

```
Out[18]: 0.9999892437081274
```

```
In [19]: from sklearn.linear_model import Ridge,Lasso
```

```
In [20]: dr=Ridge(alpha=10)
dr.fit(x_train,y_train)
```

```
Out[20]: Ridge(alpha=10)
```

```
In [21]: dr.score(x_test,y_test)
```

```
Out[21]: -0.37909098645744344
```

```
In [22]: dr.score(x_train,y_train)
```

```
Out[22]: 0.005138638530347239
```

```
In [23]: la=Lasso(alpha=10)
la.fit(x_train,y_train)
```

```
Out[23]: Lasso(alpha=10)
```

```
In [24]: la.score(x_test,y_test)
```

```
Out[24]: -0.3841553067906367
```

In [25]: `la.score(x_train,y_train)`

Out[25]: 0.0

In []: