
GE23131-Programming Using C-2024





M is 1 and N is 5 so you have to calculate maximum and minimum sum using (5-1 =) 4 elements.

Maximum sum using the 4 elements would be (2+3+4+5=)14.

Minimum sum using the 4 elements would be (1+2+3+4=)10.

Difference will be 14-10=4.

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
    int main(){
 2 v
3
        int t;
4
        scanf("%d",&t);
        while(t--){
 5 1
6
            int n,m,d,min,temp;
            scanf("%d %d",&n,&m);
8
            d=n-m;
            int arr[n];
10
            for(int i=0;i<n;i++)</pre>
11
            scanf("%d",&arr[i]);
12
            for(int j=0;j<n;j++){</pre>
13
                min=j;
14
                 for(int k=j;k<n;k++){</pre>
15
                    if(arr[k]<arr[min])</pre>
16
                    min=k;
17
18
                temp=arr[min];
19
                 arr[min]=arr[j];
20
                arr[j]=temp;
21
22
            int maxsum=0,minsum=0;
23
            for(int a=0;a<d;a++)</pre>
24
            minsum+=arr[a];
25
            for(int b=n-1;b>m-1;b--)
26
            maxsum+=arr[b];
27
            printf("%d\n",maxsum-minsum);
28
29
30
31 }
```

	Input	Expected	Got	
~	1	4	4	~
	5 1			
	1 2 3 4 5			

Passed all tests! <

Correct

γ riag question

midichlorians count in vaccine batch is more than midichlorians count of person. A doctor receives a new set of report which contains midichlorians count of each infected patient, Practo stores all vaccine doctor has and their midichlorians count. You need to determine if doctor can save all patients with the vaccines he has. The number of vaccines and patients are equal.

Input Format

First line contains the number of vaccines - N. Second line contains N integers, which are strength of vaccines. Third line contains N integers, which are midichlorians count of patients.

Output Format

Print a single line containing 'Yes' or 'No'.

Input Constraint

1 < N < 10

Strength of vaccines and midichlorians count of patients fit in integer.

SAMPLE INPUT

```
5
123 146 454 542 456
100 328 248 689 200
```

SAMPLE OUTPUT

No

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
     int main()
2
3 ₹ {
        int n,min1,min2,temp,flag=1;
5
        scanf("%d",&n);
        int vac[n],pat[n];
6
7
        for(int i=0;i<n;i++)</pre>
        scanf("%d",&vac[i]);
        for (int i=0;i<n;i++)</pre>
10
        scanf("%d",&pat[i]);
11
```

```
15
16
            for(int k=j;k<n;k++)</pre>
17
18
                 if(vac[k]<vac[min1])</pre>
19
                 min1=k;
20
                if(pat[k]<pat[min2])</pre>
21
                 min2=k;
22
23
            temp=vac[min1];
            vac[min1]=vac[j];
24
25
            vac[j]=temp;
26
27
                    temp=pat[min2];
                    pat[min2]=pat[j];
28
                    pat[j]=temp;
29
30
31
                 for(int i=0;i<n;i++){</pre>
32
                    if(vac[i]<=pat[i]){</pre>
33
                        flag=0;
34
                        break;
35
36
37
                if(flag==1)
38
                 printf("Yes");
39
                 else
40
                 printf("No");
41
42
43
44
45
46
```

	Input	Expected	Got	
~	5	No	No	~
	123 146 454 542 456			
	100 328 248 689 200			

Question **3**Correct
Marked out of 1.00

F Flag question

You are given an array of n integer numbers a_1, a_2, \ldots, a_n . Calculate the number of pair of indices (i, j) such that $1 \le i < j \le n$ and a_i xor $a_j = 0$.

Input format

- First line: **n** denoting the number of array elements
- Second line: n space separated integers **a**₁, **a**₂, . . . , **a**_n.

Output the required number of pairs.

Constraints

 $1 \le n \le 10^6$ $1 \le a_i \le 10^9$

SAMPLE INPUT

5 13143

SAMPLE OUTPUT

2

Explanation

The 2 pair of indices are (1, 3) and (2,5).

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
3 ₹ {
4
         int n,count=0;
        scanf("%d",&n);
         int arr[n];
         for(int i=0;i<n;i++)
scanf("%d",&arr[i]);</pre>
8
         for(int i=0;i<n-1;i++){</pre>
             for(int j=i+1;j<n;j++)</pre>
10
11 🔻
12
                 if((arr[i]^arr[j])==0)
13
                  count++;
14
15
         printf("%d",count);
16
17 }
```

	Input	Expected	Got	
~	5 1 3 1 4 3	2	2	~

Passed all tests! <

Question 4
Correct
Marked out of 1.00

Flag question

You are given an array **A** of non-negative integers of size **m**. Your task is to sort the array in non-decreasing order and print out the original indices of the new sorted array.

Example:

 $A = \{4,5,3,7,1\}$

After sorting the new array becomes $A = \{1,3,4,5,7\}$.

The required output should be "4 2 0 1 3"

INPUT:

The first line of input consists of the size of the array

The next line consists of the array of size m

OUTPUT:

Output consists of a single line of integers

CONSTRAINTS:

1<=m<=106

0<=A[i]<=106

NOTE: The indexing of the array starts with 0.

SAMPLE INPUT

5

45371

42013

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
 2
     int main()
 3 ₹ {
 4
        int n;
        scanf("%d",&n);
        int arr[n];
        for(int i=0;i<n;i++)</pre>
 8
        scanf("%d",&arr[i]);
        int max=arr[0];
10
        for(int i=1;i<n;i++)</pre>
11 1
12
            if(arr[i]>max)
13
            max=arr[i];
14
        }
15
        max++;
16
        int min=0;
17
        for(int b=0;b<n;b++)</pre>
18
19
            for(int b=0;b<n;b++){</pre>
20
                if(arr[b]<arr[min])</pre>
21
                min=b;
22
            printf("%d ",min);
23
24
            arr[min]=max;
25
26
27 }
```

	Input	Expected	Got	
~	5 4 5 3 7 1	4 2 0 1 3	4 2 0 1 3	~

Passed all tests! <

inish review