

TE 01_STLA_M6 Jeep Migration_NorthBound_API_Interface_ Specification

Status: Ready for Release

Ver: 1.3

03-Feb-2026

	Initials	Sign & Date
Prepared by	Tata Elxsi	03/02/26
Approved by	PM	03/02/26

Company Confidential.

Tata Elxsi

1. Revision History

Rev. No	Modified Date	Affected Sections/ Pages	Description
0.1	27-Nov-2025	All	Initial Draft
0.2	28-Nov-2025	All	Addressed Peer review comments
0.3	28-Nov-2025	Section 4.7 removed, Section 3 updated, Section 5.1 updated	Addressed SQA review comments
1.0	28-Nov-2025	-	Release to STLA
1.1	04-Dec-2025	Section 6.2.3,7.2,10.2.4,10.2.5,10.2.6,11.2.1,11.2.7,13.2.1	Addressed FEQMA queries and Release to Jeep Life & STLA.
1.2	12-Dec-2025	5.2.3.5,13.2,13.2.3.6,13.2.5.6,13.2.6.6	Addressed STLA comments and Release to STLA
1.3	03-Feb-2026	14.2.4,5.2.7,5.2.6,7.2.3,11.2,14.2.1,13.2.6	Vehicle streaming API is removed, IMEI validation API is added, account deletion API is added, Logout API is added, Ongoing trip details response change, Response changes in GeoFence API, DMS API change,actionType change for minimumtripdistance, Added Remote Command history API.

2.Contents

1. Revision History	2
2.Contents	4
3.Acronyms and Abbreviations	15
4. Overview	16
4.1 Scope of this document	16
4.2 API Communication Domain URL.....	16
4.3 Coding Format.....	16
4.4 URI Format	16
4.5 Request Methods	16
4.6 Response Codes.....	17
5. Registration and Login APIs.....	18
5.1 List of Registration and Login APIs	18
5.2 API Description.....	18
5.2.1 Registration to the application	18
5.2.1.1 URI.....	18
5.2.1.2 Invocation Method	18
5.2.1.3 Request Header	18
5.2.1.4 Request Body	18
5.2.1.5 Response Body.....	19
5.2.1.6 Sample Request and Response.....	19
5.2.2 Login to the application with password.....	19
5.2.2.1 URI.....	19
5.2.2.2 Invocation Method	19
5.2.2.3 Request Header	19
5.2.2.4 Request Body	19
5.2.2.5 Response Body.....	20
5.2.2.6 Sample Request and Response.....	20
5.2.3 To fetch access token using refresh token	21
5.2.3.1 URI API used to post token to get refresh token	21
5.2.3.2 Invocation Method	21
5.2.3.3 Request Header	21
5.2.3.4 Request Body	21

5.2.3.5 Response Body.....	21
5.2.3.6 Sample Request and Response.....	22
5.2.4 Change Password API	23
5.2.4.1 URI.....	23
5.2.4.2 InvocationMethod POST	23
5.2.4.3 Request Header	23
5.2.4.4 Request Body	24
5.2.4.5 Response Body.....	24
5.2.4.6 Sample Request and Response.....	24
5.2.5 Forgot Password	24
5.2.5.1 URI.....	24
5.2.5.2 InvocationMethodPOST	25
5.2.5.3 Request Header	25
5.2.5.4 Request Body	25
5.2.5.5 Response Body.....	25
5.2.5.6 Sample Request and Response.....	25
5.2.6 Logout.....	25
5.2.6.1 URIAPI used to logout the user	25
5.2.6.2 Invocation Method	26
5.2.6.3 Request Header	26
5.2.6.4 Request Body	26
5.2.6.5 Response Body.....	26
5.2.6.6 Sample Request and Response.....	26
5.2.7 Delete user from platform APIThe API is used to delete the user account from platform.....	27
5.2.7.1 URI.....	27
5.2.7.2 Invocation Method	27
5.2.7.3 Request Header	27
5.2.7.4 Request Body	27
5.2.7.5 Response Body.....	27
5.2.7.6 Sample Request and Response.....	27
6. Token Generation.....	28
6.1 List of Token Generation APIs	28
6.2 API Description.....	28
6.2.1 Login/generate user token API	28
6.2.1.1 URI.....	28

6.2.1.2 Invocation Method	28
6.2.1.3 Request Header	28
6.2.1.4 Request Body	28
6.2.1.5 Response Body.....	28
6.2.1.6 Sample Request and Response.....	29
6.2.2 To fetch access token using refresh token	30
6.2.2.1 URI.....	30
6.2.2.2 Invocation Method	30
6.2.2.3 Request Header	30
6.2.2.4 Request Body	30
6.2.2.5 Response Body.....	30
6.2.2.6 Sample Request and Response.....	30
6.2.3 Generate application token API.....	31
6.2.3.1 URI.....	31
6.2.3.3 Request Header	32
6.2.3.4 Request Body	32
6.2.3.5 Response Body.....	32
6.2.3.6 Sample Request and Response.....	32
7. Driving Behaviour APIs	34
7.1 List of Driving Behaviour APIs	34
7.2 API Description.....	34
7.2.1 Get the trip details of a vehicle based on trip id	34
7.2.1.1 URI.....	34
7.2.1.2 Invocation Method	34
7.2.1.3 Request Header	34
7.2.1.4 Request Body	34
7.2.1.5 Response Body.....	34
7.2.1.6 Sample Request and Response.....	35
7.2.2 Get list of trip details	36
7.2.2.1 URI.....	36
7.2.2.2 Invocation Method	36
7.2.2.3 Request Header	36
7.2.2.4 Request Body	36
7.2.2.5 Response Body.....	36
7.2.2.6 Sample Request and Response.....	37
7.2.3 Get the ongoing trip detail of a vehicle	37

7.2.3.1 URI.....	37
7.2.3.2 Invocation Method	37
7.2.3.3 Request Header	37
7.2.3.4 Request Body	37
7.2.3.5 Response Body.....	38
7.2.3.6 Sample Request and Response.....	38
7.2.4 Get the trip consolidation summary with driving score	39
7.2.4.1 URI.....	39
7.2.4.2 Invocation Method	39
7.2.4.3 Request Header	39
7.2.4.4 Request Body	39
7.2.4.5 Response Body.....	39
7.2.4.6 Sample Request and Response.....	40
8. Location APIs	40
8.1 Location APIs.....	40
8.2 API Description.....	40
8.2.1 Get live location stream of vehicle	40
8.2.1.1 URI.....	40
8.2.1.2 Invocation Method	41
8.2.1.3 Request Header	41
8.2.1.4 Request Body	41
8.2.1.5 Response Body.....	41
8.2.1.6 Sample request and response	41
8.2.2 Get latest location of vehicle	41
8.2.2.1 URI.....	41
8.2.2.2 Invocation Method	41
8.2.2.3 Request Header	42
8.2.2.4 Request Body	42
8.2.2.5 Response Body.....	42
8.2.2.6 Sample request and response	42
9. Events APIs.....	43
9.1 Events APIs	43
9.2 API Description.....	43
9.2.1 Get vehicleStatus details.....	43
9.2.1.1 URI.....	43
9.2.1.2 Invocation Method	43

9.2.1.3 Request Header	43
9.2.1.4 Request Body	44
9.2.1.5 Response Body.....	44
9.2.1.6 Sample request and response	45
10. Notification Setting APIs.....	45
10.1 List of Notification Setting APIs.....	45
10.2 API Description.....	46
10.2.1 Post notification setting to platform with snooze period	46
10.2.1.1 URI.....	46
10.2.1.2 Invocation Method	46
10.2.1.3 Request Header	46
10.2.1.4 Request Body	46
10.2.1.5 Response Body.....	47
10.2.1.6 Sample Request and Response.....	47
10.2.2 Fetch notification setting to platform with snooze period	47
10.2.2.1 URI.....	47
10.2.2.2 Invocation Method	47
10.2.2.3 Request Header	48
10.2.2.4 Response Body.....	48
10.2.2.5 Sample Response	48
10.2.3 Update notification setting to platform with snooze period	48
10.2.3.1 URI.....	48
10.2.3.2 Invocation Method	49
10.2.3.3 Request Header	49
10.2.3.4 Request Body	49
10.2.3.5 Response Body.....	49
10.2.3.6 Sample Request and Response.....	49
10.2.4 Post notification setting to platform with disable/enable option	50
10.2.4.1 URI.....	50
10.2.4.2 Invocation Method	50
10.2.4.3 Request Header	50
10.2.4.4 Request Body	50
10.2.4.5 Response Body.....	50
10.2.4.6 Sample Request and Response.....	51
10.2.5 Fetch notification setting to platform with enable/disable option	51
10.2.5.1 URI.....	51

10.2.5.2 Invocation Method	52
10.2.5.3 Request Header	52
10.2.5.4 Response Body.....	52
10.2.5.5 Sample Response	52
10.2.6 Update notification setting to platform with disable/enable option	53
10.2.6.1 URI.....	53
10.2.6.2 Invocation Method	53
10.2.6.3 Request Header	53
10.2.6.4 Request Body	53
10.2.6.5 Response Body.....	53
10.2.6.6 Sample Request and Response.....	53
11. Vehicle Tracking APIs.....	54
11.1 List of Vehicle Tracking APIs	54
11.2 API Description.....	54
11.2.1 Create geo fence	54
11.2.1.1 URI.....	54
11.2.1.2 Invocation Method	55
11.2.1.3 Request Header	55
11.2.1.4 Request Body	55
11.2.1.5 Response Body.....	56
11.2.1.6 Sample request and response	56
11.2.2 Update fence Details based on VIN and fence Id.....	57
11.2.2.1 URI.....	57
11.2.2.2 Invocation Method	57
11.2.2.3 Request Header	57
11.2.2.4 Request Body	57
11.2.2.5 Response Body.....	58
11.2.2.6 Sample request and response	58
11.2.3 Delete geo fence based on fence Id	59
11.2.3.1 URI.....	59
11.2.3.2 Invocation Method	59
11.2.3.3 Request Header	59
11.2.3.4 Request Body	59
11.2.3.5 Response Body.....	60
11.2.3.6 Sample request and response	60
11.2.4 Get geo fence details based on fence type and VIN	60

11.2.4.1 URI.....	60
11.2.4.2 Invocation Method	60
11.2.4.3 Request Header	60
11.2.4. 4 Request Body	60
11.2.4.5 Response Body.....	60
11.2.4.6 Sample request and response	61
11.2.5 Create curfew fence	63
11.2.5.1 URI.....	63
11.2.5.2 Invocation Method	63
11.2.5.3 Request Header	63
11.2.5.4 Request Body –	63
11.2.5.5 Response Body.....	64
11.2.5.6 Sample request and response	64
11.2.6 Get curfew details for the VIN	65
11.2.6.1 URI.....	65
11.2.6.2 Invocation Method	65
11.2.6.3 Request Header	65
11.2.6. 4 Request Body	65
11.2.6.5 Response Body.....	65
11.2.6.6 Sample request and response	66
11.2.7 Update curfew Details based on VIN and curfew Id.....	66
11.2.7.1 URI.....	66
11.2.7.2 Invocation Method	66
11.2.7.3 Request Header	66
11.2.7.4 Request Body	66
11.2.7.5 Response Body.....	67
11.2.7.6 Sample request and response	67
11.2.8 Delete curfew based on curfew Id	68
11.2.8.1 URI.....	68
11.2.8.2 Invocation Method	68
11.2.8.3 Request Header	68
11.2.8.4 Request Body	68
11.2.8.5 Response Body.....	68
11.2.8.6 Sample request and response	68
12.Alert APIs	70
12.1 Alert APIs.....	70

12.2 API Description.....	70
12.2.1 Create the Registration for fcm	70
12.2.1.1 URI.....	70
12.2.1.2 Invocation Method	70
12.2.1.3 Request Header	70
12.2.1.4 Request Body	70
12.2.1.5 Response Body.....	71
12.2.1.6 Sample Request and Response.....	71
12.2.2 Delete FCM by MobileId	71
12.2.2.1 URI.....	71
12.2.2.2 Invocation Method	71
12.2.2.3 Request Header	71
12.2.2.4 Request Body	71
12.2.2.5 Response Body.....	71
12.2.2.6 Sample Request and Response.....	72
12.2.3 Get the List of all Notifications	72
12.2.3.1 URI.....	72
12.2.3.2 Invocation Method	72
12.2.3.3 Request Header	72
12.2.3.4 Request Body	72
12.2.3.5 Response Body.....	72
12.2.3.6 Sample Request and Response.....	73
12.2.4 To delete notifications based on id	73
12.2.4.1 URI.....	73
12.2.4.2 Invocation Method	74
12.2.4.3 Request Header	74
12.2.4.4 Request Body	74
12.2.4.5 Response Body.....	74
12.2.4.6 Sample Request and Response.....	74
12.2.5 Update the Notification as read	74
12.2.5.1 URI.....	74
12.2.5.2 Invocation Method	74
12.2.5.3 Request Header	74
12.2.5.4 Request Body	74
12.2.5.5 Response Body.....	74
12.2.5.6 Sample Request and Response.....	75

13. Remote Command APIs	75
13.1 List of remote command APIs	75
13.2 API Description.....	76
13.2.1 Trigger remote command – Blinkers.....	76
13.2.1.1 URI.....	76
13.2.1.2 Invocation Method	77
13.2.1.3 Request Header	77
13.2.1.4 Request Body	77
13.2.1.5 Response Body.....	77
13.2.1.6 Sample Request and Response.....	78
13.2.2 Trigger remote command - Remote Door Lock-Unlock Command	79
13.2.2.1 URI.....	79
13.2.2.2 Invocation Method	79
13.2.2.3 Request Header	79
13.2.2.4 Request Body	79
13.2.2.5 Response Body.....	80
13.2.2.6 Sample Request and Response.....	80
13.2.3 Trigger remote command – Honk	81
13.2.3.1 URI.....	82
13.2.3.2 Invocation Method	82
13.2.3.3 Request Header	82
13.2.3.4 Request Body	82
13.2.3.5 Response Body.....	82
13.2.3.6 Sample Request and Response.....	83
13.2.4 Fetch Remote Commands by Command ID.....	83
13.2.4.1 URI.....	84
13.2.4.2 Invocation Method	84
13.2.4.3 Request Header	84
13.2.4.4 Request Body	84
13.2.4.5 Response Body.....	84
13.2.4.6 Sample Request and Response.....	84
13.2.5 Trigger remote command – speedalertcommand	85
13.2.5.1 URI.....	85
13.2.5.2 Invocation Method	85
13.2.5.3 Request Header	85
13.2.5.4 Request Body	85

13.2.5.5 Response Body.....	86
13.2.5.6 Sample Request and Response.....	86
13.2.6 Trigger remote command - userdefinedminimumtripsettingcommand.....	87
13.2.6.1 URI.....	87
13.2.6.2 Invocation Method.....	87
13.2.6.3 Request Header.....	87
13.2.6.4 Request Body.....	87
13.2.6.5 Response Body.....	88
13.2.6.6 Sample Request and Response.....	88
13.2.7 Remote Command to check command history.....	89
13.2.7.1 URI.....	89
13.2.7.2 Invocation Method.....	89
13.2.7.3 Request Header.....	89
13.2.7.4 Response Body.....	90
13.2.7.5 Sample Request and Response.....	90
14. DMS APIs.....	92
14.1 List of DMS APIs.....	92
14.2 API Description.....	92
14.2.1 Customer Onboarding API.....	92
14.2.1.1 URI.....	92
14.2.1.2 Invocation Method.....	93
14.2.1.3 Request Header.....	93
14.2.1.4 Request Body.....	93
14.2.1.5 Response Body.....	94
14.2.1.6 Sample Request and Response.....	94
14.2.2 Dongle replacement/swap API.....	95
14.2.2.1 URI.....	95
14.2.2.2 Invocation Method.....	95
14.2.2.3 Request Header.....	95
14.2.2.4 Request Body.....	95
14.2.2.5 Response Body.....	95
14.2.2.6 Sample Request and Response.....	96
14.2.3 API to update the service packages (Service Termination).....	96
14.2.3.1 URI.....	96
14.2.3.2 Invocation Method.....	97
14.2.3.3 Request Header.....	97

14.2.3.4 Request Body	97
14.2.3.5 Response Body.....	97
14.2.3.6 Sample Request and Response.....	97
14.2.4 IMEI Validation.....	98
14.2.4.1 URI.....	98
14.2.4.2 Invocation Method	98
14.2.4.3 Request Header	98
14.2.4.4 Request Body	98
14.2.4.5 Response Body.....	98
14.2.4.6 Sample Request and Response.....	98

3.Acronyms and Abbreviations

Acronyms	Abbreviations
CVIP	Connected Vehicle India Platform
IOT	Internet of Things
API	Application Programming Interface
REST	Representational State Transfer
JSON	Java Script Object Notation
NBI	North Bound Interface
CRUD	Create Retrieve Update Delete
URL	Uniform Resource Allocator
URI	Uniform Resource Identifier
UUID	Universal Unique Identifier
IDM	Identity Management
L4	Layer 4
UID	Unique-ID
CAN	Controller Area Network
SOC	State Of Charge
SOH	State Of Health
OTA	Over the Air
UBI	Usage Based Insurance
FCM	Firebase Cloud Messaging

4. Overview

4.1 Scope of this document

This document captures the following aspects of North bound API for Mobile Application in Connected Vehicle India Platform (CVIP) for following features

Features	Number of APIs
Registration and Login APIs	7
Token Generation	3
Driving Behaviour APIs	4
Vehicle Tracking APIs	8
Alert APIs	5
Location APIs	2
Events APIs	1
Notification Settings	6
Remote Commands	7
DMS API	4
Emergency Alerts API	Not in CVIP scope. Will be handled by JeepLifeServer

4.2 API Communication Domain URL

Domain URL
https://cvipapi-preprod.fca-india.com

North Bound API uses the HTTPS v1.1 protocol and uses the following access port:

4.3 Coding Format

Request and response packets use the JSON format.

4.4 URI Format

NBI APIs are designed based on the REST Architecture.

The RESTful URI of resources use the following format:

<https://ip:port/{context-path}/{rest-path}>

Element	Description
ip:port	NBI service interface IP and port
context-path	Context-path (such as cpi,jeep,etc..)
rest-path	Resource path (such as devices, auth, etc...)

4.5 Request Methods

Operations performed on the IoT platform resources shall comply with the HTTP methods.

The operations performed can be classified into: create, retrieve, update and delete (CRUD) as described below:

Method	Resource Operation
GET	Obtaining resources
POST	Creating resources

Method	Resource Operation
PUT	Updating existing resources
DELETE	Deleting existing resources

4.6 Response Codes

Each IoT platform NBI request shall be associated with a response status code.

Some of the response status codes along with the description is listed below:

Status Code	Description
200 OK	A request is successfully received, and the request response header or data body will be sent in the response.
201 Created	The POST or PUT operation is successful.
204 No Content	The server has successfully fulfilled the request and that there is no additional content to send in the response payload body.
400 Bad Request	The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, invalid request message framing, or deceptive request routing).
401 Unauthorized	Similar to 403 Forbidden, but specifically for use when authentication is required and has failed or has not yet been provided.
403 Forbidden	The request was a valid request, but the server is refusing to respond to it. 403 error semantically means "unauthorized", i.e. the user does not have the necessary permissions for the resource. If the cause cannot be disclosed, 404 Not Found is returned.
404 Not Found	The server has not found anything matching the Request-URI.
405 Method Not Allowed	The method specified in the Request-Line is not allowed for the resource identified by the Request-URI.
409 Conflict	The request could not be processed because of conflict in the request, such as an edit conflict between multiple simultaneous updates.
414 Request-URI Too Long	The URL can contain a maximum of 2083 characters.
429 Too Many Requests	The user has sent too many requests in a given amount of time.
500 Internal Server Error	A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

5. Registration and Login APIs

This section describes the Registration and Login APIs used in Mobile Application.

5.1 List of Registration and Login APIs

The following table provides the list of Registration and Login APIs:

No	API Description	Method	API Context	API Path
1	User Registration	POST	/jeep/users	/register
2	User Login	POST	/jeep/users	/login
3	To fetch access token using refresh token	POST	/jeep/users	/refreshToken
4	Change Password API	POST	/jeep/users	/changePassword
5	Forgot Password	POST	/jeep/users	/forgotPassword
6	Logout	POST	/jeep/users	/logout
7	Delete account API	POST	/jeep/users	/delete

5.2 API Description

The APIs are listed, and the corresponding URI, Invocation method, request and response are explained in each API description

5.2.1 Registration to the application

NB API Interface ID : NB-REGISTRATION_LOGIN-001

This API request can be used to Register/update user password to CVIP

5.2.1.1 URI

<https://<ServerIP>:<ServerPort>/jeep/users/register>

5.2.1.2 Invocation Method

POST

5.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	Application Token
<i>Content-Type</i>	String	application/json

5.2.1.4 Request Body

Parameter	Type	Description
<i>mobileNum</i>	string	Registered Mobile number of user
<i>countryCode</i>	string	Country code
<i>password</i>	String	Password for the user

5.2.1.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>statusCode</i>	String	200 ok response
<i>message</i>	String	User is successfully registered

5.2.1.6 Sample Request and Response

HTTP Request: *POST* /jeep/users/register

```
{
  "mobileNum": "9385698874",
  "countryCode": "+91"
  "password": "Password@123"
}
```

HTTP Response: 200 OK

```
{
  "message": "User is successfully registered.",
  "statusCode": 200
}
```

5.2.2 Login to the application with password

NB API Interface ID : NB-REGISTRATION_LOGIN-002

This API request can be used to login to the application.

5.2.2.1 URI

<https://<ServerIP>:<serverPort>/jeep/users/login>

5.2.2.2 Invocation Method

POST

5.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	Application Token
<i>Content-Type</i>	String	application/json

5.2.2.4 Request Body

Parameter	Type	Description
<i>mobileNum</i>	String	Registered Mobile number of user
<i>countryCode</i>	String	Country code
<i>password</i>	String	Password for the user

5.2.2.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
statusCode	String	200 ok response
token	Object	Token details

Token Object

Parameter	Type	Description
accessToken	String	Access token to access CVIP platform APIs
refreshToken	String	Refresh token for the user
expiresIn	Integer	Expiry time in seconds

5.2.2.6 Sample Request and Response

HTTP Request: *POST* /jeep/users/login

```
{
  "mobileNum": "9385698874",
  "countryCode": "+91",
  "password": "Password@123"
}
```

HTTP Response:200 OK

```
{
  "statusCode": 200,
  "token": {
    "accessToken": "eyJraWwQIoiIrYnhpd2xMUG9qYjZpMTZzTGtBSzQrQ25UZlBmSnM4Tnp1cWNUMDhmSVhnPSIsImFsZyI6IlJTMjU2In0.eyJzdWIiOiJkMTUzZWQwYS1iMDcxLTcwOTItNzdiNSlmODQ4NTVkbGtYXNjbHJpZCJpc3MiOiJodHRwc3plLWVvY29nbml0byl1pZHAuYXAtc29ldGgtMS5hbWF6b25hd3MuY29tXC9hcC1zb3V0aC0xX2ozQWJ4SWk5ciIsImNsaWVudF9pZCI6IjQzNjUybXM0YmxpNzBwbHRTY2loMTk4cW5mIiwib3JpZ2luX2p0aSI6IjBkOTgzMmQzLTA1bmJyYGRlZS1hZmQzLTNlNmZkMmZlYjFkNyIsImV2ZW50X2lkIjoimDVmMmUzOTctYTBJNC0NDMxLWFFjMzgtMzkwMDMxNWVkNzkwiIiwidG9rZW5fdXNlIjoiyWNjZXNzIiwic2NvcGUiOiJhd3MuY29nbml0by5zaWduaW4udXNlcis5hZGlpb3IiOiJmFlDGhfZGltZSI6MTc2MzY1MDEzNywiZXBwIjoiaXNjYUzNzM3LCJpYXQiOjE3NjM2NTAxMzcscImp0aSI6IjRiNGJkLTRjZDUtNGYzZil1OWVhLUU4ZWY4YzY0YWYyMiIsInVzZXJ1eWw1IjoizDE1M2VkMGETyJA3MS03MDkyLTc3YjUtZjg0ODU1ZDUyMjc0In0.JwZkjDS7v7VWyPQnbnKBEej7kx2Rd-tocrFOu2aEwvjPnfNyTEPeYsq7Gd_1cnirKLlqqq2t2juTQJpaz9FPfjXEL3-q_24CWvr1WtTuTUqAtY-8aycovq4Kr6RSzpy6oCFJqrRK2dO--0w-H7YoMJ7H3eqy6B31PHMy_9iu42YTpmEOyo9WyOQ-UnxpQHmf1_miPSx1ULhggAlEyEQYyTPWq01-XzxIxkQkvQhbjDdeoX6sD7v0NUkw817U1AalQxrUadUbsuDntCAzV1kgWU5YPh-MsTs4SwingOGqG2cWHXli3AYKcJcZcudECpNajeYMrMs5gzcS9F20p82KKNrmg",
    "refreshToken": "eyJjdHkiOiJKV1QiLCJlbmMiOiJBbmJ1R0NNIiwiaWYwXnIjoilUNBLU9BRVAifQ.CAI8SkglBlfLjVO8KHpoSVcjFQvv10hqgs3h7ft6aARKRh6ZO_MKX75RJA59XQqRqTiVZUYxZUgai p3JTqDMKqAwzs-Rw9SBTnnOpHeG2ewGxi9VfBSnDpm53jpvLQ9CjqLc4KqB8A78cfkxHy5D2NX4cvJHe6ebtMkFWgu gykTOlnnkMM42Ub3zPu_EwjJCNP1nPwJD80-CnK9Z6hiX3RC_qhowoD5rS630SLYDwJ6exdkRbMvo3199yKoRWIA4740SMVOHUpMhm8Jl1t5S1aP SqnZUvuPCr3Gui05IhtSmC4zsL4LbhWGuigq6gL5ZwyQLMNThxmreEdpTaRLB8A.4U-rHA4FFae6Ecrc.UxYoLSmaNivBf0pYFgtknCZ_QrVdaL7syw7asny3dhkaDJGTkaASPlyzfBV1Pn tOfCiYDcMrtusN720bygNdrc fIFubRQjgxXdATGKK1CVmOzHD9RFtp3ZNeASavpgVUhDtyZGHbb
```

```
vUZZLsaXB3tEM8M0UtYOdoweE5o8rR07pjooifuyJl9jBlhlDP2qmYkXKtKvfDO_1-
8Wf4Bq23XKs-
P6fVGUXUrg9b9ygvj8fXKV26NB3G3TEYJVRegZt5j1UqWanIb9bhZICgDCzYkL0lKMLJ4-
MOOZ9ANnCNlj04K5qcYkyneBY1whUSXnhhfVBXwO6GFzP3egF3YVDvZFh_lbUEGPqRXzcTfJzmW
ecvt0ZKDPB8M3o7rmVpX5XI_g1ByYyqw4x78x2gKt5Z1kR9mH4C7eJ-
RBUVbUhQXxD0w7uKlSnSm0HsO7x2dHCOBDTsEt7hRJUE_OAGe83LLb_GAsoeof8ilzFUG4YkbrTN
tgPjRE6F1_JmH_KYSGSyg8G_L0Lv1fBfOLFfrK5icNCgqbpXzLLIO9Romh13m6t1hEv48_T6jbu
o6iWeMo-wvg0X-
PHz1chQkM1U8tU3QJtaJjhtyEFctK97eK5uzoDFxB7aS3qi9mLJD2m5_tP7a3_R9QZcoZnn9zuv7
8HqDqrMVqO129WUZpZRd4pkiiyemELK3iy0UrmpVos-
CU2PK2864QKtato4oX8XGjUGXfDhTPZ2INGJIrgiUR0UHxeUV4SozKMGEHlvU_54Tm0o-
9zd2UQDY0TyrRKpeJa--0MVC9uqhsqMXG9c3XWbc297gYqDqVvXBy4GRgPvEv2I-
U_SS6Tb6NQQMDPbX-E_w3c3NmVPh59ECTeny9Rbq1YEEExfaIOEwzbp211FfeGqtvh-
03aQfjj56GSs4IDo_GR6kwLLSZ7mWb8ffRoLdQKB0THWR_VKIB-
x2QIPzCE5gW8wdCauQ_0otVmqrK3VPbwnz_Pf4xMdvgc61Y0sirj9QT43rBFhzondfttlbMPfqVG
Mel5FKgw8bWerfY54TdHfIaOWvG_6j1O3zZN2pvJbEUemsV6JEP-
KmQGuedMjp2WEI1B3gPumD8nPv8XXszNeQGzjpw3RxT8pr-
XszQG9GGf38ilwkIYPTUDCDpPUHozsRXYDmxkLsl3YtaskJ-
G5V1zFj3EsYCq_Lqu_SJcw9lItcf0VOCjgPjTTT9gkzWN5z458VRt9vTzh6pQ9nI9Kz0tfGZ6Vm8
FXE9pAaQZ4W54_jt_nVNfxRQkCIj3HA__7dG1UnPI3xFq5zvUslggC1U8cKQBx2tdPahMT33cHF1
Cv8mFpatJXJl9usTg.PwpMj8jpJLFM3yhbOP98Tw",
    "expiresIn": 3600
  }
}
```

5.2.3 To fetch access token using refresh token

NB API Interface ID : NB-REGISTRATION_LOGIN-003

This API request can be used to fetch access token using refresh token.

5.2.3.1 URI

API used to post token to get refresh token

<https://<ServerIP>:<serverPort>/jeep/users/refreshToken>

5.2.3.2 Invocation Method

POST

5.2.3.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

5.2.3.4 Request Body

Parameter	Type	Description
<i>token</i>	String	Refresh token of the user

5.2.3.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>accessToken</i>	String	Access token of the user

<i>refreshToken</i>	String	Refresh token of the user
<i>expiresIn</i>	Integer	Expiry time in seconds(same as citroen- 3600 seconds)

5.2.3.6 Sample Request and Response

HTTP Request: *POST* /jeep/users/refreshToken

```

{
  "token":
    "eyJjdHkiOiJKV1QiLCJlbmMiOiJBMjU2R0NNIiwiaWVwbnIjoIoiU1NBLU9BRVAifQ.CAI8SkGBlfLjV
    O8KHpOSVcjFQvv10hqgs3h7ft6aRKRh6ZO_MKX75RJA59XQqRqTiVZUyXzUgaip3JTqDMKqAwzS-
    Rw9SBTnnOpHeG2ewGxi9VfBSnDpm53jpvLQ9CjqLc4KqB8A78cfkxHy5D2NX4cVJHe6ebtMkFWgu
    gykTOLnnkMM42Ub3zPu_EwjJCNVP1nPwJWD80-
    CnK9Z6hiX3rC_qhowoDx5rS630SLyDwJe6xdKrbMvo3199yKoRwIA4740SMVOHUpMhm8J1t5S1aP
    SqnZUvuPCr3Gui05IhtSmC4zsL41zBhWGuiq6gL5ZwyQ1MNTThxmr-EdpTaRLB8A.4U-
    rHA4FFae6Ecrk.UxYoL1saNivBf0pYFgtknCZ_OrVdaL7syw7asny3dhkaDJGTkaASP1yzfBV1Pn
    tOfCiyDcMrtuSN720byqNdrC_fIFubRQjgxxDatGKK1CvmOzHD9RfTP3ZNeASavpgVUhDtyZGhBb
    vUZZLSaXB3tEM8M0UtYOdowE5o8rR07pjooifuyJl9jBlhlDP2qmYkXKtKvfDO_1-
    8Wf4Bq23XKs-
    P6fVGUXUrg9b9ygvj8fXKV26NB3G3TEYJVRegZt5j1UqWanIb9bhZicGdCzYkLolKMlJ4-
    MOOZ9ANnCNlj04K5qcYkyneBY1whUSXnhhfVBXwO6GFzP3egF3YVDvZFh_lbUEGPqRXzcTfJzwmH
    ecvt0ZKDPB8M3o7rmVpX5XI_g1ByYyqw4x78x2gKt5Z1kR9mH4C7eJ-
    RBUVbUhQXxD0w7uKlSnSm0HsO7x2dHCOBDTSet7hRJUe_OAGe83LLb_GASoeof8ilzFUG4YkbrTN
    tgPjRE6F1_JmH_KYSGSyg8G_L0Lv1fBfOLFfrK5icNCgqbpXzLLIO9Romh13m6t1hEv48_T6jbwu
    o6iWeMo-wvg0X-
    PHz1chQkMlU8tU3QJtaJjhtyEFctK97eK5uzoDFxB7aS3qi9mLJD2m5_tP7a3_R9QZcoZnn9zuv7
    8HqDqrMVqO129WUZpZRd4pkiyemElK3iy0UrmPvos-
    CU2PK2864QktatO4ox8XGjUGXfDhTPZ2INGJIRgiUR0UHxeUV4SozKMGEhlvU_54Tm0o-
    9zd2UQDY0TyrRKpeJa--0MVC9uqhsqMXG9c3XWBc297gYqDqVXBy4GRgPvEv2I-
    U_SS6Tb6YQMDPbX-E_w3c1NmvPh59ECTeny9Rbq1YEExfaIOEwzbp21lFfeGqtvh-
    03aQfjj56GS4lDo_GR6kwLLS27mWb8ffR0LdQKB0THWR_VKIB-
    x2QIPzCE5gW8wdCauQ_0otVmqrK3VPbnz_Pf4xMdvgc6lY0sirj9QT43rBFhzondfttlbMPfqVG
    Mel5FKgw8bWerfy54TdHfIaOWvG_6j103zZN2pvJbEUemsV6JEP-
    KmQGuedMjp2WEI1B3gPumD8nPv8XXszNeQGzjpw3RxT8pr-
    XsZQG9GGf38ilwkIYPTUDCDpPUHozsRXYDmxkLsl3YtaskJ-
    G5V1zFj3EsYcQ_Lqu_SJcw9lItcf0VOCjgPjTTT9gkzWN5z458VRt9vTzh6pQ9nI9Kz0tfGZ6Vm8
    FXE9pAaQZ4W54_jt_nVNfxRQkCIj3HA__7dG1UnPI3xFq5zvuS1ggC1U8cKQBX2tdPahMT33cHF1
    Cv8mFpatJXJl9usTg.PwpMj8jPjLFM3yhbOP98Tw "
}

```

HTTP Response:200 OK

```
{  
  "accessToken":  
    "eyJraWQwOiIrYnhpd2xMUG9qYjZpMTZzTGtBSzQRQ25UZlBmSnM4Tnp1cWNUMDhmSVhnPSIsImFz  
    ZyI6IlJTMjU2In0.eyJzdWIiOiJkMTUzZWQwYS1iMDcxLTcwOTItNzdiNS1mODQ4NTVhbnRyYnZQi  
    LCJpc3MiOiJodHRwczcplLwvY29nbml0byl1pZHAAUYXAtc29ldGgtMS5hbWF6b25hd3MuY29tXC9h  
    cC1zb3V0aC0xX2ozQWJ4SWk5ciIsImNsaWVudF9pZCI6IjZnNjUybXM0YmxpNzBwbHRTY2loMTk4  
    cW5mIiwib3JpZ2luX2p0aSI6IjFlMWE5OWNmLTBmMTUtNDU0NS04NmMzLTI5NTM3YzA5ODA2NSIs  
    ImV2ZW50X2lkIjoijnkyZTAzZGMtOtkwMi00NTIiLTg4YzYtNWQyYWNiZTc3OWJlIiwiidG9rZW5f  
    dXNlIjoiiYWNjZXNziIiwic2NvcGUiOiJhd3MuY29nbml0by5zaWduaW4udXNlcii5hZGlpb3IsImF1  
    dGhfZGltdSI6MTc2MzYlMDU5MywiZXBwIjoixNzYzNjU0MTkzLCJpYXQyOjE3NjM2NTA1OTMsImp0  
    aSI6IjY0NDk5njU4LTdjdjZtNDJhZi04MmMxLTc0NTczNWlINWIRiZiIsInVzZXJuYW1lIjoizDE1  
    M2VkMGETyJyA3MS03MDkYLtc3YjUtzjgOODU1ZDUyMjc0In0.qmVblrvwm3S1mcB8YW9FOxFB6wJi  
    6yFxOqlf_3a6Vq-OISwCRtx7ZAG3NGmtypR2rfSttvQFHh19T7MX-HoZea6NWdIBRuplv1-  
    WlUagrqrNI0xmKv4Txh7qmh-fl63ndexlJgcW5XmWH-g8-  
    ny2geais0WOk55bZ54q o4uvU48D7jh5AgGrndhZz2qTCqBuYrxDKCuIf0dKSd9jsrWjHIWKDqS00
```

```

1D1PdF1ldNT7L88YJCVf_QQM-ZohBnyKe5Tp79a_YC66EAfjIoHMrKxUtm3sKgCSEc2mB-
hMlHzUpGz25ABS6o-hphxoCt9FnCONYrRtizkg1WF0j-wnZQ41A",
"refreshToken":
"eyJjdHkiOiJKV1QiLCJlbmMiOiJBMjU2R0NNIiwiaWxnbG9kaWkiOiJ1NBLU9BRVAifQ.evage37H21NOE
183esOaC1sZ1G5dud8F56ebv-
rgOaIebFWfOcJKMt32oM31WuvbLHfkg1KooIeohQ3_3ftLnAofhoYBhmiFFlqENF03wexA7GYMv7
iv-wc25h_8kyIXPOHHYZZ-C8HUfjZbFiOP_i6MzmRXFG61F-V6GGyaTbsa-sDGIV-
xjXLQdomTfA_xnGkuFKeHi6sNBROFT47wK7_6rtZ_etwO-2-
qH42G1HdzjXOH0tOlOIdm5t43gYSQAr-
d7RIhB8wf5SIjQMcbjYLenpRnyGgsROmdapuFYyfolhXLtSSX5XHmZGaBb8n8U5roC-
mR2KLQysv-vVusUw.uAc7wZsIOpexhTvh.wAERCj1tgsmRazahgME4op5_L-
Dz7EnXaIEXXbdpXiJtN7cQS6ifcMpEPKJcMPCvsHgwNlklSfyqN-
vMq_vGI6FUSKvWAtH6mBUGUG0Cog-
hX0acsS6chFabfRSS0QYorVgE2kpxM5TX8RL33IdrNhBFFPEeeNrYskMWWjM1U97K5okiaJopkLe-
vUcVii826pqpC8qCtHjvJFCrxTERgrH2wxvPJfMi4Fp4RDNwFJHk1bRT-
fFlHtHRfPCCpATUjHmSzSojk6CCsU8esKoyjzzE4ASEI3VT04rR06zoAb1Nwm3lu0UBt1bbnLhW
jv-
7OwWRCG8yWCzadeEUq280CVWYVilx47AekoENXiXm1sxgHiUSFzo0z8LEXiZlnMEE4Qblqni1Mya
FeMhfGAtRPhwlpBrZVlrGzWvTR20cg-
C9_C2kVBhoTOMnmP8RkjowM7YFf39aAyDUSobWXyayFbEz3d7FK6F3H01WnQWonCoZf08KOs2D0s
dizSB_J0dZOjPLRmuMsg07cPQZ8HIoBgbp6Fwz1Q5zGm2cJiuqYqvDTu4ArDhbPHwb0COhG_NbQF
eDxnp_7o0ZiBEAYX2RWNuWnsYzizfEkVCga8J_cW5H7TujYW00PnlmgnDGiuWx7cjJKob06nq1oB
J9Nx-
j586zT8ze17EsQoM46jdy4LBAtJc2PqiMUGTulY6NtcJ1SVWyxuqXv2q_cKZF9BeFd3qH5Y3dcap
zHfoIcEzULEFIBr2jNRiXjp2JxYnBA_iQfdblo9fbksw8_Cmq4XoT7VezSYQvLISxo8NWYyg0P8M
lsicSk8Sa904q08DWZQmJm5Q6PSL0ianJ-
ibDhcs_XeplwrZZtxDbDfPtaHuxgmNcirT7Y2MdS1CKVA3hjQ-
u0xFTTCKHZBtNJBHk1heBEnbTA2g-MzFcte7HEScZ6vd_nDqKgBA-
19no0seXm_JC9VfSWn0o3G6X86i8B8jp9QOYAmahHfaWsAbG9CdGZ4uxBz_Cge1zomeDL6gtCODN
M2AWUlbo9GFtmfelSUZGQQfgtgYtzaUMVHOQFrfbNMD7CB5WIib1cQ9xQEjTE5PGCVzOPNkKNm1Q
ck70yJlrCaA0qAcasm5ZUbKcNt95JLB_jZE17D7-Vh81Gk2hNvGh7qSDPdsfBGKOVupxM2Xo4-
zHvbg0_nsvYmDznOjjb-
nAOKLaKhZwmyRECPg7u4iATM3XSJL830aZ9HET8mxSIErSV2cSUjkedZJda8xEKKgYr2Upkk3vYZ
uwLFnr_hpWjeytlL3hrP_A81qKJc7X3X-j27wg-RfbU1UuMJI-F2nYqu-v5L1lRZ1N8NHb0Q.w-
UtuOYOJRKpM7vqEpgceg",
"expiresIn": 3600
}

```

5.2.4 Change Password API

NB API Interface ID : NB-REGISTRATION_LOGIN-004

This API request can be used to change Password

5.2.4.1 URI

<https://<ServerIP>:<port>/jeep/users/changePassword>

5.2.4.2 Invocation Method

POST

5.2.4.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

5.2.4.4 Request Body

Parameter	Type	Description
<i>mobileNum</i>	String	Registered Mobile number of user
<i>countryCode</i>	String	Country code for the mobile number
<i>currentPassword</i>	String	Old Password of user
<i>newPassword</i>	String	New password of user

5.2.4.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>message</i>	String	Password updated successfully
<i>mobileNum</i>	String	Mobile Number with countrycode
<i>statusCode</i>	String	200 ok response

5.2.4.6 Sample Request and Response

HTTP Request: *POST* [/jeep/users/changePassword](#)

```
{  
  "mobileNum": "9385698874",  
  "countryCode": "+91",  
  "currentPassword": "Password@123",  
  "newPassword": "Password@1"  
}
```

HTTP Response: *200 OK*

```
{  
  "message": "Password updated successfully",  
  "mobileNum": "+919385698874",  
  "statusCode": 200  
}
```

5.2.5 Forgot Password

NB API Interface ID : NB-REGISTRATION_LOGIN-005

This API request can be used to trigger forgot Password

5.2.5.1 URI

<https://<ServerIP>:<serverPosrt>/jeep/users/forgotPassword>

5.2.5.2 InvocationMethod

POST

5.2.5.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	Application Token
<i>Content-Type</i>	String	application/json

5.2.5.4 Request Body

Parameter	Type	Description
<i>mobileNum</i>	String	Mobile number of user
<i>countryCode</i>	String	Country code for the user
<i>newPassword</i>	String	New Password for the user

5.2.5.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>message</i>	String	Password was reset
<i>mobileNum</i>	String	Mobile number of the user with country code
<i>statusCode</i>	String	200 ok Response

5.2.5.6 Sample Request and Response

HTTP Request: *POST* [/jeep/users/forgotPassword](#)

```
{
  "mobileNum": "9385698874",
  "countryCode": "+91"
  "newPassword": "Password@1234"
}
```

HTTP Response: *200 OK*

```
{
  "message": "Password was reset",
  "mobileNum": "+919385698874",
  "statusCode": 200
}
```

5.2.6 Logout

NB API Interface ID : NB-REGISTRATION_LOGIN-006

This API request can be used to logout the user account.

5.2.6.1 URI

API used to logout the user

<https://<ServerIP>:<serverPort>/jeep/users/logout>

5.2.6.2 Invocation Method*POST***5.2.6.3 Request Header**

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

5.2.6.4 Request Body

Parameter	Type	Description
<i>token</i>	String	Access token of the user

5.2.6.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>statusCode</i>	String	200 ok response
<i>message</i>	String	User logged out successfully

5.2.6.6 Sample Request and Response**HTTP Request: POST /jeep/users/logout**

```
{
  "token":
    "eyJhdHkiOiJKV1QiLCJlbmMiOiJBMjU2R0NNIiwiaWxnIjoiU1NBLU9BRVAifQ.CAI8SkglBfLjV
    O8KHpOSVcjFQvvl0hggS3h7fT6aRRh6ZO_MKX75RJA59XQqRqTiVZUyXzUgaip3JTqDMKqAwzS-
    Rw9SBTnnOpHeG2ewGxI9VfBSnDpm53jpvLQ9CjgKc4KqB8A78cfkxHy5D2NX4cVJHe6ebtMkFWgu
    gykTOLnnkMM42Ub3zPu_EwjJCNVPlnTpWJD8O-
    CnK9Z6hiX3rC_qhowoDx5rS630SLyDwJe6xdKrbMvo3199yKoRwIA4740SMVOHUpMhm8J1t5S1aP
    SqnZUvuPcr3Gui05IHtSmC4zsL4lZBhWGuiq6gL5ZwyQ1MNThxmr-EdpTaRLB8A.4U-
    rHA4FFae6Ecrk.UxYoL1saNIvBf0pYFgtknCZ_OrVdaL7syw7asny3dhkaDJGTkaASP1yzfBVlPn
    tOFCiyDcMrtuSN720byqNdrC_fIFUbRQjgxxDaTGKK1CVmOzHD9RftP3ZNeASavpgVUhDtyZGhBb
    vUZZLsaXB3tEM8M0UtYodowE5o8rR07pjooifuyJl9jBlhlDP2qmYkXKtKvfDO_1-
    8Wf4Bq23XKs-
    P6fVGUXUrg9b9ygvj8fXKV26NB3G3TEYJVRRegZt5j1UqWanIb9bhZicGdCzYkL0lKMLJ4-
    MOOZ9ANnCNlj04K5qcYkyneBYlwhUSXnhhfVBXwO6GFzP3egF3YVDvZFh_lbUEGPqRXzcTfJzmwH
    ecvt0ZKDPB8M3o7rmVpX5XI_g1ByYyqw4x78x2gKc5Z1kR9mH4C7eJ-
    RBUVbUhQXxD0w7uKlSnSm0HsO7x2dHCOBDTsEt7hRJUE_OAGe83LLb_GAsoeof8ilzFUG4YkbrTN
    tgPjRE6F1_JmH_KYSGSyg8G_L0Lv1fBfOLFfrK5icNCgqbpXzLLIO9Romh13m6t1hEv48_T6jbuw
    o6iWeMo-wvg0X-
    PHz1chQkMlU8tU3QJtaJjhtyEFctK97eK5uzoDFxB7aS3qi9mLJD2m5_tP7a3_R9QZcoZnn9zuv7
    8HqDqrMVq0129WUZpZRd4pkIyemELK3iy0UrmpVos-
    CU2PK2864QKtat04oX8XGjUGXfDhTPZ2INgJIrgiUR0UHxeUV4SozKMGEHlvU_54Tm0o-
    9zd2UQDY0TyrRKpeJa--0MVC9uqhsqMXG9c3XWBC297gYqDqVvXBy4GRgPvEv2I-
    U_SS6Tb6NQQMDPbX-E_w3c3NmVPh59ECTeny9Rbq1YEEExfaIOEwzbp211FfeGqtvh-
    03aQfjj56GSs4IDo_GR6kwLLSZ7mWb8ffRoLdQKB0THWR_VKIB-
    x2QIPzCE5gW8wdCauQ_0otVmqrK3VPbwnz_Pf4xMdvGc61Y0sirj9QT43rBFhzondfttlbMPfqVG
    Mel5FKGw8bWeRfY54TdHfIaOWvG_6j1O3zZN2pvJbEUemsV6JEP-
    KmQGuedMjp2WEI1B3gPumD8nPv8XXszNeQGzjpw3Rxt8pr-
    XsZQG9GGf38i1wkIYPTUDCDpPUHozsRXYDmxkLsl3YtaskJ-
    G5V1zFj3EsYCq_Lqu_SJcw9lItcf0VOCjgPjTTT9gkzWN5z458VRt9vTzh6pQ9nI9Kz0tFGZ6Vm8
```

```
FXE9pAaQZ4W54_jt_nVNfxRQkCIj3HA__7dGlUnPI3xFq5zvuS1ggC1U8cKQBX2tdPahMT33cHF1
Cv8mFpatJXJl9usTg.PwpMj8jpJLFM3yhbOP98Tw "
```

HTTP Response:200 OK

```
{
  "statusCode" : 200,
  "message" : " User logged out successfully"
}
```

5.2.7 Delete user from platform API

The API is used to delete the user account from platform

5.2.7.1 URI

<https://<ServerIP>:<serverPort>/jeep/users/delete>

5.2.7.2 Invocation Method

DELETE

5.2.7.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	Application Token
<i>Content-Type</i>	String	application/json

5.2.7.4 Request Body

Parameter	Type	Description
<i>mobileNum</i>	string	Registered Mobile number of user
<i>countryCode</i>	string	Country code

5.2.7.5 Response Body

Parameter	Type	Description
<i>statusCode</i>	String	200 ok response
<i>message</i>	String	User deleted successfully

5.2.7.6 Sample Request and Response

HTTP Response:200 OK

```
{
  "statusCode" : 200,
  "message" : " User deleted successfully"
}
```

6. Token Generation

This section describes the token generation APIs for Mobile Application.

6.1 List of Token Generation APIs

The following table provides the list of Token generation APIs:

No	API Description	Method	API Context	API Path
1	To generate access token	POST	/jeep/users	/login
2	To generate access token from refresh token	POST	/jeep/users	/refreshToken
3	To generate Application token	POST	/jeep/users	/appToken

6.2 API Description

This API request can be used to generate tokens to be used for all CVIP APIS as authorization header.

6.2.1 Login/generate user token API

NB API Interface ID : NB-TOKEN_GENERATION-001

This API request can be used to login to the application.

6.2.1.1 URI

<https://<ServerIP>:<serverPort>/jeep/users/login>

6.2.1.2 Invocation Method

POST

6.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	Application Token
<i>Content-Type</i>	String	application/json

6.2.1.4 Request Body

Parameter	Type	Description
<i>mobileNum</i>	String	Registered Mobile number of user
<i>countryCode</i>	String	Country code
<i>password</i>	String	Password for the user

6.2.1.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>statusCode</i>	String	200 ok response

<i>token</i>	<i>Object</i>	<i>Token details</i>
--------------	---------------	----------------------

Token Object

Parameter	Type	Description
<i>accessToken</i>	String	Access token to access platform APIs
<i>refreshToken</i>	String	Refresh token for the user
<i>expiresIn</i>	Integer	Expiry time in seconds

6.2.1.6 Sample Request and Response

HTTP Request: *POST* /jeep/users/login

```
{
  "mobileNum": "9385698874",
  "countryCode": "+91",
  "password": "Password@123"
}
```

HTTP Response:200 OK

[illegible]

```

8HqDqrMVqO129WUzpzRd4pkiyemElK3iy0UrmpVos-
CU2PK2864QKtato4oX8XGjUGXfDhTPZ2INgJIrgiUR0UHxeUV4SozKMGEHlvU_54Tm0o-
9zd2UQDY0TyrRKpeJa--0MVC9uqhsqMXG9c3XWbc297gYqDqVVXBy4GRgPvEv2I-
U_SS6Tb6NQqMDPbX-E_w3c3NmVPh59ECTeny9Rbq1YEEExfaIOEwzbp211FfeGqtvh-
03aQfjj56GSs4IDo_GR6kwLLSZ7mWb8ffRoLdQKB0THWR_VKIB-
x2QIPzCE5gW8wdCauQ_0otVmqrK3VPbwnz_Pf4xMdvGc61Y0sirj9QT43rBFhzondfttlbMPfQVG
Mel5FKgw8bWerfY54TdHfIaOWvG_6j1O3zZN2pvJbEUemsV6JEP-
KmQGuedMjp2WEI1B3gPumD8nPv8XXszNeQGzjpw3RxT8pr-
XszQG9GGf38i1wkIYPTUDCDpPUHozsRXYDmxkLs13YtaskJ-
G5V1zFj3EsYCq_Lqu_SJcw9lItcf0VOCjgPjTTT9gkzWN5z458VRt9vTzh6pQ9nI9Kz0tfGZ6Vm8
FXE9pAaQZ4W54_jt_nVNfxRQkCIj3HA__7dG1UnPI3xFq5zvuS1ggC1U8cKQBx2tdPahMT33cHF1
Cv8mFpatJXJl9usTg.PwpMj8jpJLFM3yhbOP98Tw ",
    "expiresIn": 3600
  }
}

```

6.2.2 To fetch access token using refresh token

NB API Interface ID : NB-TOKEN_GENERATION-002

This API request can be used to fetch access token using refresh token.

6.2.2.1 URI

<https://<ServerIP>:<serverPort>/jeep/users/refreshToken>

6.2.2.2 Invocation Method

POST

6.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

6.2.2.4 Request Body

Parameter	Type	Description
<i>token</i>	String	Refresh token of the user

6.2.2.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>accessToken</i>	String	Access token of the user
<i>expiresIn</i>	Integer	Expiry time in seconds

6.2.2.6 Sample Request and Response

HTTP Request: POST /jeep/users/refreshToken

```

{
  "token":
    "eyJhdGkiOiJKV1QiLCJlbmMiOiJBMjU2R0NNIiwiaWF0IjoiU1NBLU9BRVAifQ.CAI8SkqBlfLjV
    O8KHpOSVcjFQvvl0hqgs3h7fT6aRRh6ZO_MKX75RJA59XQqRqTiVZUyXzUgaip3JTqDMKqAwzS-

```

Rw9SBTnnOpHeG2ewGxI9VfBSnDpm53jpvLQ9CjQcL4KqB8A78cfkxHy5D2NX4cVJHe6ebtMkFWgu
gykTOLnnkMM42Ub3zPu_EwjJCNVP1nPwJD80-
CnK9Z6hiX3rC_ghowDx5rS630SLyDwJe6xdKrbMvo3199yKoRwIA4740SMVOHUpMhm8J1t5S1aP
SqNZUvuPCr3Gui05IHtSmC4zsL41zBhWGuiq6gL5ZwyQ1MNTxmr-EdpTaRLB8A.4U-
rHA4FFae6Ecrk.UxYoL1saNIvBf0pYFgtknCZ_OrVdaL7syw7asny3dhkaDJGTkaASPlzfBV1Pn
tOFciYDcMrtuSN720byqNdrC_fIFUbRQjgxxDaTGKK1CVmOzHD9RftP3ZNeASavpgVUhDtyZGhBb
vUZZLSaXB3tEM8M0UtYOdoweE5o8rR07pjoofuyJl9jBlh1DP2qmYkXKtKvfDO_1-
8Wf4Bq23XKs-
P6fVGUXUrg9b9ygvj8fXKV26NB3G3TEYJvRegZt5j1UqWanIb9bhZicGdCzYkLOlKMLJ4-
MOOZ9ANnCN1j04K5qcYkyneBY1whUSXnhhfVBXwO6GFzP3egF3YVDvZFh_lbUEGPqRXzcTfJzmW
ecvt0ZKDPB8M3o7rmVpX5XI_g1ByYyqw4x78x2gKt5Z1kR9mH4C7eJ-
RBUVBuHqXxD0w7uKlSnSm0Hs07x2dHCOBDTSEt7hRJUE_OAGe83LLb_GASoeof8ilzfUG4YkbrTN
tgPjRE6F1_JmH_KYSGSyg8G_L0Lv1fBfOLFfrK5icNCgqbpXzLLIO9Romh13m6t1hEv48_T6jbbw
o6iWeMo-wvg0X-
PHzlchQkM1U8tU3QJtaJjhtyEFctK97eK5uzoDFxB7aS3qi9mLJD2m5_tP7a3_R9QZcoZnn9zuv7
8HqDqrMVqQ129WUZpZrD4pkiiyemElK3iy0UrmPvos-
CU2PK2864QKtatO4oX8XGjUGXFdhTPZ2IngJirgiUR0UHxeUV4SozKMGEHlvU_54Tm0o-
9zd2UQDY0TyrRKpeJa--0MVC9uqhsqMXG9c3XWBC297gYqDqVvXBy4GRgPvEv2I-
U_SS6Tb6NQqMDpX-E_w3c3NmvPh59ECTeny9Rbq1YEExfaI0Ewzbp21lFfeGqtvh-
03aQfjj56GSs4IDo_GR6kwLLSZ7mWb8ffRoLdQKB0THWR_VKIB-
x2QIPzCE5gW8wdCauQ_0otVmqrK3VPbwnz_Pf4xMdvgc61Y0sirj9QT43rBFhzondfttlbMPfqVG
Me15FKgw8bWeRfY54TdHfIaOWvG_6j103zzN2pvJbEUemsV6JEP-
KmQGuedMjp2WEI1B3gPumD8nPv8XXszNeQGzjpw3RxT8pr-
XsZQG9GGf38ilwkIYPTUDCDpPUHozsRXYDmxkLsl3YtaskJ-
G5V1zfJ3EsYcQ_Lqu_SJcw9lItcf0VOCjgPjTTT9gkzWN5z458VRt9vTzh6pQ9nI9Kz0tfGZ6Vm8
FXE9pAaQZ4W54_jt_nVNfxRQKCIj3HA__7dG1UnPI3xFq5zvuS1ggC1U8cKQBx2tdPahMT33cHF1
Cv8mFpatJXJl9usTg.PwpMj8jpJLFM3yhbOP98Tw "

HTTP Response:200 OK

```
{  
  "accessToken":  
    "eyJraWQioiIrYnhpd2xMUG9qYjZpMTZzTGtBSzQrQ25UZlBmSnM4Tnp1cWNUMDhmSVhnPSIsImFfs  
    ZyI6IlJTMjU2In0.eyJzdWiiOiJkMTUzZWQwYSliMDcxLTcwOTItNzdiNSlmODQ4NTVknTIyNzQi  
    LCJpc3MiOiJodHRwczcpcLlwvY29nbml0bylpZHAuYXAtc29ldGgtMS5hbWF6b25hd3MuY29tXC9h  
    cC1zb3V0aC0xX2ozQWJ4SWh5ciIsImNsaWVudF9pZCI6IjZnNjUybXM0YmxpNzBwbHRTY2loMTk4  
    cW5mIiwib3JpZ2luX2p0aSI6IjFlMWE5OWNmLTBmMTUtNDU0NS04NmZlLTl5NTM3YzA5ODA2NSIs  
    ImV2ZW50X2lkIjoijnkyZTAzZGMtOTkwMi00NTI1LTg4YzYtNWQ2YWNiZTc3OWJlIiwidG9rZW5f  
    dXN1IjoiYWNjaXNzIiwic2NvcGUioiJhd3MuY29nbml0by5zaWduaW4udXN1ci5hZGlpbilIsImF1  
    dGhfdGltZSI6MTE2MzY1MDU5MywiZXhwIjoxNzYzNjU0MTkzLCJpYXQioje3NjM2NTA1OTMsImp0  
    aSI6IjY0NDk5NjU4LTdjdjYzMtNDJhZi04MmMxLTc0NTEzNWlIXmRiZiIsInVzZXJuYW11IjoiZDE1  
    M2VkMGEtYjA3MS03MDkyLTc3YjU0ODU1ZDUyMjc0In0.qmVblrvwm3S1mCb8YW9FOxFB6wJi  
    6yFxOqlf_3a6Vq-OISwCrTx7ZAG3NGmtypR2rFsttvQFHh19T7MX-HoZea6NWDIBruplv1-  
    WlUagrqrNI0xmKv4Txx7qmhf163ndex1JgcW5XmWH-g8-  
    ny2geais0WQk55bZ54g_o4uvU48D7jh5aGrndhZz2qTCqBuYrxDKCuIf0dKsD9jsrwJHIWKDQS00  
    lD1PdF1ldnt7L88YJCvf_QQM-ZohBnyKe5Tp79a_YC66EafjIoHMrKxUtm3sKgCSEc2mB-  
    hM1HzUpGz25ABS6o-hphxoCt9FnCONyrRtizkg1WFOj-wnzQ41a",  
  "expiresIn": 3600  
}
```

6.2.3 Generate application token API

NB API Interface ID : NB-TOKEN GENERATION-003

This API request can be used to generate token for server-to-server communication.

6.2.3.1 URI

<https://<ServerIP>:<serverPort>/jeep/authentication/login>


```
q_24cWVr1WtTuTUqAtY-8aycovq4Kr6RSzpy6oCFJqrRK2dO--0w-  
H7YoMJ7H3eqy6B3lPHMy_9iu42YTpmEOyo9WyOQ-UnxpQHmf1_miPSx1ULhggAlEyEQYyTPWq01-  
XzxIkxQkVQhbJDdeoX6sD7v0NUkw817UlAalQxrUAdUbsuDntCAzV1kgWU5YPh-  
MsTs4SwinG0qG2cWHXli3AYKcJcZcudECpNajeYMrM5gzcS9F20p82KkNRmg",  
    "expiresIn": 3600  
}  
}
```

7. Driving Behaviour APIs

This section describes the Driving behaviour NB APIs for Mobile Application.

7.1 List of Driving Behaviour APIs

The following table provides the list of Driving behaviour APIs:

No	API Description	Method	API Context	API Path
1	Get the trip details of a vehicle based on trip id	GET	/jeep/trip	/{{ vinNum }}/tripId/{{ tripId }}
2	Get list of trip details	GET	/jeep/trip	/{{ vinNum }}/details
3	Get ongoing trip details of vehicle	GET	/jeep/trip	/{{ vinNum }}/ongoing
4	Get Trip consolidation summary with driving score	GET	/jeep/trip	/{{ vinNum }}/summary
Save minimum trip distance is considered and added in Remote commands API path (Section:13.2.6)				

7.2 API Description

7.2.1 Get the trip details of a vehicle based on trip id

NB API Interface ID : NB-DRIVING_BEHAVIOUR-001

This API request can be used to fetch the trip details of a vehicle based on trip id.

7.2.1.1 URI

<https://<ServerIP>:<serverPort>/jeep/trip/{{ vinNum }}/tripId/{{ tripId }}>

7.2.1.2 Invocation Method

GET

7.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

7.2.1.4 Request Body

NIL

7.2.1.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>vehicleId</i>	String	Device Vin Num
<i>tripId</i>	String	Unique id for the trip
<i>tripName</i>	String	Name of the trip

Parameter	Type	Description
tripRoute	List	List of 12 latitude and longitude values that will cover whole the destination from start to end
tripStartDate	String	Start date and time of the trip
tripEndDate	String	End date and time of the trip
minimumTripDistance	Integer	Minimum distance configured to start the trip
engineOffTime	Integer	EngineOffTime configured for trip start
distanceTravelled	Float	Total distance travelled in the trip
avgVehicleSpeed	Float	Average speed of the vehicle in the trip
totalTimeTravelled	Float	Trip start time to current time
hardBrake	Float	Total time the hard brake applied
hardAcceleration	Float	Aggressive acceleration of Vehicle
tripType	String	Type of the Trip
maxVehicleSpeed	Float	Maximum vehicle speed
noOfSharpTurns	Integer	Num of Sharp turns

7.2.1.6 Sample Request and Response

HTTP Request: *GET /jeep/trip/{vinNum}/tripId/* MCANJREB2401192511202501

HTTP Response: 200 OK

```
{
  "vehicleId": "MCANJREB1MFA65412",
  "tripId": " MCANJREB2401192511202501",
  "tripName": " Trip 2511202501",
  "tripRoute": [
    "12.947794745383469,80.23294226011618",
    "12.949575420967099,80.22629296982068",
    "12.94868540970674,80.2152680048508",
    "12.948409704521726,80.21143313092277",
    "12.948854182288102,80.20630847444329",
    "12.9485746844448,80.20980435694977",
    "12.948570010149918,80.20981374308525",
    "12.949147730463299,80.21909952413553",
    "12.950003440119959,80.23123384215033",
    "12.948331223137107,80.23337507218656",
    "12.948272685665003,80.23337331212491",
    "12.948259905803559,80.23336409015582"
  ],
  "tripStartDate": "2021-06-24T02:28:17Z",
  "tripEndDate": "2021-06-24T02:39:18Z",
  "distanceTravelled": 10,
  "minimumTripDistance": 3,
  "engineOffTime": 5,
  "avgVehicleSpeed": 8,
  "totalTimeTravelled": 11.024067,
```

```
"hardBrake": 0,
"hardAcceleration": 0,
"tripType": "Active Trip",
"maxVehicleSpeed": 12,
"noOfSharpTurns": 2}
```

7.2.2 Get list of trip details

NB API Interface ID : NB-DRIVING_BEHAVIOUR-002

This API request can be used to fetch the list of trips

7.2.2.1 URI

<https://<ServerIP>:<ServerPort>/jeep/trip/{vinNum}/details?pageNo=1>

7.2.2.2 Invocation Method

GET

7.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

7.2.2.4 Request Body

NIL

7.2.2.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>vehicleId</i>	String	Device Vin Num
<i>Count</i>	Integer	Total number of trips
<i>tripStartDate</i>	String	Start date and time of the trip
<i>distanceTravelled</i>	Float	Total distance travelled for the date range
<i>tripId</i>	String	Unique id for the trip
<i>tripEndDate</i>	String	End date and time of the trip
<i>totalTimeTravelled</i>	Float	Total time the vehicle in travel

tripName	String	Name of the trip
minimumTripDistance	Integer	Minimum distance configured to start the trip
engineOffTime	Integer	EngineOffTime configured for trip start
tripStartLocation	String	Trip start location
tripEndLocation	String	Trip end location
noOfSharpTurns	Integer	Sharp turn count

7.2.2.6 Sample Request and Response

HTTP Request: *GET* /trip/012345667868/details?pageNo=1

HTTP Response: 200 OK

```
{
  "count": 1,
  "tripListResponseDTO": [{
    "vehicleId": "MCANJREB1MFA65412",
    "tripId": "MCANJREB2401192511202501",
    "minimumTripDistance": 3,
    "engineOffTime": 5,
    "tripName": "Trip 2511202501",
    "tripStartLocation": "1.2.2.8",
    "tripEndLocation": "1.2.2.8",
    "tripStartDate": "2021-06-24T03:47:24Z",
    "tripEndDate": "2021-06-24T03:47:36Z",
    "distanceTravelled": 0.0,
    "totalTimeTravelled": 0.205
  }]
}
```

7.2.3 Get the ongoing trip detail of a vehicle

NB API Interface ID : NB-DRIVING_BEHAVIOUR-003

This API request can be used to fetch the current trip info for particular device.

7.2.3.1 URI

The following URI will be used to fetch the current trip info for particular device.

<https://<ServerIP>:<serverPort>/jeep/trip/{vinNum}/ongoing>

7.2.3.2 Invocation Method

GET

7.2.3.3 Request Header

Parameter	Type	Description
Authorization	String	User Token
Content-Type	String	application/json

7.2.3.4 Request Body

NIL

7.2.3.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
vehicleId	String	Device Vin Num
tripId	String	Unique id for the trip
tripName	String	Name of the trip
minimumTripDistance	Integer	Minimum distance configured to start the trip
engineOffTime	Integer	EngineOffTime configured for trip start
Location	String	Start location of trip
tripStartDate	String	Start date and time of the trip
distanceTravelled	Float	Total distance travelled till current location
totalTimeTravelled	Float	Trip start time to current time
vehicleSpeed	Float	Current speed of the vehicle in the trip
hardBrake	Float	Total time the hard brake applied
hardAcceleration	Float	Aggressive acceleration of the vehicle
tripType	String	Type of the Trip
tripCurrentStatus	String	Current status of the trip
ignitionStatus	String	Ignition status of the vehicle
createdTimeStamp	String	Created timestamp
updatedTimeStamp	String	Updated timestamp

7.2.3.6 Sample Request and Response

HTTP Request: *GET /jeep/trip/MCANJREB1MFA65412/ongoing*

HTTP Response: *200 OK*

```
{
  "vehicleId": "MCANJREB1MFA65412",
  "minimumTripDistance": 3,
  "engineOffTime": 5,
```

```

"tripId": "MCANJREB2401192511202501 ",
"tripName": " Trip 2511202501",
"location": "1.2,2.8",
"tripStartDate": "2021-06-24T03:47:36Z",
"distanceTravelled": 0.0,
"totalTimeTravelled": 1272.6564,
"vehicleSpeed": 4.0,
"createdTimeStamp": "2021-06-24T03:47:36Z",
"updatedTimeStamp": "2021-06-24T16:33:14Z",
"hardBrake": 0.0,
"hardAcceleration": 0.0,
"tripType": "Active Trip",

"tripCurrentStatus": "Idle",
"ignitionStatus": "Contact"
}

```

7.2.4 Get the trip consolidation summary with driving score

NB API Interface ID : NB-DRIVING_BEHAVIOUR-004

This API request can be used to fetch the trip summary for particular device based on the timestamp.

7.2.4.1 URI

<https://<ServerIP>:port/jeep/trip/{vinNum}/summary?starttime={starttime}&endtime={endtime}>

7.2.4.2 Invocation Method

GET

7.2.4.3 Request Header

Content-Type: application/json

7.2.4.4 Request Body

NIL

7.2.4.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
vehicleId	String	Device Vin Num
distanceTravelled	Float	Total distance travelled for the date range
totalTimeTravelled	Float	Total time the vehicle in travel
avgVehicleSpeed	Float	Average speed of the vehicle travelled during the period
hardBrake	Float	Total time the hard brake applied
hardAcceleration	Float	Aggressive acceleration of Vehicle

noOfTrips	Integer	Total number of trips in the requested range
ignitionStatus	String	Status of ignition
drivingScore	Float	Driving score with respective timestamp

7.2.4.6 Sample Request and Response

HTTP Request: *GET /jeep/trip/MCANJREB1MFA65412/summary? starttime=26-May-2020*

01:40&endtime=29-Jun-2021 10:41

Content-Type: application/json

HTTP Response: *200 OK*

```
{
  "vehicleId": "MCANJREB1MFA65412",
  "distanceTravelled": "80 km",
  "totalTimeTravelled": "2 hrs",
  "avgVehicleSpeed": "40 km/hr",
  "hardBrake": "0 mins",
  "hardAcceleration": 0,
  "noOfTrips": 3,
  "ignitionStatus": "Contact",
  "drivingScore": 40.0
}
```

8. Location APIs

This section describes vehicle Location API for mobile application.

8.1 Location APIs

The following table provides the list of location APIs:

No	API Description	Method	API Context	API Path
1	Get live location stream of vehicle	GET	/jeep/location	/stream/{vinNum}
2	Get the latest location of vehicle	GET	/jeep/location	/vinNum

8.2 API Description

The APIs are listed, and the corresponding URI, Invocation method, request and response are explained in each API description

8.2.1 Get live location stream of vehicle

NB API Interface ID : NB-LOCATION_TRACKING-001

This API request can be used to get continuous live location of vehicle as a stream when the trip is active.

8.2.1.1 URI

<https://<ServerIP>:<serverPort>/jeep/location/stream/{vinNum}>

8.2.1.2 Invocation Method

GET

8.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

8.2.1.4 Request Body

NIL

8.2.1.5 Response Body

Response shall consist of the following response body in text/ event-stream format:

Parameter	Type	Description
<i>x</i>	double	Latitude
<i>y</i>	Double	longitude
<i>Ts</i>	Long	Epoch time
<i>coarseAngle</i>	double	CoarseAngle value from device

8.2.1.6 Sample request and response**HTTP Request:** *GET /jeep/location/stream/MCANJREB1MFA65412***HTTP Response:** *200 OK**A continuous stream of data in below format will be returned on latest location published from device.**data:{"x":20.123125125,"y":80.624861246,"ts":1629984859,"coarseAngle":0.0}**data:{"x":20.123125125,"y":80.624861246,"ts":1629984883,"coarseAngle":0.0}**data:{"x":20.123125125,"y":80.624861246,"ts":1629984903,"coarseAngle":0.0}***8.2.2 Get latest location of vehicle**

NB API Interface ID : NB-LOCATION_TRACKING-002

This API request can be used to get latest location of vehicle.

8.2.2.1 URI<https://<ServerIP>:<serverPort>/jeep/location/{vehicleId}>**8.2.2.2 Invocation Method**

GET

8.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

8.2.2.4 Request Body

NA

8.2.2.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>vehicleId</i>	String	Vehicle id
<i>lat</i>	Double	Latitude
<i>lon</i>	Double	Longitude
<i>signalTs</i>	String	Timestamp
<i>createdTime</i>	String	Timestamp
<i>updatedAtTime</i>	String	Timestamp

8.2.2.6 Sample request and response**HTTP Request:** *GET* /location /MCANJREB1MFA65412**HTTP Response:** *200 OK*

```
{
  "vehicleId":"MCANJREB1MFA65412",
  "lat":17.23424614,
  "lon":81.12864916,
  "signalTs":"2021-08-31T11:00:00",
  "createdTime":"2021-08-31T11:00:00",
  "updatedAtTime":"2021-08-31T11:00:00"
}
```

9. Events APIs

This section describes NB APIs for Events for mobile application.

9.1 Events APIs

The following table provides the list of Events APIs:

No	API Description	Method	API Context	API Path
2	Get vehicle status	GET	/jeep/vehicleStatus	/vinNum}

9.2 API Description

The APIs are listed and the corresponding URI, Invocation method, request and response are explained in each API description

9.2.1 Get vehicleStatus details

NB API Interface ID : NB-EVENTS-002

This API request can be used to get details of a vehicle Status.

9.2.1.1 URI

<https://<ServerIP>:<serverPort>/jeep/vehicleStatus/{vehicleId}>

9.2.1.2 Invocation Method

GET

9.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

9.2.1.4 Request Body

NA

9.2.1.5 Response Body

Response shall consist of the following response body in text/ event-stream format:

Parameter	Type	Description
signalTimeStamp	String	signalTimeStamp
ignitionStatus	String	IgnitionStatus(ignition status of vehicle to be used by Application)
gpsLat	double	gpsLat
gpstLong	double	gpstLong
speed	double	Speed
remoteBlinkerStatus	String	Status of blinker
remoteHonkStatus	String	Status of honk
odometer	float	Odometer
deviceConnectedState	String	device connection state
disconnectionType	String	Type of connection
fuelPercentage	Float	Percentage of fuellevel
coarseAngle	double	Coarse Angle value
dongleSignalStrength	String	Dongle signal strength
vehicleIgnitionStatus	String	Ignition Status of the vehicle
userDefinedSpeed	String	User defined speed
vehicleStateHealth	Map<String,String>	Diagnostic alerts
vehicleImmobilization	String	Vehicle immobilization status

fotaStatus	String	Status of fota installation
coolant	Float	Coolant value in celsius
battery	Float	Battery value in volts

9.2.1.6 Sample request and response

HTTP Request: *GET /jeep/vehicleStatus/MCANJREB1MFA65412*

HTTP Response: *200 OK*

```
{
  "signalTimeStamp": 1765966404584,
  "ignitionStatus": "ACC",
  "gpsLat": 12.948102120794934,
  "gpstLong": 80.23299128430646,
  "speed": 0.0,
  "remoteBlinkerStatus": "OFF",
  "remoteHonkStatus": "OFF",
  "odometer": 36504.0,
  "deviceConnectedState": "CONNECTED",
  "disconnectionType": "NA",
  "fuelPercentage": 35.0,
  "coarseAngle": 283.0,
  "dongleSignalStrength": 4.0,
  "vehicleIgnitionStatus": "NA",
  "userDefinedSpeed": null,
  "vehicleStateHealth": null,
  "fotaStatus": null,
  "coolant": 91.0,
  "battery": 14.08
}
```

10. Notification Setting APIs

This section describes the Notification Settings APIs.

10.1 List of Notification Setting APIs

The following table provides the list of Notification Setting APIs which can be utilized for Mobile application:

No	API Description	Method	API Context	API Path
1	Post notification setting with snooze period	POST	/jeep/notification	/setting/{vinNum}
2	Fetch notification setting with snooze period	GET	/jeep/notification	/setting/{vinNum}
3	Update notification setting with snooze period	PUT	/jeep/notification	/setting/{vinNum}
4	Post notification setting with	POST	/jeep/notification	/setting/preferences/{vin}

	enable/disable option			Num}
5	Fetch notification setting with enable/disable option	GET	/jeep/notification	/setting/preferences/{vinNum}
6	Update notification setting with enable/disable option	PUT	/jeep/notification	/setting/preferences/{vinNum}

10.2 API Description

The APIs are listed and the corresponding URI, Invocation method, request and response are explained in each API description.

10.2.1 Post notification setting to platform with snooze period

NB API Interface ID : NB-NOTIFICATION_SETTING-001

This API is used to post notification setting with snooze period only if the alert is Enabled through Enable/disable option.

10.2.1.1 URI

API to post notification setting with snooze period

<https://<ServerIP>:port/jeep/notification/setting/{vinNum}>

10.2.1.2 Invocation Method

POST

10.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

10.2.1.4 Request Body

Request shall consist of following request body in json format.

Parameter	Type	Description
<i>vinNo</i>	String	vinNo
<i>alertStatus</i>	String	Alert status(A/D)
<i>alertType</i>	String	Type of alert(Possible values - SpeedAlert,Towing,ParkingDisturbance,EngineIdle, DeviceRemoval)
<i>snoozePeriod</i>	String	Snooze period
<i>startTimeStamp</i>	Date	<i>startTimeStamp</i>

<i>endTimeStamp</i>	Date	<i>endTimeStamp</i>
---------------------	------	---------------------

10.2.1.5 Response Body

Response shall consist of following after successful processing at platform level

Parameter	Type	Description
<i>statusCode</i>	Int	Status code
<i>Message</i>	String	Success/failure message

10.2.1.6 Sample Request and Response

HTTP Request: POST /jeep/notification/setting/MCANJREB1MFA65412

```
{
  "vinNo": "MCANJREB1MFA65412",
  "settings": [
    {
      "alertType": "SpeedAlert",
      "alertStatus": "D",
      "snoozePriod": "10 mins",
      "startTimeStamp": 1650963692593,
      "endTimeStamp": 1650964292593
    }
  ]
}
```

HTTP Response:200 OK

```
{
  "statusCode": 200,
  "message": "Successfully setted timer for the alert "
}
```

10.2.2 Fetch notification setting to platform with snooze period

NB API Interface ID : NB-NOTIFICATION_SETTING-002

This API is used to fetch notification setting with snooze period.

10.2.2.1 URI

API to fetch notification setting with snooze period

<https://<ServerIP>:port/jeep/notification/setting/{vinNum}>

10.2.2.2 Invocation Method

GET

10.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

10.2.2.4 Response Body

Response shall consist of following request body in json format.

Parameter	Type	Description
<i>alertStatus</i>	String	Alert status(A/D)
<i>alertType</i>	String	Type of alert
<i>snoozePeriod</i>	String	Snooze period
<i>startTimeStamp</i>	Date	<i>startTimeStamp</i>
<i>endTimeStamp</i>	Date	<i>endTimeStamp</i>

10.2.2.5 Sample Response

HTTP Request: GET /jeep/notification/setting/ MCANJREB1MFA65412

```
{
  "id": "62a863733ea0f3506080d86c",
  "vinNo": " MCANJREB1MFA65412",
  "settings": [
    {
      "alertType": "SpeedAlert",
      "alertStatus": "D",
      "snoozePriod": "10 mins",
      "startTimeStamp": 1655202745544,
      "endTimeStamp": 1655203045544
    }
  ]
}
```

10.2.3 Update notification setting to platform with snooze period

NB API Interface ID : NB-NOTIFICATION_SETTING-003

This API is used to update notification setting with snooze period.

10.2.3.1 URI

API to update notification setting with snooze period

<https://<ServerIP>:port /jeep/notification/setting/{vinNum}>

10.2.3.2 Invocation Method

PUT

10.2.3.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

10.2.3.4 Request Body

Request shall consist of following request body in json format.

Parameter	Type	Description
<i>vinNo</i>	String	vinNo
<i>alertStatus</i>	String	Alert status(A/D)
<i>alertType</i>	String	Type of alert(SpeedAlert,Towing,ParkingDisturbance,EngineIdle,DeviceRemoval)
<i>snoozePeriod</i>	String	Snooze period
<i>startTimeStamp</i>	Date	<i>startTimeStamp</i>
<i>endTimeStamp</i>	Date	<i>endTimeStamp</i>

10.2.3.5 Response Body

Response shall consist of following after successful processing at platform level

Parameter	Type	Description
<i>statusCode</i>	Int	Status code
<i>Message</i>	String	Success/failure message

10.2.3.6 Sample Request and Response

HTTP Request: PUT /jeep/notification/setting/MCANJREB1MFA65412

```
{
  "vinNo": "MCANJREB1MFA65412",
  "settings": [
    {
      "alertType": "SpeedAlert",
      "alertStatus": "A",
      "snoozePriod": "5 mins",
      "startTimeStamp": 1654751108,
      "endTimeStamp": 1655203045544
    }
  ]
}
```

```
]
}
```

Content-Type: application/json

HTTP Response:200 OK

```
{
  "statusCode": 200,
  "message": "Successfully updated status for the alert "
}
```

10.2.4 Post notification setting to platform with disable/enable option

NB API Interface ID : NB-NOTIFICATION_SETTING-004

This API is used to post notification setting for all alerts at once for the vin with enable("A") option.

10.2.4.1 URI

API to post notification setting with enable/disable option.

<https://<ServerIP>:port/jeep/notification/setting/preferences/{vinNum}>

10.2.4.2 Invocation Method

POST

10.2.4.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

10.2.4.4 Request Body

Request shall consist of following request body in json format.

Parameter	Type	Description
<i>vinNo</i>	String	vinNo
<i>alertStatus</i>	String	Alert status(A/D)
<i>alertType</i>	String	Type of alert(SpeedAlert,Towing,ParkingDisturbance,EngineIdle,DeviceRemoval)

10.2.4.5 Response Body

Response shall consist of following after successful processing at platform level

Parameter	Type	Description
<i>statusCode</i>	Int	Status code
<i>Message</i>	String	Success/failure message

10.2.4.6 Sample Request and Response

HTTP Request: POST /jeep/notification/setting/preferences/MCANJREB1MFA65412

```
{
  "vinNo": "MCANJREB1MFA65412",
  "settings": [
    {
      "alertType": "SpeedAlert",
      "alertStatus": "A"
    },
    {
      "alertType": "Towing",
      "alertStatus": "A"
    },
    {
      "alertType": "EngineIdle",
      "alertStatus": "A"
    },
    {
      "alertType": "ParkingDisturbance",
      "alertStatus": "A"
    },
    {
      "alertType": "DeviceRemoval",
      "alertStatus": "A"
    }
  ]
}
```

HTTP Response:200 OK

```
{
  "statusCode": 200,
  "message": "Successfully enabled/disable notification for the alert "
}
```

10.2.5 Fetch notification setting to platform with enable/disable option

NB API Interface ID : NB-NOTIFICATION_SETTING-005

This API is used to fetch notification setting.

10.2.5.1 URI

API to fetch notification setting

<https://<ServerIP>:port/jeep/notification/setting/preferences/{vinNum}>

10.2.5.2 Invocation Method

GET

10.2.5.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

10.2.5.4 Response Body

Response shall consist of following request body in json format.

Parameter	Type	Description
<i>alertStatus</i>	String	Alert status(A/D)
<i>alertType</i>	String	Type of alert

10.2.5.5 Sample Response

HTTP Request: GET /jeep/notification/setting/preferences/MCANJREB1MFA65412

```
{
  "id": "62a863733ea0f3506080d86c",
  "vinNo": "MCANJREB1MFA65412",
  "settings": [
    {
      "alertType": "SpeedAlert",
      "alertStatus": "A"
    },
    {
      "alertType": "Towing",
      "alertStatus": "A"
    },
    {
      "alertType": "EngineIdle",
      "alertStatus": "A"
    },
    {
      "alertType": "ParkingDisturbance",
      "alertStatus": "A"
    },
    {
      "alertType": "DeviceRemoval",
      "alertStatus": "A"
    }
  ]
}
```

10.2.6 Update notification setting to platform with disable/enable option

NB API Interface ID : NB-NOTIFICATION_SETTING-006

This API is used to update notification setting with enable/disable option.

10.2.6.1 URI

API to update notification setting with enable/disable option.

<https://<ServerIP>:port /jeep/notification/setting/preferences/{vinNum}>

10.2.6.2 Invocation Method

PUT

10.2.6.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

10.2.6.4 Request Body

Request shall consist of following request body in json format.

Parameter	Type	Description
<i>vinNo</i>	String	vinNo
<i>alertStatus</i>	String	Alert status(A/D)
<i>alertType</i>	String	Type of alert(SpeedAlert,Towing,ParkingDisturbance,EngineIdle,DeviceRemoval)

10.2.6.5 Response Body

Response shall consist of following after successful processing at platform level

Parameter	Type	Description
<i>statusCode</i>	Int	Status code
<i>Message</i>	String	Success/failure message

10.2.6.6 Sample Request and Response

HTTP Request: PUT /jeep/notification/setting/preferences/MCANJREB1MFA65412

```
{
  "vinNo": "MCANJREB1MFA65412",
  "settings": [
    {
      "alertType": "Towing",
```

```

"alertStatus": "D",
},
{
"alertType": "EngineIdle",
"alertStatus": "D",
}
]
}

```

HTTP Response:200 OK

```

{
"statusCode": 200,
"message": " Successfully updated notification for the vin "
}

```

11. Vehicle Tracking APIs

This section describes the Vehicle Tracking NB APIs.

11.1 List of Vehicle Tracking APIs

The following table provides the list of Vehicle Tracking APIs which can be utilized for Mobile application

No	API Description	Method	API Context	API Path
1	Create geo Fence	POST	/jeep/fence	/vinNum}
2	Update Fence Details based on VIN and fence Id	PUT	/jeep/fence	/vinNum}/{fenceId}
3	Delete fence based on fence Id	DELETE	/jeep/fence	/vinum}/{fenceId}
4	Get fence details based on fence type and VIN	GET	/jeep/fence	/vinNum}/fenceType/{fenceType}
5	Create curfew fence	POST	/jeep/fence	/curfew/{vinNum}
6	Get curfew details along with curfew Id for vinNum	GET	/jeep/fence	/curfew/(vinNum)
7	Update curfew details based on vin and curfewId	PUT	/jeep/fence	/curfew/{vinNum}/{curfewId}
8	Delete curfew based on curfewId	DELETE	/jeep/fence	/curfew/{vinNum}/{curfewId}

11.2 API Description

The APIs are listed and the corresponding URI, Invocation method, request and response are explained in each API description.

11.2.1 Create geo fence

NB API Interface ID : NB-VEHICLE_TRACKING-001

This API request is used to create a geo fence from the mobile application

11.2.1.1 URI

The following URI will be used for creating the geo fence.

<https://<ServerIP>:<ServerPort>/jeep/fence/{vinNum}>

11.2.1.2 Invocation Method

POST

11.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

11.2.1.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Type	Value Range	Description
<i>fenceType</i>	String	{location}	Fence Type
<i>fenceStatus</i>	String	{A/D}	Status of the Fence
<i>fenceGeometry</i>	String	{Circle}	Geometry of the fence
<i>transitionType</i>	String	{IN, OUT, INOUT}	Transition type of the fence
<i>centre</i>	List<gpsLat,gpsLong>		List of coordinates for Centre point for circle
<i>gpsLat</i>	Double		GPS latitude
<i>gpsLong</i>	Double		GPS longitude
<i>fenceMode</i>	String		Mode of the Fence
<i>fenceName</i>	String		Name of the fence
<i>isInfinite</i>	String	{true/false}	isInfinite
<i>radius</i>	Double		Radius
<i>daysofWeek</i>	List		Days of the Week("MON", "FRI", "SAT", "SUN", "TUE", "WED", "THU")
<i>startTime</i>	String		StartTime of the Fence
<i>endTime</i>	String		EndTime of the Fence
<i>timeMode</i>	String		Time mode 1.TimeMode to be set, when isinfinite is set as false – timeMode is either

Parameter	Type	Value Range	Description
			full_day(ends at the end of the day) or the manual start and end timestamp to be set. 2.TimeMode to be set as skip,when isinfinite is true

11.2.1.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
fenceName	String	Name of the Fence
fenceId	String	Id of the Fence
fenceStatus	String	Status of the Fence
message	String	Success/Error message

11.2.1.6 Sample request and response

POST jeep/fence/ MCANJREB1MFA65412

HttpRequest: For creating Circular fence

```
{
  "fenceName": "Home",
  "fenceType": "location",
  "fenceGeometry": "CIRCLE",
  "fenceStatus": "A",
  "transitionType": "INOUT",
  "centre": {
    "gpsLat": -0.126821,
    "gpsLong": 51.495885
  },
  "radius": 1000,
  "timeMode": "skip",
  "isInfinite": "true",
  "fenceMode": "radius",
  "daysOfWeek": [
    "MON",
    "THU",
    "SAT"
  ]
}
```

HttpResponse:

201 CREATED

```
{
  "fenceName": "Home",
  "message": "Successfully created Fence",
  "fenceId": "6489d0d5-9d02-4bdc-b052-a76d0f94bb73",
  "fenceStatus": "A"
}
```

400 BAD REQUEST

```
{
  "statusCode": 400,
  "message": "Malformed request syntax; Missing mandatory parameters"
}
```

11.2.2 Update fence Details based on VIN and fence Id

NB API Interface ID : NB-VEHICLE_TRACKING-002

This API request is used to update the fence details for geo fence

11.2.2.1 URI

The following URI will be used to update fence status for geo fence.

<https://<ServerIP>:<ServerPort>/jeep/fence/{vinNum}/{fenceId}>

11.2.2.2 Invocation Method

PUT

11.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

11.2.2.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Type	Value Range	Description
<i>fenceType</i>	String	{location}	Fence Type
<i>fenceStatus</i>	String	{A/D}	Status of the Fence
<i>fenceGeometry</i>	String	{Circle}	Geometry of the fence
<i>transitionType</i>	String	{IN, OUT, INOUT}	Transition type of the fence
<i>fenceMode</i>	String		Mode of the fence
<i>isInfinite</i>	String	false/true	Is infinite of the fence
<i>centre</i>	List<gpsLat,gpsLongitude>		List of coordinates for Centre point for circle

Parameter	Type	Value Range	Description
gpsLat	Double		GPS latitude
gpsLong	Double		GPS longitude
radius	Double		Radius
daysofWeek	List		Days of the Week("MON", "FRI", "SAT", "SUN", "TUE", "WED", "THU")
startTime	String		StartTime of the Fence
endTime	String		EndTime of the Fence
timeMode	String		Time mode value – full_day or start and endTime

11.2.2.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
fenceName	String	Name of the Fence
fenceId	String	Id of the Fence
fenceStatus	String	Status of the Fence
message	String	Success/Error message

11.2.2.6 Sample request and response

HttpRequest: PUT jeep/fence/MCANJREB1MFA65412/d5ce7fe9-0583-44be-b30c-4b73a9da520b

```
{
  "fenceName": "Radius Fence"
  "fenceType": "location",
  "fenceGeometry": "CIRCLE",
  "fenceStatus": "A",
  "transitionType": "INOUT",
  "centre": {
    "gpsLat": -0.126821,
    "gpsLong": 51.495885
  },
  "radius": 1000,
```

```
"isInfinite": "true",
"fenceMode": "radius",
"daysOfWeek": [
  "MON",
  "THU",
  "SAT"
],
"timeMode": "skip"
}
```

HttpResponse:**200 OK**

```
{
  "fenceName": " Radius Fence",
  "message": "Successfully updated Fence",
  "fenceId": "77f9c987-3c5d-44a6-a3e1-ff90c7c00ee7",
  "fenceStatus": "A"
}
```

400 BAD REQUEST

```
{
  "statusCode": 400,
  "message": "Malformed request syntax; Missing mandatory parameters"
}
```

11.2.3 Delete geo fence based on fence Id

NB API Interface ID : NB-VEHICLE_TRACKING-003

This API request is used to delete the geo fence.

11.2.3.1 URI

The following URI will be used to delete geo fence.

<https://<ServerIP>:<serverPort>/jeep/fence/{vinNum}/{fenceId}>

11.2.3.2 Invocation Method

DELETE

11.2.3.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

11.2.3.4 Request Body

NIL

11.2.3.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
statusCode	Integer	Status code
fenceName	String	Name of the Fence
Message	String	Success/Error message

11.2.3.6 Sample request and response

HTTP Request: DELETE

/jeep/fence/MCANJREB1MFA65412/d5ce7fe9-0583-44be-b30c-4b73a9da520b

HTTP Response:

```
{  
  "fenceName": "Radius Fence",  
  "message": "Deleted Fence Successfully",  
  "fenceId": "83b0d932-d963-4276-a0e1-2e1b612a279e"  
}
```

11.2.4 Get geo fence details based on fence type and VIN

NB API Interface ID : NB-VEHICLE_TRACKING-004

This API request is used to get the geo fence details based on type and VIN

11.2.4.1 URI

The following URI will be used to fetch geo fence details.

<https://<ServerIP>:<serverPort>/jeep/fence/{vinNum}/fenceType/{fenceType}>

11.2.4.2 Invocation Method

GET

11.2.4.3 Request Header

Parameter	Type	Description
Authorization	String	User Token
Content-Type	String	application/json

11.2.4.4 Request Body

NIL

11.2.4.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
fenceMode	String	Mode of the Fence

VinNo	String	Vin No of the Fence Created
fenceName	String	Name of the Fence
fenceId	String	Id of the Fence
fenceType	String	Type of the Fence
fenceStatus	String	Status of the Fence
fenceGeometry	String	Geometry of the Fence
transitionType	String	Transition Type of the Fence
isInfinite	String	isInfinite of the fence
startTime	Integer	timeStart of the Fence
endTime	Integer	timeEnd of the Fence
createdTimeStamp		createdTimeStamp of the fence
updatedTimeStamp		updatedTimeStamp of the fence
radius	Double	Radius of the Fence
Centre	List of points	Centre of the Fence
daysOfWeek	List	Days of week for fence("MON", "FRI", "SAT", "SUN", "TUE", "WED", "THU")
fenceName	String	Name of the Fence

11.2.4.6 Sample request and response

HTTP Request: GET

/jeep/fence/ MCANJREB1MFA65412/fenceType/location

HTTP Response:

```
[
  {
    "vinNo": "MZZCBZKCZRV019635",
    "fenceName": "Radius Fence1",
    "fenceId": "9413e016-f461-4e5b-81c2-7813805dacb8",
    "fenceType": "location",
    "fenceMode": "radius",
    "fenceStatus": "D",
    "fenceGeometry": "CIRCLE",
    "transitionType": "INOUT",
    "centre": {
      "gpsLat": 12.948365090565762,
      "gpsLong": 80.23313649243396
    },
    "radius": 1000.0,
    "isInfinite": "true",
    "timeMode": "skip",
    "daysOfWeek": [
      "TUE",
      "MON",
      "THU"
    ],
    "createdTimeStamp": 1767073722679,
    "updatedTimeStamp": 1767073722679
  },
  {
    "vinNo": "MZZCBZKCZRV019635",
    "fenceName": "Radius Fence1",
    "fenceId": "2b9be7fc-cf7e-4550-8bce-708b1fb62c6a",
    "fenceType": "location",
    "fenceMode": "radius",
    "fenceStatus": "D",
    "fenceGeometry": "CIRCLE",
    "transitionType": "INOUT",
    "centre": {
      "gpsLat": 12.948365090565762,
      "gpsLong": 80.23313649243396
    },
    "radius": 1000.0,
    "startTime": "2025-12-08T12:10:37Z",
    "endTime": "2025-12-08T15:05:37Z",
    "isInfinite": "false",
    "timeMode": "full_day",
    "daysOfWeek": [
      "TUE",
      "MON",
      "THU"
    ],
    "createdTimeStamp": 1767073753859,
    "updatedTimeStamp": 1767073753859
  },
  {
    "vinNo": "MZZCBZKCZRV019635",
    "fenceName": "Radius Fence2",
    "fenceId": "84e947d8-c38f-460e-bbc5-4b9c541952a0",
    "fenceType": "location",
    "fenceMode": "radius",
```

```

        "fenceStatus": "A",
        "fenceGeometry": "CIRCLE",
        "transitionType": "INOUT",
        "centre": {
            "gpsLat": 12.948365090565762,
            "gpsLong": 80.23313649243396
        },
        "radius": 1000.0,
        "startTime": "2025-12-08T12:10:37Z",
        "endTime": "2025-12-08T15:05:37Z",
        "isInfinite": "false",
        "timeMode": "full_day",
        "daysOfWeek": [
            "TUE",
            "MON",
            "THU"
        ],
        "createdTimeStamp": 1767077874611,
        "updatedTimeStamp": 1767077994706
    }
]

```

11.2.5 Create curfew fence

NB API Interface ID : NB-VEHICLE_TRACKING-005

This API request is used to create a curfew from the mobile application

11.2.5.1 URI

The following URI will be used for creating the curfew.

<https://<ServerIP>:<ServerPort>/jeep/fence/curfew/{vinNum}>

11.2.5.2 Invocation Method

POST

11.2.5.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

11.2.5.4 Request Body –

The request body shall contain the following parameters in JSON format:

Parameter	Type	Value Range	Description
<i>curfewName</i>	String		Name of the fence
<i>fenceStatus</i>	String		A/D status
<i>daysofWeek</i>	List		Days of the Week("MON" , "FRI" ,

			"\"SAT\" "\"SUN\" "\"TUE\" "\"WED\" "\"THU\")
startTime	String		StartTime of the Fence
endTime	String		EndTime of the Fence

11.2.5.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
curfewName	String	Name of the Fence
curfewId	String	Id of the Fence
message	String	Success/Error message

11.2.5.6 Sample request and response

POST jeep/fence/curfew/MCANJREB1MFA65412

HttpRequest:

```
{
  "curfewName": "Home",
  "fenceStatus": "A",
  "startTime": "2021-09-20T17:16:25Z",
  "endTime": "2021-09-20T22:46:25Z",
  "daysOfWeek": [
    "MON",
    "THU",
    "SAT"
  ],
}
```

HttpResponse:

201 CREATED

```
{
  "curfewName": "Home",
  "message": "Successfully created Fence",
  "curfewId": "6489d0d5-9d02-4bdc-b052-a76d0f94bb73"
}
```

400 BAD REQUEST

```
{
  "statusCode": 400,
  "message": "Malformed request syntax; Missing mandatory parameters"
}
```

11.2.6 Get curfew details for the VIN

NB API Interface ID : NB-VEHICLE_TRACKING-006

This API request is used to get the curfew details for VIN

11.2.6.1 URI

The following URI will be used to fetch curfew fence details.

<https://<ServerIP>:<serverPort>/jeep/fence/curfew/{vinNum}>

11.2.6.2 Invocation Method

GET

11.2.6.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

11.2.6. 4 Request Body

NIL

11.2.6.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>curfewName</i>	String	Name of the Fence
<i>curfewId</i>	String	Id of the Fence
<i>fenceStatus</i>	String	Status of the Fence
<i>startTime</i>	String	timeStart of the Fence
<i>endTime</i>	String	timeEnd of the Fence
<i>createdTimeStamp</i>		createdTimeStamp of the fence
<i>updatedTimeStamp</i>		updatedTimeStamp of the fence

11.2.6.6 Sample request and response**HTTP Request: GET**

/jeep/fence/curfew/MCANJREB1MFA65412

HTTP Response:

```
[
  {
    "id": "61095ba9398473d75c647ef6",
    "curfewName": "curfew : 2021-08-03T20:37:21.357",
    "curfewId": "bcbfbcfbf-50f4-47be-a8d6-21273d0ede1a",
    "fenceStatus": "A",
    "starttime": "2021-08-03T20:37:21.357Z",
    "endtime": "2021-08-04T20:37:21.357Z",
    "createdTimeStamp": 1628003241357,
    "updatedTimeStamp": 1628003241357
  }
]
```

11.2.7 Update curfew Details based on VIN and curfew Id

NB API Interface ID : NB-VEHICLE_TRACKING-007

This API request is used to update the curfew details

11.2.7.1 URI

The following URI will be used to update curfew details

<https://<ServerIP>:<ServerPort>/jeep/fence/curfew/{vinNum}/{curfewId}>

11.2.7.2 Invocation Method

PUT

11.2.7.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

11.2.7.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Type	Value Range	Description
<i>fenceStatus</i>	String	{A/D}	Status of the Fence
<i>starttime</i>	String		Start time of fence
<i>daysOfWeek</i>	List		Days of the week("MON", "FRI", "SAT", "SUN", "TUE", "WED", "THU")

endtime	String		End time of fence
---------	--------	--	-------------------

11.2.7.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
curfewName	String	Name of the Fence
curfewId	String	Id of the Fence
fenceStatus	String	Status of the Fence
message	String	Success/Error message

11.2.7.6 Sample request and response

HttpRequest: PUT /jeep/fence/curfew/MCANJREB1MFA65412/d5ce7fe9-0583-44be-b30c-4b73a9da520b

```
{
  "fenceStatus": "A",
  "startTime": "2021-09-20T17:16:25Z",
  "endTime": "2021-09-20T22:46:25Z",
  "daysOfWeek": [
    "MON",
    "THU",
    "SAT"
  ]
}
```

HttpResponse:

200 OK

```
{
  "curfewName": "Home : 2021-08-03T21:32:11.341Z",
  "message": "Successfully updated Fence",
  "curfewId": "77f9c987-3c5d-44a6-a3e1-ff90c7c00ee7",
  "fenceStatus": "A"
}
```

400 BAD REQUEST

```
{
  "statusCode": 400,
  "message": "Malformed request syntax; Missing mandatory parameters"
}
```

11.2.8 Delete curfew based on curfew Id

NB API Interface ID : NB-VEHICLE_TRACKING-008

This API request is used to delete the curfew fence.

11.2.8.1 URI

The following URI will be used to delete geo fence.

<https://<ServerIP>:<serverPort>/jeep/fence/curfew/{vinNum}/{curfewId}>

11.2.8.2 Invocation Method

DELETE

11.2.8.3 Request Header

Content-Type: application/json

11.2.8.4 Request Body

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

11.2.8.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>curfewId</i>	String	Curfew Id
<i>curfewName</i>	String	Name of the Fence
<i>Message</i>	String	Success/Error message

11.2.8.6 Sample request and response

HTTP Request: DELETE

/jeep/fence/curfew/MCANJREB1MFA65412/d5ce7fe9-0583-44be-b30c-4b73a9da520b

HTTP Response:

```
{  
  "curfewName": "Home",  
  "message": "Deleted Fence Successfully",  
  "curfewId": "83b0d932-d963-4276-a0e1-2e1b612a279e"  
}
```


12.Alert APIs

This section describes the Alert NB APIs for Mobile Application.

12.1 Alert APIs

The following table provides the list of Alert APIs:

No	API Description	Method	API Context	API Path
1	Create the Registration for fcm	POST	/jeep/pushnotification	/fcm
2	Delete the Registered fcm by mobileId	DELETE	/jeep/pushnotification	/fcm/db2df05256acd8ff
3	Get the list of all notifications	GET	/jeep/notification	/vin/{vinNum}
4	Delete a Notification	DELETE	/jeep/notification	/notificationId
5	Update Notification as Read	PUT	/jeep/notification	/notificationId

12.2 API Description

The APIs are listed, the corresponding URI, Invocation method, request and response are explained in each API description

12.2.1 Create the Registration for fcm

#NB API Interface ID : NB-ALERTS-001

This API request can be used to create the Registration for FCM.

12.2.1.1 URI

<https://<ServerIP>:<serverPort>/jeep/pushnotification/fcm>

12.2.1.2 Invocation Method

POST

12.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

12.2.1.4 Request Body

Parameter	Type	Description
<i>userName</i>	String	Mobile Number with the country code
<i>mobileId</i>	String	Unique id for the mobile
<i>fcmToken</i>	String	Fcm Token of the Notification
<i>appVersion</i>	String	appVersion of the Notification
<i>platform</i>	String	platform of the Notification

12.2.1.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>statusCode</i>	Integer	Status code of the response
<i>message</i>	String	Response Message

12.2.1.6 Sample Request and Response

HTTP Request: *POST* /jeep/pushnotification/fcm

Content-Type: application/json

```
{
  "appVersion" : "0.48",
  "fcmToken" : "cnyY_0b10qg:APA91bEkaj8hs9Vv4FDdFY0jpC8QqgNPeEim1w0-
pv4R0fKWDa9ecTHrygSmU0vJJMgsYOc_eCw175zI5itXjnq4Mrmx-
IOfK2ETOGmNbzmxbzZAFuLqreE0C8MhemUwebxBhFVNpONy",
  "mobileId" : "db2df05256acd8ff",
  "platform" : "android",
  "userName" : "918888888450"
}
```

HTTP Response: *200 OK*

```
{
  "statusCode": 200,
  "message": "Fcm Token registered to the userName 918888888450"
}
```

12.2.2 Delete FCM by MobileId

#NB API Interface ID : NB-ALERTS-002

This API request can be used to delete FCM by mobileId.

12.2.2.1 URI

The following URI will be used to delete FCM by mobileId.

<https://<ServerIP>:<serverPort>/jeep/pushnotification/fcm/{mobileId}>

12.2.2.2 Invocation Method

DELETE

12.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

12.2.2.4 Request Body

NIL

13.2.2.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
statusCode	Integer	Status code of the response
message	String	Response Message

12.2.2.6 Sample Request and Response

HTTP Request: *DELETE /jeep/pushnotification/fcm/db2df05256acd8ff*

Content-Type: application/json

HTTP Response: *200 OK*

```
{
  "statusCode": 200,
  "message": "Fcm Token deleted mobileDeviceId db2df05256acd8ff"
}
```

12.2.3 Get the List of all Notifications

NB API Interface ID : NB-ALERTS-003

This API request can be used to get the list of all Notification.

12.2.3.1 URI

<https://<ServerIP>:<ServerPort>/jeep/notification/vin/{vinNum}>

12.2.3.2 Invocation Method

GET

12.2.3.3 Request Header

Parameter	Type	Description
Authorization	String	User Token
Content-Type	String	application/json

12.2.3.4 Request Body

NIL

12.2.3.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
vinNo	String	Device Vin Num
Count	Integer	Count of the notifications
notifications	List	List of all the notification parameters
notificationId	String	notificationId of the Notification
signalTimeStamp	Integer	SignalTimeStamp of the Notification
alertName	String	Name of the Alert(Speedalert,Tow,ParkingDisturbance,curfew,geofence,Engin eldle)
alertState	String	State of the Alert

Parameter	Type	Description
Body	String	Body of the notification
Title	String	Title of the Notification
Read	String	Read/Unread state of the notification
gpsLat	String	Latitude value
gpsLong	String	Longitude

12.2.3.6 Sample Request and Response

HTTP Request: *GET /jeep/notification/vin/MCANJREB1MFA65412*

Content-Type: application/json

HTTP Response: *200 OK*

```
{
  "count": 2,
  "notifications": [
    {
      "notificationId": "48b79b3b-3e44-420c-aef2-8ce5d33d4ed5",
      "vinNo": "MCANJREB1MFA65412",
      "createdTimeStamp": 1626677223964,
      "updatedTimeStamp": 1626677223964,
      "signalTimeStamp": 1626677222585,
      "alertName": "curfew",
      "alertState": "A",
      "body": "Your vehicle is being used past <curfewName> curfew ",
      "gpsLat": "56.3109224",
      "gpsLong": "44.00 44295",
      "read": false
    },
    {
      "notificationId": "0a95a02d-3285-46c0-9789-ff29c066e735",
      "vinNo": "MCANJREB1MFA65412",
      "signalTimeStamp": 1626677222585,
      "alertName": "speedalert",
      "alertState": "A",
      "body": "Your vehicle has gone over the speed limit",
      "gpsLat": "56.3109224",
      "gpsLong": "44.0044295",
      "read": false
    }
  ]
}
```

12.2.4 To delete notifications based on id

NB API Interface ID : NB-ALERTS-004

This API request can be used to Delete a Notification.

12.2.4.1 URI

<https://<ServerIP>:<serverPort>/jeep/notification/{notificationId}>

12.2.4.2 Invocation Method*DELETE***12.2.4.3 Request Header**

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

12.2.4.4 Request Body

NIL

12.2.4.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>statusCode</i>	Integer	Status code of the response
<i>Message</i>	String	Response Message

12.2.4.6 Sample Request and Response**HTTPRequest:** *DELETE* /jeep/notification/48b79b3b-3e44-420c-aef2-8ce5d33d4ed5**HTTP Response:**200 OK

```
{
  "statusCode": 200,
  "message": "Notification with notification id 0a95a02d-3285-46c0-9789-ff29c066e735deleted successfully"
}
```

12.2.5 Update the Notification as read

NB API Interface ID : NB-ALERTS-005

This API request can be used to Update the Notification as read.

12.2.5.1 URI<https://<ServerIP>:<serverPort>/jeep/notification/{notificationId}>**12.2.5.2 Invocation Method***PUT***12.2.5.3 Request Header**

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

12.2.5.4 Request Body

NIL

12.2.5.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
-----------	------	-------------

statusCode	Integer	Status code of the response
message	String	Response Message

12.2.5.6 Sample Request and Response

HTTP Request: *PUT /jeep/notification/0a95a02d-3285-46c0-9789-ff29c066e735*

HTTP Response:*200 OK*

```
{  
    "statusCode": 200,  
    "message": "Notification made as Read Successfully"  
}
```

13. Remote Command APIs

13.1 List of remote command APIs

The following table provides the list of remote command APIs which can be utilized for Mobile app:

No	API Description	Method	API Context	API Path
1	Trigger remote command - Blinkers	POST	/jeep/commands	/vinno
2	Trigger remote command - Door lock/unlock	POST	/jeep/commands	/vinno
3	Trigger remote command - Honk	POST	/jeep/commands	/vinno
4	Get command status based on command id	GET	/jeep/commands	/device/vin/{vinNum}/command/{comma

				ndId}
5	Trigger remote command - speedalertcommand	POST	/jeep/commands	/vinno
6	Trigger remote command - userdefinedminimumtripsettingcommand	POST	/jeep/commands	/vinno
7	Remote command to check command history	GET	/jeep/commands	/audit/{vinNum}

13.2 API Description

The APIs are listed, and the corresponding URI, Invocation method, request and response are explained in each API description.

Status Code	Description
200 OK	A request is successfully received, and the request response header or data body will be sent in the response.
201 Created	The POST or PUT operation is successful.
400 Bad Request	The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, invalid request message framing, or deceptive request routing).
401 Unauthorized	Similar to 403 Forbidden, but specifically for use when authentication is required and has failed or has not yet been provided.
403 Forbidden	The request was a valid request, but the server is refusing to respond to it. 403 error semantically means "unauthorized", i.e. the user does not have the necessary permissions for the resource. If the cause cannot be disclosed, 404 Not Found is returned.
404 Not Found	The server has not found anything matching the Request-URI.
201 accepted	The request has been accepted
303 See Other	The request was received successfully, but response is available at different URI and client must fetch it using GET request.
204 No content	The response is received if no data is present

13.2.1 Trigger remote command – Blinkers

NB API Interface ID : NB-REMOTE_COMMANDS-001

This API is used to trigger command.

13.2.1.1 URI

API to post command to DONGLE

<https://<ServerIP>:<ServerPort>/jeep/commands/vinno>

13.2.1.2 Invocation Method

POST

13.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

13.2.1.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Mandatory	Type	Value Range	Description
<i>deviceVinno</i>	Yes	String		Vehicle Identifier
<i>actionType</i>	Yes	String	1–255 characters	Capability name that needs to be operated on (based on the capability name of the device type to which the device belongs) - remoteblinkeroncommand/remoteblinkeroffcommand

13.2.1.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>deviceVinno</i>	String	Vehicle Identifier
<i>actionType</i>	String	Capability name was operated on (based on the capability name of the device type to which the device belongs)
<i>Command</i>	Integer/String	Capability (supported) value
<i>commandId</i>	String	Command identifier
<i>commandURI</i>	String	URI of the command status API
<i>commandStatus</i>	String	Command status
<i>commandResponse</i>	String	Command response
<i>Comments</i>	String	Comments about the command triggered
<i>userId</i>	Integer	ID of the User operating on the device
<i>accountId</i>	Integer	Account ID to which the device belongs
<i>createdTimestamp</i>	Integer	Timestamp of when the command was triggered to the device
<i>estimatedCompletion</i>	Integer	Forecasted completion time for the command
<i>timeout</i>	Integer	Command timeout value

Parameter	Type	Description
sessionId	String	Session Identifier
commandAPIWarEntryTimestamp	long	Time at which command is received
commandMethod	String	Type of method
correlationId	String	Correlation Id of the command
timestampBeforePublishingToKafka	long	Time at which the command is send for processing

13.2.1.6 Sample Request and Response

HTTP Request: POST /jeep/commands/vinno

Blinker on command

```
{
  "deviceVinno": "MCANJREB1MFA65412",
  "actionType": "remoteblinkeroncommand"
}
```

HTTP Response:201 Created

```
{
  "deviceVinno": " MCANJREB1MFA65412",
  "comments": "Your Request with Command Id 50182602-d79a-11ef-bd87-731d82d83387 is in progress",
  "createdTimestamp": "2025-11-20T07:22:04.048Z",
  "sessionId": "eea6b471-bc60-4c9c-be41-d9406ae352d3",
  "commandAPIWarEntryTimestamp": 1737424324018,
  "commandMethod": "POST",
  "commandId": "50182602-d79a-11ef-bd87-731d82d83387",
  "userId": 0,
  "command": null,
  "actionType": "remoteblinkeroncommand",
  "accountId": "0",
  "commandStatus": "accepted",
  "commandResponse": null,
  "correlationId": "868655eh-942b-11ed-979c-216f9g4f517a",
  "timestampBeforePublishingToKafka": 1737424324048,
  "commandURI": "/cpi/jeep/commands"
}
```

Blinker off command

```
{
  "deviceVinno": "MCANJREB1MFA65412",
  "actionType": "remoteblinkeroffcommand"
}
```

HTTP Response:201 Created

```
{
```

```

"deviceVinno": "MCANJREB1MFA65412",
"comments": "Your Request with Command Id 50182602-d79a-11ef-bd87-731d82d83387 is in progress",
"createdTimestamp": "2025-11-20T07:22:04.048Z",
"sessionId": "eea6b471-bc60-4c9c-be41-d9406ae352d3",
"commandAPIWarEntryTimestamp": 1737424324018,
"commandMethod": "POST",
"commandId": "50182602-d79a-11ef-bd87-731d82d83387",
"userId": 0,
"command": null,
"actionType": "remoteblinkeroffcommand",
"accountId": "0",
"commandStatus": "accepted",
"commandResponse": null,
"correlationId": "868655eh-942b-11ed-979c-216f9g4f517a",
"timestampBeforePublishingToKafka": 1737424324048,
"commandURI": "/api/jeep/commands"
}

```

13.2.2 Trigger remote command - Remote Door Lock-Unlock Command

NB API Interface ID : NB-REMOTE_COMMANDS-002

This API is used to trigger command.

13.2.2.1 URI

API to post command to DONGLE

<https://<ServerIP>:<ServerPort>/jeep/commands/vinno>

13.2.2.2 Invocation Method

POST

13.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

13.2.2.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Type	Value Range	Description
<i>deviceVinno</i>	String		Vehicle Identifier
<i>actionType</i>	String	1–255 characters	Capability name that needs to be operated on (based on the capability name of the device type to which the device belongs) - remotelockcommand/remotedoorunlockcommand

13.2.2.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
deviceVinno	String	Vehicle Identifier
actionType	String	Capability name was operated on (based on the capability name of the device type to which the device belongs)
Command	Integer/String	Capability (supported) value
commandId	String	Command identifier
commandURI	String	URI of the command status API
commandStatus	String	Command status
commandResponse	String	Command response
Comments	String	Comments about the command triggered
userId	Integer	ID of the User operating on the device
accountId	Integer	Account ID to which the device belongs
createdTimestamp	Integer	Timestamp of when the command was triggered to the device
estimatedCompletion	Integer	Forecasted completion time for the command
timeout	Integer	Command timeout value
sessionId	String	Session Identifier
commandAPIWarEntryTimestamp	long	Time at which command is received
commandMethod	String	Type of method
correlationId	String	Correlation Id of the command
timestampBeforePublishingToKafka	long	Time at which the command is send for processing

13.2.2.6 Sample Request and Response

HTTP Request: POST /jeep/commands/vinno

- **Remote Door Lock command**

```
{
  "deviceVinno": "MCANJREB1MFA65412",
  "actionType": "remotedoorlockcommand"
}
```

HTTP Response:201 Created

```
{
```

```

"deviceVino": "MCANJREB1MFA65412",
"comments": "Your Request with Command Id f8f70b64-d79a-11ef-bd87-67722ec6813d is in progress",
"createdTimestamp": "2025-01-21T07:26:47.366Z",
"sessionId": "9ba53964-dcd3-4780-9a68-c149ec39f8e8",
"commandAPIWarEntryTimestamp": 1737424607322,
"commandMethod": "POST",
"commandId": "f8f70b64-d79a-11ef-bd87-67722ec6813d",
"userId": 0,
"command": null,
"actionType": "remotedoorlockcommand",
"accountId": "0",
"commandStatus": "accepted",
"commandResponse": null,
"correlationId": "ee5a12b3-e027-11ed-ab1d-8104634dea8d",
"timestampBeforePublishingToKafka": 1737424607366,
"commandURI": "/cpi/jeep/commands"
}

```

- **Remote Door UnLock command**

```

{
  "deviceVino": "MCANJREB1MFA65412",
  "actionType": "remotedoorunlockcommand"
}

```

HTTP Response:201 Created

```

{
  "deviceVino": "MCANJREB1MFA65412",
  "comments": "Your Request with Command Id 07b8d0c5-d79b-11ef-bd87-d38a080b4435 is in progress",
  "createdTimestamp": "2025-01-21T07:27:12.123Z",
  "sessionId": "b8a951ed-1d22-4b33-a78e-24199eba0235",
  "commandAPIWarEntryTimestamp": 1737424632096,
  "commandMethod": "POST",
  "commandId": "07b8d0c5-d79b-11ef-bd87-d38a080b4435",
  "userId": 0,
  "command": null,
  "actionType": "remotedoorunlockcommand",
  "accountId": "0",
  "commandStatus": "accepted",
  "commandResponse": null,
  "correlationId": "ff301ab3-dd09-11ed-b792-9d7b3f5f3ab2",
  "timestampBeforePublishingToKafka": 1737424632123,
  "commandURI": "/cpi/jeep/commands"
}

```

13.2.3 Trigger remote command – Honk

NB API Interface ID : NB-REMOTE_COMMANDS-003

This API is used to trigger command.

13.2.3.1 URI

API to post command to DONGLE

<https://<ServerIP>:<ServerPort>/jeep/commands/vinno>

13.2.3.2 Invocation Method

POST

13.2.3.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

13.2.3.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Mandatory	Type	Value Range	Description
<i>deviceVinno</i>	Yes	String		Vehicle Identifier
<i>actionType</i>	Yes	String	1–255 characters	Capability name that needs to be operated on (based on the capability name of the device type to which the device belongs) - remotehonkcommand

13.2.3.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>deviceVinno</i>	String	Vehicle Identifier
<i>actionType</i>	String	Capability name was operated on (based on the capability name of the device type to which the device belongs)
<i>Command</i>	Integer/String	Capability (supported) value
<i>commandId</i>	String	Command identifier
<i>commandURI</i>	String	URI of the command status API
<i>commandStatus</i>	String	Command status
<i>commandResponse</i>	String	Command response
<i>Comments</i>	String	Comments about the command triggered
<i>userId</i>	Integer	ID of the User operating on the device
<i>accountId</i>	Integer	Account ID to which the device belongs

createdTimestamp	Integer	Timestamp of when the command was triggered to the device
estimatedCompletion	Integer	Forecasted completion time for the command
timeout	Integer	Command timeout value
sessionId	String	Session Identifier
commandAPIWarEntryTimestamp	long	Time at which command is received
commandMethod	String	Type of method
correlationId	String	Correlation Id of the command
timestampBeforePublishingToKafka	long	Time at which the command is send for processing

13.2.3.6 Sample Request and Response

HTTP Request: POST /jeep/commands/vinno

Remote honk

```
{
  "deviceVinno": "MCANJREB1MFA65412",
  "actionType": "remotehonkcommand"
}
```

HTTP Response:201 Created

```
{
  "deviceVinno": "MCANJREB1MFA65412",
  "comments": "Your Request with Command Id 50182602-d79a-11ef-bd87-731d82d83387 is in progress",
  "createdTimestamp": "2025-11-20T07:22:04.048Z",
  "sessionId": "eea6b471-bc60-4c9c-be41-d9406ae352d3",
  "commandAPIWarEntryTimestamp": 1737424324018,
  "commandMethod": "POST",
  "commandId": "50182602-d79a-11ef-bd87-731d82d83387",
  "userId": 0,
  "command": null,
  "actionType": "remotehonkcommand",
  "accountId": "0",
  "commandStatus": "accepted",
  "commandResponse": null,
  "correlationId": "868655eh-942b-11ed-979c-216f9g4f517a",
  "timestampBeforePublishingToKafka": 1737424324048,
  "commandURI": "/cpi/jeep/commands"
}
```

13.2.4 Fetch Remote Commands by Command ID

NB API Interface ID : NB-REMOTE_COMMANDS-004

This API is used to fetch the remote commands.

13.2.4.1 URI

API to post notification setting

<https://<ServerIP>:<ServerPort>/jeep/commands/device/vin/{vinNum}/command/{commandId}>

13.2.4.2 Invocation Method

GET

13.2.4.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

13.2.4.4 Request Body

NIL

13.2.4.5 Response Body

Response shall consist of following after successful processing at platform level

Parameter	Type	Description
<i>deviceId</i>	Integer	Platform device ID
<i>Command</i>	Integer/String	Capability (supported) value
<i>commandId</i>	String	Command identifier
<i>commandStatus</i>	String	Command status
<i>commandResponse</i>	String	Command response
<i>Comments</i>	String	Comments about the command triggered
<i>userId</i>	Integer	ID of the User operating on the device
<i>updatedBy</i>	Integer	ID of the device account
<i>createdBy</i>	Integer	ID of the device account
<i>createdTimeStamp</i>	String	Time at which command is created
<i>correlationId</i>	String	Correlation Id of the command
<i>updatedTimestamp</i>	String	Time at which command status is updated

13.2.4.6 Sample Request and Response

HTTP Request: GET /jeep/commands/device/vin/MCANJREB1MFA65412/command/59096796-d787-11ef-923f-75e6cf94dc87

Content-Type: application/json

HTTP Response:200 OK

```
{
  "comments": "Command timed out",
  "updatedBy": 1147,
  "commandStatus": "Timed Out",
  "createdBy": 1147,
  "createdTimeStamp": "2025-01-21T05:06:19.000Z",
  "commandResponse": null,
  "correlationId": "868655eh-942b-11ed-979c-216f9g4f517a",
  "commandId": "59096796-d787-11ef-923f-75e6cf94dc87",
  "deviceId": 110291,
  "updatedAtTimestamp": "2025-01-21T05:06:49.005Z",
  "userId": 0,
  "command": "remoteBlinkercommand"
}
```

13.2.5 Trigger remote command – speedalertcommand

NB API Interface ID : NB-REMOTE_COMMANDS-005

This API is used for speedalertcommand.

13.2.5.1 URI

API to post command to DONGLE

<https://<ServerIP>:<ServerPort>/jeep/commands/vinno>

13.2.5.2 Invocation Method

POST

13.2.5.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

13.2.5.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Type	Value Range	Description
<i>deviceVinno</i>	String		Vehicle Identifier
<i>actionType</i>	String	1–255 characters	Capability name that needs to be operated on (based on the capability name of the device type to which the device belongs) - speedalertcommand
<i>speed</i>	Integer		Speed limit value

13.2.5.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
deviceVinno	String	Vehicle Identifier
actionType	String	Capability name was operated on (based on the capability name of the device type to which the device belongs)
Command	Integer/String	Capability (supported) value
commandId	String	Command identifier
commandURI	String	URI of the command status API
commandStatus	String	Command status
commandResponse	String	Command response
Comments	String	Comments about the command triggered
userId	Integer	ID of the User operating on the device
accountId	Integer	Account ID to which the device belongs
createdTimestamp	Integer	Timestamp of when the command was triggered to the device
estimatedCompletion	Integer	Forecasted completion time for the command
timeout	Integer	Command timeout value
sessionId	String	Session Identifier
commandAPIWarEntryTimestamp	long	Time at which command is received
commandMethod	String	Type of method
correlationId	String	Correlation Id of the command
timestampBeforePublishingToKafka	long	Time at which the command is send for processing

13.2.5.6 Sample Request and Response

HTTP Request: POST /jeep/commands/vinno

SpeedalertCommand

```
{
  "deviceVinno": "MCANJREB1MFA65412",
  "actionType": "speedalertcommand",
  "command": {
    "speed": 80
  },
}
```

HTTP Response:201 Created

```
{
  "deviceVinno": "MCANJREB1MFA65412",
  "comments": "Your Request with Command Id 0ea99212-cb88-11f0-8bc2-b93621f09c44 is in progress",
  "createdTimestamp": "2025-11-27T17:26:07.049Z",
  "sessionId": "1f7bec36-5a82-4523-9983-4f1c4fa74676",
  "commandAPIWarEntryTimestamp": 1764244566649,
  "commandMethod": "POST",
  "commandId": "0ea99212-cb88-11f0-8bc2-b93621f09c44",
  "userId": 0,
  "command": {
    "speed": 80
  },
  "actionType": "speedalertcommand",
  "accountId": "0",
  "commandStatus": "accepted",
  "commandResponse": null,
  "correlationId": "e08b28ea-9301-11ed-907e-63c9d81137fe",
  "timestampBeforePublishingToKafka": 1764244567049,
  "commandURI": "/cpi/jeep/commands"
}
```

13.2.6 Trigger remote command – userdefinedminimumtripsettingcommand

NB API Interface ID : NB-REMOTE_COMMANDS-006

This API is used for triggering userdefinedminimumtripsettingcommand.

13.2.6.1 URI

API to post command to DONGLE

<https://<ServerIP>:<ServerPort>/jeep/commands/vinno>

13.2.6.2 Invocation Method

POST

13.2.6.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

13.2.6.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Type	Value Range	Description
<i>deviceVinno</i>	String		Vehicle Identifier
<i>actionType</i>	String	1–255 characters	Capability name that needs to be operated on (based on the capability name of the device type to which the device belongs) -

			userdefinedminimumtripsettingcommand
distance	Integer		Distance limit value
engineoffTime	Integer		Engine off time in seconds

13.2.6.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
deviceVinno	String	Vehicle Identifier
actionType	String	Capability name was operated on (based on the capability name of the device type to which the device belongs)
Command	Integer/String	Capability (supported) value
commandId	String	Command identifier
commandURI	String	URI of the command status API
commandStatus	String	Command status
commandResponse	String	Command response
Comments	String	Comments about the command triggered
userId	Integer	ID of the User operating on the device
accountId	Integer	Account ID to which the device belongs
createdTimestamp	Integer	Timestamp of when the command was triggered to the device
estimatedCompletion	Integer	Forecasted completion time for the command
timeout	Integer	Command timeout value
sessionId	String	Session Identifier
commandAPIWarEntryTimestamp	long	Time at which command is received
commandMethod	String	Type of method
correlationId	String	Correlation Id of the command
timestampBeforePublishingToKafka	long	Time at which the command is send for processing

13.2.6.6 Sample Request and Response

HTTP Request: POST /jeep/commands/vinno

minimumtripdistance

```
{
  "deviceVinno": "MCANJREB1MFA65412",
```

```

    "actionType": " userdefinedminimumtripsettingcommand ",
    "command": "{
    "minimumTripDistance": 3,
    "engineOffTime": 5
    },
  }

```

HTTP Response:201 Created

```

{
  "deviceVino": "MCANJREB1MFA65412",
  "comments": "Your Request with Command Id 0ea99212-cb88-11f0-8bc2-b93621f09c44 is in progress",
  "createdTimestamp": "2025-11-27T17:26:07.049Z",
  "sessionId": "1f7bec36-5a82-4523-9983-4f1c4fa74676",
  "commandAPIWarEntryTimestamp": 1764244566649,
  "commandMethod": "POST",
  "commandId": "0ea99212-cb88-11f0-8bc2-b93621f09c44",
  "userId": 0,
  "command": {
    " minimumTripDistance ": 3
    "engineOffTime": 5
  },
  "actionType": " userdefinedminimumtripsettingcommand ",
  "accountId": "0",
  "commandStatus": "accepted",
  "commandResponse": null,
  "correlationId": "e08b28ea-9301-11ed-907e-63c9d81137fe",
  "timestampBeforePublishingToKafka": 1764244567049,
  "commandURI": "/cpi/jeep/commands"
}

```

13.2.7 Remote Command to check command history

NB API Interface ID : NB-REMOTE_COMMANDS-007

This API is used for getting command history

13.2.7.1 URI

<https://<ServerIP>:<ServerPort>/jeep/commands/audit/{vinNum}>

13.2.7.2 Invocation Method

GET

13.2.7.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	User Token
<i>Content-Type</i>	String	application/json

13.2.4.4 Request Body

NIL

13.2.7.5 Response Body

Response shall consist List of all the Commands parameters of the following response body in JSON format:

Parameter	Type	Description
commandId	String	Command identifier
command	String	Capability (supported) value
deviceId	List	Platform device ID
comments	String	Comments about the command triggered
commandStatus	Integer	Command status
createdBy	Int	ID of the device account
createdTimeStamp	Date	Timestamp of when the command was triggered to the device
updatedBy	Int	ID of the device account
updatedTimestamp	Date	Time at which command status is updated
userId	Int	ID of the User operating on the device
correlationId	String	Correlation Id of the command

13.2.7.6 Sample Request and Response

HTTP Request: *GET /api/jeep/commands/audit/T123ZTZT867657777*

Content-Type: application/json

HTTP Response: *200 OK*

```
[
  {
    "comments": "Command Process success",
    "updatedBy": 65,
    "commandStatus": "Success",
    "createdBy": 65,
    "createdTimeStamp": "2022-08-30 07:50:38.000",
    "commandResponse": {
```

```
        "returnCode": "succeeded",
        "errorCode": 0,
        "commandRspPayload": "CUSTOMER"
    },
    "correlationId": "45ee3134-8c28-4735-b208-c1g8bae52534",
    "commandId": "56430450-280a-11ed-a0bb-5d4dd0695191",
    "deviceId": 113916,
    "updatedTimestamp": "2022-08-30 07:50:38.457",
    "userId": 0,
    "command": "remoteblinkeroffcommand"
},
{
    "comments": "Command Process success",
    "updatedBy": 65,
    "commandStatus": "Success",
    "createdBy": 65,
    "createdTimeStamp": "2022-08-30 07:50:27.000",
    "commandResponse": {
        "returnCode": "succeeded",
        "errorCode": 0,
        "commandRspPayload": "AUTHORIZED"
    },
    "correlationId": "45ee3134-8c28-4735-b208-c1g8bae52534",
    "commandId": "4fd77e20-280a-11ed-a0bb-5d4dd0695191",
    "deviceId": 113916,
    "updatedTimestamp": "2022-08-30 07:50:28.126",
    "userId": 0,
    "command": "remotehonkcommand"
}
]
```

14. DMS APIs

14.1 List of DMS APIs

The following table provides the list of DMS APIs which can be utilized for Mobile application:

No	API Description	Method	API Context	API Path
1	Customer Onboarding API	POST	/jeep/dms	/customers
2	Dongle replacement/swap API	PUT	/jeep/dms	/swap
3	Service Termination API	PUT	/jeep/dms	/servicesubscription
4	IMEI Validation	POST	/jeep	/imei/validation

14.2 API Description

The APIs are listed, and the corresponding URI, Invocation method, request and response are explained in each API description.

14.2.1 Customer Onboarding API

NB API Interface ID : NB-DMS-001

This API is used to trigger customer creation.

14.2.1.1 URI

API to post customer creation details

<https://<ServerIP>:<ServerPort>/jeep/dms/customers>

14.2.1.2 Invocation Method

POST

14.2.1.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	Application Token
<i>Content-Type</i>	String	application/json

14.2.1.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Type	Description
<i>vehicleId</i>	String	Vehicle Identifier
<i>imei</i>	String	imei number for the device
<i>vehicleType</i>	String	Vehicle Type information(ICE)
<i>customerID</i>	String	Unique customer identification number (customer ID can have string length of 12 characters and should be of this format. 1 to 3 char - IND – Country Code,4 th character: J for Jeep, 5th character: P for Personal, 6th and 7th character are year in yy format 8th-12th character are the serial number. Example: INDJP2601651 Kindly note that CVIP expects for unique customer id for each customer
<i>customerType</i>	String	Type of customer <Personal>
<i>customerDetails</i>	Object	Details of customer
<i>serviceActivation</i>	Object	Service details

Customer Details Object

Parameter	Type	Description
<i>mobileNumber</i>	String	Mobile Number of the customer
<i>countryCode</i>	String	Country code of mobile Number

Service Activation Object

Parameter	Type	Description
<i>serviceId</i>	String	Unique service plan id. ServiceId can have String length of 16 characters. Ex:

		INDJP26016514567 Format : Customer Id + last 4 digits of VIN
serviceTier	String	Subscription plan selected by the customer <Gold/Silver/Platinum>
startDateTime	String (yyyy-MM-dd HH:mm:ss)	Subscription plan start time. String should be in the dateformat mentioned in type. (IST time Format)
endDateTime	String (yyyy-MM-dd HH:mm:ss)	Subscription plan end time. String should be in the dateformat mentioned in type. (IST Time Format)

14.2.1.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
statusCode	Integer	Success/failure status code
message	String	Response message

14.2.1.6 Sample Request and Response

HTTP Request: POST /jeep/dms/customers

```
{
  "vehicleId": "MCANJREB1MFA65412",
  "imei": "356741424242424",
  "vehicleType": "ICE",
  "customerID": "INDJP2601651",
  "customerType": "Personal",
  "customerDetails": {
    "mobileNumber": "9944111823",
    "countryCode": "+91",
  },
  "serviceActivation": {
    "serviceId": "INDJP26016514567",
    "serviceTier": "Gold",
    "startDateTime": "2023-02-22T18:00:00Z",
    "endDateTime": "2025-02-22T18:00:00Z"
  }
}
```

HTTP Response:200 OK

```
{
  "statusCode": 200,
  "message": "customer created successfully."
}
```

400 BAD REQUEST (Failure)

```
{
  "statusCode": 400,
  "message": "customer already exists with customer id INDJP2601651."
}
```

14.2.2 Dongle replacement/swap API

NB API Interface ID : NB-DMS-002

This API is used to swap Dongle in CVIP based on Swap Type.

14.2.2.1 URI

API to post Dongle swap details

<https://<ServerIP>:<ServerPort>/jeep/dms/swap>

14.2.2.2 Invocation Method

PUT

14.2.2.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	Application Token
<i>Content-Type</i>	String	application/json

14.2.2.4 Request Body

The request body shall contain the following parameters in JSON format:

Parameter	Type	Description
<i>vehicleId</i>	String	Vehicle identification number
<i>swapType</i>	String	Swap type information <Dongle>
<i>existingSerialNo</i>	String	Existing Serial number of Dongle.
<i>newSerialNo</i>	String	New Serial Number of Dongle or Battery depending on swap Type.

14.2.2.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
statusCode	Integer	Success/failure status code
message	String	Response message

14.2.2.6 Sample Request and Response

HTTP Request: PUT /jeep/dms/swap

```
{
  "vehicleId": "MCANJREB1MFA65412",
  "swapType ": "Dongle",
  "existingSerialNo": "A234ZTZT00000000161",
  "newSerialNo": "A234ZTZT00000000162"
}
```

HTTP Response:200 OK

```
200 OK
{
  "statusCode": 200,
  "message": "Swap Details updated successfully for vin MCANJREB1MFA65412"
}
400 BAD REQUEST (FAILURE)
{
  "statusCode": 400,
  "message": "Dongle: A23ZTZT00008994 Not mapped to vehicle"
}
400 BAD REQUEST (FAILURE)
{
  "statusCode": 400,
  "message": "Dongle: A0123456789T is already mapped to vehicle"
}
```

14.2.3 API to update the service packages (Service Termination)

NB API Interface ID : NB-DMS-003

This API request is used to update the service subscriptions of user as Terminated.

14.2.3.1 URI

API to update service details for termination

<https://<ServerIP>:<ServerPort>/dms/servicesubscription>

14.2.3.2 Invocation Method

PUT

14.2.3.3 Request Header

Parameter	Type	Description
<i>Authorization</i>	String	Application Token
<i>Content-Type</i>	String	application/json

14.2.3.4 Request Body

The following request parameters shall be used to invoke the API.

Parameter	Type	Description
<i>vehicleId</i>	String	Vehicle identification number
<i>serviceId</i>	String	Unique service plan id
<i>serviceRequestType</i>	String	Type should be Termination

14.2.3.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>statusCode</i>	Integer	Success/failure status code
<i>message</i>	String	Response message

14.2.3.6 Sample Request and Response

HTTP Request

PUT /dms/servicesubscription

Request Type: Termination

```
{  
  "vehicleId": "MCANJREB1MFA65412",  
  "serviceId": "IYSG86",  
  "serviceRequestType": "termination"  
}
```

Http Response Body

200 Ok:

```
{
  "statusCode": 200,
  "message": "Service details updated for serviceId IYSG86"
}

400 BAD REQUEST (FAILURE):
{
  "statusCode": 400,
  "message": "Invalid serviceId"
}
```

14.2.4 IMEI Validation

NB API Interface ID : NB-DMS -004

This API request can be used for IMEI validation.

14.2.4.1 URI

<https://<ServerIP>:<port> /jeep/imei/validation>

14.2.4.2 Invocation Method

POST

14.2.4.3 Request Header

Content-Type: application/json

Parameter	Type	Description
<i>Authorization</i>	string	User Token

14.2.4.4 Request Body

Parameter	Type	Description
<i>vinNum</i>	string	Vehicle vin number
<i>imei</i>	string	Device IMEI number

14.2.4.5 Response Body

Response shall consist of the following response body in JSON format:

Parameter	Type	Description
<i>statusCode</i>	String	Success/Failure status code
<i>message</i>	String	Imei validation is successful

14.2.4.6 Sample Request and Response

HTTP Request: POST [/jeep/imei/validation](https://<ServerIP>:<port> /jeep/imei/validation)

Content-Type: application/json

```
{
  "vinNum": "Z234ZTZT000000096"
  "imei": "356741396767554"
}
```

HTTP Response:*200 OK*

```
{  
  "statusCode" : 200,  
  "message" : "Imei validation is successful"  
}
```