

# INSURANCE POLICY MANAGEMENT SYSTEM

## 1. Features to Implement

1. Add Policy – Allows users to add a new insurance policy (PolicyID, HolderName, PolicyType, Premium, ExpiryDate).
2. View Policies – Displays all insurance policies.
3. Update Policy – Provides an interface to modify policy details.
4. Delete Policy – Allows users to remove a policy record.  
Search Policy (Optional) – Enables searching by holder name or policy type.

## 2. Project Folder Structure

Folder	Contents
src/com.insurance.dao/	PolicyDAO.java, PolicyDAOImpl.java
src/com.insurance.model/	Policy.java
src/com.insurance.servlet/	AddPolicyServlet.java, ViewPolicyServlet.java, UpdatePolicyServlet.java, DeletePolicyServlet.java
src/com.insurance.util/	DBConnection.java
WebContent/view/	add_policy.jsp, view_policies.jsp, update_policy.jsp, index.jsp
WebContent/css/	styles.css

## 3. Database Schema

Column Name	Data Type	Constraints
policyid	INT	PRIMARY KEY, AUTO_INCREMENT
holdername	VARCHAR(100)	NOT NULL
policytype	VARCHAR(50)	NOT NULL
premium	DOUBLE	NOT NULL
expirydate	DATE	NOT NULL

### CODE:

#### PACKAGES FILES

#### Insurance Policy Management System:

##### com.insurance.dao:

##### Insurance.DAO.java:

```
package com.insurance.servlet;

import jakarta.servlet.ServletException;
import jakarta.servlet.annotation.WebServlet;
import jakarta.servlet.http.*;
import java.io.IOException;
import com.insurance.dao.PolicyDAOImpl;
@WebServlet("/deletePolicy")
public class DeletePolicyServlet extends HttpServlet {
    protected void doGet(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        int id = Integer.parseInt(request.getParameter("id"));
```

```

        new PolicyDAOImpl().deletePolicy(id);
        response.sendRedirect(request.getContextPath() + "/viewPolicy");
    }
}

```

### InsuranceDAOImpl.java:

```

package com.insurance.dao;
import java.sql.*;
import java.util.*;
import com.insurance.model.Policy;
import com.insurance.util.DBConnection;
public class PolicyDAOImpl implements PolicyDAO {
    @Override
    public boolean addPolicy(Policy policy) {
        String sql = "INSERT INTO policy(holdername, policytype, premium, expirydate)
VALUES(?,?,?,?)";
        try (Connection con = DBConnection.getConnection();
            PreparedStatement ps = con.prepareStatement(sql)) {
            ps.setString(1, policy.getHolderName());
            ps.setString(2, policy.getPolicyType());
            ps.setDouble(3, policy.getPremium());
            ps.setDate(4, policy.getExpiryDate());
            return ps.executeUpdate() > 0;
        } catch (Exception e) {
            e.printStackTrace();
        }
        return false;
    }
    @Override
    public List<Policy> getAllPolicies() {
        List<Policy> list = new ArrayList<>();
        try (Connection con = DBConnection.getConnection();
            PreparedStatement ps = con.prepareStatement("SELECT * FROM policy");
            ResultSet rs = ps.executeQuery()) {

            while (rs.next()) {
                Policy p = new Policy();
                p.setPolicyId(rs.getInt("policyid"));
                p.setHolderName(rs.getString("holdername"));
                p.setPolicyType(rs.getString("policytype"));
                p.setPremium(rs.getDouble("premium"));
                p.setExpiryDate(rs.getDate("expirydate"));
                list.add(p);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
        return list;
    }
    @Override
    public boolean updatePolicy(Policy policy) {
        String sql = "UPDATE policy SET holdername=?, policytype=?, premium=?, expirydate=?

```

```

WHERE policyid=?";
    try (Connection con = DBConnection.getConnection();
        PreparedStatement ps = con.prepareStatement(sql)) {
        ps.setString(1, policy.getHolderName());
        ps.setString(2, policy.getPolicyType());
        ps.setDouble(3, policy.getPremium());
        ps.setDate(4, policy.getExpiryDate());
        ps.setInt(5, policy.getPolicyId());
        return ps.executeUpdate() > 0;
    } catch (Exception e) {
        e.printStackTrace();
    }
    return false;
}

@Override
public boolean deletePolicy(int policyId) {
    try (Connection con = DBConnection.getConnection();
        PreparedStatement ps = con.prepareStatement("DELETE FROM policy WHERE
policyid=?")) {
        ps.setInt(1, policyId);
        return ps.executeUpdate() > 0;
    } catch (Exception e) {
        e.printStackTrace();
    }
    return false;
}

@Override
public Policy getPolicyById(int policyId) {
    Policy p = null;
    try (Connection con = DBConnection.getConnection();
        PreparedStatement ps = con.prepareStatement("SELECT * FROM policy WHERE
policyid=?")) {
        ps.setInt(1, policyId);
        ResultSet rs = ps.executeQuery();
        if (rs.next()) {
            p = new Policy();
            p.setPolicyId(rs.getInt("policyid"));
            p.setHolderName(rs.getString("holdername"));
            p.setPolicyType(rs.getString("policytype"));
            p.setPremium(rs.getDouble("premium"));
            p.setExpiryDate(rs.getDate("expirydate"));
        }
    } catch (Exception e) {
        e.printStackTrace();
    }
    return p;
}
}

```

## **com.insurance.model:**

### **Policy.java:**

```
package com.insurance.model;
import java.sql.Date;
public class Policy {
    private int policyId;
    private String holderName;
    private String policyType;
    private double premium;
    private Date expiryDate;
    public Policy() {}
    public Policy(String holderName, String policyType, double premium, Date expiryDate) {
        this.holderName = holderName;
        this.policyType = policyType;
        this.premium = premium;
        this.expiryDate = expiryDate;
    }
    public int getPolicyId() { return policyId; }
    public void setPolicyId(int policyId) { this.policyId = policyId; }
    public String getHolderName() { return holderName; }
    public void setHolderName(String holderName) { this.holderName = holderName; }
    public String getPolicyType() { return policyType; }
    public void setPolicyType(String policyType) { this.policyType = policyType; }
    public double getPremium() { return premium; }
    public void setPremium(double premium) { this.premium = premium; }
    public Date getExpiryDate() { return expiryDate; }
    public void setExpiryDate(Date expiryDate) { this.expiryDate = expiryDate; }
}
```

## **com.insurance.servlet:**

### **AddPolicyServlet.java:**

```
package com.insurance.servlet;
import jakarta.servlet.ServletException;
import jakarta.servlet.annotation.WebServlet;
import jakarta.servlet.http.*;
import java.io.IOException;
import java.sql.Date;
import com.insurance.dao.PolicyDAOImpl;
import com.insurance.model.Policy;
@WebServlet("/addPolicy")
public class AddPolicyServlet extends HttpServlet {
    protected void doPost(HttpServletRequest req, HttpServletResponse res) throws IOException {
        String holderName = req.getParameter("holderName");
        String policyType = req.getParameter("policyType");
        double premium = Double.parseDouble(req.getParameter("premium"));
        Date expiryDate = Date.valueOf(req.getParameter("expiryDate"));
        Policy policy = new Policy(holderName, policyType, premium, expiryDate);
        PolicyDAO dao = new PolicyDAOImpl();
    }
}
```

```

        dao.addPolicy(policy);
        res.sendRedirect("viewPolicies");
    }
}

```

### DeletePolicyServlet.java:

```

package com.insurance.servlet;
import jakarta.servlet.ServletException;
import jakarta.servlet.annotation.WebServlet;
import jakarta.servlet.http.*;
import java.io.IOException;
import com.insurance.dao.PolicyDAOImpl;
@WebServlet("/deletePolicy")
public class DeletePolicyServlet extends HttpServlet {
    protected void doGet(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        int id = Integer.parseInt(request.getParameter("id"));
        new PolicyDAOImpl().deletePolicy(id);
        response.sendRedirect(request.getContextPath() + "/viewPolicy");
    }
}

```

### UpdatePolicyServlet.java:

```

package com.insurance.servlet;
import com.insurance.dao.PolicyDAO;
import com.insurance.dao.PolicyDAOImpl;
import com.insurance.model.Policy;
import jakarta.servlet.ServletException;
import jakarta.servlet.annotation.WebServlet;
import jakarta.servlet.http.HttpServlet;
import jakarta.servlet.http.HttpServletRequest;
import jakarta.servlet.http.HttpServletResponse;
import java.io.IOException;
import java.sql.Date;
@WebServlet("/updatePolicy")
public class UpdatePolicyServlet extends HttpServlet {
    protected void doPost(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        int policyId = Integer.parseInt(request.getParameter("policyid"));
        String holderName = request.getParameter("holdername");
        String policyType = request.getParameter("policytype");
        double premium = Double.parseDouble(request.getParameter("premium"));
        Date expiryDate = Date.valueOf(request.getParameter("expirydate"));
        Policy policy = new Policy();
        policy.setPolicyId(policyId);
        policy.setHolderName(holderName);
        policy.setPolicyType(policyType);
        policy.setPremium(premium);
        policy.setExpiryDate(expiryDate);
        new PolicyDAOImpl().updatePolicy(policy);
    }
}

```

```
        response.sendRedirect(request.getContextPath() + "/viewPolicy");
    }
}
```

#### **ViewPolicyServlet.java:**

```
package com.insurance.servlet;

import jakarta.servlet.*;
import jakarta.servlet.annotation.WebServlet;
import jakarta.servlet.http.*;
import java.io.IOException;
import java.util.List;
import com.insurance.dao.PolicyDAOImpl;
import com.insurance.model.Policy;

@WebServlet("/viewPolicy")

public class ViewPolicyServlet extends HttpServlet {

    protected void doGet(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {

        List<Policy> list = new PolicyDAOImpl().getAllPolicies();
        request.setAttribute("policies", list);

        RequestDispatcher rd = request.getRequestDispatcher("view/view_policies.jsp");
        rd.forward(request, response);

    }

}
```

#### **com.school.util:**

#### **DBConnection.java:**

```
package com.insurance.util;

import java.sql.Connection;
import java.sql.DriverManager;

public class DBConnection {

    private static final String URL = "jdbc:mysql://localhost:3306/insurance_db";

    private static final String USER = "root";

    private static final String PASSWORD = "mysql@123";

}
```

```
public static Connection getConnection() {  
    Connection con = null;  
    try {  
        Class.forName("com.mysql.cj.jdbc.Driver");  
        con = DriverManager.getConnection(URL, USER, PASSWORD);  
    } catch (Exception e) {  
        e.printStackTrace();  
    }  
    return con;  
}  
}
```

### **JSP Files:**

#### **index.jsp:**

```
<html>  
  
<head>  
  
    <title>Insurance Policy Management</title>  
  
</head>  
  
<body>  
  
    <h2>Insurance Policy Management</h2>  
  
    <a href="add_policy.jsp">Add Policy</a><br><br>  
    <a href=" ../viewPolicy">View Policies</a>  
  
</body>  
  
</html>
```

#### **add\_policy.jsp:**

```
<html>  
  
<head>  
  
    <title>Add Policy</title>  
  
</head>  
  
<body>
```

```
<h2>Add Policy</h2>
```

```
<form action="<%=request.getContextPath()%>/addPolicy" method="post">
```

```
    Holder Name: <input type="text" name="holdername" required><br><br>
```

```
    Policy Type: <input type="text" name="policytype" required><br><br>
```

```
    Premium: <input type="number" name="premium" required><br><br>
```

```
    Expiry Date: <input type="date" name="expirydate" required><br><br>
```

```
    <input type="submit" value="Add Policy">
```

```
</form>
```

```
</body>
```

```
</html>
```

**update\_student.jsp:**

```
<%@ page import="com.insurance.model.Policy" %>
```

```
<%
```

```
    Policy p = (Policy) request.getAttribute("policy");
```

```
    if (p == null) {
```

```
        out.println("<h3>Policy not found!</h3>");
```

```
        return;
```

```
    }
```

```
%>
```

```
<html>
```

```
<head>
```

```
    <title>Update Policy</title>
```

```
</head>
```

```
<body>
```

```
<h2>Update Insurance Policy</h2>
```

```
<form action="#{pageContext.request.contextPath}/updatePolicy" method="post">
```

```
    <input type="hidden" name="policyid" value="<%= p.getPolicyId() %>">
```



Holder Name:

```
<input type="text" name="holdername" value="<%= p.getHolderName() %>" required>
```

```
<br><br>
```

Policy Type:

```
<input type="text" name="policytype" value="<%= p.getPolicyType() %>" required>
```

```
<br><br>
```

Premium:

```
<input type="number" name="premium" value="<%= p.getPremium() %>" required>
```

```
<br><br>
```

Expiry Date:

```
<input type="date" name="expirydate" value="<%= p.getExpiryDate() %>" required>
```

```
<br><br>
```

```
<input type="submit" value="Update Policy">
```

```
</form>
```

```
<br>
```

```
<a href="$ {pageContext.request.contextPath} /viewPolicies">
```

Back to Policy List

```
</a>
```

```
</body>
```

```
</html>
```

#### **view\_student.jsp:**

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
```

```
pageEncoding="UTF-8"%>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>Insert title here</title>
```

```

</head>

<body>

<%@ page import="java.util.*,com.insurance.model.Policy" %>

<h2>Policy List</h2>

<a href="<%=request.getContextPath()%>/add_policy.jsp">Add Policy</a><br><br>

<table border="1">

<tr>

<th>ID</th>

<th>Holder Name</th>

<th>Policy Type</th>

<th>Premium</th>

<th>Expiry Date</th>

<th>Action</th>

</tr>

<%

List<Policy> list = (List<Policy>) request.getAttribute("policies");

for (Policy p : list) {

%>

<tr>

<td><%= p.getPolicyId() %></td>

<td><%= p.getHolderName() %></td>

<td><%= p.getPolicyType() %></td>

<td><%= p.getPremium() %></td>

<td><%= p.getExpiryDate() %></td>

<td>

<a href="<%=pageContext.request.contextPath%>/editPolicy?id=<%=p.id%>">

Edit /

</a>

```

```

        <a href="<%=request.getContextPath()%/>deletePolicy?id=<%= p.getPolicyId()
%>">Delete</a>

    </td>

</tr>

<% } %>

</table>

</body>

</html>

```

#### delete\_student.jsp:

```

<%

    String id = request.getParameter("id");

%>

<html>

<head>

    <title>Delete Policy</title>

</head>

<body>

<h2>Delete Policy Confirmation</h2>

<p>Are you sure you want to delete Policy ID: <b><%= id %></b>?</p>

<a href=" ../deletePolicy?id=<%= id %>">

    <button>Yes, Delete</button>

</a>

<a href=" ../viewPolicies">

    <button>No, Cancel</button>

</a>

</body>

</html>

```

HOME PAGE:

# Insurance Policy Management

[Add Policy](#) | [View Policies](#)

ADD POLICY PAGE:

## Add Policy

Holder Name:

John Doe

Policy Type:

Health

Premium:

1200

Expiry Date:

2024-12-31

Add Policy

UPDATE POLICY PAGE:

Update Policy

Holder Name:

Alice Smith

Policy Type:

Vehicle

Premium:

980

Expiry Date:

2027-12-31

Update Policy

POLICY PAGE AFTER UPDATE:

Policy List

ID	Name	Type	Premium	Expiry	Action
1	John Doe	Health	1200	2024-12-31	<a href="#">Delete</a>
2	Alice Smith	Vehicle	980	2025-06-30	<a href="#">Delete</a>

[Add New](#)

POLICY PAGE AFTER DELETE:

Policy List

ID	Name	Type	Premium	Expiry	Action
					<a href="#">Add New</a>

[Add New](#)