Clear

/tmp/BZbFgwQ0li.o
14

```
gcc /tmp/BZbFgwQ0li.c -lm
/tmp/BZbFgwQ0li.c: In function 'main':
/tmp/BZbFgwQ0li.c:3:15: warning: initialization of 'const int *' from 'int' makes pointer
    from integer without a cast [-Wint-conversion]
    3 | int const * p=5;
      |               ^
/tmp/BZbFgwQ0li.c:4:1: warning: implicit declaration of function 'printf' [-Wimplicit
    -function-declaration]
    4 | printf("%d",++(*p));
      | ^~~~~~
/tmp/BZbFgwQ0li.c:1:1: note: include '<stdio.h>' or provide a declaration of 'printf'
  +++ |+#include <stdio.h>
    1 | void main()
/tmp/BZbFgwQ0li.c:4:1: warning: incompatible implicit declaration of built-in function
    'printf' [-Wbuiltin-declaration-mismatch]
    4 | printf("%d",++(*p));
      | ^~~~~~
/tmp/BZbFgwQ0li.c:4:1: note: include '<stdio.h>' or provide a declaration of 'printf'
/tmp/BZbFgwQ0li.c:4:13: error: increment of read-only location '*p'
    4 | printf("%d",++(*p));
      |             ^~
```

Output

Clear

/tmp/BZbFgwQ0li.o
Hello World

Output

Clear

/tmp/FE4Pj9Q6t4.o

Enter the value of n: 5
```
    1
   12
  123
 1234
12345
```

Output

Clear

```
/tmp/FE4Pj9Q6t4.o
Enter the number of elements in the array: 3
Enter the elements of the array:
1
2
3
Enter the element to search: 4
-1
```

/tmp/FE4Pj9Q6t4.o

umar

```
            |                ^
9 1

...Program finished with exit code 3
Press ENTER to exit console.
```

```
/tmp/BZbFgwQ0li.o
-2.333333
```

```
/tmp/BZbFgwQ0li.o
2  2  2  2  2  2  3  4  6  5
```

Clear

/tmp/FE4Pj9Q6t4.o
64