

DAT405 Assignment 4 – Group 53

Venkata Sai Dinesh Uddagiri - (17 hrs)

Madumitha Venkatesan - (17 hrs)

November 29, 2022

Problem 1

1. Note that the email files contain a lot of extra information, besides the actual message. Ignore that for now and run on the entire text. Further down (in the higher-grade part), you will be asked to filter out the headers and footers.
2. We don't want to train and test on the same data. Split the spam and the ham datasets in a training set and a test set. ('hamtrain', 'spamtrain', 'hamtest', and 'spamtest') [?].

```
# Functions that write the mail content and type to data frame
def readFileContent(path, type):
    rows=[]
    for file_name in os.listdir(path):
        file = os.path.join(path, file_name)
        if os.path.isfile(file):
            with open(file, encoding='latin-1' ) as file:
                rows.append({'message': file.read(), 'type': type})
    return pd.DataFrame(rows)

# read mail and its classification in to data frame(classification Ham=0 & Spam =1)
email_easy_ham_df = readFileContent('./20021010_easy_ham/easy_ham/', 0)
email_hard_ham_df = readFileContent('./20021010_hard_ham/hard_ham/', 0)
email_spam_df = readFileContent('./20021010_spam/spam/', 1)

#Splitting data in to test and train sets
easy_hamtrain,easy_hamtest=train_test_split(email_easy_ham_df, test_size =0.3 ,
    random_state =4)
hard_hamtrain,hard_hamtest=train_test_split(email_hard_ham_df, test_size =0.3 ,
    random_state =4)
hamtrain=pd.concat([easy_hamtrain,hard_hamtrain])
hamtest= pd.concat([easy_hamtest,hard_hamtest])

spamtrain, spamtest= train_test_split(email_spam_df, test_size =0.3 , random_state =4)
```

Listing 1: read mail and its classification in to data frame and Splitting the spam and the ham datasets in a training set and a test set.

Problem 2

1. Uses four datasets ('hamtrain', 'spamtrain', 'hamtest', and 'spamtest')
2. Trains a Naïve Bayes classifier (e.g. Sklearn) on 'hamtrain' and 'spamtrain', that classifies the test sets and reports True Positive and False Negative rates on the 'hamtest' and 'spamtest' datasets. You can use 'CountVectorizer' to transform the email texts into vectors.

Please note that there are different types of Naïve Bayes Classifier in SKlearn ([Documentation here](https://scikit-learn.org/stable/modules/naive_bayes.html)).

Test two of these classifiers that are well suited for this problem

- Multinomial Naive Bayes
- Bernoulli Naive Bayes.

```
def naive_bayes(x_train, x_test, y_train, y_test, vectorizer=None):
    #create a Count Vectorizer and fit it to the training set of data.
    if vectorizer==None:
        vectorizer = CountVectorizer()
        vectorizer.fit(x_train)
        x_train_vec = vectorizer.transform(x_train)
        x_test_vec = vectorizer.transform(x_test)

    fig, ((ax1, ax2)) = plt.subplots(1, 2,figsize=(10,10))

    #Train the Multinomial Naive Bayes model with train sets
    mnb = MultinomialNB().fit(x_train_vec, y_train)
    #Predict the values with test sets
    mnb_predict = mnb.predict(x_test_vec)
    tp_mnb, fp_mnb, fn_mnb, tn_mnb = confusion_matrix(y_test,mnb_predict).ravel()
    plot_confusion_matrix(mnb, x_test_vec, y_test, ax=ax1, colorbar=False, normalize='
    true', cmap = 'OrRd')

    #Train the Bernoulli Naive Bayes model with train sets
    bnb = BernoulliNB().fit(x_train_vec, y_train)
    #Predict the values with test sets
    bnb_predict = bnb.predict(x_test_vec)
    tp_bnb, fp_bnb, fn_bnb, tn_bnb = confusion_matrix(y_test,bnb_predict).ravel()
    plot_confusion_matrix(bnb, x_test_vec, y_test, ax=ax2, colorbar=False, normalize='
    true', cmap = 'OrRd')

    # Declaring labels and title for each subplot
    ax1.set_xlabel('Predicted type of email\n ham=0 & spam=1')
    ax1.set_ylabel('Actual type of email\n ham=0 & spam=1')
    ax1.set_title('Multinomial Naive Bayes\n'+str(metrics.
    accuracy_score(y_test, mnb_predict)*100)+'\n'+str('tp: '+str((tp_mnb/(tp_mnb+fp_mnb))
    *100)+ ', fn: '+ str((fn_mnb/(tn_mnb+fn_mnb))*100), size=10)
    ax2.set_xlabel('Predicted type of email\n ham=0 & spam=1')
    ax2.set_ylabel('Actual type of email\n ham=0 & spam=1')
    ax2.set_title('Bernoulli Naive Bayes\n'+str(metrics.
    accuracy_score(y_test, bnb_predict)*100)+'\n'+str('tp: '+str((tp_bnb/(tp_bnb+fp_bnb))
    *100)+ ', fn: '+ str((fn_bnb/(tn_bnb+fn_bnb))*100), size=10)
    plt.subplots_adjust(wspace=0.3)
    plt.show()

    print("Multinomial naive Bayes classifier, Accuracy score:", metrics.
    accuracy_score(y_test, mnb_predict)*100)
    print("Multinomial naive Bayes True Positive rate:", str((tp_mnb/(tp_mnb+fp_mnb))
    *100))
    print("Multinomial naive Bayes False Negative rate:", str((fn_mnb/(tn_mnb+fn_mnb))
    *100))
```

```

print("Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb",tp_mnb, fp_mnb,
fn_mnb, tn_mnb)

print("Bernoulli naive Bayes classifier, Accuracy score:", metrics.accuracy_score(
y_test, bnb_predict)*100)
print("Bernoulli naive Bayes True Positive rate:", str((tp_bnb/(tp_bnb+fp_bnb))
*100))
print("Bernoulli naive Bayes False Negative rate:", str((fn_bnb/(tn_bnb+fn_bnb))
*100))
print("Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb",tp_bnb, fp_bnb,
fn_bnb, tn_bnb)

#Concatinating hamtrain & spamtrain
train_df=pd.concat([hamtrain,spamtrain])
#Concatinating hamtest & spamtest
test_df=pd.concat([hamtest,spamtest])
#Assigning data to the variables that will be used to develop the model
x_train = train_df['message']
y_train = train_df['type']
x_test = test_df['message']
y_test = test_df['type']
naive_bayes(x_train, x_test, y_train, y_test)

```

Listing 2: Training and Testing Multinomial Naive Bayes model and Bernoulli Naive Bayes.




Figure 1: Test results of Multinomial Naive Bayes model and Bernoulli Naive Bayes using confusion matrix

The multinomial classifier takes into account the frequency with which a feature (in our data, the word) occurs, whereas the Bernoulli classifier just takes into account whether the feature (word) occurs or not. In Bernoulli classifier, when more than one element is sent into the classifier during fitting, the value is immediately transformed to 1, indicating that the term appears in the text without taking frequency into account. Bernoulli classifier is used when features are binary.

From the observation of above confusion matrices, True positive rate, False negative rate and accuracy scores of Multinomial Naive Bayes and Bernoulli Naive Bayes models. We can say that Multinomial Naive Bayes performed well when compared to Bernoulli Naive Bayes for the given emails data. In the two models Ham data has been classified with more accuracy with only little variation. But the Spam mails are classified well in the Multinomial Naive Bayes, whereas in Bernoulli Naive Bayes 77 percent of the spam mails are classified as Ham mails which will impact the user very badly. When we consider total accuracy of the model, the multinomial model classifies data with more accuracy with 3.5 percent of mails, predicted wrong (false negative and false positive). False negative in our problem means mail is spam but predicted as Ham (If user doesn't recognise mail as spam, then user will be at risk), False positive means Ham but predicted as spam (If mail has some important data but recognised as spam, then user might miss some important data).

From the above differences and observation, we can say that classification of the email based on frequency as feature has determined type of mail more accurately. Which means for email classification, Multinomial Naive Bayes model is best suited.

Problem 3

Run your program on
-Spam versus easy-ham
-Spam versus hard-ham.

By reading the question it looks like we need to run Spam versus easy-ham and Spam versus hard-ham data on program created in question2(trained with easy ham, hard ham and spam data) but it was not clearly stated. So considering this we have written the code for Spam versus easy-ham and Spam versus hard-ham using total trained data as well as respective trained data also. This the reason we have splitted the hard ham and easy ham data to train and test sets individually in question1.

```
# Spam versus easy-ham trained with full data and tested with easy ham and spam data
def easyHam_spam_total_train(vectorizer=None):
    test_easyHam_spam_df=pd.concat([easy_hamtest,spamtest])
    x_train = train_df['message']
    y_train = train_df['type']
    x_easyHam_spam_test = test_easyHam_spam_df['message']
    y_easyHam_spam_test = test_easyHam_spam_df['type']
    naive_bayes(x_train, x_easyHam_spam_test, y_train, y_easyHam_spam_test,vectorizer=
    vectorizer)
easyHam_spam_total_train()
```

Listing 3: Spam versus easy-ham trained with full data and test only with easy ham and spam data




Figure 2: Test result - Spam versus easy-ham trained with full data and test only with easy ham and spam data

```
# Spam versus hard-ham trained with full data and tested only with Hard ham and spam
data
def hardHam_spam_total_train(vectorizer=None):
    test_hardHam_spam_df=pd.concat([hard_hamtest,spamtest])
    x_train = train_df['message']
    y_train = train_df['type']
    x_hardHam_spam_test = test_hardHam_spam_df['message']
    y_hardHam_spam_test = test_hardHam_spam_df['type']
    naive_bayes(x_train, x_hardHam_spam_test, y_train, y_hardHam_spam_test,vectorizer=
vectorizer)
hardHam_spam_total_train()
```

Listing 4: Spam versus hard-ham trained with full data and tested with Hard ham and spam data




Figure 3: Test result - Spam versus hard-ham trained with full data and test only with hard ham and spam data

For Spam versus easy-ham and Spam versus hard-ham using total trained data:

By observing above confusion matrices, accuracy score of Spam versus easy-ham, is more when compared to the, Spam versus hard-ham, in both the classifications. As it is difficult to classify type(Ham or Spam) between Spam versus hard-ham. But multinomial performed better than bernoulli with both the Spam versus easy-ham and Spam versus hard-ham data. One more observation we made is that spam mails are classified with same accuracy in both the models when tested with Spam versus easy-ham and Spam versus hard-ham respectively. Even though test data different, this occur because as both the classifications are done, with the model trained on same data and number of spam mails used are same.

```
# Spam versus easy-ham trained and tested with easy ham and spam data
def easyHam_spam_train(vectorizer=None):
    train_easyHam_spam_df=pd.concat([easy_hamtrain,spamtrain])
    test_easyHam_spam_df=pd.concat([easy_hamtest,spamtest])
    x_easyHam_spam_train = train_easyHam_spam_df['message']
    y_easyHam_spam_train = train_easyHam_spam_df['type']
    x_easyHam_spam_test = test_easyHam_spam_df['message']
    y_easyHam_spam_test = test_easyHam_spam_df['type']
    naive_bayes(x_easyHam_spam_train, x_easyHam_spam_test, y_easyHam_spam_train,
    y_easyHam_spam_test,vectorizer=vectorizer)
easyHam_spam_train()
```

Listing 5: Spam versus easy-ham trained and tested with easy ham and spam data




Figure 4: Test result - Spam versus easy-ham trained and tested with easy ham and spam data

```
# Spam versus hard-ham trained and tested with Hard ham and spam data
def hardHam_spam_train(vectorizer=None):
    train_hardHam_spam_df=pd.concat([hard_hamtrain,spamtrain])
    test_hardHam_spam_df=pd.concat([hard_hamtest,spamtest])
    x_hardHam_spam_train = train_hardHam_spam_df['message']
    y_hardHam_spam_train = train_hardHam_spam_df['type']
    x_hardHam_spam_test = test_hardHam_spam_df['message']
    y_hardHam_spam_test = test_hardHam_spam_df['type']
    print(x_hardHam_spam_train.shape,y_hardHam_spam_train.shape,x_hardHam_spam_test.
    shape,y_hardHam_spam_test.shape)
    naive_bayes(x_hardHam_spam_train, x_hardHam_spam_test, y_hardHam_spam_train,
    y_hardHam_spam_test,vectorizer=vectorizer)
hardHam_spam_train()
```

Listing 6: Spam versus hard-ham trained and tested with Hard ham and spam data




Figure 5: Test result - Spam versus hard-ham trained and tested with Hard ham and spam data

For Spam versus easy-ham and Spam versus hard-ham using respective trained data:

By observing above confusion matrices, accuracy score of Spam versus easy-ham, is more when compared to the, Spam versus hard-ham, in both the classifications. As it is difficult to classify type(Ham or Spam) between Spam versus hard-ham. But multinomial performed better than bernoulli in both the Spam versus easy-ham and Spam versus hard-ham data. Which is same as when model trained with, complete trained data. But when we compared these accuracy with the accuracy obtained, when model trained with only respective data is higher in all the cases. Which means the model trained on the extra data leads to decrease in performance classification.

Problem 4

To avoid classification based on common and uninformative words it is common to filter these out.

a. Argue why this may be useful. Try finding the words that are too common/uncommon in the dataset.

b. Use the parameters in Sklearn's 'CountVectorizer' to filter out these words. Update the program from point 3 and run it on your data and report your results.

You have two options to do this in Sklearn: either using the words found in part (a) or letting Sklearn do it for you. Argue for your decision-making.

```
#code to Find common/uncommon words in data set
ham_df = pd.concat([email_easy_ham_df, email_hard_ham_df, email_spam_df])
countHam = Counter(" ".join(ham_df["message"]).split()).most_common()
dataHam = pd.DataFrame.from_dict(countHam)
dataHam_words = dataHam[0]
print(dataHam_words.head(30).to_numpy())
print(dataHam_words.tail(30).to_numpy())
```

Listing 7: Find common/uncommon words in data set

Output:

Most Common Words ['the' '2002' 'to' ',' 'for' 'with' 'from' 'by' 'of' 'and' 'Received:' 'a' 'id' 'Sep' 'in' 'is' 'ESMTP' '+0100' 'that' 'I' 'td' 'you' 'Aug' 'localhost' 'on' 'Oct' 'be' 'it' '=' '[127.0.0.1]']

Least Common Words ['65.00)' 'XBR' 'NORTH' '180.00' 'SOUTH' '190.00' '280.' '70)' '265.' '95)' 'E)' 'WET' '145.00' '205.' '60)' 'F)' 'G)' '110.00' '25)' 'H)' 'VISIONARY' '310.00' '615.' '305)' '1-623 - 972 - 5999' 'Hours : ' 'Mon.' 'Mail.' 'convenience.' 'mailto : bm7@btamail.net.cn?subject = Remove']

The finding the common/uncommon words in the dataset helps to train the model with data of words which are good indicators, to classify between the spam or ham. The common words such as com, from etc.. can be found most commonly in both the spam and ham emails, which are uninformative to classify.

```
#Creating word count vectorizer with words that appear more than 90% of the time,
words that appear in just one email, and common English words
vectorizer = CountVectorizer(max_df = 0.90, min_df = 2, stop_words="english")
easyHam_spam_total_train(vectorizer=vectorizer)
easyHam_spam_train(vectorizer=vectorizer)
```

Listing 8: Spam versus Easy-ham with count vectorizer Filter




Figure 6: Test result - Spam versus Easy-ham with count vectorizer Filter using full train data




Figure 7: Test result - Spam versus Easy-ham with count vectorizer Filter using respective train data

```
#Creating word count vectorizer with words that appear more than 90% of the time,
words that appear in just one email, and common English words
vectorizer = CountVectorizer(max_df = 0.90, min_df = 2, stop_words="english")
hardHam_spam_total_train(vectorizer=vectorizer)
hardHam_spam_train(vectorizer=vectorizer)
```

Listing 9: Spam versus Hard-ham with count vectorizer Filter




Figure 8: Test result - Spam versus Hard-ham with count vectorizer Filter using full train data




Figure 9: Test result - Spam versus Hard-ham with count vectorizer Filter using respective train data

As mentioned in the question, there are two ways to filter out these words. One approach is to use the extracted lists of most common/uncommon words of ham/spam emails. Another approach is to filter out common words using the built-in stop word list for English.

However, by looking at the data, we can see that the spam and ham data sets are imbalanced in size. If we build our model to ignore the words that are the most common or uncommon, it's possible that we will also delete words that make it clear whether an email is spam or ham. Choosing how many words should be considered common or uncommon and stopping them is another challenging decision.

Therefore, we have decided to employ the CountVectorizer method while utilizing stop words and built-in arguments. In this method, we've given the CountVectorizer three arguments: the first is "stop words = 'english'" which will automatically filter out many of the most popular English words; the second is "max df=0.90" which will force the model to avoid using the top 10 percent of most popular words for classification; and the third argument is "min df=2" which will cause all words that appear in fewer than two emails—that is, if the word appears in

Assignment4-1

November 29, 2022

0.0.1 Appendix

1 DAT405 Introduction to Data Science and AI

1.1 2022-2023, Reading Period 2

1.2 Assignment 4: Spam classification using Naïve Bayes

There will be an overall grade for this assignment. To get a pass grade (grade 5), you need to pass items 1-3 below. To receive higher grades, finish items 4 and 5 as well.

The exercise takes place in a notebook environment where you can chose to use Jupyter or Google Colabs. We recommend you use Google Colabs as it will facilitate remote group-work and makes the assignment less technical. Hints: You can execute certain linux shell commands by prefixing the command with `!`. You can insert Markdown cells and code cells. The first you can use for documenting and explaining your results the second you can use writing code snippets that execute the tasks required.

In this assignment you will implement a Naïve Bayes classifier in Python that will classify emails into spam and non-spam (“ham”) classes. Your program should be able to train on a given set of spam and “ham” datasets. You will work with the datasets available at <https://spamassassin.apache.org/old/publiccorpus/>. There are three types of files in this location: - easy-ham: non-spam messages typically quite easy to differentiate from spam messages. - hard-ham: non-spam messages more difficult to differentiate - spam: spam messages

Execute the cell below to download and extract the data into the environment of the notebook – it will take a few seconds. If you chose to use Jupyter notebooks you will have to run the commands in the cell below on your local computer, with Windows you can use 7zip (<https://www.7-zip.org/download.html>) to decompress the data.

```
[57]: #Download and extract data
#!wget https://spamassassin.apache.org/old/publiccorpus/20021010_easy_ham.tar.
      ↪bz2
#!wget https://spamassassin.apache.org/old/publiccorpus/20021010_hard_ham.tar.
      ↪bz2
#!wget https://spamassassin.apache.org/old/publiccorpus/20021010_spam.tar.bz2
#!tar -xjf 20021010_easy_ham.tar.bz2
#!tar -xjf 20021010_hard_ham.tar.bz2
#!tar -xjf 20021010_spam.tar.bz2
```

The data is now in the three folders `easy_ham`, `hard_ham`, and `spam`.

```
[58]: #!/ls -lah
```

```
[59]: import os
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.feature_extraction.text import CountVectorizer
from sklearn.naive_bayes import MultinomialNB
from sklearn.naive_bayes import BernoulliNB
from sklearn import metrics
from sklearn.metrics import plot_confusion_matrix, confusion_matrix
import matplotlib.pyplot as plt
import seaborn as sns
import numpy as np
from collections import Counter
```

###1. Preprocessing: 1. Note that the email files contain a lot of extra information, besides the actual message. Ignore that for now and run on the entire text. Further down (in the higher-grade part), you will be asked to filter out the headers and footers. 2. We don't want to train and test on the same data. Split the spam and the ham datasets in a training set and a test set. (hamtrain, spamtrain, hamtest, and spamtest)

```
[60]: # Functions that write the mail content and type to data frame
def readFileContent(path, type):
    rows=[]
    for file_name in os.listdir(path):
        file = os.path.join(path, file_name)
        if os.path.isfile(file):
            with open(file, encoding='latin-1' ) as file:
                rows.append({'message': file.read(), 'type': type})
    return pd.DataFrame(rows)

# read mail and its classification in to data frame(classification Ham=0 & Spam
    ↳=1)
email_easy_ham_df = readFileContent('./20021010_easy_ham/easy_ham/', 0)
email_hard_ham_df = readFileContent('./20021010_hard_ham/hard_ham/', 0)
email_spam_df = readFileContent('./20021010_spam/spam/', 1)

#Splitting data in to test and train sets
easy_hamtrain,easy_hamtest=train_test_split(email_easy_ham_df, test_size =0.3 ,↳
    ↳random_state =4)
hard_hamtrain,hard_hamtest=train_test_split(email_hard_ham_df, test_size =0.3 ,↳
    ↳random_state =4)
hamtrain=pd.concat([easy_hamtrain,hard_hamtrain])
hamtest= pd.concat([easy_hamtest,hard_hamtest])

spamtrain, spamtest= train_test_split(email_spam_df, test_size =0.3 ,↳
    ↳random_state =4)
```

###2. Write a Python program that: 1. Uses four datasets (`hamtrain`, `spamtrain`, `hamtest`, and `spamtest`) 2. Trains a Naïve Bayes classifier (e.g. Sklearn) on `hamtrain` and `spamtrain`, that classifies the test sets and reports True Positive and False Negative rates on the `hamtest` and `spamtest` datasets. You can use `CountVectorizer` to transform the email texts into vectors. Please note that there are different types of Naïve Bayes Classifier in SKlearn ([Documentation here](#)). Test two of these classifiers that are well suited for this problem - Multinomial Naive Bayes - Bernoulli Naive Bayes.

Please inspect the documentation to ensure input to the classifiers is appropriate. Discuss the differences between these two classifiers.

```
[61]: from warnings import simplefilter
      # ignore all future warnings
      simplefilter(action='ignore', category=FutureWarning)

[62]: def naive_bayes(x_train, x_test, y_train, y_test, vectorizer=None):
      #create a Count Vectorizer and fit it to the training set of data.
      if vectorizer==None:
          vectorizer = CountVectorizer()
          vectorizer.fit(x_train)
          x_train_vec = vectorizer.transform(x_train)
          x_test_vec = vectorizer.transform(x_test)

      fig, ((ax1, ax2)) = plt.subplots(1, 2,figsize=(10,10))

      #Train the Multinomial Naive Bayes model with train sets
      mnb = MultinomialNB().fit(x_train_vec, y_train)
      #Predict the values with test sets
      mnb_predict = mnb.predict(x_test_vec)
      tp_mnb, fp_mnb, fn_mnb, tn_mnb = confusion_matrix(y_test,mnb_predict).
      ↪ravel()
      plot_confusion_matrix(mnb, x_test_vec, y_test, ax=ax1, colorbar=False,
      ↪normalize='true', cmap = 'OrRd')

      #Train the Bernoulli Naive Bayes model with train sets
      bnb = BernoulliNB().fit(x_train_vec, y_train)
      #Predict the values with test sets
      bnb_predict = bnb.predict(x_test_vec)
      tp_bnb, fp_bnb, fn_bnb, tn_bnb = confusion_matrix(y_test,bnb_predict).
      ↪ravel()
      plot_confusion_matrix(bnb, x_test_vec, y_test, ax=ax2, colorbar=False,
      ↪normalize='true',cmap = 'OrRd')

      # Declaring labels and title for each subplot
      ax1.set_xlabel('Predicted type of email\n ham=0 & spam=1')
      ax1.set_ylabel('Actual type of email\n ham=0 & spam=1')
```

```



ax1.set_title('Multinomial Naive Bayes\n'+ 'Accuracy Score: '+str(metrics.
↳accuracy_score(y_test, mnb_predict)*100)+'\n'+ 'tp: '+str((tp_mnb/
↳(tp_mnb+fp_mnb))*100)+ ', fn: '+ str((fn_mnb/(tn_mnb+fn_mnb))*100), size=10)
ax2.set_xlabel('Predicted type of email\n ham=0 & spam=1')
ax2.set_ylabel('Actual type of email\n ham=0 & spam=1')
ax2.set_title('Bernoulli Naive Bayes\n'+ 'Accuracy Score: '+str(metrics.
↳accuracy_score(y_test, bnb_predict)*100)+'\n'+ 'tp: '+str((tp_bnb/
↳(tp_bnb+fp_bnb))*100)+ ', fn: '+ str((fn_bnb/(tn_bnb+fn_bnb))*100), size=10)
plt.subplots_adjust(wspace=0.3)
plt.show()

print("Multinomial naive Bayes classifier, Accuracy score:", metrics.
↳accuracy_score(y_test, mnb_predict)*100)
print("Multinomial naive Bayes True Positive rate:", str((tp_mnb/
↳(tp_mnb+fp_mnb))*100))
print("Multinomial naive Bayes False Negative rate:", str((fn_mnb/
↳(tn_mnb+fn_mnb))*100))
print("Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb",tp_mnb,
↳fp_mnb, fn_mnb, tn_mnb)

print("Bernoulli naive Bayes classifier, Accuracy score:", metrics.
↳accuracy_score(y_test, bnb_predict)*100)
print("Bernoulli naive Bayes True Positive rate:", str((tp_bnb/
↳(tp_bnb+fp_bnb))*100))
print("Bernoulli naive Bayes False Negative rate:", str((fn_bnb/
↳(tn_bnb+fn_bnb))*100))
print("Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb",tp_bnb,
↳fp_bnb, fn_bnb, tn_bnb)

#Concatinating hamtrain & spamtrain
train_df=pd.concat([hamtrain,spamtrain])
#Concatinating hamtest & spamtest
test_df=pd.concat([hamtest,spamtest])
#Assigning data to the variables that will be used to develop the model
x_train = train_df['message']
y_train = train_df['type']
x_test = test_df['message']
y_test = test_df['type']
naive_bayes(x_train, x_test, y_train, y_test)

```


Multinomial naive Bayes classifier, Accuracy score: 96.67338709677419
 Multinomial naive Bayes True Positive rate: 99.28656361474435
 Multinomial naive Bayes False Negative rate: 17.880794701986755
 Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 835 6 27 124
 Bernoulli naive Bayes classifier, Accuracy score: 88.00403225806451
 Bernoulli naive Bayes True Positive rate: 99.64328180737218
 Bernoulli naive Bayes False Negative rate: 76.82119205298014
 Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 838 3 116 35

Your discussion here

1.2.1 3.Run your program on



- Spam versus easy-ham
- Spam versus hard-ham.

```
[63]: # Spam versus easy-ham trained with full data and test only with easy ham and
      ↪spam data
def easyHam_spam_total_train(vectorizer=None):
    test_easyHam_spam_df=pd.concat([easy_hamtest,spamtest])
    x_train = train_df['message']
    y_train = train_df['type']
    x_easyHam_spam_test = test_easyHam_spam_df['message']
    y_easyHam_spam_test = test_easyHam_spam_df['type']
    naive_bayes(x_train, x_easyHam_spam_test, y_train,
    ↪y_easyHam_spam_test,vectorizer=vectorizer)
    easyHam_spam_total_train()
```



Multinomial naive Bayes classifier, Accuracy score: 97.05561613958561
 Multinomial naive Bayes True Positive rate: 100.0
 Multinomial naive Bayes False Negative rate: 17.880794701986755
 Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 766 0 27 124
 Bernoulli naive Bayes classifier, Accuracy score: 87.24100327153762
 Bernoulli naive Bayes True Positive rate: 99.86945169712794
 Bernoulli naive Bayes False Negative rate: 76.82119205298014
 Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 765 1 116 35

```
[64]: # Spam versus hard-ham trained with full data and tested only with Hard ham and
      ↪spam data
def hardHam_spam_total_train(vectorizer=None):
    test_hardHam_spam_df=pd.concat([hard_hamtest,spamtest])
    x_train = train_df['message']
    y_train = train_df['type']
    x_hardHam_spam_test = test_hardHam_spam_df['message']
    y_hardHam_spam_test = test_hardHam_spam_df['type']
    naive_bayes(x_train, x_hardHam_spam_test, y_train,
    ↪y_hardHam_spam_test,vectorizer=vectorizer)
hardHam_spam_total_train()
```



Multinomial naive Bayes classifier, Accuracy score: 85.39823008849558

Multinomial naive Bayes True Positive rate: 92.0

Multinomial naive Bayes False Negative rate: 17.880794701986755

Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 69 6 27 124



Bernoulli naive Bayes classifier, Accuracy score: 47.78761061946903

Bernoulli naive Bayes True Positive rate: 97.33333333333334

Bernoulli naive Bayes False Negative rate: 76.82119205298014

Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 73 2 116 35

```
[65]: # Spam versus easy-ham trained and tested with easy ham and spam data
def easyHam_spam_train(vectorizer=None):
    train_easyHam_spam_df=pd.concat([easy_hamtrain,spamtrain])
    test_easyHam_spam_df=pd.concat([easy_hamtest,spamtest])
    x_easyHam_spam_train = train_easyHam_spam_df['message']
    y_easyHam_spam_train = train_easyHam_spam_df['type']
    x_easyHam_spam_test = test_easyHam_spam_df['message']
    y_easyHam_spam_test = test_easyHam_spam_df['type']
    naive_bayes(x_easyHam_spam_train, x_easyHam_spam_test,
    ↪y_easyHam_spam_train, y_easyHam_spam_test,vectorizer=vectorizer)
    easyHam_spam_train()
```



Multinomial naive Bayes classifier, Accuracy score: 96.29225736095965

Multinomial naive Bayes True Positive rate: 99.86945169712794

Multinomial naive Bayes False Negative rate: 21.85430463576159

Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 765 1 33 118

Bernoulli naive Bayes classifier, Accuracy score: 90.40348964013086


Bernoulli naive Bayes True Positive rate: 99.60835509138381

Bernoulli naive Bayes False Negative rate: 56.29139072847682

Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 763 3 85 66

```
[66]: # Spam versus hard-ham trained and tested with Hard ham and spam data
def hardHam_spam_train(vectorizer=None):
    train_hardHam_spam_df=pd.concat([hard_hamtrain,spamtrain])
    test_hardHam_spam_df=pd.concat([hard_hamtest,spamtest])
    x_hardHam_spam_train = train_hardHam_spam_df['message']
    y_hardHam_spam_train = train_hardHam_spam_df['type']
    x_hardHam_spam_test = test_hardHam_spam_df['message']
    y_hardHam_spam_test = test_hardHam_spam_df['type']
    print(x_hardHam_spam_train.shape,y_hardHam_spam_train.
    ↪shape,x_hardHam_spam_test.shape,y_hardHam_spam_test.shape)
    naive_bayes(x_hardHam_spam_train, x_hardHam_spam_test,
    ↪y_hardHam_spam_train, y_hardHam_spam_test,vectorizer=vectorizer)
    hardHam_spam_train()
```

(525,) (525,) (226,) (226,)



Multinomial naive Bayes classifier, Accuracy score: 93.80530973451327
 Multinomial naive Bayes True Positive rate: 84.0
 Multinomial naive Bayes False Negative rate: 1.3245033112582782
 Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 63 12 2 149
 Bernoulli naive Bayes classifier, Accuracy score: 84.070796460177
 Bernoulli naive Bayes True Positive rate: 54.666666666666664
 Bernoulli naive Bayes False Negative rate: 1.3245033112582782
 Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 41 34 2 149

For Spam versus easy-ham and Spam versus hard-ham using respective trained data:

By observing above confusion matrices, accuracy score of Spam versus easy-ham, is more when compared to the, Spam versus hard-ham, in both the classifications. As it is difficult to classify type(Ham or Spam) between Spam versus hard-ham. But multinomial performed better than bernoulli in both the Spam versus easy-ham and Spam versus hard-ham data. Which is same as when model trained with, complete trained data. But when we compared these accuracy with the accuracy obtained, when model trained with complete trained data. The accuracy obtained when model trained with only reselective data is higher in all the cases. Which means the model trained on the extra data leads to decrease in performance classification.

###4. To avoid classification based on common and uninformative words it is common to filter these out.

a. Argue why this may be useful. Try finding the words that are too common/uncommon in the dataset.

b. Use the parameters in Sklearn's `CountVectorizer` to filter out these words. Update the program from point 3 and run it on your data and report your results.

You have two options to do this in Sklearn: either using the words found in part (a) or letting


Sklearn do it for you. Argue for your decision-making.

```
[67]: #code to Find common/uncommon words in data set
ham_df = pd.concat([email_easy_ham_df, email_hard_ham_df,email_spam_df])
countHam = Counter(" ".join(ham_df["message"]).split()).most_common()
dataHam = pd.DataFrame.from_dict(countHam)
dataHam_words=dataHam[0]
print("Most Common Words ",dataHam_words.head(30).to_numpy())
print("Least Common Words ",dataHam_words.tail(30).to_numpy())
```

Most Common Words ['the' '2002' 'to' '>' 'for' 'with' 'from' 'by' 'of' 'and' 'Received:' 'a' 'id' 'Sep' 'in' 'is' 'ESMTP' '+0100' 'that' 'I' '<td' 'you' 'Aug' 'localhost' 'on' 'Oct' 'be' 'it' '=' '[127.0.0.1)']]


Least Common Words ['\$65.00).' 'XBR' 'NORTH' '\$180.00' 'SOUTH' '\$190.00' '\$280.' '\$70)' '\$265.' '\$95)' 'E)' 'WET' '\$145.00' '\$205.' '\$60)' 'F)' 'G)' '\$110.00' '\$25)' 'H)' 'VISIONARY' '\$310.00' '\$615.' '\$305)' '1-623-972-5999' 'Hours:' 'Mon.' 'Mail.' 'convenience.' 'mailto:bm7@btamail.net.cn?subject=Remove']

```
[68]: #Creating word count vectorizer with words that appear more than 90% of the
time, words that appear in just one email, and common English words
vectorizer = CountVectorizer(max_df = 0.90, min_df = 2, stop_words="english")
easyHam_spam_total_train(vectorizer=vectorizer)
easyHam_spam_train(vectorizer=vectorizer)
```





Multinomial naive Bayes classifier, Accuracy score: 99.45474372955289

Multinomial naive Bayes True Positive rate: 99.86945169712794
 Multinomial naive Bayes False Negative rate: 2.6490066225165565
 Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 765 1 4 147
 Bernoulli naive Bayes classifier, Accuracy score: 98.36423118865866
 Bernoulli naive Bayes True Positive rate: 99.73890339425587
 Bernoulli naive Bayes False Negative rate: 8.609271523178808
 Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 764 2 13 138



Multinomial naive Bayes classifier, Accuracy score: 98.90948745910578
 Multinomial naive Bayes True Positive rate: 99.86945169712794
 Multinomial naive Bayes False Negative rate: 5.960264900662252
 Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 765 1 9 142
 Bernoulli naive Bayes classifier, Accuracy score: 98.03707742639041
 Bernoulli naive Bayes True Positive rate: 99.34725848563968
 Bernoulli naive Bayes False Negative rate: 8.609271523178808
 Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 761 5 13 138

```
[69]: #Creating word count vectorizer with words that appear more than 90% of the
      ↪time, words that appear in just one email, and common English words
vectorizer = CountVectorizer(max_df = 0.90, min_df = 2, stop_words="english")
hardHam_spam_total_train(vectorizer=vectorizer)
hardHam_spam_train(vectorizer=vectorizer)
```



Multinomial naive Bayes classifier, Accuracy score: 94.24778761061947

Multinomial naive Bayes True Positive rate: 88.0

Multinomial naive Bayes False Negative rate: 2.6490066225165565

Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 66 9 4 147



Bernoulli naive Bayes classifier, Accuracy score: 88.05309734513274

Bernoulli naive Bayes True Positive rate: 81.33333333333333

Bernoulli naive Bayes False Negative rate: 8.609271523178808

Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 61 14 13 138

(525,) (525,) (226,) (226,)




```
Multinomial naive Bayes classifier, Accuracy score: 92.47787610619469
Multinomial naive Bayes True Positive rate: 77.33333333333333
Multinomial naive Bayes False Negative rate: 0.0
Multinomial naive Bayes tp_mnb, fp_mnb, fn_mnb, tn_mnb 58 17 0 151
Bernoulli naive Bayes classifier, Accuracy score: 86.72566371681415
Bernoulli naive Bayes True Positive rate: 64.0
Bernoulli naive Bayes False Negative rate: 1.9867549668874174
Bernoulli naive Bayes tp_bnb, fp_bnb, fn_bnb, tn_bnb 48 27 3 148
```

##5. Eeking out further performance Filter out the headers and footers of the emails before you run on them. The format may vary somewhat between emails, which can make this a bit tricky, so perfect filtering is not required. Run your program again and answer the following questions: - Does the result improve from 3 and 4? - The split of the data set into a training set and a test set can lead to very skewed results. Why is this, and do you have suggestions on remedies? - What do you expect would happen if your training set were mostly spam messages while your test set were mostly ham messages?

Re-estimate your classifier using `fit_prior` parameter set to `false`, and answer the following questions: - What does this parameter mean? - How does this alter the predictions? Discuss why or why not.

[]:

[]: