



BSc (Hons) in **Information Technology**
Specialized in AI
IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 03

Objective & Lecture Mapping: In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:
`'grid_size': (self.width, self.height)`
`'walls': list(self.walls)`
`'all_food': list(self.food_positions)`

Step 1.2: Implementing BFS, DFS, and UCS

You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent` .
2. Import required structures: `from collections import deque` and `import heapq` .
3. **BFS:** Create `def bfs_search(...)` . Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)` . Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)` . Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__` , add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'` .
2. In `sense_and_act(self, percept)` , check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']` , execute the search method matching `self.active_algo` , and store the resulting sequence of actions in `self.plan` .
4. Return the first action from the plan using `return self.plan.pop(0)` .
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

Based on your implementation and Lecture 04, complete the following analytical questions.

1. **(Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?**

The State Space is the complete set of all possible states and transitions that can exist in the environment. In our grid, each valid coordinate can represent a state. The Search Tree is the structure generated by the search algorithm as it explores these states from the initial state toward the goal. Therefore, the state space describes what states are possible, while the search tree describes how the algorithm explores those states.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

The reached set prevents the search algorithm from repeatedly exploring the same states. It keeps track of states that have already been reached, avoiding unnecessary repeated exploration and infinite loops. Without the reached set, the DFS agent could keep moving between already visited grid cells and enter an infinite loop, especially when the search encounters cycles in the grid.

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

"BFS explores level by level, so because every movement costs the same, the first path it finds is the shortest. DFS goes deep into one direction first without comparing path lengths, so it can take a longer and winding route."

4. (Evaluate) If we scaled `visual\_grid\_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

"BFS is memory-intensive because it stores many nodes at the same depth, giving it approximately $O(b^d)$ space complexity. DFS stores mainly the current path and branches, giving approximately $O(bm)$ space. Therefore, DFS uses much less memory, while BFS can run out of memory on a very large grid."

Once Completed Get a PDF of the completed File and Push into the Week 03 branch in the Github Project

Finalize and Lock Lab 03 Documentation



FACULTY OF COMPUTING