

XPath Syntax

[◀ Previous](#)

[Next ▶](#)

XPath uses path expressions to select nodes or node-sets in an XML document. The node is selected by following a path or steps.

The XML Example Document

We will use the following XML document in the examples below.

```
<?xml version="1.0" encoding="UTF-8"?>

<bookstore>

  <book>
    <title lang="en">Harry Potter</title>
    <price>29.99</price>
  </book>

  <book>
    <title lang="en">Learning XML</title>
    <price>39.95</price>
  </book>

</bookstore>
```

Selecting Nodes

XPath uses path expressions to select nodes in an XML document. The node is selected by following a path or steps. The most useful path expressions are listed below:

Expression	Description
<i>nodename</i>	Selects all nodes with the name " <i>nodename</i> "
/	Selects from the root node
//	Selects nodes in the document from the current node that match the selection no matter where they are
.	Selects the current node
..	Selects the parent of the current node
@	Selects attributes

In the table below we have listed some path expressions and the result of the expressions:

Path Expression	Result
bookstore	Selects all nodes with the name "bookstore"
/bookstore	Selects the root element bookstore

bookstore/book	Selects all book elements that are children of bookstore
//book	Selects all book elements no matter where they are in the document
bookstore//book	Selects all book elements that are descendant of the bookstore element, no matter where they are under the bookstore element
//@lang	Selects all attributes that are named lang

Predicates

Predicates are used to find a specific node or a node that contains a specific value.

Predicates are always embedded in square brackets.

In the table below we have listed some path expressions with predicates and the result of the expressions:

Path Expression	Result
/bookstore/book[1]	Selects the first book element that is the child of the bookstore element. Note: In IE 5,6,7,8,9 first node is[0], but according to W3C, it is [1]. To solve this problem in IE, set the SelectionLanguage to XPath: <i>In JavaScript: <code>xml.setProperty("SelectionLanguage","XPath");</code></i>
/bookstore/book[last()]	Selects the last book element that is the child of the bookstore element
/bookstore/book[last()-1]	Selects the last but one book element that is the child of the bookstore element
/bookstore/book[position()<3]	Selects the first two book elements that are children of the bookstore element
//title[@lang]	Selects all the title elements that have an attribute named lang
//title[@lang='en']	Selects all the title elements that have a "lang" attribute with a value of "en"
/bookstore/book[price>35.00]	Selects all the book elements of the bookstore element that have a price element with a value greater than 35.00
/bookstore/book[price>35.00]/title	Selects all the title elements of the book elements of the bookstore element that have a price element with a value greater than 35.00

Selecting Unknown Nodes

XPath wildcards can be used to select unknown XML nodes.

Wildcard	Description
*	Matches any element node
@*	Matches any attribute node
node()	Matches any node of any kind

In the table below we have listed some path expressions and the result of the expressions:

Path Expression	Result
/bookstore/*	Selects all the child element nodes of the bookstore element
//*	Selects all elements in the document

Selecting Several Paths

By using the | operator in an XPath expression you can select several paths.


In the table below we have listed some path expressions and the result of the expressions:

Path Expression	Result
//book/title //book/price	Selects all the title AND price elements of all book elements
//title //price	Selects all the title AND price elements in the document
/bookstore/book/title //price	Selects all the title elements of the book element of the bookstore element AND all the price elements in the document

◀ Previous

Next ▶

COLOR PICKER



HOW TO

- Tabs
- Dropdowns
- Accordions
- Convert Weights
- Animated Buttons
- Side Navigation
- Top Navigation
- Modal Boxes
- Progress Bars
- Parallax
- Login Form
- HTML Includes
- Google Maps
- Range Sliders
- Tooltips
- Slideshow
- Filter List
- Sort List

SHARE



CERTIFICATES

HTML, CSS, JavaScript, PHP, jQuery, Bootstrap and XML.

[Read More »](#)

[REPORT ERROR](#)
[PRINT PAGE](#)
[FORUM](#)
[ABOUT](#)

Top 10 Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [SQL Tutorial](#)
- [PHP Tutorial](#)
- [jQuery Tutorial](#)
- [Angular Tutorial](#)
- [XML Tutorial](#)

Top 10 References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [W3.CSS Reference](#)
- [Browser Statistics](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [HTML Character Sets](#)
- [jQuery Reference](#)
- [AngularJS Reference](#)

Top 10 Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [W3.CSS Examples](#)
- [HTML DOM Examples](#)
- [PHP Examples](#)
- [ASP Examples](#)
- [jQuery Examples](#)
- [Angular Examples](#)
- [XML Examples](#)

Web Certificates

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [jQuery Certificate](#)
- [PHP Certificate](#)
- [Bootstrap Certificate](#)
- [XML Certificate](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2017 by Refsnes Data. All Rights Reserved.
Powered by W3.CSS.

