

AItable API Reference manual | AITable Developer Center

<https://developers.aitable.ai/api/reference#tag/Record>



Reminder:

The current API is in beta, we may add new interface return value properties, but will not remove properties that already exist. If the API does not return the data you need, feel free to feedback to us.

This reference manual is intended to help you gain a comprehensive understanding of the AITable API.

Recommendation:

If you haven't learned about the AITable API before, it is recommended that you start with [AITable API Introduction](#).

The navigation area on the left side of this page provides detailed information about each API interface (including records, fields, views, attachments, spaces, and working directories).

The code area on the right of this page allows you to find sample requests and sample responses for each API interface, making it easy to copy the code you need directly.

Introduction

The base URL for the AITable API request is `https://aitable.ai`.

Note: https requests must be used, not http requests.

The AITable API follows the RESTful API convention as much as possible, i.e. data is added, deleted, and checked via `GET`, `POST`, `PATCH`, and `DELETE` requests to the space and AITable resources.

The request and response bodies are encoded in JSON format.

The parameter names in JSON use camel naming (e.g. `viewId`) and are case sensitive.

Authentication

Way 1: By API token

API Token is the user authentication token. When you send an API request to the AITable server, you must include `Authorization: Bearer {Your API Token}` in the request header to facilitate the server's authentication of the user's identity. After successful authentication, this API request will have the same privileges as

the user's operations in the AITable interface, i.e. whatever data the user can operate on the interface, this request can also operate on it.
Take the following cURL request as an example.

```
curl "https://aitable.ai/fusion/v1/datasheets/{datasheetId}/records" \
  -H "Authorization: Bearer {Your API Token}" \
```

Its request header includes.

Name	Data Type	Required	Format of Value	Example Value
Authorization	String (string)	Yes	Bearer {Your API Token}	Bearer uskYtInkHozf sMikhh0yfoS

For specific authentication operations, please refer to [Quick Start](#)

Way 2: OAuth2 (WIP)

Restrictions

When sending API requests, you need to be aware of several restrictions: frequency restrictions, interface restrictions, usage restrictions.

Frequency limits

Different space levels will have the following API request rates limits when requesting the API using user tokens:

- Free space: 2 QPS, suitable for API learning and experience.
- Plus space: 5 QPS, suitable for personal application development.
- Pro space: 10 QPS, suitable for team application development and operation.
- Enterprise space: 20 QPS, suitable for enterprise-level internal application development and high-concurrency scenarios.

Click to view [the pricing page of AITable](#)

If the request frequency exceeds the limit, an error "Operation too frequent" will be displayed (error status code 429).

API limits

- Get records interface: Get up to 1000 rows of records at a time.
For example, if you want to fetch 10000 rows of records in bulk, you need to call the Get Records interface at least 10 times.

- Create records interface: Create up to 10 rows of records at a time.
For example, if you want to create 1000 rows of records in a batch, you need to call the Create Record interface at least 100 times.
- Update records interface: update up to 10 rows of records at a time.
For example, if you want to update 1000 rows of records in a batch, you need to call the Update Record interface at least 100 times.
- Delete records interface: Delete up to 10 rows of records at a time.
For example, if you want to delete 1000 rows of records in a batch, you need to call the Delete Record interface at least 100 times.
- Upload attachments interface: only 1 attachment can be uploaded at a time.
If you need to upload multiple files, you need to call this interface repeatedly.

Usage limits

There are two types of usage limits: one is the limit of API usage; the other is the limit of space resource usage, for details, please refer to [pring_page](#).

The maximum capacity of uploading attachments to a single space is 1 GB.

Status Codes

Each time you send an API request, the application returns a business status code and a corresponding message.

If the request fails, you can troubleshoot it based on the status code and error message returned.

HTTP Status Code	Response Message	Business Status Code	Description
200	SUCCESS	200	GET , PATCH , DELETE requests work and return results as expected
201	SUCCESS	200	POST request works and returns results as expected
200	Cannot find the specified datasheet	301	Possible scenarios: 1) The datasheet may have been deleted 2) The user cannot find the

			datasheet in their own space list
200	Failed to upload attachment	426	Possible scenarios: ① Attachments exceed the 1 GB size limit ② The space has reached its maximum attachment capacity
200	The number of uploaded attachments exceeds the limit	428	Upload attachments can only upload one per call, beyond this error will be reported
200	Operation without node permission	602	Users do not have access rights to the specified datasheet (e.g., manageable, editable, or read-only)
200	(Refer to the specific error message)	400	Parameter exception, data verification exception
401	Authentication failure	401	Possible scenarios: ① API Token is not passed in the request header ② API Token is incorrect
403	Prohibit access	403	Possible scenarios: ① The number of API calls has exceeded the limit

			② Unable to get the API usage quota for the space, please try again later
404	Interface does not exist	404	Please check if the request address is correct
429	Operate too often	429	The maximum request Different space levels will have the following API request rates limits,you can read the AITable pricing_page
500	SERVER_ERROR (code)	500	Unhandled exceptions for internal services
200	You have exceeded the "Public Beta" limit of 50,000 lines	304	The number of rows in the table has reached the maximum number of rows in a single table, please replace the number of tables as soon as possible to avoid data loss

Record

At the present time, AITable is open to the interfaces of getting records, creating records, updating records and deleting records.
The data structure of the records is as follows.

Properties	Description
recordId	string record ID e.g.

	"rec1jV9eWxcaB"
createdAt	number The creation time of the record, in timestamp format e.g. 1624960629000
updatedAt	number The modification time of this record, in timestamp format e.g. 1624964696000
fields	object the data of the corresponding field in a record, returned in the format <pre>{"fieldName": fieldValue}</pre>

When using the [Create Records](#) or [Update Records](#) API to write to fields, you need to understand the data type and structure of each field value.

Note: calculated fields do not allow values to be written actively, including: AutoNumber, Formula, MagicLookUp, LastModifiedTime, CreatedTime, LastModifiedBy, CreatedBy, etc.

For reference, the following table lists the values of different types of fields:

Field Types	Description
SingleText	string returns a string without "\n" line breaks e.g. {"fieldName": "an example title"}
Text	string returns a string with "\n" line breaks e.g. {"fieldName": "a long text"}
SingleSelect	string returns the selected option as a string e.g. {"fieldName": "done"}

MultiSelect	array of strings returns the selected options as an array of strings e.g. <code>{"fieldName": ["Option1", "Option2"]}</code>
Number	number returns a positive or negative number. The return result will not include the precision or symbol given in the field settings. e.g. <code>{"fieldName": 1998}</code>
Currency	number returns a positive or negative number. The return result will not include the precision or symbol given in the field settings. e.g. <code>{"fieldName": 999}</code>
Percent	number returns a positive or negative number. The return result will not include the precision or symbol given in the field settings. e.g. <code>{"fieldName": 0.1}</code>
DateTime	number returns a timestamp in milliseconds e.g. <code>{"fieldName": 1678723200000}</code>
Attachment	array of attachment

objects

returns an array of attachment objects. Each object includes the following properties:

1. mimeType (string): the media type of the attachment;
2. name (string): the name of the attachment;
3. size (number): the size of the attachment (byte);
4. width (number): the width of the image (px), if the attachment is an image;
5. height (number): the height of the image (px), if the attachment is an image;
6. token (string): the access path of the attachment;
7. preview (string): the preview image URL that you can open in a browser, if the attachment is a PDF

e.g. `{"fieldName": [{"id": "atcFagvJrELTS", "name": "logo.png", "size": 6396, "mimeType": "image/png", "token": "space/2023/03/17/ee1bb79d3fd847e383e21c9b0bd53dfc", "width": 424, "height": 80, "url": "https://legacy-`

	<pre>s1.aitable.ai/space /2023/03/17/ee1bb79 d3fd847e383e21c9b0b d53dfc"}]]}</pre>
Member	array of unit objects returns an array of unit objects. A unit describes the roles in a Space such as a member or a team. - id: string, the ID of the organizational unit - type: number, the type of organizational unit, 1 is the group, 3 is the member - name: string, the name of the group or member - avatar: string, avatar URL, read-only, not writable e.g. <pre>{"fieldName": [{"id":"1291258301781176321","type":3,"name":"Jane","avatar":"https://s1.aitable.ai/space/2023/02/09/79e112dd10424ac7842256736e4f5568"}]}}</pre>
Checkbox	boolean returns true as boolean format if the checkbox is checked. Otherwise the return result will not include this Checkbox field. e.g. <pre>{"fieldName": true}</pre>
Rating	number

	returns a positive number between 1 and 10. The return result will not include this field if the value is empty. e.g. <code>{"fieldName": 5}</code>
URL	url object returns a URL object, including title (webpage title), text (webpage address), favicon (webpage icon) e.g. <code>{"fieldName": {"title": "AITable", "text": "https://aitable.ai", "favicon": "https://legacy-s1.aitable.ai/space/2022/12/08/f8693e8f39774a1c8f0b937f39da0e17"}}</code>
Phone	string returns a phone number as a string e.g. <code>{"fieldName": "(310) 3xx-5xxx"}</code>
Email	string returns a email address as a string e.g. <code>{"fieldName": "support@aitable.ai"}</code>
WorkDoc	array of workdoc objects returns an array of workdoc objects. Each object includes the following properties: - documentId : string , document ID

	- title: string , document title e.g. <code>{"fieldName": [{"documentId":"doc CqiLTtyx4l","title" :"I am title"}]}</code>
OneWayLink	array of record IDs (strings) returns an array of strings. Each string is the ID of a record that is added into the One-way link field. e.g. <code>{"fieldName": ['recz9eeg6lSEa']}</code>
TwoWayLink	array of record IDs (strings) returns an array of strings. Each string is the ID of a record that is added into the Two-way link field. e.g. <code>{"fieldName": ['recz9eeg6lSEa']}</code>
MagicLookUp	array of any returns a number, string, or array. The Lookup result is calculated by the system. You can't write into the Lookup field by API. e.g. <code>{"fieldName": ['Reference data 1', 'Reference data 2']}</code>
Formula	string number boolean returns a number, string, or boolean result. The formula result is calculated by the system. You can't write into the

	Formula field by API.
AutoNumber	number returns a positive number. The system automatically generates the numbers so you can't write into the field by API. e.g. <code>{"fieldName": 1}</code>

Get Records

This interface is used to get the records of the specified datasheet.

- Request address:
<https://aitable.ai/fusion/v1/datasheets/{datasheetId}/records>
- Request method: `GET`
- Request header must contain: `Authorization: Bearer {your API Token}`

The area on the right provides sample requests for cURL, Javascript SDK for your reference.

If you need more detailed operation guidance, you can read the [get-records](#) operation guide of API Guide.

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

datasheetId required	string Example: dst0Yj5aNeoHldqvf6 AITable Datasheet ID
-------------------------	--

query Parameters

pageSize	number Default: 100 Example:
----------	------------------------------------

	pageSize=100 How many records are returned per page. By default, 100 records are returned per page. The value range is an integer from 1 to 1000.
maxRecords	number Example: maxRecords=1000 How many records are returned in total. If maxRecords and pageSize are used at the same time, and the value of maxRecords is less than the total number of records, only the setting of maxRecords will take effect.
pageNum	number Default: 1 Example: pageNum=1 Specifies the page number of the page, which is used in conjunction with the pageSize parameter. For example, 'pageSize=1000&pageNum=2' returns records between 1001 and 2000.
sort	Array of objects

	Sort the returned records. Sort is an array of multiple sort objects. The structure of a single sort object is <code>{"order": "asc or desc", "field": "Field name or field ID"}</code>. Query Example <code>sort[][field]=Customer Name&sort[][order]=asc</code>, The returned records are sorted alphabetically in the Customer Name column. If sort and viewId are used at the same time, the sort condition specified by sort will overwrite the sort condition in the view.
recordIds	Array of strings Example: recordIds=rec4zxfWB5uyM Returns a specified record. Example of obtaining multiple records: <code>&recordIds=rec4zxfWB5uyM&,rec1NflLgtzjY</code>. The returned results are sorted according to the order in which the recordIds are passed in. No paging, up to 1000 records can be returned each time.

viewId	string Example: viewId=viwG9I1VPD6nH When the viewId is not explicitly specified, all records and fields are returned. When the viewId is explicitly specified, all records in the specified view will be returned in turn according to the sorting in the specified view. Note that the hidden fields in the view will not appear in the returned results.
fields	Array of strings The returned record results are limited to the specified fields. cURL Query Example. 1. <code>&fields=name,age</code> (when <code>&fieldKey=name</code>) 2. <code>&fields=fldWooy3c3Puz,fldEAr5y7Go5S</code> (when <code>&fieldKey=id</code>). Both of the above two writing methods specify that the returned record only contains two columns 「Name」 and 「Age」 .

filterByFormula	string Use smart formulas to filter records. The formula can be used for reference 《Formula Overview》. If filterByFormula and viewId are used at the same time, all records in the specified view that meet this formula will be returned. Query Example. <pre>&filterByFormula={Title}="title 1"</pre> (You need to use the encodeURIComponent() function to escape the '{Title}="Heading 1"'.) You can accurately match the record with the value of "Heading 1" in the "Heading" column.
cellFormat	string Default: "json" Enum: "string" "json" The type of the value in the cell. The default is <code>json</code>. When <code>string</code> is specified, all values will be automatically converted to string format. When <code>string</code> is specified, if the returned

	records contain date-time values, these values will use the time zone given in the following order (priority from high to low): 1. If the date-time field has set a time zone, use that one. 2. If the user has set a time zone in user settings, use that one. 3. Use the default time zone (UTC-5, America/Toronto)
fieldKey	string Default: "name" Enum: "name" "id" The key used when querying fields and returning fields. The default is 'name' (field name). When 'id' is specified, fieldId will be used as the query and return method (use 'id' can avoid code invalidation caused by modifying field names).

Request samples

- cURL

- JavaScript SDK

```
curl -X GET \
  "https://aitable.ai/fusion/v1/datasheets/{Replace with yours
  datasheetId}/records" \
  -H "Authorization: Bearer {Replace your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    • "pageNum": 1,
    • "records": [],
    • "pageSize": 100,
    • "total": 500
  }
}
```

Create Records

This interface is used to create a new record in the specified datasheet. A maximum of 10 records can be created in a single request.

- Request address:
<https://aitable.ai/fusion/v1/datasheets/{datasheetId}/records>
- Request method: **POST**
- The request header must contain.

- **Authorization:** Bearer {your API Token}
- **Content-Type:** application/json

Example requests for cURL, Javascript SDK are provided in the area on the right

for your reference.
A POST packet will contain a `records` array with several records to be created. The object `fields` contains the fields to be created in a record and the corresponding values, and can contain any number of field values; fields not explicitly specified will be left blank.

If you need more detailed instructions, you can read the [create-records](#) instructions in the API Guide.

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

<code>datasheetId</code> required	string Example: <code>dst0Yj5aNeoHIdqvf6</code> AI Table Datasheet ID
--------------------------------------	--

query Parameters

<code>viewId</code>	string Example: <code>viewId=viwG9l1VPD6nH</code> When the <code>viewId</code> is not explicitly specified, all fields that are not empty are returned; When the <code>viewId</code> is explicitly specified, the fields that are not hidden and are not empty in the specified view are returned.
---------------------	---

Request Body schema: `application/json`

Request body structure

required	Array of objects (FieldCreateRo) The record data to be created, including the recorded fields and field values.
fieldKey	string Default: "name" Enum: "name" "id" The key used when writing fields and returning fields. The default is 'name' (field name). If you want to use fieldId as the write and return method, you need to explicitly specify it as 'id' (using 'id' can avoid code invalidation caused by modifying field names).

Request samples

- Payload
- cURL
- JavaScript SDK

Content type
application/json

```
{
  • "records": [
    ○ {},
```

```

    ○ {}
  • ],
  • "fieldKey": "name"
}

```

Response samples

- 201

Content type
application/json

```

{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    ○ "records": []
  • }
}

```

Update Records

This interface is used to update the records in the specified datasheet. A maximum of 10 records can be updated in a single request.

- Request address:
<https://aitable.ai/fusion/v1/datasheets/{datasheetId}/records>
- Request method: `PATCH`
- The request header must contain.

```

○ Authorization: Bearer {your API Token}
○ Content-Type: application/json

```

Example requests for cURL, Javascript SDK are provided in the right area for your reference.

The object `fields` contains the fields in a record to be updated and the corresponding values. Only fields that are explicitly specified will update the data, fields that are not specified will retain the old values.

If you need to clear the value of a field, you can set it to `null`. For example,

"Status": null will clear the value of the "Status" column corresponding to the record.

If you need more detailed operation instructions, you can read the [Update Records](#) operation guide of the "API Guide".

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

datasheetId required	string Example: dst0Yj5aNeoHldqv6 A1Table Datasheet ID
-------------------------	---

query Parameters

viewId	string Example: viewId=viwG9l1VPD6nH When the viewId is not explicitly specified, all fields that are not empty are returned; When the viewId is explicitly specified, the fields that are not hidden and are not empty in the specified view are returned.
--------	--

Request Body schema: application/json

Request body structure

records required	Array of arrays
---------------------	-----------------

	The record data to be updated, including the record fields and field values.
fieldKey	string Default: "name" Enum: "name" "id" The key used when writing fields and returning fields. The default is 'name' (field name). If you want to use fieldId as the write and return method, you need to explicitly specify it as 'id' (using 'id' can avoid code invalidation caused by modifying field names).

Request samples

- Payload
- cURL
- JavaScript SDK

Content type
application/json

```
{
  • "records": [
    • {},
    • {}
  • ],
  • "fieldKey": "name"
}
```

Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  •  
    "data": {  
  
      ○ "records": []  
    }  
}
```

Delete Record

This interface is used to delete records from a particular datasheet. A maximum of 10 records can be deleted in a single request.

- Request address:
<https://aitable.ai/fusion/v1/datasheets/{datasheetId}/records>
- Request method: **DELETE**
- The request header must contain.

- **Authorization:** Bearer {your API Token}
- **Content-Type:** application/json

Example requests for cURL, Javascript SDK are provided in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [delete-records](#) operation guide in the "API Guide".

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

--	--

datasheetId required	string Example: dst0Yj5aNeoHldqvf6 Aitable Datasheet ID
-------------------------	--

query Parameters

recordIds required	Array of strings Example: recordIds=recwZ6yV3Srv3 ID of the record to be deleted.
-----------------------	--

Request samples

- cURL
- JavaScript SDK

```
curl -X DELETE \
  "https://aitable.ai/fusion/v1/datasheets/{Replace yours
datasheetId}/records?recordIds={Replace with the one you want to
delete recordId}" \
  -H "Authorization: Bearer {Replace your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  • "data": true
```

}

Field

The data structure of the fields is as follows.

Properties	Description
id	<code>string</code> , field ID Example values: <code>fldsRHWJZwFcM</code>
name	<code>string</code> , field name Example values: <code>Order number</code>
type	<code>string</code> , Field types, possible values are listed in the section Field Types and Attributes Example values: <code>SingleText</code>
editable	<code>boolean</code> , Field permissions, i.e. column permissions , <code>true</code> for editable, <code>false</code> for read-only Example values: <code>true</code>
property	<code>object</code> ,Field attributes.Different fields have different attributes, see the section Field Types and Attributes for details on the attributes of various fields Example values: <code>{"defaultValue":"To be added"}</code>
isPrimary	<code>boolean</code> , Is the primary field Example values:

	<code>true</code>
desc	<code>string</code> , Field descriptions, i.e. column descriptions Example values: <code>This column is the automatic generation of the single number, do not manually modify</code>

Field Types and Attributes

AltTable currently has the following field types.

The type of field returned by the interface	The type of the corresponding field
SingleText	single-line text
Text	Multi-line text
SingleSelect	Single choice
MultiSelect	Multiple choice
Number	Number
Currency	Currency
Percent	Percentage
DateTime	Datetime
Attachment	Attachment
Member	Member
Checkbox	Check
Rating	Rating
URL	Website
Phone	A telephone number.
Email	Email
WorkDoc	WorkDoc
OneWayLink	One-way link
TwoWayLink	Two-way link
MagicLookUp	MagicLookUp
Formula	Intelligent formula
AutoNumber	Autoincrement

	number
CreatedTime	Create Timestamp
LastModifiedTime	Modify Timestamp
CreatedBy	Created by
LastModifiedBy	Updated by
Button	Button

The following section describes the properties of each field type in detail. When the "Get Field" interface is called, the following results are returned for each field type.

SingleText

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "SingleText",
  "property": {
    "defaultValue": ""
  }
}
```

Field Properties	Data Type	Description
defaultValue	string	When creating a new record, the default value of the corresponding cell of this field, the default is empty

Text

No field properties are available at this time.

SingleSelect

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "SingleSelect",
  "property": {
    "options": [
      {
        "id": "optpTVSGk0R2M",

```

```

        "name": "Elevit",
        "color": {
          "name": "indigo_4",
          "value": "#5586FF"
        }
      },
      {
        "id": "optqX2Bw479FG",
        "name": "OAD",
        "color": {
          "name": "blue_4",
          "value": "#55CDEF"
        }
      }
    ]
  }
}

```

Field Properties	Data Type	Description
options	object arrays	List of all available options

Description of the parameters contained under options.

Parameters	Data Type	Description
id	string	option ID
name	string	option name
color	object	The color of the option, including the name and value of the color

MultiSelect

The field properties are the same as the radio selection.

Number

Return a sample fragment of the result (containing only field types and attributes).

```

{
  "type": "Number",
  "property": {
    "defaultValue": "2",
    "precision": 0,
    "commaStyle": ",",
    "symbol": "Square meters"
  }
}

```

```
}
```

Field Properties	Data Type	Description
defaultValue	string	The default value for this field when creating a new record, default is empty.
precision	number	Indicates the number of decimal places, i.e., the precision of the number. The values are 0 (for integers), 1 (to one decimal place), 2 (to two decimal places), 3 (to three decimal places), 4 (to four decimal places)
commaStyle	string	Thousand separator, set this property to separate thousands of digits by a comma, such as 1,000. default is empty (optional)
symbol	string	numeric units, displayed to the right of the number, default is null (optional)

Currency

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "Currency",
  "property": {
    "defaultValue": "1000.00",
    "precision": 2,
    "symbol": "¥",
    "symbolAlign": "Default"
  }
}
```

Field Properties	Data Type	Description
defaultValue	string	The default value for this field when creating a new record, the default is null.
precision	number	Indicates the number of decimal places, i.e., the precision of the number. The values are 0 (for integers), 1 (to one decimal place), 2 (to two decimal places), 3 (to three decimal places), 4 (to four decimal places)
symbol	string	currency symbol, can be any custom character
symbolAlign	string	currency symbol (optional). The default value is Default (the currency unit is immediately to the left of the value), other values are Left (the currency unit is fixed to the left), Right (the currency unit is fixed to the right).

Percent

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "Percent",
  "property": {
    "defaultValue": "0.85",
    "precision": 1
  }
}
```

```
}  
}
```

Field Properties	Data Type	Description
defaultValue	string	The default value of the cell corresponding to this field when creating a new record, the default is empty.
precision	number	Indicates the number of decimal places to convert the field value to a percentage, i.e., the percentage precision. The values are 0 (for integers), 1 (to one decimal place), 2 (to two decimal places), 3 (to three decimal places), 4 (to four decimal places). For example, if the field value is 0.22, it will be displayed as 22% if the percentage precision is 0. If the percentage precision is 1, it will be displayed as 22.0%

Datetime

Return a sample fragment of the result (containing only field types and attributes).

```
{  
  "type": "DateTime",  
  "property": {  
    "dateFormat": "YYYY/MM/DD hh:mm",  
    "includeTime": true,  
    "timeFormat": "hh:mm",  
    "autoFill": true,  
    "timeZone": "Asia/Hongkong",  
  }  
}
```



```

    "includeTimeZone": true
  }
}

```

Field Properties	Data Type	Description
dateFormat	string(enum)*	YYYY/MM/DD, YYYY-MM-DD, DD/MM/YYYY, YYYY-MM, MM-DD, YYYY, MM, DD
includeTime	Boolean	Whether to display the time
timeFormat	string(enum)	HH:mm, hh:mm
autoFill	Boolean	Whether to auto-fill the time when creating a new record
timeZone	String	Time zone
includeTimeZone	Boolean	Whether to display time zone

The value of the date field returns timestamp without restricted format. The `format` information in the field property can be used for formatting, see [day.js format](#) for the meaning.

If you don't want to handle date formatting and want the returned result to be consistent with the view display, you can assign `cellFormat` to `string` in the interface request parameters, and all the returned content will be a string.

For available values for `timeZone` property, please refer to [List of Time Zones](#).
Example: `Asia/Shanghai` °

Attachment

No field properties are available at this time.

Member

Return a sample fragment of the result (containing only field types and attributes).

```

{
  "type": "Member",
  "property": {
    "isMulti": true,
    "shouldSendMsg": true
  }
}

```

```
}
```

Field Properties	Data Type	Description
isMulti	Boolean	If or not multiple members can be selected
shouldSendMsg	Boolean	Whether to send an in-site message to a member when it is mentioned in the member column

Description of the parameters contained under options.

Parameters	Data Type	Description
id	String	The user's organizational unit id (different from the actual user id) on the current space, hereafter referred to as the member id. e. g. Bob's member id on space A is different from his member id on space B
name	String	member name
type	String	member type, including Member (for users with physical accounts) and Team (for organizational units in the space, such as departments, groups, etc.)
avatar	String	URL of the member's avatar

Checkbox

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "Checkbox",
  "property": {
    "icon": "white_check_mark"
  }
}
```

Field Properties	Data Type	Description
icon	string(enum)	Please refer to Expression Pack Enumeration

Rating

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "Rating",
  "property": {
    "icon": "star",
    "max": 5
  }
}
```

Field Properties	Data Type	Description
icon	string(enum)	Please refer to Expression Pack Enumeration
max	Number	The maximum value of the rating, from 1-10

URL

No field properties are available at this time.

Phone

No field properties are available at this time.

Email

No field properties are available at this time.

WorkDoc

No field properties are available at this time.

OneWayLink

Two datasheets A and B are connected by a link field, and there will be an association field in A that is associated with B.

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "OneWayLink",
  "property": {
    "foreignDatasheetId": "dstgr2YN264s7CXKVs",
    "limitToViewId": "viwY4B8pmiMoi",
    "limitSingleRecord": true
  }
}
```

Field Properties	Data Type	Description
foreignDatasheetId	String	Related datasheet ID
limitSingleRecord	Boolean	Whether to select only a single record
limitToViewId	String	Specifies a view of the associated datasheet, limiting the selection to the records under that view

TwoWayLink

Two datasheets A and B are connected by a link field, and there will be an association field in A that is associated with B, and a link field in B that is associated with A. This pair of related fields is called a **brother field**.

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "TwoWayLink",
  "property": {
    "foreignDatasheetId": "dstgr2YN264s7CXKVs",
    "brotherFieldId": "fldxxxxxxxx",
    "limitToViewId": "viwY4B8pmiMoi",
    "limitSingleRecord": true
  }
}
```

Field Properties	Data Type	Description
foreignDatasheetId	String	Related datasheet ID
brotherFieldId	String	Related field ID
limitSingleRecord	Boolean	Whether to select only a single record
limitToViewId	String	Specifies a view of the associated datasheet, limiting the selection to the records under that view

MagicLookup

The MagicLookup field is a field attached to a OneWayLink or TwoWayLink field. It is a dynamic computed field, and the cell itself does not store any value. Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "MagicLookup",
  "property": {
    "relatedLinkFieldId": "fldhBGpM3y1Tq",
    "targetFieldId": "fldS2mgS18LE1",
    "rollupFunction": "VALUES",
    "valueType": "Array",
    "entityField": {
      "datasheetId": "dstgr2YN264s7CXKVs",
      "field": {
        "id": "fldS2mgS18LE1",
        "name": "title",
        "type": "SingleText",
        "property": {
          "defaultValue": ""
        },
        "editable": true
      }
    },
    "enableFilterSort": true,
    "sortInfo": {
      "rules": [
        {
          "fieldId": "fld7aautAK1h",
          "desc": false
        }
      ]
    }
  },
}
```

```

    "filterInfo": {
      "conjunction": "and",
      "conditions": [
        {
          "fieldId": "fldL74kjFHak",
          "fieldType": "Number",
          "operator": "isGreater",
          "value": [13]
        }
      ]
    },
    "lookUpLimit": "ALL"
  }
}

```

Field Properties	Data Type	Description
relatedLinkFieldId	String	The associated field ID of the referenced current datasheet
targetFieldId	String	the field ID of the queried field in the associated datasheet
hasError	Boolean	When a lookup dependent associated field is deleted or converted, the referenced value may not be retrieved properly
entityField	Object	The entity fields are finally referenced, excluding MagicLoopUp fields.If an error exists, the entity field may not exist.
rollupFunction	String	aggregate function
valueType	String	Return value type, including <code>String</code> , <code>Boolean</code> , <code>Number</code> , <code>DateTime</code> , <code>Array</code>
format	Object	Returns the result of a number or date formatting operation when the return

value is of type
Number or DateTime

- Description of the `rollupFunction` values refer to [Lookup Product Manual](#) for the meaning of the parameters.

Function Name	Return Value Type	Description
VALUES	array	Original values
AVERAGE	number	average
COUNT	number	non-null count
COUNTA	number	non-null value count
COUNTALL	number	full count
SUM	number	Total
MIN	number/datetime	minimum
MAX	number/datetime	maximum
AND	boolean	and operation
OR	boolean	or operation
XOR	boolean	eXclusive OR operation
CONCATENATE	string	concatenate to text
ARRAYJOIN	string	comma-join
ARRAYUNIQUE	array	Deduplication
ARRAYCOMPACT	array	filter all null values

- Description of the parameters contained under `entityField`.

Parameters	Data Type	Description
datasheetId	String	the datasheet ID of the entity field
field	Object	A <code>Field</code> object other than <code>LookUp</code> , a <code>MagicLookUp</code> can refer to a field of a <code>MagicLookUp</code> type from another datasheet, but ultimately an entity field will exist.

Note: If you use this field feature in your application, you will need to handle exceptions when a reference error is detected for the field.

- The parameters included under `format` are described below.

Parameters	Data Type	Description
type	String	formatting type <code>DateTime</code> , <code>Number</code> , <code>Percent</code> , <code>Currency</code>
format	Object	The specific format of the different formatting types

Formatted as date.

Parameters	Data Type	Description
dateFormat	String	Date format, e.g. <code>YYYY/MM/DD</code>
timeFormat	String	Time format, e.g. <code>hh:mm</code> , <code>HH:mm</code>
includeTime	Boolean	Whether to display the time
timeZone	String	Time zone
includeTimeZone	Boolean	Whether to display time zone

Formatted as a number or percentage:

Parameters	Data Type	Description
precision	Number	numeric precision or percentage precision

Formatted as currency:

Parameters	Data Type	Description
precision	Number	Precision
symbol	String	currency symbol

- Explanation of parameters contained in `sortInfo` :

Parameters	Data Type	Description
rules	array	An array of sorting rules. Currently, only one sorting rule can be specified (the array can only have one element).

Explanation of parameters contained in the `rules` array:

Parameters	Data Type	Description
fieldId	string	The ID of the field used for sorting.
desc	boolean	Whether to sort in descending order.

- Explanation of parameters contained in `filterInfo` :

Parameters	Data Type	Description
conjunction	string	Combination mode of filter conditions: <code>and</code> requires all filter conditions to be met; <code>or</code> requires any one filter condition to be met.
conditions	array	Array of filter conditions

Explanation of parameters contained in `conditions` :

Parameters	Data Type	Description
fieldId	string	Field ID of the filter field
fieldType	string	Field type of the filter field
operator	string	Operator of the filter condition. See the table below for available values.
value	array	Reference value of the filter condition. For example, if the filter condition is "greater than 3", the reference value is 3, and the value would be <code>[3]</code> .

Explanation of possible values for `operator` :

Value	Description
-------	-------------

is	Filters the field whose value is equal to the reference value
isNot	Filters the field whose value is not equal to the reference value
contains	Filters the field whose value contains the reference value
doesNotContain	Filters the field whose value does not contain the reference value
isEmpty	Filters the field whose value is empty
isNotEmpty	Filters the field whose value is not empty
isGreater	Filters the field whose value is greater than the reference value
isGreaterEqual	Filters the field whose value is greater than or equal to the reference value
isLess	Filters the field whose value is less than the reference value
isLessEqual	Filters the field whose value is less than or equal to the reference value
isRepeat	Filters the field whose value contains duplicate items

- Explanation of possible values for `lookUpLimit` :

Value	Description
ALL	Displays all referenced record values.
FIRST	Displays only the first referenced record value.

Formula

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "Formula",
  "property": {
    "expression": "",
    "valueType": "String",
    "hasError": false
  }
}
```

Field Properties	Data Type	Description
expression	string*	formula expression
valueType	string(enum)*	Return value type, including <code>String</code> , <code>Boolean</code> , <code>Number</code> , <code>DateTime</code> , <code>Array</code>
hasError	boolean	The calculated value may not be retrieved properly when the relevant field dependent on the formula is deleted or converted.
format	object	When the return value is of type <code>Number</code> or <code>DateTime</code> , it returns a number or date formatted in the same format as the lookup.

Same as magiclookup, exceptions need to be handled when errors are

encountered.

AutoNumber

DescriptionNo field properties are available at this time.

CreatedTime

Same as DateTime.

LastModifiedTime

Same as DateTime.

CreatedBy

The member id is at the space level and the creator id is at the account level.
Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "CreatedBy",
  "property": {
    "options": [
      {
        "id": "e9cbc839fd1b49be85b1f7b0977047e2",
        "name": "Coco",
        "avatar": "https://s1.aitable.ai/default/avatar004.jpg"
      }
    ]
  }
}
```

Field Properties	Data Type	Description
options	option[]	Members whose fields have been selected by the current member

Description of the parameters contained under options.

Parameters	Data Type	Description
id	string*	user id
name	string*	user nickname
avatar	string*	URL of user avatar

LastModifiedBy

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "type": "LastModifiedBy",
  "property": {
    "options": [
      {
        "id": "e9cbc839fd1b49be85b1f7b0977047e2",
        "name": "Coco",
        "avatar": "https://s1.aitable.ai/default/avatar004.jpg"
      }
    ]
  }
}
```

Field Properties	Data Type	Description
options	option[]	Current field stored users

Description of the parameters contained under options.

Parameters	Data Type	Description
id	string*	user id
name	string*	user nickname
avatar	string*	URL of user avatar

Button

Return a sample fragment of the result (containing only field types and attributes).

```
{
  "id": "fldb6L4FznMbZ",
  "name": "Button",
  "type": "Button",
  "property": {
    "text": "Click to start",
    "style": {
      "type": "Background",
      "color": {
        "name": "deepPurple_5",
        "value": "#B0A4F5"
      }
    }
  },
  "action": {
    "type": "openLink",
  }
}
```

```

      "openLink": {
        "type": "Url",
        "expression": "https://aitable.ai"
      }
    },
    "editable": false
  }
}

```

Field Properties	Data Type	Description
text	String	Button text
style	Object	Button style
action	Object	Button action

- Explanation of parameters contained in `style` :

Parameters	Data Type	Description
type	String	Button style type: Background, OnlyText. \n Default is Background
color	Object	Button style color

- Explanation of parameters contained in `color` :

Parameters	Data Type	Description
name	String	Color name, see the name of color value list for details
value	String	Color value, not required. See the name of color value list for details

- Explanation of parameters contained in `action` :

Parameters	Data Type	Description
type	String	Button action type: <code>OpenLink</code> , <code>TriggerAutomation</code> . Currently only <code>OpenLink</code> support for now in the API
openLink	Object	Click to open a link

- Explanation of parameters contained in `openLink` :

Parameters	Data Type	Description
type	String	Link type: Url, Expression

expression	String	Pure url or The expression of the url
------------	--------	---------------------------------------

Get Field

This interface is used to get information about all fields in the specified datasheet that you have permission to view.

A maximum of 200 fields can be created in a single datasheet. Requests for fields return the results in a single pass, without paging.

- Request address: <https://aitable.ai/fusion/v1/datasheets/{datasheetId}/fields>
- Request method: **GET**
- Request header must contain: **Authorization: Bearer {your API Token}**

Example requests for cURL, Javascript SDK are provided in the area on the right for your reference.

If you need more detailed operation instructions, you can read the [Get Fields](#) operation guide of the "API Guide".

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

datasheetId required	string Example: dst0Yj5aNeoHldqvf6 AITable Datasheet ID
-------------------------	--

query Parameters

viewId	string Example: viewId=viwG9l1VPD6nH View ID. If you specify a view, the returned fields are in the same order as the view. Hidden
--------	---

fields will not be returned.

Request samples

- cURL
- JavaScript SDK
- Python SDK

```
curl -X GET \
  "https://aitable.ai/fusion/v1/datasheets/{Replace with yours
datasheetId}/fields" \
  -H "Authorization: Bearer {Replace your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    • "fields": []
  • }
}
```

Create Field

This interface is used to create new fields in the specified datasheet. A maximum of 200 fields can be created in a single datasheet.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/datasheets/{datasheetId}/fields>
- Request method: **POST**

- The request header must contain.
 - `Authorization: Bearer {your API Token}`
 - `Content-Type: application/json`

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
datasheetId required	string Example: dstNiC6R9MryevVaC Q Datasheet ID

Request Body schema: application/json

Request body structure

type required	string Field Type SingleText
name required	string Field name, no more than 100 characters
required	object Single line text attribute

Request samples

- Payload
- cURL
- JavaScript SDK
- Python SDK

Content type
application/json

Example

SingleText

```
{  
  
  • "type": "SingleText",  
  • "name": "Title",  
  •  
    "property": {  
  
      ◦ "defaultValue": "Default text text"  
    }  
}
```

Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  •  
    "data": {  
  
      ◦ "id": "fldupsvkr2ATB",  
      ◦ "name": "Title"  
    }  
}
```

}

Delete Field

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
datasheetId required	string Example: dstNiC6R9MryevVaCQ Datasheet ID
fieldId required	string Example: fld7r18G7eSOu field ID, field ID can be obtained through the field interface

Request samples

- cURL
- JavaScript SDK
- Python SDK

```
curl -X DELETE \
  "https://aitable.ai/fusion/v1/spaces/spcjXzqVrjaP3/datasheets/dstNiC6R9MryevVaCQ/fields/fldxxxxxx" \
  -H "Authorization: Bearer {Your API Token}"
```

Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  • "data": { }  
}
```

View

The data structure of view is as follows.

Attributes	Description
id	string* ID of view e.g. <code>viwpdA8TUBp5r</code>
name	string* Name of view e.g. <code>All Orders</code>
type	string(enum)* <code>Grid</code> , <code>Gallery</code> , <code>Kanban</code> , <code>Gantt</code> , <code>Calendar</code> , <code>Architecture</code> e.g. <code>Grid</code>

Get View

This interface is used to fetch all views of the specified datasheet.
The request to fetch the views returns the results in one go, without paging.

- Request address: <https://aitable.ai/fusion/v1/datasheets/{datasheetId}/views>
- Request method: `GET`
- Request header must contain: `Authorization: Bearer {your API Token}`

Example requests for cURL, Javascript SDK are provided in the area on the right for your reference.

If you need a more detailed operation guide, you can read the [Get Views](#) operation guide in the "API Guide".

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

datasheetId required	string Example: dst0Yj5aNeoHldqvf6 AItable Datasheet ID
-------------------------	--

Request samples

- cURL
- JavaScript SDK

```
curl -X GET \  
"https://aitable.ai/fusion/v1/datasheets/{Replace with yours  
datasheetId}/views" \  
-H "Authorization: Bearer {Replace your API Token}"
```

Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  •  
    "data": {  
      • "views": []  
    }  
}
```

Datasheet

At the moment, only the interface for creating tables is open for AITable.

Create Datasheet

This interface is used to create a datasheet with the specified fields in the specified space. A maximum of 200 fields can be created in a single request in a newly created datasheet.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/datasheets>
- Request method: **POST**
- The request header must contain.

- **Authorization:** Bearer {your API Token}
- **Content-Type:** application/json

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
---------------------	---

Request Body schema: application/json

Request body structure

name required	string Datasheet name, no more than 100 characters
description	string

	Table description, no more than 500 characters
folderId	string The folder ID; if it is blank, it will be the working directory by default
preNodeId	string The ID of the previous node. If it is empty, it will be moved to the first place
	Array of objects (FieldItemRo) Field list. If it is blank, 3 columns of default fields will be added

Request samples

- Payload
- cURL
- JavaScript SDK
- Python SDK

Content type
application/json

```
{
  • "name": "My Datasheet",
  • "description": "This is a description",
  • "folderId": "fodn173Q0e8nC",
  • "preNodeId": "dstQJl6BGku1WfLPTD",
  •
  "fields": [
```

```
    ○ {}
  • ]
}
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    ○ "id": "dstbs2U7mt8AEqgKuh",
    ○ "createdAt": 1648648690000,
    ○ "fields": []
  • }
}
```

Attachment

Currently the AITable is only open for uploading attachments.

Upload Attachment

This interface is used to upload an attachment and bind the attachment to a datasheet.

After uploading the attachment, the attachment data is not directly inserted into the datasheet. Instead, it needs to be inserted into a field of type attachment by using either the `Create records` or `Update records` API.

Only one attachment can be uploaded per request. If you need to upload multiple files, you need to call this interface repeatedly.

- Request address:

<https://aitable.ai/fusion/v1/datasheets/{datasheetId}/attachments>

- Request method: **POST**
- The request header must contain.
 - **Authorization:** Bearer {your API Token}
 - **Content-Type:** multipart/form-data

Example requests for cURL, Javascript SDK are provided in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [Upload Attachments](#) operation guidance in the "API Guide".

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

datasheetId required	string Example: dst0Yj5aNeoHldqvf6 AItable Datasheet ID
-------------------------	--

Request Body schema: multipart/form-data

Request body structure

file required	string <binary> The local absolute path of the attachment to be uploaded.
------------------	--

Request samples

- cURL
- JavaScript SDK

```
curl -X POST \  
"https://aitable.ai/fusion/v1/datasheets/{Replace with yours  
datasheetId}/attachments" \  
-H "Authorization: Bearer {Replace your API Token}" \  

```

```
-H "Content-Type: multipart/form-data" \
-F "file=@{Replace with your local file path}"
```

Response samples

- 201

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    • "token": "space/2020/07/28/6fdc652231a8480398e302606ae28213",
    • "name": "9d4911932181f254433a86b05797f9a6.jpeg",
    • "size": 7194,
    • "width": 479,
    • "height": 478,
    • "mimeType": "image/jpeg",
    • "preview": "***",
    • "url": "***"
  • }
}
```

Space

The data structure of space is as follows.

Attributes	Description
id	string* ID of space e.g. <code>spcX9P2xUcKst</code>
name	string* Name of space e.g. <code>test space</code>
isAdmin	boolean

whether the current
requesting user is the
admin of the space
e.g. `true`

Get the List of Spaces

This interface is used to get all spaces created or invited to by the current requesting user.

- Request address: <https://aitable.ai/fusion/v1/spaces>
- Request method: `GET`
- Request header must contain: `Authorization: Bearer {your API Token}`

Example requests for cURL, Javascript SDK are provided in the area on the right for your reference.

If you need more detailed operation instructions, you can read the [Get List of Spaces](#) operation guide in the "API Guide".

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

Request samples

- cURL
- JavaScript SDK

```
curl -X GET \
  "https://aitable.ai/fusion/v1/spaces" \
  -H "Authorization: Bearer {Replace your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
```

- `"success": true,`
- `"code": 200,`
- `"message": "SUCCESS",`
-

```

    "data": {
      ○ "spaces": []
    • }
  }

```

Node

The data structure of single file node is as follows.

Attributes	Description
id	string* ID of file node e.g. <code>fodvfSPGFpMFH</code>
name	string* Name of file node e.g. <code>R&D Department</code>
icon	string Icon of file node e.g. 🤖
type	string(enum)* <code>Datasheet</code> , <code>Mirror</code> , <code>Folder</code> , <code>Form</code> , <code>Dashboard</code> , <code>Automation</code> e.g. <code>Folder</code>
isFav	boolean Pin status. This parameter indicates whether the current node is pinned to the "Pin" section in the left sidebar e.g. <code>true</code>
permission	number API tokens are generated based on individual accounts. Users can retrieve a list of file nodes that they have specific permissions for using

	the API token.. 0 : Manager, able to add, delete views and records field, and allowed to edit fields, but nable to add and delete fields. 1 : Editor, able to add, delete views and records field, and allowed to edit fields, but unable to add and delete fields. 2 : Update-only, able to view, add and edit records, but unable to delete records. 3 : Read-only, only allowed to view the data. For more details about file node permissions can be found here: https://help.aitable.ai/docs/guide/faq-permission-settings e.g. 0
children	array of nodes Only returned when Get Node Details is requested • The children information will only be returned when the file type is Folder . Under children , there is a list of file nodes in the folder one level down. e.g. <pre>[{"id":"fodwrbgo8lDpbUjZzm","name":"Procurement"}]</pre>

	<pre>management", "type": "Folder", "icon": "👤", ", "isFav": true}, {"id": "fodwrbgo8lDp bUjZzm", "name": "Pro curement management", "type": "Folder", "icon": "👤", ", "isFav": true}]</pre>
parentId	string Only returned when requesting Get Node List and Search Nodes. Parent node ID. This attribute specifies the ID of the parent node for the current node. If the node does not have a parent node, then this attribute is not returned e.g. <code>fodwrbgo8lDpbUjZzm</code>

Get Node List

This interface is used to get a list of the outermost files in the working directory of a given space, which supports Fusion API v3 with a new data engine that provides better performance and a more efficient API experience, see [Fusion API v3](#) for details.

The "Get Node List" interface only supports returning the outermost list of files in the working directory. If you want to return a list of all nodes in the working directory, you can call both the ["Get Node details"](get-node-details#example: get a list of files and details under a specified folder) interface to do so.

Possible file types to be fetched include datasheets, folders, forms, dashboards, automations, etc.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/nodes>
- Request method: **GET**
- Request header must contain: **Authorization: Bearer {your API Token}**

Example requests for cURL, Javascript SDK are provided in the area on the right for your reference.

If you need more detailed operation instructions, you can read the [Get Node List](#) operation guide of the "API Guide".



path Parameters

spaceId required	string Example: spczdmQDfBAn5 Space ID
---------------------	---

Request samples

- cURL
- JavaScript SDK

```
curl -X GET \
  "https://aitable.ai/fusion/v1/spaces/{Replace with yours
spaceId}/nodes" \
-H "Authorization: Bearer {Replace your API Token}"
```



Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    ○ "nodes": []
  • }
}
```

Search Nodes

This interface provides a way for users to retrieve file nodes based on specific types, permissions, and queries, without having to consider the folder hierarchy. The supported node types for retrieval include: Folder, Dashboard, Form, Dashboard, Mirror and Automation.

- Request URL: <https://vika.cn/fusion/v2/spaces/{spaceId}/nodes>
- Request method: `GET`
- The request header must include: `Authorization: Bearer {your API Token}`

Example requests for cURL are provided in the area on the right for your reference.

If you need more detailed operation instructions, you can read the [Search Nodes](#) operation guide of the "API Guide".

path Parameters

spaceId required	string Example: spczdmQDfBAn5 Space ID
---------------------	---

query Parameters

type required	string Enum: "Folder" "Datasheet" "Form" "Dashboard" "Mirror" Example: type=Datasheet The type of file node, value in ("Folder", "Datasheet", "Form", "Dashboard", "Mirror"). The values are case-sensitive.
permissions	Array of numbers

Default: [0,1,2,3]
Items Enum: 0 1 2 3

0: Manager, able to add, delete views and records field, and allowed to edit fields, but unable to add and delete fields.

1: Editor, able to add, delete views and records field, and allowed to edit fields, but unable to add and delete fields.

2: Update-only, able to view, add and edit records, but unable to delete records.

3: Read-only, only allowed to view the data.

By providing the permissions associated with their API token, users can retrieve all file nodes within their account that match those permissions. If this parameter is empty, return all accessible file nodes.

For example, if you want to get all file nodes where records can be added, pass the parameter like this

permissions=0,1,2

For more details about file node permissions can be found here:

<https://help.aitable.ai>

	/docs/guide/faq-permission-settings
query	string This parameter enables searching for file nodes with specific keywords and returns a list of matching nodes based on partial name matches.

Request samples

- cURL
- JavaScript SDK
- Python SDK

```
curl -X GET \
  "https://aitable.ai/fusion/v2/spaces/{Replace with yours
spaceId}/nodes?type=Datasheet" \
  -H "Authorization: Bearer {Replace your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    • "nodes": []
  }
}
```

}

Get Node Details

This interface is used to get the details of the specified file in the working directory of the specified space.
Possible file types to be fetched include datasheets, folders, forms, dashboards, etc.
If the specified file type is a folder, it will get the list of the outermost files under that folder and their details; if the specified file is of other types, it will get the details of that file.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/nodes/{nodeId}>
- Request method: `GET`
- Request header must contain: `Authorization: Bearer {your API Token}`

Example requests for cURL, Javascript SDK are provided in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [Get Node Details](#) operation guidance in the "API Guide".

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spczdmQDfBAn5 Space ID
nodeId required	string Example: fodTXAYEmQ5rd File node ID, such as AITable Datasheet ID, folder ID, collection table ID or dashboard ID

Request samples

- cURL
- JavaScript SDK

```
curl -X GET \
  "https://aitable.ai/fusion/v1/spaces/{Replace with yours
spaceId}/nodes/{Replace with yours nodeId}" \
  -H "Authorization: Bearer {Replace your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    • "id": "fodwrbgo8lDpbUjZzm",
    • "name": "Procurement management",
    • "type": "Folder",
    • "icon": "👑",
    • "isFav": true,
    • "children": [ ]
  • }
}
```

Create embedded links

This interface is used to create an "embed link" to a specified node, such as a datasheet or a dashboard. If all parameters in the payload have the same value, the generated linkId (the last string of the url path) is the same. If the parameter values of the payload are different, the generated linkId will also be different.

- Request address:

<https://aitable.ai/fusion/v1/spaces/{spaceId}/nodes/{nodeId}/embedlinks>

- Request method: **POST**
- The request header must contain.
 - **Authorization:** Bearer {your API Token}
 - **Content-Type:** application/json

If you need more detailed instructions, you can read the [Create Embedded Links](#) instructions in the API Guide.

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
nodeId required	string Example: dstS94qPZFXjC1LKns Node ID, support Datasheet, Dashboard and Form

Request Body schema: application/json

	object (EmbedLinkPayloadDto)
theme	string (This attribute is temporarily closed) The default value is light, theme color, dark light

Request samples

- Payload
- cURL
- JavaScript SDK
- Python SDK

Content type
application/json

```
{  
  
  • "payload": {  
  
    ○ "primarySideBar": {},  
    ○ "viewControl": {},  
    ○ "bannerLogo": true,  
    ○ "permissionType": "string"  
  },  
  • "theme": "string"  
}
```

Response samples

- 201

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  •  
    "data": {  
  
      ○ "payload": {},  
      ○ "theme": "string",  
      ○ "linkId": "string",  
      ○ "url": "string"  
    },  
  • }  
}
```

}

Get list of embedded links

This interface is used to get a list of embedded links for the specified node(deleted embedded links are not returned), such as a datasheet or a dashboard.
A datasheet can create up to 30 embedded links. The result is returned once upon request, without pagination.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/nodes/{nodeId}/embedlinks>
- Request method: **GET**
- Request header must contain: **Authorization: Bearer {your API Token}**

The right area provides an example of a cURL request for your reference.

If you need more detailed operation instructions, you can read the [Get Embedded Links List](#) operation guide in the "API Guide".

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
nodeId required	string Example: dstS94qPZFXjC1LKn s Node ID

Request samples

- cURL
- JavaScript SDK
- Python SDK

```
curl -X GET
```

```
'https://aitable.ai/fusion/v1/spaces/spcjXzqVrjaP3/nodes/dstWUHwzTHd2
YQaXEE/embedlinks' \
-H 'Authorization: Bearer {Replace your API Token}'
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": [
    • {}
  • ]
}
```

Delete embedded link

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
nodeId required	string Example: dstS94qPZFXjC1LKn s Node ID
linkId	

required	string Example: embb90a52cfc02a4f83 Embed Link ID
----------	--

Request samples

- cURL
- JavaScript SDK
- Python SDK

```
curl -X DELETE
'https://aitable.ai/fusion/v1/spaces/spcjXzqVrjaP3/nodes/dstWUHwzTHd2
YQaXEE/embedlinks/embb90a52cfc02a4f83' \
-H 'Authorization: Bearer {Replace your API Token}'
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS"
}
```

AI

Currently, the AITable only supports the chat completions API and is only available to whitelisted users. [Click here to apply](#)

Create chat completions

This interface is used to create chat completions.

- Request address: https://aitable.ai/fusion/v1/ai/{ai_id}/chat/completions
- Request method: **POST**
- Request header must contain:
 - **Authorization:** Bearer {Your API Token}
 - **Content-Type:** application/json

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [Create chat completions](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

aiId required	string Example: ai_zxLeHGV3ac32YYC AI ID
------------------	---

Request Body schema: application/json

Request body structure

model required	string ID of the model to use, like "gpt-3.5-turbo". See the Bot Model list
required	Array of objects A list of messages comprising the conversation so far.
	Array of AiFunction (object)

	A list of functions the model may generate JSON inputs for.
function_call	object Controls how the model responds to function calls. "none" means the model does not call a function, and responds to the end-user. "auto" means the model can pick between an end-user or calling a function. Specifying a particular function via {"name":\ "my_function"} forces the model to call that function. "none" is the default when no functions are present. "auto" is the default if functions are present.
temperature	number [0 .. 2] What sampling temperature to use, between 0 and 2. Higher values like 0.8 will make the output more random, while lower values like 0.2 will make it more focused and deterministic.
top_p	number

	An alternative to sampling with temperature, called nucleus sampling, where the model considers the results of the tokens with top_p probability mass. So 0.1 means only the tokens comprising the top 10% probability mass are considered.
stream	boolean If set, partial message deltas will be sent, like in ChatGPT. Tokens will be sent as data-only server-sent events as they become available, with the stream terminated by a data:[DONE] message.
stop	string/array/null Up to 4 sequences where the API will stop generating further tokens.
max_tokens	number The maximum number of tokens to generate in the chat completion.
presence_penalty	

	number [-2 .. 2] Number between -2.0 and 2.0. Positive values penalize new tokens based on whether they appear in the text so far, increasing the model's likelihood to talk about new topics.
frequency_penalty	number [-2 .. 2] Number between -2.0 and 2.0. Positive values penalize new tokens based on their existing frequency in the text so far, decreasing the model's likelihood to repeat the same line verbatim.
user	string A unique identifier representing your end-user, which can help us to monitor and detect abuse.

Request samples

- Payload
- cURL
- JavaScript SDK
- Python SDK

Content type
application/json

```
{
  • "model": "gpt-3.5-turbo",
  •
  • "messages": [
    • {}
  • ],
  •
  • "functions": [
    • {}
  • ],
  •
  • "function_call": {
    • "name": "my_function"
  • },
  • "temperature": 1,
  • "top_p": 1,
  • "stream": false,
  • "stop": null,
  • "max_tokens": 5,
  • "presence_penalty": 0,
  • "frequency_penalty": 0,
  • "user": "user123456"
}
```

Response samples

- 200

Content type
application/json

```
{
  • "id": "aitable_ai_CkZH2zQokhry31j_1693452659",
  • "conversation_id": "CS-0253eb8d-d6c6-4543-88d4-fcb555f52982",
  • "actions": null,
  • "object": "chat.completion",
  • "created": 1693452659,
  • "model": "gpt-3.5-turbo",

```

- - `"choices": [`
 - `{}`
 - `],`
-
- - `"usage": {`
 - `"prompt_tokens": 9,`
 - `"completion_tokens": 12,`
 - `"total_tokens": 21,`
 - `"total_cost": 21,`
 - `"result": "\n\nHello there, how may I assist you today"`
- `}`
- `}`

Member

The data structure of the Member is as follows.

Properties	Type	Description	Example Value
unitId	string	Member's unitId	"T7fL3jV4KvX1cY2dGmS9sPqZzN6rWnB"
name	string	Member's name	"John"
avatar	string	The resource address for the member's avatar.	" https://s1.aitable.ai/public/2023/05/16/00a91wbb47fd0594fbc975d2d764a45q "
email	string	Member's email address	" test@aitable.ai "
mobile	object	Member's phone number	<code>{ "number": "12345678901", "areaCode": "+86" }</code>
status	integer	Member's status, whether joined space (1:joined, 0:not joined)	1
type	string	Member's type	"Member"

		("PrimaryAdmin" indicates the Primary admin of the space, "SubAdmin" indicates the sub-admin of the space, "Member" indicates the member in the space)	
teams	array of object	Teams to which the member belongs.	<pre>[{"unitId": "VS1SejiywaMWbiGMEHAohh62T9EPmmlh", "name": "test", "sequence": 1, "parentUnitId": "YN3YT97EPGL9ZA0loc9V2kNQnWb9ivKW"}, ...]</pre>
roles	array of object	Roles associated with the member.	<pre>[{"unitId": "sZ6gJ9L2HxP5XW1fRtNwE4zKqVcY7yM", "name": "role A", "sequence": 1}, ...]</pre>

Get a member

This interface is used to get the specified member's information.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/members/{unitId}>
- Request method: **GET**
- Request header must contain: **Authorization: Bearer {Your API Token}**

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [Get a member](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
unitId required	string Example: kD8tPcZ3fYxSjV9qW vL5X2TmQbN1nR6 Member's unitId

query Parameters

sensitiveData	string Example: sensitiveData=true Fill in "true" to get sensitive member data such as phone number and email address.
---------------	---

Request samples

- cURL

```
curl -X GET \
'https://aitable.ai/fusion/v1/spaces/{spaceId}/members/{unitId}?
sensitiveData=true' \
-H 'Authorization: Bearer {Your API Token}'
```

Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  •  
    "data": {  
  
      ○ "unitId": "kD8tPcZ3fYxSjV9qWvL5X2TmQbN1nR6",  
      ○ "name": "John",  
      ○ "email": "john@aitable.ai",  
      ○ "mobile": {},  
      ○ "status": 1,  
      ○ "type": "PrimaryAdmin",  
      ○ "teams": [],  
      ○ "roles": []  
    }  
  }  
}
```

Update a member

This interface is used to update a member.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/members/{unitId}>
- Request method: **PUT**
- Request header must contain:

- **Authorization:** Bearer {Your API Token}
- **Content-Type:** application/json

Example requests for cURL is in the area on the right for your reference.
The request body includes the properties and corresponding values to be updated in the member. Only the explicitly specified properties will be updated, while the properties that are not specified will retain their old values.

If you need more detailed operation guidance, you can read the [Update a member](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
unitId required	string Example: kD8tPcZ3fYxSjV9qW vL5X2TmQbN1nR6 Member's unitId

query Parameters

sensitiveData	string Example: sensitiveData=true Fill in "true" to get sensitive member data such as phone number and email address.
---------------	---

Request Body schema: application/json

Request body structure

name	string Member's name
teams	Array of strings The unitIds of teams to which the member belongs.
roles	

	Array of strings
	The unitIds of roles associated with the member.

Request samples

- Payload
- cURL

Content type
application/json

```
{  
  
  • "name": "John",  
  •  
    "teams": [  
  
      ○ "X9vJ6R2qFzL8sK1mVxZcPwNtY3gT5yD"  
    ],  
  •  
    "roles": [  
  
      ○ "gP5zF7xW1mC2nQ4sXrKjV8bT6tL9yH"  
    ]  
  }  
}
```

Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  •  
}
```

```

    "data": {
      "unitId": "kD8tPcZ3fYxSjV9qWvL5X2TmQbN1nR6",
      "name": "John",
      "email": "john@aitable.ai",
      "mobile": {},
      "status": 1,
      "type": "PrimaryAdmin",
      "teams": [],
      "roles": []
    }
  }
}

```

Delete a member

This interface is used to delete a member.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/members/{unitId}>
- Request method: **DELETE**
- Request header must contain:
 - Authorization: Bearer {Your API Token}**

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [Delete a member](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
unitId required	string Example: kD8tPcZ3fYxSjV9qW vL5X2TmQbN1nR6

The unitId of the member to be deleted.

Request samples

- cURL

```
curl -X DELETE \
'https://aitable.ai/fusion/v1/spaces/{spaceId}/members/{unitId}' \
-H 'Authorization: Bearer {Your API Token}'
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS"
}
```

Team

The data structure of the Team is as follows.

Properties	Type	Description	Example Value
unitId	string	The unique ID of the team.	"C7dVpM3tBxL4jT6hRyK5WwQsZgX8fNv"
name	string	Team's name	"Team A"
sequence	integer	The sorting order of the team at the current hierarchy level. In the	1

		Contacts, teams are sorted in ascending order based on this sequence number. If there are duplicate sequence numbers within the same hierarchy level, the teams will be sorted in ascending order based on their creation time.	
parentUnitId	string	The unitId of the parent team to which the team belongs.	"nL2vU7tZwKfR4aGxQyJjXq6YbP5mS9c"
roles	array of object	Roles associated with the team.	[{"unitId": "M3sJ6mL4fY9xN1yZpRtG7wKvX2TcVq", "name": "role A", "sequence": 1}, ...]

List the team members

This interface is used to get the list of members under the specified team.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/teams/{unitId}/members>
- Request method: **GET**
- Request header must contain: **Authorization: Bearer {Your API Token}**

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [List the team members](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
unitId required	string Example: X9vJ6R2qFzL8sK1m VxZcPwNtY3gT5yD Team's unitId

query Parameters

pageSize	number Example: pageSize=100 The number of members to return per page. The default is to return 100 members per page. The valid range for this parameter is an integer from 1 to 1000.
pageNum	number Example: pageNum=1 The page number for pagination, used in conjunction with the pageSize parameter. For example, pageSize=1000&pageNum=2 will return records from 1001 to

	2000.
sensitiveData	string Example: sensitiveData=true Fill in "true" to get sensitive member data such as phone number and email address.

Request samples

- cURL

```
curl -X GET \
  "https://aitable.ai/fusion/v1/spaces/{spaceId}/teams/{unitId}/members?sensitiveData=true" \
  -H "Authorization: Bearer {Your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    • "pageNum": 1,
    • "pageSize": 100,
    • "total": 500,
    • "members": []
  }
}
```

List sub teams

This interface is used to get the list of teams under the specified team.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/teams/{unitId}/children>
- Request method: **GET**
- Request header must contain: **Authorization: Bearer {Your API Token}**

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [List teams](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
unitId required	string Example: X9vJ6R2qFzL8sK1m VxZcPwNtY3gT5yD Team's unitId

query Parameters

pageSize	number Example: pageSize=100 The number of teams to return per page. The default is to return 100 teams per
----------	---

	page. The valid range for this parameter is an integer from 1 to 1000.
pageNum	number Example: pageNum=1 The page number for pagination, used in conjunction with the pageSize parameter. For example, pageSize=1000&pageNum=2 will return records from 1001 to 2000.

Request samples

- cURL

```
curl -X GET \
  "https://aitable.ai/fusion/v1/spaces/{spaceId}/teams/{unitId}/children" \
  -H "Authorization: Bearer {Your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
```

- "success": true,
- "code": 200,
- "message": "SUCCESS",
-

```

    "data": {
      ○ "pageNum": 1,
      ○ "pageSize": 100,
      ○ "total": 500,
      ○ "teams": []
    }
  }
}

```

Create a team

This interface is used to create a team.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/teams>
- Request method: **POST**
- Request header must contain:

- **Authorization:** Bearer {Your API Token}
- **Content-Type:** application/json

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [Create a team](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
---------------------	---

Request Body schema: application/json

Request body structure

name required	string Team's name
------------------	---------------------------

sequence	number The sorting order of the team at the current hierarchy level. In the Contacts, teams are sorted in ascending order based on this sequence number. If there are duplicate sequence numbers within the same hierarchy level, the teams will be sorted in ascending order based on their creation time.
parentUnitId	string The unitId of the parent team to which the team belongs.
roles	Array of strings Roles associated with the member.

Request samples

- Payload
- cURL

Content type
application/json

```
{
```

- "name": "Team A",
- "sequence": 1,

- "parentUnitId": "bD3fT4cL9wZ5mN8xSsK7qVvRjXhGpY",
-
- "roles": [
 - "gP5zF7xWlmc2nQ4sXrKjV8bT6tL9yH"
-]

```
}

```

Response samples

- 201

Content type
application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    • "unitId": "X9vJ6R2qFzL8sK1mVxZcPwNtY3gT5yD",
    • "name": "Team A",
    • "sequence": 1,
    • "parentUnitId": "bD3fT4cL9wZ5mN8xSsK7qVvRjXhGpY",
    • "roles": []
  }
}
```

Update a team

This interface is used to update a team.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/teams/{unitId}>
- Request method: **PUT**
- Request header must contain:
 - **Authorization:** Bearer {Your API Token}
 - **Content-Type:** application/json

Example requests for cURL is in the area on the right for your reference. The request body includes the properties and corresponding values to be updated in the team. Only the explicitly specified properties will be updated, while the properties that are not specified will retain their old values.

If you need more detailed operation guidance, you can read the [Update a team](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
unitId required	string Example: zJ6TuQvH2RtNfSx9e Y7XKgD1oWcE5pV The unitId of the team to be updated.

Request Body schema: application/json

Request body structure

name	string Team's name
sequence	number The sorting order of the team at the current hierarchy level. In the Contacts, teams are sorted in ascending order

	based on this sequence number. If there are duplicate sequence numbers within the same hierarchy level, the teams will be sorted in ascending order based on their creation time.
parentUnitId	string The unitId of the parent team to which the team belongs.
roles	Array of strings Roles associated with the member.

Request samples

- Payload
- cURL

Content type
application/json

```
{
  • "name": "Team A",
  • "sequence": 1,
  • "parentUnitId": "bD3fT4cL9wZ5mN8xSsK7qVvRjXhGpY",
  •
  "roles": [
    • "gP5zF7xW1mC2nQ4sXrKjV8bT6tL9yH"
  • ]
}
```


Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  •  
    "data": {  
  
      ○ "unitId": "X9vJ6R2qFzL8sK1mVxZcPwNtY3gT5yD",  
      ○ "name": "Team A",  
      ○ "sequence": 1,  
      ○ "parentUnitId": "bD3fT4cL9wZ5mN8xSsK7qVvRjXhGpY",  
      ○ "roles": []  
    }  
  }  
}
```

Delete a team

This interface is used to delete a team.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/teams/{unitId}>
- Request method: DELETE
- Request header must contain:

- Authorization: Bearer {Your API Token}

If you need more detailed operation guidance, you can read the [Delete a team](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string
---------------------	--------

	Example: spcjXzqVrjaP3 Space ID
--	---

query Parameters

unitId required	string Example: unitId=zJ6TuQvH2RtNfSx9eY7XKgD1oWcE5pV The unitId of the team to be deleted.
--------------------	---

Request samples

- cURL

```
curl -X DELETE \
'https://aitable.ai/fusion/v1/spaces/{spaceId}/teams/{unitId}' \
-H 'Authorization: Bearer {Your API Token}'
```

Response samples

- 200

Content type
application/json

```
{
  "success": true,
  "code": 200,
  "message": "SUCCESS"
}
```

Role

The data structure of the Role is as follows.

Properties	Type	Description	Example Value
unitId	string	Role's unitId	"sZ6gJ9L2HxP5XW1fRtNwE4zKqVcY7yM"
name	string	Role's name	"Finance"
sequence	integer	The sorting order of roles starts from 2000 and increases incrementally, such as "2001, 2002, 2003". The sorting sequence of roles can have duplicates, and if there are duplicates, the roles are further sorted in ascending order based on their creation time.	2001

List units under the role

This interface is used to get the members and teams associated with the role.

- Request address:
<https://aitable.ai/fusion/v1/spaces/{spaceId}/roles/{unitId}/units>
- Request method: **GET**
- Request header must contain: **Authorization: Bearer {Your API Token}**

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [List units under the role](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

--	--

spaceId required	string Example: spcjXzqVrjaP3 Space ID
unitId required	string Example: gP5zF7xW1mC2nQ4 sXrKjV8bT6tL9yH Role's unitId

query Parameters

sensitiveData	string Example: sensitiveData=true Fill in "true" to get sensitive member data such as phone number and email address.
---------------	---

Request samples

- cURL

```
curl -X GET \
  "https://aitable.ai/fusion/v1/spaces/{spaceId}/roles/{unitId}/units?
  sensitiveData=true" \
  -H "Authorization: Bearer {Your API Token}"
```

Response samples

- 200

Content type

application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    ○ "members": [],
    ○ "teams": []
  • }
}
```

List roles

This interface is used to get the list of roles in the space.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/roles>
- Request method: GET
- Request header must contain: Authorization: Bearer {Your API Token}

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [List roles](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
---------------------	---

query Parameters

pageSize	number Example:
----------	--------------------

	pageSize=100 The number of roles to return per page. The default is to return 100 roles per page. The valid range for this parameter is an integer from 1 to 1000.
pageNum	number Example: pageNum=1 The page number for pagination, used in conjunction with the pageSize parameter. For example, pageSize=1000&pageNum=2 will return records from 1001 to 2000.

Request samples

- cURL

```
curl -X GET \
  "https://aitable.ai/fusion/v1/spaces/{spaceId}/roles" \
  -H "Authorization: Bearer {Your API Token}"
```

Response samples

- 200

Content type
application/json

```
{
```

```

• "success": true,
• "code": 200,
• "message": "SUCCESS",
•
  "data": {
    "pageNum": 1,
    "pageSize": 100,
    "total": 500,
    "roles": []
  }
}

```

Create a role

This interface is used to create a role.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/roles>
- Request method: `POST`
- Request header must contain:

- `Authorization: Bearer {Your API Token}`
- `Content-Type: application/json`

Example requests for cURL is in the area on the right for your reference.

If you need more detailed operation guidance, you can read the [Create a role](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
---------------------	---

Request Body schema: `application/json`

Request body structure

name required	string Role's name
sequence	number The sorting order of roles starts from 2000 and increases incrementally, such as "2001, 2002, 2003". The sorting sequence of roles can have duplicates, and if there are duplicates, the roles are further sorted in ascending order based on their creation time.

Request samples

- Payload
- cURL

Content type
application/json

```
{
  • "name": "Finance",
  • "sequence": 2001
}
```

Response samples

- 201

Content type

application/json

```
{
  • "success": true,
  • "code": 200,
  • "message": "SUCCESS",
  •
  "data": {
    • "unitId": "gP5zF7xWlmC2nQ4sXrKjV8bT6tL9yH",
    • "name": "Finance",
    • "sequence": 2001
  • }
}
```

Update a role

This interface is used to update a role.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/roles/{unitId}>
- Request method: **PUT**
- Request header must contain:
 - **Authorization:** Bearer {Your API Token}
 - **Content-Type :** application/json

Example requests for cURL is in the area on the right for your reference. The request body includes the properties and corresponding values to be updated in the role. Only the explicitly specified properties will be updated, while the properties that are not specified will retain their old values.

If you need more detailed operation guidance, you can read the [Update a role](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3
---------------------	-------------------------------------

	Space ID
unitId required	string Example: kD8tPcZ3fYxSjV9qW vL5X2TmQbN1nR6 The unitId of the role to be updated.

Request Body schema: application/json

Request body structure

name	string Role's name
sequence	number The sorting order of roles starts from 2000 and increases incrementally, such as "2001, 2002, 2003". The sorting sequence of roles can have duplicates, and if there are duplicates, the roles are further sorted in ascending order based on their creation time.

Request samples

- Payload
- cURL

Content type
application/json

```
{  
  
  • "name": "Finance",  
  • "sequence": 2001  
}
```

Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS",  
  •  
    "data": {  
  
      • "unitId": "gP5zF7xW1mC2nQ4sXrKjV8bT6tL9yH",  
      • "name": "Finance",  
      • "sequence": 2001  
    }  
}
```

Delete a role

This interface is used to delete a role.

- Request address: <https://aitable.ai/fusion/v1/spaces/{spaceId}/roles/{unitId}>
- Request method: **DELETE**
- Request header must contain:

- **Authorization:** Bearer {Your API Token}

If you need more detailed operation guidance, you can read the [Delete a role](#).

If you have more complex interface requests, you can refer to the following parameters and combine them by yourself.

path Parameters

spaceId required	string Example: spcjXzqVrjaP3 Space ID
unitId required	string Example: kD8tPcZ3fYxSjV9qW vL5X2TmQbN1nR6 The unitId of the role to be deleted.

Request samples

- cURL

```
curl -X DELETE \  
'https://aitable.ai/fusion/v1/spaces/{spaceId}/roles/{unitId}' \  
-H 'Authorization: Bearer {Your API Token}'
```

Response samples

- 200

Content type
application/json

```
{  
  
  • "success": true,  
  • "code": 200,  
  • "message": "SUCCESS"  
}
```