Selected Topics in Frontiers of Statistics First Assignment

12111620 Yixuan Ding

March 19, 2024

Graph Generation

As the question mentioned: First generate a undirected graph with 100 nodes,the smallest degree of each node is 2, the largest is 20. Also, the degree distribution of the graph is: $p(k) = k^{-2.5}$. After that, randomly select edges and turn them into directed edges, making the graph being directed.
As for code implementation, first define a function named *generate_degree_sequence* to generate a sequence of nodes whose degrees according with demand, then also define a function named *generate_directed_graph* for final graph generation.
The network visualization is shown as:



Figure 1: Network Visualization

PageRank Algorithm Implementation

For the first problem, PageRank algorithm is implemented into graph generated before, with $\beta = 0.85$. Below is the implemented detail, which also define in the code script *calculate_pagerank*:

Algorithm 1 PageRank

```
N ← Number of nodes in graph
Initialize the pagerank of each node 1/N
for _ in range(max_iterations) do
    for node in graph.nodes() do
        sum_pr ← 0
        if graph has neighbor then
            for node in graph's neighbors do
                if node's neighbor is null then
                    Continue
                end if
                sum_pr += node's pagerank / number of node's neighbors
            end for
        else
            sum_pc ← 0
        end if
        new pagerank of node ← (1-β)/N + β * sum_pr
    end for
    if Converge then
        break
    end if
    pagerank ← new_pagerank
end for
```

```
PageRank值:
Node 14: 0.017040120920571705
Node 82: 0.015293414665075418
Node 60: 0.013084040281199227
Node 54: 0.011274999999999999
Node 62: 0.01047899255775792
Node 9: 0.01
Node 15: 0.01
Node 11: 0.01
Node 61: 0.01
Node 17: 0.01
Node 36: 0.009978285882848575
Node 98: 0.009900929695972635
Node 91: 0.009778030660956217
Node 16: 0.009491605120881976
Node 78: 0.009310392994993292
Node 58: 0.009155200212174825
Node 88: 0.007716946717129669
Node 39: 0.007689995035863737
Node 63: 0.007397600034886073
Node 69: 0.0073616124689449905
Node 8: 0.007138687500000002
Node 6: 0.007117853916042166
```

Figure 2: Part of Pagerank Outcome

Conduct the algorithm, then we can get the pagerank for each node, after that, discover the relationship of pagerank and degrees for nodes, which has a correlation coefficient of 0.503. The relationship is shown by the figure below:



Figure 3: Relationship of Pagerank and Degree of nodes

Spam Farm Design

Based on the graph generated before, design a spam farm to simulate an attack to the origin network to boosting the pagerank of the target page. The structure of spamfarm consists of three aspects:

- Accessible Nodes: Composed by the original node of directed graph, which represents the common webpage(harmless)
- Target Page: Page that we want to boost its pagerank by means of adding spam page
- Spam Pages: Harmful pages in the network, aiming for boosting pagerank of target page; need to be detected and removed.



Figure 4: Design of Spamfarm

To discover the relationship of target page's pagerank and the number of spam pages, a figure is shown below:



Figure 5: Relationship of Spam Number and Pagerank of Target Page

It is easy to find that as the number of spam pages growing, the pagerank of target page will become higher.

TrustRank Algorithm Implementation

In order to solve the spam farm situation, trustrank algorithm is introduced and implemented in the following report. Randomly, select 5% percent of the accessible node to be trust node, according to which trustrank of each node is calculated and analyzed.

Algorithm 2 TrustRank

```
seedsize ← 5% amount of number of accessible nodes
Trustvalue ← 1/seedsize
Initialize the trustrank of each node        ▷ Randomly Select trust nodes from accessible nodes
for _ in range(max_iterations) do
    for node in graph.nodes() do
        sum_pr ← 0
        if graph has neighbor then
            for node in graph's neighbors do
                if node's neighbor is null then
                    Continue
                end if
                sum_pr += node's trustrank / number of node's neighbors
            end for
        else
            sum_pc ← 0
        end if
        if node is trust node then
            new trustrank of node ← (1 − β) ∗ trust_value + β ∗ sum_pr
        else
            new trustrank of node ← β ∗ sum_pr
        end if
    end for
    if Converge then
        break
    end if
    trustrank ← new_trustrank
end for
```



Figure 6: Part of Trustrank Outcome

Spam Mass Calculation

By utilizing the trust page, pagerank of the spammed graph is calculated, combined with the trustrank, spammass can be calculated:

$$SpamMass = \frac{P - T}{P}$$

where P denotes pagerank, and T denotes trustrank.
Part of Spam Mass outcome is shown below: It is obvious that spam page has heavier spam mass, which means they are more likely to be spam pages.



Figure 7: Part of Spam Mass Outcome

Appendix

More relevant detailed information you can find in: **Github Repository**