pom文件

```
<dependency>
    <groupId>com.github.rjeschke</groupId>
    <artifactId>txtmark</artifactId>
    <version>0.16</version>
</dependency>
```

[ERROR] Could not resolve dependencies for project com.example:readtime-java:jar:1.0-SNAPSHOT: Could not find artifact com.github.rjeschke:txtmark:jar:0.16 in central (https://repo.maven.apache.org/maven2)

```
<plugin>
    <groupId>org.apache.maven.plugins</groupId>
    <artifactId>maven-compiler-plugins</artifactId>
    <version>3.8.1</version>
    <configuration>
        <source>1.8</source>
        <target>1.8</target>
    </configuration>
</plugin>
```

[ERROR] Source option 5 is no longer supported. Use 6 or later.
[ERROR] Target option 1.5 is no longer supported. Use 1.6 or later.

```
import org.apache.http.client.fluent.Request;
```

[ERROR] src/main/java/StackAPI.java:[1,37] package org.apache.http.client.fluent does not exist

```
@Override
protected T crossover(T parent1, T parent2) {
    double randDouble = 0.5; // Fix: Determine a sensible legacy strategy
(default 0.1)
```

[ERROR] Some problems were encountered while processing the POMs:
[FATAL] Non-parseable POM /home/repos/100SolidJavaDebug2/pom.xml: only whitespace content allowed before start tag and not @ (position: START_DOCUMENT seen @... @1:2) @ line 1, column 2
@

理解有限

```
void testOnWildcards() {
    EventEmitter ee = new EventEmitter(true);
    List<Object> stack = new ArrayList<>();
    Object token = new Object();
```

[ERROR] src/test/java/SyncTestCase.java:[77,27] no suitable constructor found for EventEmitter(boolean)
constructor EventEmitter.EventEmitter() is not applicable
(actual and formal argument lists differ in length)
constructor EventEmitter.EventEmitter(boolean,boolean,int) is not applicable
(actual and formal argument lists differ in length)
constructor EventEmitter.EventEmitter(java.lang.String,boolean,boolean,int) is not applicable
(actual and formal argument lists differ in length)

```
FMFTRLMachine learner = new FMFTRLMachine(fmDim, fmInitDev, L1, L2, L1Fm, L2Fm,
D, alpha, beta, alphaFm, betaFm);
```

[ERROR] src/main/java/RunModelExample.java:[28,33] constructor FMFTRLMachine in class FMFTRLMachine cannot be applied to given types;
required: int,double,double,double,double,double,int,double,double,double,double,double
found: int,double,double,double,double,double,int,double,double,double,double,double
reason: actual and formal argument lists differ in length

```
// DeMoji.java
public class Demoji {
    public static Pattern emojiPattern;
    public static Map<String, String> codeToDescMap;
    …
```

[ERROR] src/main/java/DeMoji.java:[25,8] class Demoji is public, should be declared in a file named Demoji.java

```
public static String encodeUrl(int n, int min_length) {
    UrlEncoder encoder = new UrlEncoder(DEFAULT_ALPHABET, DEFAULT_BLOCK_SIZE);
    return encoder.encodeUrl(n, min_length);
}
public String encodeUrl(int n, int min_length) {
    return enbase(encode(n), min_length);
}
```

[ERROR] src/main/java/ShortUrl.java:[45,19] method encodeUrl(int,int) is already defined in class ShortUrl

```
import RegexExpr;
```

[ERROR] src/main/java/impl/SequenceExpr.java:[3,17] '.' expected

生成不完整

```
Iterator<Map.Entry<String, JsonNode>> fields = jsonNode.fields();
```

[ERROR] src/main/java/Forecast.java:[49,25] package Map does not exist

```
public static void setDerivedUnitsAndConstants() {
    mS = 1e-3 * S;
    uS = 1e-6 * S;
    nS = 1e-9 * S;
    // Magnetic fields and fluxes
```

[ERROR] src/main/java/NumericalUnits.java:[264,23] reached end of file while parsing

语法问题

"next code token" predictors

```
public static String encodeUrl(int n, int min_length) {
    UrlEncoder encoder = new UrlEncoder(DEFAULT_ALPHABET, DEFAULT_BLOCK_SIZE);
    return encoder.encodeUrl(n, min_length);
}

private class UrlEncoder {
    …
```

[ERROR] src/main/java/ShortUrl.java:[36,30] non-static variable this cannot be referenced from a static context

```
System.out.print(clui.c.lightBlue(frame) + " " + clui.c.grey(message) + "\r");

public class Clui {
    private Colorize c;
```

[ERROR] src/main/java/Spinner.java:[29,30] c has private access in Clui
[ERROR] src/main/java/Spinner.java:[29,62] c has private access in Clui

```
root = new UnitNode(new Position("root", "", -1), 0, "");

public abstract class UnitNode {
    protected Position position;
```

[ERROR] src/main/java/Tree.java:[12,16] UnitNode is abstract; cannot be instantiated

```
public static RegexExpr repeated(RegexExpr expr, int exactly) {
    return new RepeatedExpr(expr, exactly, exactly, true);
}
```

[ERROR] src/main/java/RegexExpr.java:[49,16] incompatible types: impl.RepeatedExpr cannot be converted to RegexExpr

```
server.send("HTTP/1.0 " + httpCode + " " + HTTP_CODES.get(httpCode) + "\r\n");
```

[ERROR] src/main/java/Utils.java:[19,20] unreported exception java.io.IOException; must be caught or declared to be thrown

```
public static int[] findDiffStart(String oldSrc, String newSrc) {
    String[] oldLines = oldSrc.split("
");
    String[] newLines = newSrc.split("
");
```

[ERROR] src/main/java/FindDiff.java:[5,42] unclosed string literal
[ERROR] src/main/java/FindDiff.java:[6,1] unclosed string literal
[ERROR] src/main/java/FindDiff.java:[7,42] unclosed string literal
[ERROR] src/main/java/FindDiff.java:[8,1] unclosed string literal

```
public static final String[] VERSION_INFO =.VERSION.split("\\.");
```

[ERROR] src/main/java/AppDirs.java:[6,48] illegal start of expression
[ERROR] src/main/java/AppDirs.java:[6,62] <identifier> expected
[ERROR] src/main/java/AppDirs.java:[6,63] illegal start of type

编码问题

```
System.out.println("🛠 Building image nytimes/blender:" + tag);
```

[ERROR] src/main/java/Build.java:[20,37] unmappable character (0xF0) for encoding US-ASCII