E1.1

```
<dependency>
    <groupId>com.github.rjeschke</groupId>
    <artifactId>txtmark</artifactId>
    <version>0.16</version>
</dependency>
```

[ERROR] Could not resolve dependencies for project com.example:readtime-java:jar:1.0-SNAPSHOT:
Could not find artifact com.github.rjeschke:txtmark:jar:0.16 in central
(https://repo.maven.apache.org/maven2)

E1.2

```
<plugin>
    <groupId>org.apache.maven.plugins</groupId>
    <artifactId>maven-compiler-plugin</artifactId>
    <version>3.8.1</version>
    <configuration>
        <source>1.8</source>
        <target>1.8</target>
    </configuration>
</plugin>
```

[ERROR] Source option 5 is no longer supported. Use 6 or later.
[ERROR] Target option 1.5 is no longer supported. Use 1.6 or later.

E1.3

```
import org.apache.http.client.fluent.Request;
```

[ERROR] src/main/java/StackAPI.java:[1,37] package org.apache.http.client.fluent does not exist

E1.4

```
@Override
protected T crossover(T parent1, T parent2) {
    double randDouble = 0.5; // Fix: Determine a sensible
legacy strategy (default 0.1)
```

[ERROR] Some problems were encountered while processing the POMs:
[FATAL] Non-parseable POM /home/repos/100SolidJavaDebug2/pom.xml: only whitespace content allowed before start tag and not @ (position: START_DOCUMENT seen @... @1:2) @ line 1, column 2 @

E2.1

```
void testOnWildcards() {
    EventEmitter ee = new EventEmitter(true);
    List<Object> stack = new ArrayList<>();
    Object token = new Object();
```

[ERROR] src/test/java/SyncTestCase.java:[77,27] no suitable constructor found for EventEmitter(boolean)
constructor EventEmitter.EventEmitter() is not applicable (actual and formal argument lists differ in length)
constructor EventEmitter.EventEmitter(boolean,boolean,int) is not applicable (actual and formal argument lists differ in length)
constructor EventEmitter.EventEmitter(java.lang.String,boolean,boolean,int) is not applicable (actual and formal argument lists differ in length)

E2.2

```
FMFTRLMachine learner = new FMFTRLMachine(fmDim,
fmInitDev, L1, L2, L1Fm, L2Fm, D, alpha, beta, alphaFm,
betaFm);
```

[ERROR] src/main/java/RunModelExample.java:[28,33] constructor FMFTRLMachine in class FMFTRLMachine cannot be applied to given types;
required: int,double,double,double,double,double,int,double,double,double,double,double
found: int,double,double,double,double,double,int,double,double,double,double
reason: actual and formal argument lists differ in length

E2.3

```
// Filename: DeMoji.java
public class Demoji {
    public static Pattern emojiPattern;
    public static Map<String, String> codeToDescMap;
    ...
```

[ERROR] src/main/java/DeMoji.java:[25,8] class Demoji is public, should be declared in a file named Demoji.java

E2.4

```
    public static String encodeUrl(int n, int min_length) {
        UrlEncoder encoder = new UrlEncoder(DEFAULT_ALPHABET, DEFAULT_BLOCK_SIZE);
        return encoder.encodeUrl(n, min_length);
    }
    public String encodeUrl(int n, int min_length) {
        return enbase(encode(n), min_length);
    }
```

[ERROR] src/main/java/ShortUrl.java:[45,19] method encodeUrl(int,int) is already defined in class ShortUrl

E2.5

```
import RegexExpr;
```

[ERROR] src/main/java/impl/SequenceExpr.java:[3,17] '.' expected

E3.1

```
Iterator<Map.Entry<String, JsonNode>> fields =
jsonNode.fields();
```

[ERROR] src/main/java/Forecast.java:[49,25] package Map does not exist

E3.2

```
public static void setDerivedUnitsAndConstants() {
    mS = 1e-3 * S;
    uS = 1e-6 * S;
    nS = 1e-9 * S;
    // Magnetic fields and fluxes
```

[ERROR] src/main/java/NumericalUnits.java:[264,23] reached end of file while parsing

E4.1

```
public static String encodeUrl(int n, int min_length) {
    UrlEncoder encoder = new UrlEncoder(DEFAULT_ALPHABET, DEFAULT_BLOCK_SIZE);
    return encoder.encodeUrl(n, min_length);
}
private class UrlEncoder {
    ...
```

[ERROR] src/main/java/ShortUrl.java:[36,30] non-static variable this cannot be referenced from a static context

E4.2

```
System.out.print(clui.c.lightBlue(frame) + " " +
clui.c.grey(message) + "\r");
public class Clui {
    private Colorize c;
    ...
```

[ERROR] src/main/java/Spinner.java:[29,30] c has private access in Clui
[ERROR] src/main/java/Spinner.java:[29,62] c has private access in Clui

E4.3

```
root = new UnitNode(new Position("root", "", -1), 0, "");

public abstract class UnitNode {
    protected Position position;
    ...
```

[ERROR] src/main/java/Tree.java:[12,16] UnitNode is abstract; cannot be instantiated

E4.4

```
// Filename: SteamAPI.java
public abstract class SteamAPI {
    public abstract String getJson(String url);
}
// Filename: SteamUser.java
public class SteamUser extends SteamAPI {
    // Missing the override of abstract method getJson
}
```

[ERROR] src/main/java/SteamUser.java:[1,8] SteamUser is not abstract and does not override abstract method getJson(java.lang.String) in SteamAPI

E4.5

```
public static RegexExpr repeated(RegexExpr expr, int
exactly) {
    return new RepeatedExpr(expr, exactly, exactly, true);
}
```

[ERROR] src/main/java/RegexExpr.java:[49,16] incompatible types: impl.RepeatedExpr cannot be converted to RegexExpr

E4.6

```
server.send("HTTP/1.0 " + httpCode + " " +
HTTP_CODES.get(httpCode) + "\r\n");
```

[ERROR] src/main/java/Utils.java:[19,20] unreported exception java.io.IOException; must be caught or declared to be thrown

E4.7

```
public static int[] findDiffStart(String oldSrc, String newSrc) {
    String[] oldLines = oldSrc.split("
");
```

[ERROR] src/main/java/FindDiff.java:[5,42] unclosed string literal
[ERROR] src/main/java/FindDiff.java:[6,1] unclosed string literal

E4.8

```
public static final String[] VERSION_INFO =.VERSION.split("\\.");
```

[ERROR] src/main/java/AppDirs.java:[6,48] illegal start of expression
[ERROR] src/main/java/AppDirs.java:[6,62] <identifier> expected
[ERROR] src/main/java/AppDirs.java:[6,63] illegal start of type

E5.1

```
System.out.println("🛠 Building image nytimes/blender:" + tag);
```

[ERROR] src/main/java/Build.java:[20,37] unmappable character (0xF0) for encoding US-ASCII