

Working with the R-ArcGIS Bridge

Michael G. Leahy PhD - mleahy@esri.ca
October 17, 2018



Agenda

- **Introduction / Overview**
- **R Scripting basics**
- **Basic use of the R-ArcGIS package in R scripts**
- **Building geoprocessing script tools using R-ArcGIS**


Introduction

An overview of R and the R-ArcGIS bridge


About




- Open Source system for statistical computation and graphics – has become de facto standard language for statisticians
- Over 13,000 packages available from the Comprehensive R Archive Network (about 11,000 a year ago, more than doubled since 2016)
- Powerful language and packages for generating plots and graphics




Source: [StackOverflow](https://stackoverflow.com)



ggvis.rstudio.com




r4stats.com



www.r-bloggers.com

About the R-ArcGIS bridge




<https://r-arcgis.github.io/>

Setup Steps

1. **Install ArcGIS Pro 1.1+ (or ArcGIS 10.3.1+)**
2. **Install R 3.3.2+ or later (<https://www.r-project.org/> or <https://mran.microsoft.com/open>)**
3. **Install the `arcgisbinding` package:**


ArcGIS Pro

Project -> Options -> Geoprocessing



ArcGIS Desktop (e.g., ArcMap)

Run the Install tool in the R Integration toolbox



Detailed Instructions: <https://github.com/R-ArcGIS/r-bridge-install>

Getting Started

- Choose/install an IDE for editing R code:
 - Default R-GUI
 - RStudio
 - Visual Studio / Visual Studio Code
- Learn R basics:
 - <https://highered-esricanada.github.io/r-arcgis-tutorials/>
- R-ArcGIS vignette, manual, samples:
 - <https://r-arcgis.github.io/assets/arcgisbinding-vignette.html>
 - <https://r-arcgis.github.io/assets/arcgisbinding.pdf>
 - <https://github.com/R-ArcGIS/r-sample-tools>

R – Third-party Packages

- **Common packages for plotting and working with data objects:**
 - `ggplot2`, `dplyr`, `tidyr`, ...
- **Statistical modelling:**
 - `car`, `lme4`, `caret`, `mgcv`
- **Spatial data / analysis:**
 - `arccgisbinding`, `sp`, `sf`, `maptools`, `spdp1yr` / `mclust`, `spgwr`, `spatstat`, `lctools` ...
- **CRAN Task Views for categorized view of packages (e.g., 'Spatial')**
 - <https://cran.r-project.org/web/views/>

R Basics

- **Basic Object Types**

Vector, Lists, Matrices, Arrays, Factors, Data Frames, Time Series

- **Basic Data Types:**

Logical, Numeric, Integer, Character, Complex, Raw

- **Variable Assignment:**

*# Creates a numeric vector with one value (= works too... *)*
`x <- 1`

- **Vectors with multiple values:**

Character vector w/ 3 values
`x <- c('apples', 'bananas', 'oranges')`

- **Install/load packages:**

Install CRAN packages (includes dependencies)
`packages.install('sp')`

Load a package in current R workspace
`library(spgwr)`

R – the dplyr package

- A fast and consistent tool for working with tabular data frames
- Adds a variety of essential methods for data frame manipulation

```
filter, arrange, select, mutate,  
summarize, ...
```

- Works with the forward-pipe operator (from the magrittr package), enabling more efficient and concise workflows in R:

```
arranged_data <- survey_data %>% filter(age > 15) %>%  
  select(education, income, age) %>% arrange(income, age)
```

Instead of:

```
filtered_data <- filter(survey_data, age > 15)  
selected_data <- select(filtered_data, education, income, age)  
arranged_data <- arrange(arranged_data, income, age)
```


Tutorial: R Basics

Using the R-ArcGIS Bridge in R

Using the `arccgisbinding` package in R

Loading the library in R

- To start working with `arccgisbinding` in R:
 - > `library(arccgisbinding)`
 - > `arc.check_product()`



```
R Console

> library(arccgisbinding)
*** Please call arc.check_product() to define a desktop license.
> arc.check_product()
product: ArcGIS Pro ( 12.2.0.12813 )
license: Advanced
version: 1.0.1.232
> |
```

Note: only needed for standalone R scripts

Using the `arcgisbinding` package in R

Working with ArcGIS datasets

- Connect to data:

```
gis_data <- arc.open(<path>)
```

- Load data:

```
features_df <- arc.select(gis_data, ...)  
raster_obj <- arc.raster(gis_data, ...)
```

- Convert projections between WKT & Proj.4:

```
arc.fromP4ToWkt("+proj=latlong +datum=wgs84")  
arc.fromWktToP4(gis_data$shapeinfo$WKT)  
arc.fromWktToP4(4326)
```

- Convert data (to `sp`, `sf`, or `raster`):

```
data_sp <- arc.data2sp(features_df)  
data_sf <- arc.data2sf(features_df)  
data_raster <- as.raster(raster_obj)
```

...

- Write data:


```
arc.write(path=<path>, data=data_sp)
```

Tutorial: Using the `arcgisbinding` package in R

Building R Script Tools

R-ArcGIS Script Tools

- Make R statistical functionality accessible to users/applications across the ArcGIS Platform:



R-ArcGIS Script Tools

Basic structure

- Main entry point for an R-script to be used as a script tool:

```
tool_exec <- function(in_params, out_params) { ... <code> ... }
```

- Get/set input and output parameters as named properties:

```
feature_data <- arc.select(arc.open(in_params$in_data), ...)  
out_params$result <- sum(feature_data$values)  
arc.write(path=out_params$out_data, data=feature_data)
```

- Return output parameters when function is finished:

```
return(out_params)
```

R-ArcGIS Script Tools

Messaging & Feedback

- Set progress label/position for UI feedback:

```
arc.progress_label("Analysis in progress...")  
arc.progress_pos(50)
```

- Print messages and warnings in the Geoprocessing window:


```
message(paste(c("Input value: ", in_params$in_val), collapse=""))  
warning("Input parameter not set, defaulting to x ...")
```

- Raise errors (and stop execution):

```
stop("Invalid input data.")
```

R-ArcGIS Script Tools

Toolbox configuration



The image shows the process of configuring a script tool in R-ArcGIS. It includes the Catalog window, the 'New Script' dialog, the 'Tool Properties: Linear-K Tool' dialog, and the 'Geoprocessing' window.

Catalog Window: The 'Toolboxes' folder is expanded, and the 'New' menu is open. The 'Script' option is selected, leading to the 'New Script' dialog.

New Script Dialog: A small dialog box with the text 'Create a new Script tool in the toolbox.'

Tool Properties: Linear-K Tool: A dialog box for configuring the 'Linear-K Tool'. It has tabs for 'General', 'Parameters', and 'Validation'. The 'Parameters' tab is active, showing a table of parameters.

	Label	Name	Data Type	Type	Direction	Category	Filter	D
0	Points	in_points	Feature Layer	Required	Input		Feature Type	
1	Lines	in_lines	Feature Layer	Required	Input		Feature Type	
2	Simulations	num_sims	Long	Required	Input			
3	Output Ta...	out_table	Table	Required	Output			
4	Output Plot	out_plot_png	File	Required	Output		File	
*			String	Required	Input			

Geoprocessing Window: A window titled 'Geoprocessing' showing the 'Linear-K Tool' in the 'Parameters' tab. It lists the tool's parameters and their values.

Tool Properties: Linear-K Tool (General Tab): A dialog box for configuring the 'Linear-K Tool'. It has tabs for 'General', 'Parameters', and 'Validation'. The 'General' tab is active, showing the tool's name, script file, and options.

Tool Properties: Linear-K Tool (Parameters Tab): A dialog box for configuring the 'Linear-K Tool'. It has tabs for 'General', 'Parameters', and 'Validation'. The 'Parameters' tab is active, showing the tool's parameters and their values.

Tool Properties: Linear-K Tool (Validation Tab): A dialog box for configuring the 'Linear-K Tool'. It has tabs for 'General', 'Parameters', and 'Validation'. The 'Validation' tab is active, showing the tool's validation rules.

Tutorial: Build an R Script Tool

Integration of R Script Tools

Using R tools in a complete workflow for analysis

Integration with ArcPy and Model Builder

```
randomGLMScript.py - C:\Users\hlawrence\Documents\ArcGIS\Projects\TorontoUCOct11\randomGLMScript.py (2.7.13)
File Edit Format Run Options Window Help
import arcpy
from arcpy.sa import *

# Check out the ArcGIS Spatial Analyst extension license
arcpy.CheckOutExtension("Spatial")

arcpy.AddMessage("")
toolboxLocation_input = arcpy.GetParameterAsText(0)
samplePointsTable_input = arcpy.GetParameterAsText(1)
trainingPointsTable_input = arcpy.GetParameterAsText(2)
outputCellSize_input = arcpy.GetParameterAsText(3)

arcpy.ImportToolbox(toolboxLocation_input)

arcpy.AddMessage("Starting Process")
samplePoints_internal = 'samplePoints_internal'
probs_internal = 'probabilities_randomforest_glm_internal'
raster_output = 'raster_output'

if arcpy.Exists("probabilities_randomforest_glm_internal"):
    arcpy.Delete_management("probabilities_randomforest_glm_internal")


arcpy.AddMessage("Processing Point Table")
#USED FOR ARCMAP
arcpy.MakeXYEventLayer_management(samplePointsTable_input, "x", "y", samplePoints_internal)
#USED FOR ARCGIS PRO
#arcpy.management.XYTableToPoint(samplePointsTable_input, samplePoints_internal)

arcpy.AddMessage("Calculating Predictions")
arcpy.PredictionTools.probmModelsRGLM(samplePoints_internal, trainingPointsTable_input, probs_internal)

arcpy.AddMessage("Running IDW")
raster_output_internal = Idw(probs_internal, 'prob', outputCellSize_input, 2, RadiusFixed(outputCellSize_input, 0))

arcpy.AddMessage("Creating Output")
arcpy.MakeRasterLayer_management(raster_output_internal, "probabilitySurfaceRGLM")
arcpy.SetParameter(4, "probabilitySurfaceRGLM")
```

Ln: 30 Col: 4



R / R-ArcGIS Resources

- R-ArcGIS Project page:
<https://r-arcgis.github.io>
- R Cheatsheets:
<https://www.rstudio.com/resources/cheatsheets/>
- Package Vignettes – E.g.:
 - R-ArcGIS Bridge (arcgisbinding):
<https://r-arcgis.github.io/assets/arcgisbinding-vignette.html>
 - Geographically Weighted Regression (spgwr):
<https://cran.r-project.org/web/packages/spgwr/vignettes/GWR.pdf>
 - Spatial Inequalities (lctools):
<https://cran.r-project.org/web/packages/lctools/vignettes/SpatialInequalities.pdf>
- Samples, Blogs, GeoNet, Videos/Tutorials, etc.:
 - <https://github.com/R-ArcGIS/r-sample-tools>
 - <https://github.com/R-ArcGIS/CHANS-tools>
 - <https://www.r-bloggers.com/>
 - <https://www.r-project.org/help.html>
 - <https://geonet.esri.com/groups/rstats>
 - <http://hed.esri.ca/resourcefinder/#/search=r/lang=en>
 - <https://learn.arcgis.com/en/projects/analyze-crime-using-statistics-and-the-r-arcgis-bridge/>
 - <https://youtu.be/i6Pc8SwWpyM?list=PLaPDDLTCmy4Z27yCYMJkyxj3WHtFBW08I>

© 2018 Esri Canada Limited. All rights reserved. Trademarks provided under license from Environmental Systems Research Institute, Inc. Other product and company names mentioned herein may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted.