

Code Home

A5: Relational schema, validation and schema refinement

Relational Schema

Relation schemas are specified in the compact notation:

R01	post (<u>id</u> , content NN , date NN DF Today, isVisible NN , points NN DF 0)
R02	answer (<u>postID</u> -> Post, isCorrect NN)
R03	question (<u>postID</u> -> Post, isClosed NN , nViews NN DF 0 CK > 0, tittle NN)
R04	postVote (<u>postID</u> -> Post, <u>posterID</u> -> user, value NN CK (== 1 OR == -1))
R05	postReport (<u>postID</u> -> Post, <u>reporterID</u> -> user, date DF Today)
R06	faqEntry (<u>id</u> , question NN , answer NN)
R07	user (<u>id</u> , username NN UK , pass_token, type NN DF REGULAR, auth_type CK auth_type=0 OR auth_type=1, email UK NN , state NN DF Active, description, img_path, points NN DF 0)
R08	contact (<u>id</u> , Message NN , userID->user, subjectID->subject NN)
R09	subject (<u>id</u> , Name NN UK)
R10	banInfo (<u>id</u> , duration, description NN , initDate DF Today, endDate CK endDate -> endDate != NULL OR isPermanent=True, isPermanent NN , userID->user NN , adminID -> user CK user. isAdmin == True NN)
R11	tagQuestion(<u>tag_id</u> ->tag NN , <u>question_id</u> -> question NN)
R12	tag (<u>id</u> , name NN UK)
R13	team (<u>id</u> , name NN UK)
R14	teamMember (<u>id</u> , name NN UK , title NN , email UK NN , joinDate NN , img_path)
R15	teamToTeamMember (<u>team_id</u> ->team NN , <u>teamMember_id</u> -> teamMember NN)

where UK means UNIQUE KEY, NN means NOT NULL, DF means DEFAULT and CK means CHECK.

Domains

Specification of additional domains:

Today	DATE DEFAULT CURRENT_DATE
User Types	ENUM ('REGULAR', 'ADMINISTRATION')
User States	ENUM ('ACTIVE', 'BANNED')

Functional Dependencies and schema validation

To validate the Relational Schema obtained from the Conceptual Model, all functional dependencies are identified, and the normalization of all relation schemas is accomplished.

Table R01 (post)	
Keys: {id}	
Functional Dependencies	
FD0101	{id} → {content, date, isVisible, points}
NORMAL FORM	BCNF

Table R02 (answer)	
Keys: {postId}	
Functional Dependencies	
FD0201	{postId} → {isCorrect}
NORMAL FORM	BCNF

Table R03 (question)	
Keys: {postId}	
Functional Dependencies	
FD0301	{postId} → {isClosed, nViews, title}
NORMAL FORM	BCNF

Table R04 (postVote)	
Keys: {postId, posterId}	
Functional Dependencies	
FD0401	{postId, posterId} → {value}
NORMAL FORM	BCNF

Table R05 (postReport)	
Keys: {postId, reporterId}	
Functional Dependencies	
FD0501	{postId, reporterId} → {date}
NORMAL FORM	BCNF

Table R06 (faqEntry)	
Keys: {id}	
Functional Dependencies	
FD0601	{id} → {question, answer}
NORMAL FORM	BCNF

Table R07 (user)	
Keys: {id}	
Functional Dependencies	
FD0701	{id} → {username, pass_token, type, auth_type, email, stateId->state, description, img_path, points}
FD0702	{username} → {id, pass_token, type, auth_type, email, stateId->state, description, img_path, points}
FD0703	{email} → {id, username, pass_token, type, auth_type, stateId->state, description, img_path, points}
NORMAL FORM	BCNF

Table R08 (contact)	
Keys: {id}	
Functional Dependencies	
FD0801	{id} → {message, userId->user, subjectId->subject}
NORMAL FORM	BCNF

Table R09 (subject)	
Keys: {id}	
Functional Dependencies	
FD0901	{id} → {name}
NORMAL FORM	BCNF

Table R10 (banInfo)	
Keys: {id}	
Functional Dependencies	
FD1001	{id} → {banDuration, description, initDate, endDate, isPermanent, userId->user NN, adminId->user}
NORMAL FORM	BCNF

Table R11 (tagQuestion)	
Keys: {tag_id, question_id}	
Functional Dependencies	
	(none)
NORMAL FORM	BCNF

Table R12 (tag)	
Keys: {id}	
Functional Dependencies	
FD1201	{id} → {name}
NORMAL FORM	BCNF

Table R13 (team)	
Keys: {id}	
Functional Dependencies	
FD1201	{id} → {name}
NORMAL FORM	BCNF

Table R14 (teamMember)	
Keys: {id}	
Functional Dependencies	
FD1201	{id} → {name, email, img_path, joinDate, title}
NORMAL FORM	BCNF

Table R15 (teamToTeamMember)	
Keys: {team_id, teamMember_id}	
Functional Dependencies	
	(none)
NORMAL FORM	BCNF

As all relations schemas are in the Boyce–Codd Normal Form (BCNF), the relational schema is also in the BCNF and therefore there is no need to be refined using normalization.

SQL Code

Link to SQL code in GitHub:

https://raw.githubusercontent.com/up201504196/lbaw1751/master/CodeHome.sql?token=AYIB0o2mOnG_7qV8jegRuVA0z5_rmUuxks5au172wA%3D%3D

```
CREATE TABLE "User" (
    id SERIAL CONSTRAINT userPK PRIMARY KEY,
    username TEXT NOT NULL UNIQUE,
    type TEXT NOT NULL DEFAULT 'REGULAR',
    pass_token TEXT NOT NULL,
    auth_type INTEGER NOT NULL,
    CHECK (auth_type = 0 OR auth_type = 1),
    email TEXT NOT NULL UNIQUE,
    state TEXT NOT NULL DEFAULT 'ACTIVE',
    description TEXT,
    img_path TEXT NOT NULL DEFAULT '0.png',
    points INTEGER NOT NULL DEFAULT 0
);

CREATE TABLE Subject(
    subjectID SERIAL CONSTRAINT subjectPK PRIMARY KEY,
    name TEXT NOT NULL UNIQUE
);

CREATE TABLE Contact(
    id SERIAL CONSTRAINT contactPK PRIMARY KEY,
    message TEXT NOT NULL,
    userID INTEGER NOT NULL REFERENCES "User",
    subjectID INTEGER NOT NULL REFERENCES Subject
);

CREATE TABLE BanInfo(
    id SERIAL CONSTRAINT banPK PRIMARY KEY,
    duration BIGINT,
    description TEXT NOT NULL,
    isPermanent BOOLEAN NOT NULL ,
    initDate TIMESTAMP WITH TIME zone DEFAULT now(),
    endDate TIMESTAMP WITH TIME zone,
    CHECK (((endDate IS NOT NULL AND endDate > now()) OR
isPermanent IS TRUE )),
    userID INTEGER NOT NULL REFERENCES "User",
    adminID INTEGER NOT NULL REFERENCES "User"
);

CREATE FUNCTION adminCheckProcedure() RETURNS TRIGGER AS $$
BEGIN
    if (not((SELECT type from User where userID = NEW.adminID)='admin'))
THEN
        RAISE EXCEPTION 'User must be admin to ban';
    END IF
    RETURN NEW;
END
$$ language plpgsql;
```

```

CREATE TRIGGER adminCheckTrigger
  BEFORE INSERT OR UPDATE on BanInfo
  EXECUTE PROCEDURE adminCheckProcedure();

CREATE TABLE Tag(
  id          SERIAL CONSTRAINT tagPK PRIMARY KEY,
  name        TEXT NOT NULL UNIQUE
);

CREATE TABLE Post (
  id          SERIAL CONSTRAINT postpk PRIMARY KEY,
  content      text NOT NULL,
  "date"       TIMESTAMP WITH TIME zone DEFAULT now() NOT NULL,
  isVisible    boolean NOT NULL,
  points       INTEGER DEFAULT 0 NOT NULL
);

CREATE TABLE Answer (
  postID       SERIAL REFERENCES Post CONSTRAINT answerpk PRIMARY KEY,
  isCorrect     boolean NOT NULL
);

CREATE TABLE Question (
  postID       SERIAL REFERENCES Post CONSTRAINT questionpk PRIMARY KEY,
  isClosed     boolean NOT NULL,
  nViews       BIGINT NOT NULL DEFAULT 0,
  CHECK (nViews > 0),
  tittle       text NOT NULL
);

CREATE TABLE TagQuestion(
  question_id  SERIAL NOT NULL REFERENCES Question,
  tag_id       SERIAL NOT NULL REFERENCES Tag,
  PRIMARY KEY(question_id, tag_id)
);

CREATE TABLE PostVote (
  postID       SERIAL REFERENCES Post NOT NULL,
  posterID     BIGINT REFERENCES "User" NOT NULL,
  value        INTEGER NOT NULL,
  CHECK (value = 1 OR value = -1),
  PRIMARY KEY(postID, posterID)
);

CREATE TABLE PostReport (
  postID       SERIAL NOT NULL,
  reporterID   BIGINT NOT NULL,
  date         TIMESTAMP WITH TIME zone DEFAULT now() NOT NULL,
  PRIMARY KEY(postID, reporterID)
);

CREATE TABLE FaqEntry (
  id          SERIAL CONSTRAINT postreportpk PRIMARY KEY,
  question     text NOT NULL,
  answer       text NOT NULL
);

```

```

CREATE TABLE Team (
  id          SERIAL CONSTRAINT teamPk PRIMARY KEY,
  name        TEXT NOT NULL
);

CREATE TABLE TeamMember (
  id          SERIAL CONSTRAINT teamMemberPK PRIMARY KEY,
  name        TEXT NOT NULL,
  email       TEXT NOT NULL,
  title       TEXT NOT NULL,
  joinDate    TIMESTAMP WITH TIME ZONE DEFAULT now() NOT NULL,
  img_path    TEXT NOT NULL DEFAULT '0.png'
);

CREATE TABLE TeamToTeamMember (
  teamId      SERIAL,
  teamMemberID SERIAL,
  PRIMARY KEY (teamId,teamMemberID)
);

ALTER TABLE Contact
  ADD CONSTRAINT userID_fk FOREIGN KEY (userID) REFERENCES "User"(id) ON
UPDATE CASCADE;

ALTER TABLE Contact
  ADD CONSTRAINT subjectIDfk FOREIGN KEY (subjectID) REFERENCES
Subject(subjectID) ON UPDATE CASCADE;

ALTER TABLE BanInfo
  ADD CONSTRAINT userIDfk FOREIGN KEY (userID) REFERENCES "User"(id) ON
UPDATE CASCADE;

ALTER TABLE BanInfo
  ADD CONSTRAINT adminIDfk FOREIGN KEY (adminID) REFERENCES "User"(id) ON
UPDATE CASCADE;

ALTER TABLE Answer
  ADD CONSTRAINT postIDfk FOREIGN KEY (postID) REFERENCES Post(id) ON
UPDATE CASCADE;

ALTER TABLE Question
  ADD CONSTRAINT postIDfk FOREIGN KEY (postID) REFERENCES Post(id) ON
UPDATE CASCADE;

ALTER TABLE TagQuestion
  ADD CONSTRAINT question_idFK FOREIGN KEY (question_id) REFERENCES
Question(postID) ON UPDATE CASCADE;

ALTER TABLE TagQuestion
  ADD CONSTRAINT tag_idFK FOREIGN KEY (tag_id) REFERENCES Tag(id) ON UPDATE
CASCADE;

ALTER TABLE PostVote
  ADD CONSTRAINT postIdFk FOREIGN KEY (postID) REFERENCES Post(id) ON
UPDATE CASCADE;

```

```

ALTER TABLE ONLY PostVote
    ADD CONSTRAINT postreport_user_fk FOREIGN KEY (posterID) REFERENCES
    "User"(id) ON UPDATE CASCADE;

ALTER TABLE ONLY PostReport
    ADD CONSTRAINT postreport_post_fk FOREIGN KEY (postID) REFERENCES
    Post(id) ON UPDATE CASCADE;

ALTER TABLE ONLY PostReport
    ADD CONSTRAINT postreport_user_fk FOREIGN KEY (reporterId) REFERENCES
    "User"(id) ON UPDATE CASCADE;

ALTER TABLE ONLY TeamToTeamMember
    ADD CONSTRAINT teamtoteammember_teamid_fk FOREIGN KEY (teamID)
    REFERENCES Team(id) ON UPDATE CASCADE;

ALTER TABLE ONLY TeamToTeamMember
    ADD CONSTRAINT teamtoteammember_teammemberid_fk FOREIGN KEY
    (teamMemberID) REFERENCES TeamMember(id) ON UPDATE CASCADE;

```

Revision History

- Added link to SQL code in GitHub.
- Fixed missing UK (Unique Key) in username from table user.

Group

- Davide Henrique Fernandes da Costa, up201503995@fe.up.pt
- Dinis Filipe da Silva Trigo, up201504196@fe.up.pt
- Diogo Afonso Duarte Reis, up201505472@fe.up.pt
- Tiago José Sousa Magalhães, up201607931@fe.up.pt