

JOINS QUERYS ASSIGNMENT

JOINS QUERYS

1. Find the total number of orders placed

```
select count(o.orderid) from customer c inner join orders o on c.customerid = o.customerid;
```

2. Find the total quantity of products sold

```
SELECT SUM(o.QUANTITY) from customer c inner join orders o on c.customerid = o.customerid;
```

3. Find the total number of products that have been sold (4q)

```
select sum(o.quantity) from product p inner join orders o on p.productid = o.productid;
```

4. Find the total number of orders by region

```
select r.region, count (o.orderid) from region r inner join orders o on r.regionid = o.regionid group by r.region;
```

5. Find the total number of returned orders

```
select count(returned) from returns r inner join orders o on r.orderid = o.orderid;
```

6. Find the total quantity of products sold in each region

```
select p.productname,r.region, sum (o.quantity) from product p inner join orders o on p.productid = o.productid inner
```

7. Find the total number of orders for each product category

```
select category, count (o.orderid) from product p inner join orders o on p.productid = o.productid group by category;
```

8. Find the total number of orders for each product subcategory

```
select subcategory, count (o.orderid) from product p inner join orders o on p.productid = o.productid group by subcategory;
```

9. Find the top 5 products with the highest number of orders

```
select p.productname, count (o.orderid) as total_orders from product p inner join orders o on p.productid = o.productid
```

10. Find the total number of customers who placed at least one order

```
select count (distinct c.customerid) from customer c inner join orders o on c.customerid = o.customerid;
```

11. Find the top 10 customers who placed the highest number of orders

```
select c.customername,c.customerid, count (o.orderid) as total_orders_placed from customer c inner join orders o on c.c
```

12. Find the customers who placed more than 5 orders

```
select c.customername, count(o.orderid) from customer c inner join orders o on c.customerid =o.customerid group by c.cu
```

13. Find the total number of orders for each product

```
select p.productname,count (o.orderid) from product p inner join orders o on p.productid = o.productid group by p.produ
```

14. Find the total quantity sold for each product category

```
select category,sum (o.quantity) from product p inner join orders o on p.productid = o.productid group by category;
```

15. Find the total quantity sold for each product subcategory

```
select subcategory,sum (o.quantity) from product p inner join orders o on p.productid = o.productid group by subcategory;
```

16. Find the top selling product in each category based on total quantity sold

```
select productname, category, sum (o.quantity) as top_selling_product from product p inner join orders o on p.productid
```

17. Find the products that were never sold

```
select p.productid,p.productname from product p left join orders o on p.productid = o.productid where o.productid is nu
```

18. Find the total number of returned orders for each region

```
select r.region, count (o.orderid) from returns rt inner join orders o on rt.orderid = o.orderid inner join region r on
```

19. Find the number of returned orders for each product category

```
select p.category, count (o.orderid) from returns rt inner join orders o on rt.orderid = o.orderid inner join product p
```

20. Find the products with the highest number of returns

```
select p.productname,count (o.orderid) as total_returns from returns r inner join orders o on r.orderid = o.orderid inn
```

21. Find the regions with the highest number of orders

```
select r.region, count (o.orderid) as highest_orders from region r inner join orders o on r.regionid = o.regionid group
```

22. Find the total number of orders placed in each year

```
select extract (year from ('1899-12-30'::date + orderdate))as order_year,count(o.orderid) as total_orders from product
inner join orders o on p.productid = o.productid group by order_year order by order_year;
```

23. Find the total number of orders placed in each month

```
select extract (month from ('1899-12-30'::date + orderdate))as order_month,count(o.orderid) as total_orders from produc
```

24. Find the month with the highest number of orders

```
select extract (month from ('1899-12-30'::date + orderdate))as order_month,count(o.orderid) as total_orders from produc
```

25. Find the total number of orders placed each day

```
select extract (day from ('1899-12-30'::date + orderdate))as order_day,count(o.orderid) as total_orders from product p
inner join orders o on p.productid = o.productid group by order_day order by order_day;
```

26. Find the total number of products sold in each year

```
select extract (year from ('1899-12-30'::date + orderdate))as order_year,sum(o.quantity) as total_sold from product p
inner join orders o on p.productid = o.productid group by order_year order by order_year;
```

27. Find the return percentage for each product (returned orders divided by total orders)

```
select p.productname,
count (distinct o.orderid) as total_orders,
count(distinct r.orderid)as returned_orders,
round(count(distinct r.orderid) * 100.0 / count(distinct o.orderid),2) as returned_percentage
from product p
inner join orders o on p.productid = o.productid
left join returns r on o.orderid = r.orderid group by p.productname order by returned_percentage desc;
```