



# CSS Variables - The var() Function

[< Previous](#)[Next >](#)

## CSS Variables

The `var()` function is used to insert the value of a CSS variable.

CSS variables have access to the DOM, which means that you can create variables with local or global scope, change the variables with JavaScript, and change the variables based on media queries.

A good way to use CSS variables is when it comes to the colors of your design. Instead of copy and paste the same colors over and over again, you can place them in variables.

## The Traditional Way

The following example shows the traditional way of defining some colors in a style sheet (by defining the colors to use, for each specific element):

### Example

```
body { background-color: #1e90ff; }

h2 { border-bottom: 2px solid #1e90ff; }

.container {
  color: #1e90ff;
  background-color: #ffffff;
```

```
padding: 15px;
}

button {
  background-color: #ffffff;
  color: #1e90ff;
  border: 1px solid #1e90ff;
  padding: 5px;
}
```

Try it Yourself »

## Syntax of the var() Function

The **var()** function is used to insert the value of a CSS variable.

The syntax of the **var()** function is as follows:

```
var(--name, value)
```

Value	Description
<i>name</i>	Required. The variable name (must start with two dashes)
<i>value</i>	Optional. The fallback value (used if the variable is not found)

**Note:** The variable name must begin with two dashes (--) and it is case sensitive!

ADVERTISEMENT

# How var() Works

First of all: CSS variables can have a global or local scope.

Global variables can be accessed/used through the entire document, while local variables can be used only inside the selector where it is declared.

To create a variable with global scope, declare it inside the `:root` selector. The `:root` selector matches the document's root element.

To create a variable with local scope, declare it inside the selector that is going to use it.

The following example is equal to the example above, but here we use the `var()` function.

First, we declare two global variables (`--blue` and `--white`). Then, we use the `var()` function to insert the value of the variables later in the style sheet:

## Example

```
:root {  
  --blue: #1e90ff;  
  --white: #ffffff;  
}  
  
body { background-color: var(--blue); }  
  
h2 { border-bottom: 2px solid var(--blue); }  
  
.container {  
  color: var(--blue);  
  background-color: var(--white);  
  padding: 15px;  
}  
  
button {  
  background-color: var(--white);  
  color: var(--blue);  
  border: 1px solid var(--blue);  
  padding: 5px;  
}
```

Try it Yourself »

Advantages of using var() are:

- makes the code easier to read (more understandable)
- makes it much easier to change the color values

To change the blue and white color to a softer blue and white, you just need to change the two variable values:

## Example

```
:root {  
  --blue: #6495ed;  
  --white: #faf0e6;  
}  
  
body { background-color: var(--blue); }  
  
h2 { border-bottom: 2px solid var(--blue); }  
  
.container {  
  color: var(--blue);  
  background-color: var(--white);  
  padding: 15px;  
}  
  
button {  
  background-color: var(--white);  
  color: var(--blue);  
  border: 1px solid var(--blue);  
  padding: 5px;  
}
```

Try it Yourself »

## Browser Support

The numbers in the table specify the first browser version that fully supports the `var()` function.

Function					

var()	49.0	15.0	31.0	9.1	36.0
-------	------	------	------	-----	------

# CSS var() Function

Property	Description
<u>var()</u>	Inserts the value of a CSS variable

[< Previous](#)

[Next >](#)

ADVERTISEMENT



COLOR PICKER



Get certified  
by completing  
a CSS  
course today!



Get started



Launch Your Web Development  
Career in Just 6 Months with  
**W3Schools Bootcamps**

Learn fullstack development from expert  
instructors. All for **\$2995**. Apply now!

Learn more

ADVERTISEMENT

ADVERTISEMENT

ADVERTISEMENT



[Report Error](#)

[Spaces](#)

[Upgrade](#)

[Newsletter](#)

[Get Certified](#)

---

## Top Tutorials

[HTML Tutorial](#)  
[CSS Tutorial](#)  
[JavaScript Tutorial](#)  
[How To Tutorial](#)  
[SQL Tutorial](#)  
[Python Tutorial](#)  
[W3.CSS Tutorial](#)  
[Bootstrap Tutorial](#)



[PHP Tutorial](#)[Java Tutorial](#)[C++ Tutorial](#)[jQuery Tutorial](#)

## Top References

[HTML Reference](#)[CSS Reference](#)[JavaScript Reference](#)[SQL Reference](#)[Python Reference](#)[W3.CSS Reference](#)[Bootstrap Reference](#)[PHP Reference](#)[HTML Colors](#)[Java Reference](#)[Angular Reference](#)[jQuery Reference](#)

## Top Examples

[HTML Examples](#)[CSS Examples](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[Java Examples](#)[XML Examples](#)[jQuery Examples](#)

## Get Certified

[HTML Certificate](#)[CSS Certificate](#)[JavaScript Certificate](#)[Front End Certificate](#)[SQL Certificate](#)[Python Certificate](#)[PHP Certificate](#)[jQuery Certificate](#)[Java Certificate](#)[C++ Certificate](#)[C# Certificate](#)[XML Certificate](#)[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content.

While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.

W3Schools is Powered by W3.CSS.

