



SCS Auto eRating Integration Guide

v1.31

Contents

VERSION HISTORY	5
OVERVIEW	11
CONSUMING THE SCS AUTO ERATING WEB SERVICE.....	12
SCS AUTO ERATING WEB SERVICE SPECIFICATIONS	13
DATA FORMAT	13
GET RATES	14
Request Schema	14
GetRatesRequest Object.....	14
VIN Decoding and Vehicle Information:	21
ProductCollection Object	22
Product Collections.....	23
Filter Object	23
Term/Mileage Filtering	23
Sample GetRates SOAP Request	23
Response Schema	25
GetRatesResponse Object.....	25
ErrorResponse Object.....	26
PlanRates Object.....	27
Plan Object	27
RateClassMoneys Object.....	29
TermMile Object	29
Deductible Object.....	29
Deductibles	30
Rate Object	30
Rating Rules	32

SCS Auto eRating Integration Guide

Tax Object	33
RateDetails Object	33
Rate Details and External Markups.....	34
Options Object	35
Option Object	35
Options and Surcharges.....	36
AdditionalContractInfo Object	36
Additional Contract Information	38
ManufactureWarranty Object	38
Sample GetRates SOAP Response.....	38
Error Messages.....	42
GET TRIMS BY VIN	43
Request Schema	43
GetTrimsByVIN Request	43
Sample GetTrimsByVIN SOAP Request.....	43
Response Schema	43
GetTrimsByVINResponse Object	43
Message Object.....	44
Trims Object	44
Trim Object.....	44
Sample GetTrimsByVIN SOAP Response	44
Error Messages.....	45
GET LIENHOLDERS	46
Request Schema	46
GetLienholderRequest Object.....	46
Sample GetLienholders SOAP Request	46
Response Schema	47
GetLienholderResponse Object.....	47
Message Object.....	47

SCS Auto eRating Integration Guide

Lienholders Object	48
Lienholder Object	48
Sample GetLienholders SOAP Response	48
Error Messages.....	49
APPENDIX	50
Polk Attribute Values	50
Aspiration	50
Cylinders.....	50
Driving Wheels	51
Fuel Type.....	51
Segmentation Code.....	52
Ton Rating.....	53
GVWR.....	55
Asset Type	55
Body Style	56

Version History

Version	Date	Description
1.0	08/01/2009	First Version
1.5	11/23/2009	Added MarkupMax and MarkupMin elements. MaxRetail and MinRetail obsolete.
1.6	7/28/2010	Added additional information to regulated retail rules section.
1.7	10/25/2010	Added * as valid value for NewUsed in rating request.
1.8	11/2/2010	Updated list of product types returned in rating response.
1.9	2/1/2011	Added Discountable to Plan Object.
1.10	6/2/2011	Updated list of ProductTypeCodes in Plan Object.
1.11	6/23/2011	Changed Vehicle Purchase Price from required to optional to match actual functionality.
1.12	7/17/2012	Added Vehicle Purchase Date to request. It has always been part of the schema but was omitted in the documentation. Vehicle Purchase Date now may be required to get rates for some plans.
1.13	8/20/2012	Added ETCH and KEY to list of product type codes

Version	Date	Description
		returned in rating response. Added DeductType = PERCENT. This was to correct an omission, not new functionality.
1.14	1/11/2013	Added “Additional Info” object to rating response.
1.15	10/17/2014	Retail Rate should be displayed for all plans regardless of RegulatedRuleID to allow for an administrator markup to be included in the rate displayed on the menu. Previously, the Net Rate was required to be displayed when RegulatedRuleID was 0 or 5.
1.16	4/20/2015	Corrected typo in FinancedAmount tag.
1.17	10/1/2015	Added Tax fields to rating response in the Rates object.
1.18	6/15/2016	New functionality added to allow rates to be requested for ranges of terms and/or mileages (see Filter object). Also added details on the Product Collection object which is existing functionality but was not included in this document previously.

Version	Date	Description
		Added Error codes to Messages table.
1.19	8/9/2016	Changes GetRates request to support new Polk fields for vehicle attributes. • Added Trim which is conditionally required when rating with either VIN or year/make/model plus vehicle attributes. • Added AssetType, BodyStyle, GVWR, EngineSize, EngineSizeUnit, and CompleteVehicle to list of vehicle attributes for rating using vehicle year, make, model, and vehicle attributes instead of VIN. • Updated valid values for all vehicle attributes since Polk has changed the attribute codes

Version	Date	Description
		for many of the vehicle attribute categories.
1.20	1/18/2017	Added GetTrimByVIN web service. This is a new web service that returns all trim values for a VIN. It can be used to get the value to send in the GetRates request for Trim.
1.21	2/22/2017	Corrected Asset Type values in Appendix . Asset Type code had previously been omitted.
1.22	12/4/2017	Added additional Asset Types to list in Appendix . Added Error Codes for Trim related error messages. Re-added NewUsed to GetRates request. This field had been accidentally removed from this document in v19.
1.23	6/1/2018	Added fields that were missing from schema.
1.24	6/3/2017	Added new fields to the Request : • Additional Base Warranty Term/Miles • Additional Powertrain Warranty Term/Miles

Version	Date	Description
		Added new fields to the Manufacturer Warranty object of the Response: • Additional Base Warranty Term/Miles • Additional Powertrain Warranty Term/Miles • Total Base Warranty Term/Miles • Total Powertrain Warranty Term/Miles Added additional error messages for these new fields.
1.25	6/22/2018	Added new fields to the Request: • Ownership • NADA Add new value in the Response for new Regulated Retail Rule Added additional error messages for these new fields.
1.26	9/5/2018	Added RateDetails object to the Rates object in the GetRates response. New fields: • Remit • Cost

Version	Date	Description
		• Retail • AdminMarkup • BaseMarkup • FIMarkup
1.27	2/7/2019	Added LienNumber to the request.
1.28	7/26/2019	Corrected typos and clarified rating rule explanation .
1.29	8/29/2019	Updated the Rate Details section to include usage details.
1.30	10/22/2020	Added GetLienholders service.
1.31	5/25/2021	Added Lienholder Group Number to the GetLienholders service. (SCS release 9.2.0) Added details to the GetLienholder service to clarify which field are required to get all lienholders.

Overview

The SEFI SCS Auto Platform provides web services that allow external systems (Integration Partners) to provide accurate rates to dealers. Customers of SEFI (Providers) on the SCS Auto platform can enable their dealers and other customers to access their rates and to submit contracts electronically via F&I Presentation and Contracting software that has a certified integration status with SCS Auto.

The integration process requires the following steps:

- 1) System Integration
 - a. SCS Auto eRating Web Service Specifications delivered to Integration Partner
 - b. SEFI sets up Integration Partner on 'DEMO' SCS Auto system
 - c. Integration Partner completes development and testing with the 'DEMO' SCS Auto system.
 - d. SEFI and Integration Partner review and verify integrated eRating functionality.
 - e. Integration Partner promoted to User Acceptance Test and production environment for SCS Auto
- 2) Seller/Dealer Activation
 - a. Integration demonstrated to Provider.
 - b. Provider activates sellers/dealers for use with Integration Partner as needed.

Consuming the SCS Auto eRating Web Service

The following is an overview of the process for consuming SCS Auto eRating Web Services from SEFI. For detailed description of all the XML tags, please refer to the XML Schema and samples in this document.

- Each Integration Partner is assigned a unique login id and a password. Partners authenticate themselves to SEFI using the assigned login id/password. The password differs between production and development environments.
- SEFI provides a URL for each Provider for eRating requests. The URLs differ between development and production environments.
- Each Provider is assigned a unique three-character Provider id. This id referred to in the documentation as a “Provider id” or TPA Code. The TPA Code is required to get rates from the eRating service.
- SCS Auto validates XML requests. If the Request XML string cannot be parsed or has invalid/missing data, the eRating Web Service will return that information in the Error Response section (along with the main response) to help troubleshoot problems. Each error consists of two components: an error number that identifies the error, and an error message that describes the error.

Sample with multiple errors

```
<Response>
  <ErrorResponse>
    <ErrorNumber>101</ErrorNumber>
    <ErrorDescription>Invalid User ID</ErrorDescription>
  </ErrorResponse>
  <ErrorResponse>
    <ErrorNumber>434</ErrorNumber>
    <ErrorDescription>Dealer access is denied</ErrorDescription>
  </ErrorResponse>
</Response>
```

SCS Auto eRating Web Service Specifications

Web Service URL

URLs are of the following format:

`https://<web service URL with virtual folder>/ScsAutoService.asmx`

As noted before, URLs will differ between production, testing, and development environments. They may also vary by provider, although it is possible for multiple providers to have the same URL. The TPA Code and the userid/password credentials determine the provider and the correct environment (production/UAT/development) to return rates from.

Data Format

The following table represents the data formats used in the XML coding (Use to reference the “Format” column in the following XML schema tables)

Data type	Description	Example
X(10)	Characters of max length of 10	ABCDEABCDE
Date	yyyy-mm-dd	2000-12-21
DateTime	yyyy-mm-ddThh:mm:ss	2000-12-21T12:24:40
N(5)	Number, max length of 5	12345
N(8,2)	Number with two decimals, max length of 8.	123456.78
Boolean	Boolean true or false	true

Get Rates

Request Schema

This schema is used to request quotes from SCS Auto eRating from a given SCS Auto provider for a given dealer.

GetRatesRequest Object

Tag	Format	Req/Opt/ Cond	Attributes	Valid values	Description
TpaCode	X(4)	R			Third Party Administrator Code. The three- or four-letter code assigned to each supported SCS Auto provider.
UserId	X(30)	R			User ID. Required for secure access to SCS Auto eRating Web Service.
Password	X(255)	R			Password. Required for secure access to SCS Auto eRating Web Service.
DealerNo	X(18)	R			The dealer number. A unique identified assigned by each SCS Auto provider to a dealer/producer.
SaleDate	Date	R			Date of sale for which the rates are to be returned.
NewUsed	X(1)	R		N – New U – Used * - All eligible plans (both new and used)	Flag used to determine whether to return new or used plans. If * is sent all eligible plans are returned (both new and used vehicle plans).

Tag	Format	Req/Opt/ Cond	Attributes	Valid values	Description
VIN	X(17)	R			Vehicle Identification Number See VIN Decoding and Vehicle Info section for more information. Note: If the VIN is provided, Vehicle year, make, model, and vehicle attributes are not needed for rating.
Trim	X(100)	C			Vehicle trim If the VIN has multiple Trims associated with it, a value is required to uniquely identify the vehicle. The trim must be valid for the VIN. See VIN Decoding and Vehicle Info section for more information. To get valid trim values for a VIN, there is a GetTrimsByVIN web service that can be used to get all valid trim values for a VIN.
VehicleYear	N(4)	C			Only required when VIN is not provided.

Tag	Format	Req/Opt/ Cond	Attributes	Valid values	Description
					See VIN Decoding and Vehicle Info section for more information.
VehicleMake	X(255)	C		From RL POLK's VIN Data	Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
VehicleModel	X(255)	C		From RL POLK's VIN Data	Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
TonRating	X(2)	C		See Appendix for values.	Payload capacity of the vehicle. Trucks only. Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
AspirationCode	X(4)	C		See Appendix for values.	Engine Information. Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
DrivingWheels	X(4)	C		See Appendix for values.	Driving Wheels. Only required when VIN is not provided.

Tag	Format	Req/Opt/ Cond	Attributes	Valid values	Description
					See VIN Decoding and Vehicle Info section for more information.
SegmentationCode	X(4)	C		See Appendix for values.	Segmentation Code. Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
Cylinders	X(4)	C		See Appendix for values.	Cylinders. Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
FuelType	X(4)	C		See Appendix for values.	Fuel Type. Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
GVWR	X(5)	C		See Appendix for values.	Gross Vehicle Weight Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
AssetType	X(25)	C		See Appendix for values.	Only required when VIN is not provided. Asset Type code should be used.

Tag	Format	Req/Opt/ Cond	Attributes	Valid values	Description
					See VIN Decoding and Vehicle Info section for more information.
BodyStyle	X(4)	O		See Appendix for values.	Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
EngineSize	N(7)	O			Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
EngineSizeUnit	X(3)	O		CC CID	CC = cubic centimeters CID = cubic inches Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
CompleteVehicle	X(1)	O		Y = Complete Vehicle N = Incomplete Vehicle	Only required when VIN is not provided. See VIN Decoding and Vehicle Info section for more information.
VehiclePurchasePrice	N(8,2)	O			Vehicle Purchase Price This field may be required in order to get rates for some plans

Tag	Format	Req/Opt/ Cond	Attributes	Valid values	Description
					such as VSC, GAP, and prepaid maintenance.
VehicleOdometer	N(6)	R			Vehicle Odometer Reading at time of sale
InserviceDate	Date	O			In Service Date. This field may be required in order to get rates for some plans such as VSC and prepaid maintenance.
VehiclePurchaseDate	Date	O			Vehicle Purchase Date. This field may be required in order to get rates for some plans such as VSC and prepaid maintenance.
FinancedAmount	N(8,2)	R			Financed Amount. <u>Required to get GAP and Extended Wear and Tear rates.</u> (Note: Some Providers may use these fields for other products besides GAP and EWT)
FinanceTerm	N(3)	R			Finance Term. <u>Required to get GAP and Extended Wear and Tear rates.</u> (Note: Some Providers may use these fields for other products besides GAP and EWT)
FinanceType	X(1)	R		B - Balloon	If it is blank value will be 'ANY'. <u>Required to</u>

Tag	Format	Req/Opt/ Cond	Attributes	Valid values	Description
				L- Lease F- Loan	<u>get GAP and Extended Wear and Tear rates.</u> (Note: Some Providers may use these fields for other products besides GAP and EWT)
FinanceApr	N(2,2)	R			<u>Required to get GAP and Extended Wear and Tear rates.</u> (Note: Some Providers may use these fields for other products besides GAP and EWT)
MSRP	N(8,2)	R			<u>Required to get GAP and Extended Wear and Tear rates.</u> (Note: Some Providers may use these fields for other products besides GAP and EWT)
GIPIteration	Boolean	O		True False	Not used
MonthlyPayment	N(8,2)	O			Not used
DOBBuyer	Date	O			Not used
DOBCoBuyer	Date	O			Not used
FullManufWarrMonths	N(3)	O			Not used
FullManufWarrMiles	N(7)	O			Not used
PowerTrainManufWarrMonths	N(3)	O			Not used
PowerTrainManufWarrMiles	N(7)	O			Not used
Surcharges	String	O			Not used
CultureName	String	O			Not used
AdditionalBaseWarrantyTerm	N(3)	O			Additional Base Warranty Term (Months)

Tag	Format	Req/Opt/ Cond	Attributes	Valid values	Description
AdditionalBaseWarrantyMiles	N(7)	O			Additional Base Warranty Miles
AdditionalPowertrainWarrantyTerm	N(3)	O			Additional Powertrain Warranty Term (Months)
AdditionalPowertrainWarrantyMiles	N(7)	O			Additional Powertrain Warranty Miles
Ownership	X(1)	C		<blank> 'N' – New 'P' – Pre-Owned	Ownership of the vehicle
NADA	N(8,2)	R			May be required for GAP and Extended Wear and Tear rates (Note: Some Providers may use these fields for other products besides GAP and EWT)
LienNumber		O			SCS Lienholder Number
ProductCollection		O	Product Collection		ProductCollection object
Filter		O	Filter		Filter object

VIN Decoding and Vehicle Information:

To get rates the rating request must contain either a VIN or a combination of vehicle year, make, model, trim and vehicle attributes. If the VIN is known, it should be used. F&I Admin uses Polk for VIN decoding and vehicle identification.

When rating using VIN, it may be necessary to send a value for Trim. Our data analysis found that some VINs have more than one Trim value. In cases where the Trim is used to classify a vehicle and there is more than one Trim value associated with a VIN, rates will only be returned if a value for Trim is sent in the rating request. In this case if no value is sent for Trim, an error will be returned with the valid trims for the VIN.

SCS Auto eRating Integration Guide

If the VIN is not available for rating, vehicle year, make, model, trim, and vehicle attributes can be used to get rates. The vehicle attributes are Ton Rating, Aspiration Code, Segmentation Code, Driving Wheels, Fuel Type, GVWR, Asset Type, Body Style, Engine Size (plus unit), and Complete/Incomplete. F&I Admin uses Polk and the values sent in the rating request must match the values that Polk provides to successfully rate a vehicle. Not all vehicle attributes may be necessary to rate all vehicles.

ProductCollection Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
Product					Grouping tag used to allow specifying more than one product in a single request.
Code	N(15)	R		VSC (Vehicle Service Contract); GAP (GAP); MNT (Maintenance); AP (Appearance Protection); PDR (Paintless Dent Repair); LTW (Limited Warranty); RHT (Tire & Wheel); THP (Theft Protection); EWT (Extended Wear & Tear); ETCH (Etch); KEY (Key Replacement); OTH (Other Aftermarket Product)	Note: This is a general list of Product Type Codes. Providers can customize the Product Type Codes they use so other codes not listed here may be used in addition to or instead of the codes listed here.

SCS Auto eRating Integration Guide

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
Description	N(3)	O			Not needed
ExtractPosition	N(6)	O			Not needed.

Product Collections

The Product Collection functionality allows the rates returned by the eRating web service to be limited to just the products specified in the ProductCollection object. For example, if "VSC" is specified as the value for Code in the ProductCollection object, then only rates for VSC will be returned.

Since product codes can vary from provider to provider, you will need the correct product codes for each provider.

Filter Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
TermMin	N(15)	R			Minimum Term Months
TermMax	N(15)	R			Maximum Term Months
MileageMin	N(6)	O			Minimum Term Mileage
MileageMax	N(6)	O			Maximum Term Mileage

Term/Mileage Filtering

The Filter functionality allows the rates returned by the eRating web service to be limited just Term Months and/or Term Mileage specified. Only plans that have the specified term months and/or term mileage will be returned. Filtering can be done using just Term or just Mileage or both.

Sample GetRates SOAP Request

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <GetRates xmlns="http://www.natinc.com/SCSAutoService/">
      <objGetRatesRequest>
        <Trim>string</Trim>
        <DealerNo>string</DealerNo>
        <NewUsed>string</NewUsed>
        <VIN>string</VIN>
        <VehicleYear>int</VehicleYear>
        <VehicleMake>string</VehicleMake>
        <VehicleModel>string</VehicleModel>
        <VehiclePurchasePrice>decimal</VehiclePurchasePrice>
      </objGetRatesRequest>
    </GetRates>
  </soap:Body>
</soap:Envelope>
```

```

<VehicleOdometer>int</VehicleOdometer>
<TonRating>string</TonRating>
<AspirationCode>string</AspirationCode>
<DrivingWheels>string</DrivingWheels>
<SegmentationCode>string</SegmentationCode>
<Cylinders>string</Cylinders>
<GVWR>string</GVWR>
<AssetType>string</AssetType>
<EngineSize>decimal</EngineSize>
<EngineSizeUnit>string</EngineSizeUnit>
<BodyStyle>string</BodyStyle>
<CompleteVehicle>string</CompleteVehicle>
<SaleDate>dateTime</SaleDate>
<FinancedAmount>decimal</FinancedAmount>
<GIPIteration>boolean</GIPIteration>
<MonthlyPayment>decimal</MonthlyPayment>
<FinanceTerm>int</FinanceTerm>
<FinanceType>string</FinanceType>
<InserviceDate>dateTime</InserviceDate>
<DOBBuyer>dateTime</DOBBuyer>
<DOBCoBuyer>dateTime</DOBCoBuyer>
<FuelType>string</FuelType>
<VehiclePurchaseDate>dateTime</VehiclePurchaseDate>
<FullManufWarrMonths>int</FullManufWarrMonths>
<FullManufWarrMiles>int</FullManufWarrMiles>
<PowerTrainManufWarrMonths>int</PowerTrainManufWarrMonths>
<PowerTrainManufWarrMiles>int</PowerTrainManufWarrMiles>
<FinanceApr>decimal</FinanceApr>
<Surcharges>string</Surcharges>
<MSRP>decimal</MSRP>
<NADA>decimal</NADA>
<ProductCollection>
  <Product>
    <Code>string</Code>
    <Description>string</Description>
    <ExtractPosition>int</ExtractPosition>
  </Product>
  <Product>
    <Code>string</Code>
    <Description>string</Description>
    <ExtractPosition>int</ExtractPosition>
  </Product>
</ProductCollection>
<CultureName>string</CultureName>
<AdditionalBaseWarrantyTerm>int</AdditionalBaseWarrantyTerm>
<AdditionalBaseWarrantyMiles>int</AdditionalBaseWarrantyMiles>
<AdditionalPowertrainWarrantyTerm>int</AdditionalPowertrainWarrantyTerm>
<AdditionalPowertrainWarrantyMiles>int</AdditionalPowertrainWarrantyMiles>
<Ownership>string</Ownership>
<LienNumber>string</LienNumber>
</objGetRatesRequest>
<Filter>
  <TermMin>int</TermMin>
  <TermMax>int</TermMax>
  <MileageMin>int</MileageMin>
  <MileageMax>int</MileageMax>
</Filter>

```



```

    </GetRates>
  </soap:Body>
</soap:Envelope>

```

Response Schema

This schema is used by SCS to return the collection of all products along with all rates for each product based on dealer's sale authority and the vehicle information for a given Provider. It also allows the rating engine to optionally return error responses.

GetRatesResponse Object

Tag	Content Items	Format	Description
GetRatesResponse/			
	PlanRates		Collection (array1..N) of PlanRate. This category contains the hierarchical response data which is subdivided by Plan, Term/Mileage, Deductible and Rate
	ErrorResponse		Object contains ErrorResponse definition. See Error Messages section for list of errors.
	ContractKeyData		This information should be ignored. The dealer information is not correct.
	ManufactureWarranties		Collection of ManufactureWarranty. This object provides Manufacturer Warranty information (base, powertrain and emissions warranty term/mileage) that has been configured for that vehicle by the provider (SCS Auto customer) whose rates are being requested. If the provider has not configured manufacturer warranty data for this vehicle, this information will not be returned.

SCS Auto eRating Integration Guide

	QuoteID	N(20)	Unique identifier that identifies the entire collection of rates returned within a single rate response.
	QuoteExpiration	Date	Date when the quote expires. After this date, a contract cannot be created based on the rates issued for this Quote ID.
	AdditionalBase WarrantyTerm	N(3)	Value specified in the eRating request.
	AdditionalBase WarrantyMiles	N(7)	Value specified in the eRating request.
	AdditionalPowertrainWarrantyTerm	N(3)	Value specified in the eRating request.
	AdditionalPowertrainWarrantyMiles	N(7)	Value specified in the eRating request.
	TotalBase WarrantyTerm	N(3)	The sum of the configured Base Warranty (term) plus the Additional Base Warranty (term)
	TotalBase WarrantyMiles	N(7)	The sum of the configured Base Warranty (miles) plus the Additional Base Warranty (miles)
	TotalPowertrainWarrantyTerm	N(3)	The sum of the configured Powertrain Warranty (term) plus the Additional Powertrain Warranty (term)
	TotalPowertrainWarrantyMiles	N(7)	The sum of the configured Powertrain Warranty (miles) plus the Additional Powertrain Warranty (miles)

ErrorResponse Object

Tag	Format	Req/ Opt/ Cond	Valid values	
ErrorNumber	Integer	C		
ErrorCode	String X(30)	C		Error code
ErrorDescription	String X(2000)	C		Error Message. See Error Messages section.

PlanRates Object

Tag	Content Items	Format	Description
PlanRate/			
	Plan		Object contains plan definition.
	RateClassMoneys		Collection (array 1..N) of RateClassMoney.
	AdditionalContractInfos		Collection (array 1..N) of AdditionalContractInfo
	ContractNo		Obsolete. No value will be returned.
	NewUsed		Vehicle Type either N = New or U = used
	ProgramTypeCode		Obsolete. No value will be returned.
	SalesAgentNo		Obsolete. No value will be returned.
	PDFFormNo		Form Number configured in SCS

Plan Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
PlanDescriptions					Not used
ProgramDescriptions					Not used
ProductTypeCode	X(4)	R		VSC – Vehicle Service Contract; GAP – GAP; MNT – Maintenance; AP – Appearance Protection; PDR – Paintless Dent Repair;	Product Type Codes Note: This is a general list of Product Type Codes. Providers are able to customize the Product Type Codes they use so other code not listed here may be returned.

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
				LTW – Limited Warranty; RHT – Tire & Wheel; THP – Theft Protection; EWT – Extended Wear & Tear; ETCH – Etch; KEY – Key Replacement; OTH – Other Aftermarket Product	
ProductTypeDescription	X(255)	R			Product Type Description
PlanCode	X(2)	R			The unique plan code
PlanDescription	X(50)	R			Plan description
ContractType	N(15)	R			Contract type
PlanId	N(15)	R			The unique identification number of plan
RateBook	N(15)	R			Rate book number
OwnershipTypeCode	X(255)	O		B- Balloon L- Lease F- Loan A – Any C- Cash	Values will be returned as configured in SCS at plan level.
ContractPlanName	X(200)	R			Contract Plan Name for plan mapping on contract PDF.
ProgramDescription	X(200)	R			Program Description
ProgramID	N(15)	R			Unique identification number of program

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
Discountable	N(1)	R		1 - Regulated rate is discountable 0 – Not discountable	If the Discountable flag is set to 1, the Retail Price (excluding taxes) for the submitted contract can be less than the Retail Price value sent in the rating response, but not greater.

RateClassMoneys Object

Tag	Content Items	Format	Description
RateClassMoneys/			
	TermMile		Object contains Term Mile definition.
	Deductible		Object contains Deductible definition.
	Rate		Object Containing Rate
	Options		Collection of Options

TermMile Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
TermId	N(15)	R			The unique number of term
Term	N(3)	R			Term
Mileage	N(7)	R			Mileage

Deductible Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
DeductTypeDescriptions					DeductTypeDescriptions object. Contains culture name for display. Currently, this will

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
					always have CultureName = EN-US
DeductId	N(15)	R			The unique identification number of the deductible
DeductAmt	N(5,2)	R		Max value is 1000	Deductible amount
DeductType	X(255)	R		“ ” = Standard; “DISP” = Disappearing; “REDUCING” = Reducing; “PERCENT” = percentage	Deductible type. When deductible type = PERCENT, the value in the DeductAmt field should be displayed as a percent not dollar amount (example: when DeductType = PERCENT and DeductAmt = 50.00, display as 50% not \$50.)
ReducedAmount	N(5,2)	R			Reducing amount, applicable when DeductType is REDUCING.

Deductibles

There are four types of deductibles that can be returned: standard, disappearing, reducing, and percent. Standard deductibles are displayed as just the deductible amount. Disappearing deductibles should be displayed as the amount plus “DISP” or “Disappearing” (example \$100 DISP or \$100 Disappearing). In the rating XML they are denoted by DeductType = DISP. Reducing deductibles should be displayed with the deductible, the amount reduced to, and “Reducing” (example \$200/50 Reducing). Reducing deductibles are denoted in the XML with DeductType = REDUCING and the XML with have a value for ReducedAmount.

Rate Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
BandCode					Not used.
OverrideFlag	Boolean	R		True	Override Flag

SCS Auto eRating Integration Guide

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
				False	
OptionGroupId	N(15)	R			Unique number that identifies option group
RateId	N(15)	R			Unique number that identifies rate
RetailRate	N(8,4)	R			Retail Rate for the product
NetRate	N(8,4)	R			Dealer Cost for the product.
MaxRetailRate	N(8,4)	R			Maximum Retail Rate for the product.
MinRetailRate	N(8,4)	R			Minimum Retail Rate for the product
RegulatedRuleId	N(1)	R		0 3 5 6	Regulated Rule Code defined for the product. See Rating Rules for details. 0 – Non-Regulated Product 3 – Where Retail Rate has to be equal to RetailRate. Markups cannot be applied to this rate. 5 – Where Markup must be between MarkupMin and MarkupMax. 6 – Where the Retail Rate (MaxRetailRate) is not greater than the Amount Financed (FinancedAmount) minus the configured MSRP or NADA %.
PDFFormNo	X(100)	O			Form Number that uniquely identifies the contract form to be used if this quote is used for a contract.
VehicleClass	X(2)	R			Vehicle Class
ExpirationDate	DateTime	R			Expiration Date of the contract if it were to be sold using this quote
ExpirationMileage	N(7)	R			Expiration Mileage of the contract it if were to be sold using this quote Will be 10000 when product type is GAP
MarkupMin	N(8,4)				The minimum amount of markup that must be applied to the net cost for this quote.
MarkupMax	N(8,4)				The maximum amount of markup that can be applied to the net cost for this quote.

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
Tax object					
RateDetails object					See

Rating Rules

SCS rating sends two elements, Net Rate (cost to the seller) and Retail Rate (cost to the customer). In most cases, dealer markup is at the discretion of the seller and the Retail Rate is defined as Net Rate + Markup. In some cases, providers on the SCS platform can restrict the amount of Markup that can be added to the Net Cost. Rules governing the Retail Rate (i.e. the Markup) are sent in the eRating response via the RegulatedRuleID element. There are four possible values that can be sent in the Rating response for the RegulatedRuleID element: 0, 3, 5, and 6.

The normal scenario is when the value of the RegulatedRuleID is 0. In this case, the seller can add any amount of markup to the NetCost to arrive at the Retail Rate to the customer. The Retail Rate from the rating response XML must be displayed to the user since the TPA/provider can add an administrator markup which is included in Retail Rate. Additional Markup can be added to the Retail Rate.

If the value of the RegulatedRuleID is 3, then the seller must sell the contract at the RetailRate value in our rating response AND not add any dealer markup. Most dealers who sell VSCs in FL will get rates with the RegulatedRuleID of 3 since the state of FL requires the dealer sell at the price filed by the provider with the state (which already includes the dealer markup). GAP insurance states (e.g. TX) are the same way.

Note: When displaying rates for plans with RegulatedRuleID = 3, the Retail Rate from the rating response XML should be displayed without any markups applied and the rate should not be editable so that the rate cannot be manually marked up. The Retail Rate plus the cost of any applicable surcharges or options should be displayed.

If the value of the RegulatedRuleID is 5, then the seller Markup must be at least MarkupMin but no more than MarkupMax.

Note: When displaying rates for plans with RegulatedRuleID = 5, the user should be able to apply a markup if it is within the MinRetailRate and MaxRetailRate range. Retail Rate plus the net cost for any applicable options or surcharges should be displayed.

If the value of the RegulatedRuleID is 6, then the seller must sell a contract at a retail rate (MaxRetailRate) that is not greater than the Amount Financed (FinancedAmount) minus the configured MSRP or NADA percentage.

Note: When displaying rates for plans with RegulatedRuleID = 6, the user should be able to specify any Retail rate as long as it is not greater than the Amount Financed (FinancedAmount) minus the configured MSRP or NADA percentage when the GAP plan uses the Regulated Retail rule “Retail cannot be greater than the Amount Financed minus $n\%$ MSRP (New) or $n\%$ NADA (Pre-Owned)”.

Tax Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
NetTaxAmt1	N(8,2)		C		Returned if taxes are configured.
NetTaxAmt2	N(8,2)		C		Returned if taxes are configured.
RetailTaxAmt1	N(8,2)		C		Returned if taxes are configured.
RetailTaxAmt1	N(8,2)		C		Returned if taxes are configured.
TotalRetailTaxAmt	N(8,2)		C		Returned if taxes are configured.
Tax1TaxLabel	X(50)		C		Returned if taxes are configured.
Tax2TaxLabel	X(50)		C		Returned if taxes are configured.

RateDetails Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
Remit	N(8,2)		C		Amount that must be remitted. This is the dealer cost. This value will be the same as the NetRate value, which is what the dealer is expected to remit to the product provide/administrator upon sale of a contract. See full explanation of functionality below.
Cost	N(8,2)		C		This is the F&I manager's cost. Cost = Remit + Admin Markup + Base Markup. When the plan is regulated retail, Cost = remit + base markup. See full explanation of functionality below.
Retail	N(8,2)		C		Retail is the Remit + Total Markup (Advanced + Base Markup + F&I

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
					Markup) See full explanation of functionality below.
AdminMarkup	N(8,2)		C		This is the Advanced Markup amount from SCS. See full explanation of functionality below.
BaseMarkup	N(8,2)		C		Base markup amount defined in the Markup Settings from the SEFI Seller Portal (DAP). See full explanation of functionality below.
FIMarkup	X(50)		C		F&I Markup amount defined in the Markup Settings from the SEFI Seller Portal (DAP). See full explanation of functionality below.

Rate Details and External Markups

If the dealer has markup settings configured in the StoneEagle F&I (SEFI) Seller Portal (DAP), these markup amount will be returned in the RateDetail object. The intent of these markup fields is to provide point of sale and menu partners suggested retail pricing using markups configured on the SEFI DAP. A common scenario in which the use of these fields may be considered is when the plan level markup settings that the SEFI DAP supports is also desired on the menu but they menu does not natively support the creation of such markups by plan. It is strongly recommended that the implementation of these markups be coordinated with SEFI and the product provider/administrator before any dealers start seeing these values on the front end. Otherwise, there is a potential for conflict between the markups that the dealer staff is used to seeing and what is configured on the SEFI DAP. The <RateDetails> object will contain the following fields: Cost, Remit, Retail, AdminMarkup (a.k.a. Advanced Markup), BaseMarkup, and FIMarkup.

- Remit: Amount that must be remitted. This is the dealer cost. This value will be the same as the NetRate value, which is what the dealer is expected to remit to the product provide/administrator upon sale of a contract.
- Cost: This is the F&I manager's cost. In the case where the dealer principal wants to limit what the F&I Manager can see in terms of cost, this field can be used since it does not show the true dealer cost. $Cost = Remit + Admin\ Markup + Base\ Markup$. When the plan is regulated retail, $Cost = remit + base\ markup$.
- Retail: Retail is the $Remit + Total\ Markup (Advanced + Base\ Markup + F\&I\ Markup)$. This is NOT always the same as the RetailRate value and must be treated as suggested Retail price that the F&I manager has discretion to discount.

SCS Auto eRating Integration Guide

- When the plan is regulated retail (e.g. VSCs in Florida), Retail = Remit + Advanced and cannot be discounted. In this scenario Retail = RetailRate.
- AdminMarkup: This is the Advanced Markup amount configured by the administrator in SCS. Typically, this is a dealer pack at the dealer ownership level and is generally not visible to dealership personnel without appropriate permissions. In regulated retail scenarios, this is the only markup added to the Remit/NetRate and it is not discountable in that scenario. In non-regulated retail scenarios, the administrator/product provider's intent is to use this markup to provide a suggested retail price to the dealership personnel. It can be discounted in non-regulated retail scenarios.
- BaseMarkup: Base markup amount defined in the Markup Settings from the SEFI Seller Portal (DAP). Typically, this is the general manager/F&I director markup that is included in the cost to the F&I manager and meant to add to the advanced markup (hence increasing the suggested retail price). This markup is included in the cost to the F&I Manager.
- FIMarkup: F&I Markup amount defined in the Markup Settings from the SEFI Seller Portal (DAP). This is usually the markup that the F&I Manager specifies as the starting point to arrive at the suggested retail price.

Options Object

Tag	Content Items	Format	Description
Options/			
	Option		Collection (array 1..N) of Options.

Option Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
OptionDescriptions					Not used.
OptionId	N(15)	R			ID for this option
Status	N(1)	R		0 - disabled 1 - enabled	Obsolete. This element of the XML is no longer in use.
OptionDesc	X(50)	R			Description of the option
RetailRate	N(5,2)	R			Retail rate of the option
NetRate	N(5,2)	R			Dealer cost of the Option
PremiumRate	N(5,2)				Not used.
CommissionRate	N(5,2)				Not used.

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
AdminRate	N(5,2)				Not used.
IsUsed	Boolean	R			Obsolete. This element of the XML is no longer in use.
IsSurcharge	Boolean	R			Identifies whether the option a surcharge or not. If 'true' then the option is a surcharge.
IsSurchargeOption	Boolean	R			Obsolete. This element of the XML is no longer in use.
PDFFormNo	X(100)	O			Form number
OptionName	X(200)	O			Option Name used to map on contract PDF

Options and Surcharges

Optional coverages and their prices are sent in the Options object. It is possible for each rate to have a different set of options associated with it. These options, when selected by the customer, will increase the cost of the contract by the OptionCost amount. Some options sent in the Options object are mandatory, in which case the value of the IsSurcharge element is True. Such options are called Surcharges, and the cost to the customer must include the cost of that option. For example, if the rate for plan Gold 12/12,000 \$0 Ded is \$388 and there is a surcharge such as 4WD/AWD which is \$100, the rate for the plan that should be displayed is \$488 (\$388 + \$100 surcharge). Surcharges can be determined by looking at the <IsSurcharge> tag in the XML. If it is true, then the option is a surcharge. When displayed on the menu, all applied surcharges should be displayed and not editable.

AdditionalContractInfo Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
FieldOrder	N(1)	R			If there are multiple additional information fields returned, FieldOrder will indicate the order the fields should be displayed on the screen. (Note: At this time there is only one additional field that can be configured so the value will always be '1'.)

SCS Auto eRating Integration Guide

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
FieldLabel	X(50)	R			The field label to display for additional information field.
FieldType	X(12)	R		Valid Values: Alphanumeric Numeric (not currently used) Date (not currently used) Currency (not currently used)	The type of data to be collected in the additional field. (Note: Only 'alphanumeric' will be returned at this time.)
Length	N(4)	R			Maximum length for data collected in additional info field. Length = 0 means that there is no required length. When the length is 0, the only limit is the max length of the field which is 20 characters. If the length is something other than 0, the data collected must length specified to be valid.
Required	Boolean	R		True False	If Required = true, the additional information must be included in the contract when contract request is submitted. If additional information is required and not submitted in contract request, an error will be returned and contract will not be submitted. If Required = false, the additional information should be submitted in the contract request but error will not be returned if the additional information is not included in the contract request.

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
Unique	Boolean	R		True False	Additional information must be a unique value (true) or not required to be unique (false). If Unique = true, validation will occur when contract is submitted and an error will be returned if value is not unique.

Additional Contract Information

The AdditionalContractInfo element will only be returned if the TPA has configured additional information that needs to be collected when a contract is submitted. Each provider can configure one additional piece of data per product type to be collected and sent in the contract request.

ManufactureWarranty Object

Tag	Format	Req/ Opt/ Cond	Attributes	Valid values	Description
Type	X(10)	R		BASE POWERTRAIN EMISSION	Type of warranty BASE POWERTRAIN EMISSION
Term	N(3)	R			Manufacturer Warranty Term
Mile	N(7)	R			Manufacturer Warranty Mileage

Sample GetRates SOAP Response

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetRatesResponse xmlns="http://www.natinc.com/SCSAutoService/">
      <GetRatesResult>
        <PlanRates>
```

SCS Auto eRating Integration Guide

```

<PlanRate>
  <Plan>
    <ProductTypeCode>VSC</ProductTypeCode>
    <ProductTypeDescription>Vehicle Service Contract</ProductTypeDescription>
    <PlanCode>UB</PlanCode>
    <PlanDescription>Basic</PlanDescription>
    <ContractType>10</ContractType>
    <PlanId>2223</PlanId>
    <RateBook>3221</RateBook>
    <OwnershipTypeCode />
    <ContractPlanName>Bronze</ContractPlanName>
    <ProgramDescription>Extended Protection 03</ProgramDescription>
    <ProgramID>1</ProgramID>
  </Plan>
  <RateClassMoneys>
    <RateClassMoney>
      <TermMile>
        <TermId>23</TermId>
        <Term>3</Term>
        <Mileage>3000</Mileage>
      </TermMile>
      <Deductible>
        <DeductId>1</DeductId>
        <DeductAmt>50.0000</DeductAmt>
        <DeductType />
      </Deductible>
      <Rate>
        <BandCode />
        <OverrideFlag>false</OverrideFlag>
        <OptionGroupId>3</OptionGroupId>
        <RateId>493825</RateId>
        <RetailRate>2100</RetailRate>
        <NetRate>2100</NetRate>
        <MaxRetailRate>0.0000</MaxRetailRate>
        <MinRetailRate>0.0000</MinRetailRate>
        <RegulatedRuleId>0</RegulatedRuleId>
        <PDFFormNo />
        <VehicleClass>F</VehicleClass>
      </Rate>
    </RateClassMoney>
  </RateClassMoneys>

```

SCS Auto eRating Integration Guide

```

<ExpirationDate>2008-08-26T00:00:00</ExpirationDate>
<ExpirationMileage>22456</ExpirationMileage>
<MarkupMin>0</MarkupMin>
<MarkupMax>0</MarkupMax>
<Tax>
  <NetTaxAmt1>10.00</NetTaxAmt1>
  <NetTaxAmt2>0.00</NetTaxAmt2>
  <RetailTaxAmt1>10.00</RetailTaxAmt1>
  <RetailTaxAmt2>0.00</RetailTaxAmt2>
  <TotalRetailTaxAmt>10.00</TotalRetailTaxAmt>
  <Tax1TaxLabel>GST</Tax1TaxLabel>
</Tax>
<RateDetails>
  <Remit>50.00</Remit>
  <Cost>50.00</Cost>
  <Retail>150.00</Retail>
  <AdminMarkup>0.00</AdminMarkup>
  <BaseMarkup>0.00</BaseMarkup>
  <FIMarkup>100.00</FIMarkup>
</RateDetails>
</Rate>
<Options>
  <Option>
    <OptionId>2</OptionId>
    <Status>1</Status>
    <OptionDesc>Refinance</OptionDesc>
    <OptionName>Refinance</OptionName>
    <RetailRate>30</RetailRate>
    <NetRate>30</NetRate>
    <PremiumRate>0</PremiumRate>
    <CommissionRate>0</CommissionRate>
    <AdminRate>0</AdminRate>
    <IsUsed>false</IsUsed>
    <IsSurcharge>false</IsSurcharge>
    <IsSurchargeOption>false</IsSurchargeOption>
    <PDFFormNo />
  </Option>
</Options>

```


SCS Auto eRating Integration Guide

```

    </RateClassMoney>
  </RateClassMoneys>
  <AdditionalContractInfos>
    <AdditionalContractInfo>
      <FieldOrder>1</FieldOrder>
      <FieldLabel>Tire/Wheel Info</FieldLabel>
      <FieldType>alphanumeric</FieldType>
      <Required>true</Required>
      <Unique>false</Unique>
    </AdditionalContractInfo/>
  </AdditionalContractInfos>
  <ContractNo />
  <NewUsed>U</NewUsed>
  <ProgramTypeCode />
  <SalesAgentNo />
  <PDFFormNo />
</PlanRate>
</PlanRates>
<ContractKeyData>
  <Gap>
    <DealerNo>ST0316 </DealerNo>
  </Gap>
  <Vsc>
    <DealerNo>BMW0002</DealerNo>
  </Vsc>
  <ProgramTypeCode />
  <SalesAgentNo />
  <PDFFormNo />
</ContractKeyData>
</GetRatesResult>
</GetRatesResponse>
</soap:Body>
</soap:Envelope>

```

Error Messages

Message Type	Error code	Message Text
Error	REQERROR	TPA Code is required.
Error	REQERROR	TPA is invalid.
Error	REQERROR	Authentication Failed. You do not have necessary permission to execute this web method.
Error		Inactive dealer for menu.
Error		Dealer does not exist.
Error	IMP_CNTR_0068	VIN could not be decoded
Error	IMP_CNTR_0069	Either VIN or Asset Type, Year, Make and Model are required
Error	ERATING_TRIMREQ	There are more rates available which require specification of a Trim value. The VIN's available Trims are [Trim1], [Trim2], ... and [Trim5]. Please resubmit the rating request with the Trim specified.
Error	INVALIDTRIM	Trim is invalid for VIN. The VIN's available Trims are [Trim1], [Trim2], ... and [Trim5].
Error	INVDADDLBASEWARR	Additional Base Warranty is invalid, both Term and Mileage must be provided.
Error	ADDLBASETERMMILEREQD	Additional Base Warranty term and mileage specified are not valid for use as an Additional Base Warranty.
Error	INVDADDLPWRWARR	Additional Powertrain Warranty is invalid, both Term and Mileage must be provided.
Error	ADDLPWRTERMMILEREQD	Additional Powertrain Warranty term and mileage specified are not valid for use as an Additional Powertrain Warranty.
Error	INVALID_Ownership	Ownership Condition is invalid.
Error	INCORRECT_Ownership	Ownership is invalid for the Sale Date and VIN/Sale Odometer combination
Error	INVALID_NADA	NADA is invalid

Get Trims By VIN

Request Schema

This web service returns all valid trim values for a VIN.

GetTrimsByVIN Request

Tag	Format	Req/ Opt /Cond	Attribute	Valid values	Description
TpaCode	X(4)	R			Third Party Administrator Code
UserId	X(30)	R			User ID issued to the requesting system
Password	X(255)	R			Password issued to the requesting system
VIN	X(17)	R			VIN used for trim lookup.

Sample GetTrimsByVIN SOAP Request

```

SOAPAction: "http://tempuri.org/ContractService/GetTrimsByVIN"
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
xmlns:scs="http://www.natinc.com/SCSAutoService/">
  <soap:Header/>
  <soap:Body>
    <GetTrimsByVIN>
      <request>
        <UserId>xxxx</UserId>
        <Password>xxxx</Password>
        <TpaCode>xxx</TpaCode>
        <VIN> 1HGCT2B96HA000295</VIN>
      </request>
    </GetTrimsByVIN>
  </soap:Body>
</soap:Envelope>

```

Response Schema

GetTrimsByVINResponse Object

Tag	Content Items	Format	Description
GetTrimsByVINResponse			
	GetTrimsByVINResult		

Tag	Content Items	Format	Description
	ResponseCode		2 = Successful, GetTrimsByVIN passed with warning. 1 = Successful, GetTrimsByVIN passed. 0 = GetTrimsByVIN failed. see Message Object for Type
	Messages	Message Object	Collection of Messages.
	Trims		

Message Object

Tag	Format	Req/Opt/Cond	Valid values	Description
Type	Integer	R	1 – Error 2 – Info 3 – Warning 4 – Success	Message Type
Code	String, X(30)	R		Returns the associated message code with each message text.
Text	String, X(2000)	R		Message Text

Trims Object

Tag	Content Items	Format	Description
Trims/			
	Trim		Collection (array 1..N) of Trims.

Trim Object

Tag	Format	Req/Opt/Cond	Attributes	Valid values	Description
Value	X(50)	R			Trim value

Sample GetTrimsByVIN SOAP Response

```
<?xml version="1.0" encoding="utf-8"?>
```

SCS Auto eRating Integration Guide

```
<soap:Envelope xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetTrimsByVINResponse xmlns="http://www.natinc.com/SCSAutoService/">
      <GetTrimsByVINResult>
        <ResponseCode>0</ResponseCode>
        <Messages/>
        <Trims>
          <Trim>
            <Value>90</Value>
          </Trim>
          <Trim>
            <Value>L5</Value>
          </Trim>
          <Trim>
            <Value>SPORT</Value>
          </Trim>
        </Trims>
      </GetTrimsByVINResult>
    </GetTrimsByVINResponse>
  </soap:Body>
</soap:Envelope>
```

Error Messages

Message Type	Error code	Message Text
Error	rfvTPACode	TPA Code is required.
Error	VD0003	TPA is invalid.
Error	VD0009	Authentication Failed. You do not have necessary permission to execute this web method.
Error	VIN_NOT_ENTER	Vehicle information is missing or not valid.
Information	NO_TRIMS	There are no Trims for the requested VIN.

Get Lienholders

Request Schema

This web service returns a list of lienholders.

GetLienholderRequest Object

Tag	Format	Req/ Opt/ Cond	Attribute	Valid values	Description
TpaCode	X(4)	R			Third Party Administrator Code
UserId	X(30)	R			User ID issued to the requesting system
Password	X(255)	R			Password issued to the requesting system
LienNumber	X(18)	O			Lienholder number used for trim lookup. If lienholder number is not specified all lienholders will be returned.
Verified	Boolean	O		True False	If 'true' then only lienholders marked as 'Verified' will be returned. If 'false' then only lienholders that are not verified will be returned. (Note: to get all lienholders, do not include value for Verified).
DealerNumber	X(18)	O			If passed, the service will return only Lienholders that are associated to the dealer based upon the configuration settings in the system.
LienHolderGroupNumber	X(18)	O			If Lienholder Group number is specified, the service will return the Lienholders in the specified Lienholder Group.

To get all lienholders for a provider, the request just needs to contain UserID, Password, and TPA Code.

Sample GetLienholders SOAP Request

```
<soap:envelope>
  <soap:Header/>
```

```

<soap:Body>
  <GetLienholders>
    <request>
      <UserId>xxxx</UserId>
      <Password>xxxx</Password>
      <TpaCode>xxx</TpaCode>
      <LienNumber>string</LienNumber>
      <Verified>boolean</Verified>
      <DealerNumber>string</DealerNumber>
      <LienHolderGroupNumber>string</LienHolderGroupNumber>
    </request>
  </GetLienholders>
</soap:Body>
</soap:Envelope>

```

Response Schema

GetLienholderResponse Object

Tag	Content Items	Format	Description
GetLienholdersResponse			
	GetLienholderResult		
	ResponseCode		2 = Successful, GetLienholders passed with warning. 1 = Successful, GetLienholders passed. 0 = GetLienholders failed. see Message Object for Type
	Messages	Message Object	Collection of Messages.
	Lienholders		

Message Object

Tag	Format	Req/Opt/Cond	Valid values	Description
Type	Integer	R	1 – Error 2 – Info 3 – Warning 4 – Success	Message Type
Code	String, X(30)	R		Returns the associated message code with each message text.
Text	String, X(2000)	R		Message Text

Lienholders Object

Tag	Content Items	Format	Description
Lienholders/			
	Lienholder		Collection (array 1..N) of Trims.

Lienholder Object

Tag	Format	Req/ Opt/ Cond	Attribut es	Valid values	Description
Number	X(18)				Lienholder Number
Name	X(60)				Lienholder Name
Address1	X(30)				Lienholder Address 1
Address2	X(30)				Lienholder Address 2
City	X(30)				Lienholder City
State	X(2)				Lienholder State
Zip	X(10)				Lienholder ZIP Code
Verified	Boolean			True False	
Preferred	Boolean			True False	
StatementType	X(2)				Statement Type
LienTypeCode	X(4)				Lienholder Type Code
LienHolderGroupNumber	X(18)				Lienholder Group Number

Sample GetLienholders SOAP Response

```

<soap:Envelope>
  <soap:Body>
    <GetLienholdersResponse>
      <GetLienholdersResult>
        <ResponseCode>0</ResponseCode>
        <Messages/>
        <Lienholders>
          <Lienholder>
            <Name>string</Name>
            <Number>string</Number>
            <Address1>string</Address1>
            <Address2>string</Address2>
          </Lienholder>
        </Lienholders>
      </GetLienholdersResult>
    </GetLienholdersResponse>
  </soap:Body>
</soap:Envelope>

```



```

        <City>string</City>
        <State>string</State>
        <Zip>string</Zip>
        <Verified>boolean</Verified>
        <Preferred>boolean</Preferred>
        <StatementType>string</StatementType>
        <LienTypeCode>string</LienTypeCode>
        <LienHolderGroupNumber>string</LienHolderGroupNumber>
    </Lienholder>
</ Lienholders>
</GetLienholdersResult>
</GetLienholdersResponse>
</soap:Body>
</soap:Envelope>

```

Error Messages

Message Type	Error code	Message Text
Error	rfvTPACode	TPA Code is required.
Error	VD0003	TPA is invalid.
Error	VD0009	Authentication Failed. You do not have necessary permission to execute this web method.
Error		Lien Holder does not exist.
Error		Invalid input in Verified.
Information		Lien Holder not found
Information	NoRecordFound	No records found

Appendix

Polk Attribute Values

Aspiration

Code	Aspiration Code Description
S	Supercharged
T	Turbocharged
I	Turbocharged w/ Intercooler
N	Normal
U	Unknown

Cylinders

Code	Cylinders Code Description
0	0 Cylinder
1	1 Cylinder
2	2 Cylinders
3	3 Cylinders
4	4 Cylinders
5	5 Cylinders
6	6 Cylinders
8	8 Cylinders
10	10 Cylinders
12	12 Cylinders
16	16 Cylinders
R	Rotary Engine
U	Unknown

Driving Wheels

Code	Driving Wheels Code Description
4FD	Front Wheel Drive w/4x4
4RD	Rear Wheel Drive w/4x4
AWD	All-Wheel Drive
FWD	Front Wheel Drive
RWD	Rear Wheel Drive
U	Unknown

Fuel Type

Code	Fuel Type Code Description
B	Electric and Gas Hybrid
Y	Electric and Diesel Hybrid
C	Convertible
G	Gas
D	Diesel
E	Electric
F	Flexible
H	Ethanol
M	Methanol
P	Propane
N	Compressed Natural Gas
R	Hydrogen Fuel Cell
U	Unknown

Segmentation Code

Segment	
Code	Segmentation Code Description
0	Luxury Exotic
2	Luxury Full Size SUV
4	Non Luxury Full Size Half Ton Pickup
5	Non Luxury Full Size Half Ton Van
6	Luxury Full Size Half Ton Pickup
7	Non Luxury Full Size 3qtr to 1 Ton Pickup
8	Non Luxury Full Size 3qtr to 1 Ton Van
9	Commercial Truck
A	Non-Luxury Sport
B	Luxury Sport
C	Luxury Mid Size SUV
D	Non-Luxury Traditional Sub Compact
E	Luxury Traditional Sub Compact
F	Non Luxury Traditional Compact
G	Luxury Traditional Compact
H	Non Luxury Traditional Mid Size
I	Luxury Traditional Mid Size
J	Non Luxury Sport Mid Size
K	Non Luxury Traditional Full Size
L	Luxury Traditional Full Size
M	Luxury Prestige Full Size
N	Non Luxury Compact Pickup
O	Non Luxury Compact SUV
P	Non Luxury Compact CUV
Q	Non Luxury Compact Van
S	Luxury Compact CUV
T	Non Luxury Mid Size Pickup
U	Non Luxury Mid Size SUV
V	Non Luxury Mid Size CUV
W	Non Luxury Mid Size Van
Y	Luxury Mid Size CUV
Z	Non Luxury Full Size SUV

Ton Rating

Code	Ton Rating Code Description
A	$\frac{1}{4}$ ton
B	$\frac{1}{2}$ ton
BC	$\frac{1}{2}$ - $\frac{3}{4}$ ton
BD	$\frac{1}{2}$ - 1 ton
BF	$\frac{1}{2}$ - 1 $\frac{3}{4}$ ton
C	$\frac{3}{4}$ ton
D	1 ton
DE	1 – 1 $\frac{1}{2}$ tons
DG	1 -2 tons
E	1 $\frac{1}{2}$ tons
EF	1 $\frac{1}{2}$ - 1 $\frac{3}{4}$ tons
EG	1 $\frac{1}{2}$ - 2 tons
EH	1 $\frac{1}{2}$ - 2 $\frac{1}{2}$ tons
EI	1 $\frac{1}{2}$ - 3 tons
EJ	1 $\frac{1}{2}$ - 3 $\frac{1}{2}$ tons
EM	1 $\frac{1}{2}$ - 5 tons
F	1 $\frac{3}{4}$ tons
FH	1 $\frac{3}{4}$ - 2 $\frac{1}{2}$ tons
FI	1 $\frac{3}{4}$ - 3 tons
FJ	1 $\frac{3}{4}$ - 4 $\frac{1}{2}$ tons
G	2 tons
GH	2 - 2 $\frac{1}{2}$ tons
GI	2 – 3 tons
GJ	2 – 3 $\frac{1}{2}$ tons
GK	2 – 4 tons
GL	2 – 4 $\frac{1}{2}$ tons
GM	2 – 5 tons
GN	2 -6 tons
H	2 $\frac{1}{2}$ tons
HI	2 $\frac{1}{2}$ - 3 tons
HJ	2 $\frac{1}{2}$ - 3 $\frac{1}{2}$ tons
HK	2 $\frac{1}{2}$ - 4 tons
HL	2 $\frac{1}{2}$ - 4 $\frac{1}{2}$ tons
HM	2 $\frac{1}{2}$ - 5 tons

SCS Auto eRating Integration Guide

Code	Ton Rating Code Description
HN	2 ½ - 6 tons
HO	2 ½ - 7 tons
HP	2 ½ - 8 tons
HQ	2 ½ - 9 tons
HR	2 ½ - 10 tons
I	3 tons
IJ	3 tons
IK	3 – 3 ½ tons
IL	3 – 4 tons
IM	3 – 4 ½ tons
IN	3 – 5 tons
IP	3 – 8 tons
J	3 ½ tons
JK	3 ½ - 4 tons
JL	3 ½ - 4 ½ tons
JM	3 ½ - 5 tons
JN	3 ½ - 6 tons
JP	3 ½ - 8 tons
JQ	3 ½ - 9 tons
JR	3 ½ - 10 tons
K	4 tons
KM	4 -5 tons
KN	4 – 6 tons
KO	4 – 7 tons
KP	4 – 8 tons
KQ	4 – 9 tons
KR	4 – 10 tons
L	4 ½ tons
LM	4 ½ - 5 tons
LN	4 ½ - 6 tons
LP	4 ½ - 8 tons
LR	4 ½ - 10 tons
M	5 tons
MN	5 – 6 tons
N	6 tons

Confidential & Proprietary

May not be reproduced or distributed without permission of StoneEagle F&I.

SCS Auto eRating Integration Guide

Code	Ton Rating Code Description
O	7 tons
OP	7 – 8 tons
P	8 tons
R	10 tons and above

GVWR

Code	GVWR Code Description
1	0 - 6,000#
2	6,001 - 10,000#
3	10,001 - 14,000#
4	14,001 - 16,000#
5	16,001 - 19,500#
6	19,501 - 26,000#
8	26,001 - 33,000#
10	33,000# +

Asset Type

Code	Asset Type Code Description
P	Passenger Car
T	Truck
M	Motorcycle
R	RV
A	ATV
B	Boat
G	Generator
LM	Lawn Mower
ME	Marine Engine
MS	Motorcycle/Scooter
PW	Personal Watercraft
S	Snowmobile
TR	Tractor
U	Utility Vehicle

Body Style

Code	Body Style Description	Notes
CC	Commercial Chassis	Passenger Car
CP	Coupe	Passenger Car
CV	Convertible	Passenger Car
HB	Hatchback	Passenger Car
HR	Hearse	Passenger Car
LM	Limousine	Passenger Car
SD	Sedan	Passenger Car
U	Unknown	Passenger Car
WG	Wagon	Passenger Car
BU	Bus Non School	Truck
CG	Van Cargo	Truck
CH	Cab Chassis	Truck
CM	Cement Mixer	Truck
FT	Fire Truck	Truck
GG	Garbage/Refuse	Truck
GL	Gliders	Truck
IC	Incomplete (Strip Chassis)	Truck
IP	Incomplete Pickup	Truck
MH	Motor Home	Truck
PK	Pickup	Truck
PV	Van Passenger	Truck
SB	Bus School	Truck
ST	Straight Truck	Truck
SV	Step Van	Truck
TR	Tractor Truck	Truck
TU	Sport Utility Truck	Truck
UT	Sport Utility Vehicle	Truck
VC	Van Camper	Truck
YY	Cutaway	Truck
AT	ATV	Motorcycle
CO	Competition	Motorcycle
CR	Cruiser	Motorcycle
DT	Dirt Bike	Motorcycle

Confidential & Proprietary

May not be reproduced or distributed without permission of StoneEagle F&I.

Code	Body Style Description	Notes
EN	Enduro	Motorcycle
MN	Mini Bike	Motorcycle
MS	Scooter	Motorcycle
SP	Sport	Motorcycle
TO	Touring	Motorcycle
TR	Traditional	Motorcycle
U	Unknown	Motorcycle
AUT	Auto Transporter	Comm. Trailer
BEV	BEVERAGE	Comm. Trailer
CCH	CONTAIN CHASSIS	Comm. Trailer
CUR	Curtainside	Comm. Trailer
DMP	Dump	Comm. Trailer
DOL	Dolly	Comm. Trailer
FBD	Flatbed	Comm. Trailer
GRN	Grain	Comm. Trailer
HPR	Hopper	Comm. Trailer
LBD	Lowbed	Comm. Trailer
LIV	LIVESTOCK	Comm. Trailer
LOG	LOGGING	Comm. Trailer
ROL	Roll Off	Comm. Trailer
SPE	Special	Comm. Trailer
TNK	Tank	Comm. Trailer
TRN	Transfer	Comm. Trailer
UNK	Unknown	Comm. Trailer
UTL	UTILITY	Comm. Trailer
VAN	VAN	Comm. Trailer