

Software and Cybersecurity Lab

CS445 Lab7

Name: Dipean Dasgupta

ID: 202151188


Task: Exploring Information gathering tools such as nmap and zenmap in Kali linux and setup of metasploitable linux os.

Exploring Nmap and Zenmap


First of all, from the application center, first of all click on **Zenmap**. Here the Ip address that we are targeting is: 45.33.32.156.

1st command: **nmap -O 45.33.32.156**

Results displayed:



Here zenmap found 1 port 30/tcp http which is open. OS detection is also performed in zenmap.



The topology of the scan is shared above.

```
File Actions Edit View Help
nmap -O -T 45.33.32.156
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-10-19 16:01 IST
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.16s latency).
Not shown: 91 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
110/tcp   closed pop3
143/tcp   closed imap
444/tcp   closed snpp
993/tcp   closed imaps
1828/tcp  closed unknown
4899/tcp  closed radmin
8000/tcp  closed http-alt
Device type: bridge|general purpose|specialized
Running (JUST GUESSED): Oracle Virtualbox (91%), QEMU (89%), Casio embedded (86%)
OS cPE: cpe:/o:oracle:virtualbox:cpe:/o:qemu:qemu
Aggressive OS guesses: Oracle Virtualbox (91%), QEMU user mode network gateway (89%), Casio QT-6000 or QT-6100 point-of-sale machine
No exact OS matches for host (test conditions non-ideal).
OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 32.39 seconds
kali@kali:~$
```

Same scan is done in **nmap** and the following was received. 2 open ports and 7 closed ports.

The screenshot shows the 'Host Details' tab in Nmap Zenmap for the host 'ec2-18-218-227-3.us-east-2.compute.amazonaws.com (18.218.227.3)'. The details include:


- Host Status:** Host is up.
- Addresses:** IPv4: 18.218.227.3, IPv6: Not available, MAC: Not available.
- Hostnames:** Name: ec2-18-218-227-3.us-east-2.compute.amazonaws.com, Type: PTR.
- Operating System:** Name: 3Com 4500G switch, Accuracy: High.
- OS Classes:** Type: switch, Vendor: 3Com, OS Family: embedded, OS Generation: Accuracy: High.

As per the OS report, scan was carried out in **3Com 4500G switch** OS.

Scanning All TCP Ports:

Target IP: 45.33.32.156


Command: **nmap -p 1-65535 -T4 45.33.32.156**



In zenmap, scan report shows:

53821 filtered tcp (host unreachable), 97 filtered tcp ports (no-response), 12415 tcp ports (reset)

2 open ports ssh and http.



Topological map.

```
New kali [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
kali@kali ~
(kali@kali)-[~]
$ nmap -p 1-65535 -T4 45.33.32.156
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-10-19 16:59 IST
Warning: 45.33.32.156 giving up on port because retransmission cap hit (6).
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.11s latency).
Not shown: 65528 closed tcp ports (reset)
PORT      STATE      SERVICE
22/tcp    open       ssh
25/tcp    filtered  smtp
80/tcp    open       http
5060/tcp  filtered  sip
9929/tcp  open       nping-echo
15201/tcp filtered  unknown
31337/tcp open       Elite

Nmap done: 1 IP address (1 host up) scanned in 5703.67 seconds

(kali@kali)-[~]
$ ping 45.33.32.156
```

In similar scan by nmap,

4 open ports found providing services: ssh, http, elite, nping echo

65528 ports were closed.

Stealth scan


```
New kali [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
kali@kali ~
Nmap done: 1 IP address (1 host up) scanned in 5703.67 seconds

(kali@kali)-[~]
$ nmap -sS -T4 45.33.32.156
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-10-19 19:09 IST
Stats: 0:00:01 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 0.55% done
Warning: 45.33.32.156 giving up on port because retransmission cap hit (6).
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.11s latency).
Not shown: 994 closed tcp ports (reset)
PORT      STATE      SERVICE
22/tcp    open       ssh
25/tcp    filtered  smtp
80/tcp    open       http
5060/tcp  filtered  sip
9929/tcp  open       nping-echo
31337/tcp open       Elite

Nmap done: 1 IP address (1 host up) scanned in 73.15 seconds

(kali@kali)-[~]
$
```


Stealth scan conducted by nmap, finds the same 4 ports as active.



Stealth scan in **zenmap** also finds the same 4 ports as open.

Target IP: 45.33.32.156


Command: **nmap -sS -T4 45.33.32.156**



Topology map shared.

Metasploitable

Installing Metasploitable:



← Create Virtual Machine

Name and operating system


Please choose a descriptive name and destination folder for the new virtual machine and select the type of operating system you intend to install on it. The name you choose will be used throughout VirtualBox to identify this machine.

Name:


Machine Folder:

Type:

Version:

64 

Allocating Memory and space:



← Create Virtual Machine

Memory size


Select the amount of memory (RAM) in megabytes to be allocated to the virtual machine.

The recommended memory size is **1024 MB**.

MB

4 MB 8192 MB

Next Cancel



← Create Virtual Machine

Hard disk

If you wish you can add a virtual hard disk to the new machine. You can either create a new hard disk file or select one from the list or from another location using the folder icon.

If you need a more complex storage set-up you can skip this step and make the changes to the machine settings once the machine is created.

The recommended size of the hard disk is **8.00 GB**.

☐ Do not add a virtual hard disk


☐ Create a virtual hard disk now

☒ Use an existing virtual hard disk file

RAM: 1GB

Disk Space: 8GB

Login to metasploitable:



```
metasploitable (backup) [running] - Oracle VM VirtualBox
File Machine View Input Devices Help
* Starting periodic command scheduler crond [ OK ]
* Starting Tomcat servlet engine tomcat5.5 [ OK ]
* Starting web server apache2 [ OK ]
* Running local boot scripts (/etc/rc.local)
nohup: appending output to 'nohup.out'
nohup: appending output to 'nohup.out' [ OK ]


Metasploit

Warning: Never expose this VM to an untrusted network!
Contact: msfdev[at]metasploit.com
Login with msfadmin/msfadmin to get started

metasploitable login: msfadmin
Password: _
```

Username: msfadmin

Password: msfadmin



```
File Machine View Input Devices Help
msfadmin@metasploitable:~$ _
```

Successfully logged in to metasploitable.