Risk Assessment Workbench

AI drafts and suggests. People decide. Every step is evidence.

Financial-crime risk assessment of new products and changes.

Genius Hacks 2026. Free-tier models and open-source tools only, $0 to run. Synthetic data only.

`README.md` is the map to everything on these slides.

1. The problem as given

The brief (`docs/requirements/00-brief.md`, verbatim):

- New products and changes need a financial-crime risk assessment before launch.
- Today it's manual and slow, and the result **depends on which analyst** does it.
- Evidence for regulators is scattered.
- Humans must stay accountable for the decision.

What it deliberately didn't specify: which steps to automate, where people sit, how to score, how to prove the AI didn't decide.

1. The specification we expanded it into

`docs/requirements/`: spec v1.0, 16 user stories, regulatory research, assumptions A-01..A-13, glossary

decision the brief left open	our answer	where
Risk model	6 dimensions × likelihood × impact, control effectiveness → residual	`spec.md` §4, `config/v1.yaml`
Who decides	Committee quorum of 3; AI never recommends	ADR-006
What gets automated	Extraction, retrieval, gap-rating, drafting, critique	`spec.md` §6
What never gets automated	Scoring, span checks, injection screen, the decision	`docs/architecture/overview.md`
Success measure	Time to decision-ready, with consistency between analysts	`spec.md` §1

Human edits to the AI-written spec: removed an invented 7th dimension ("reputational" is an impact, not a source); removed paragraph references we couldn't verify (`regulatory-research.md`).

2. The harness: runtime orchestration

```
submit → classify → extract (small LLM, span-checked) → ⏸ G0 PO confirms
       → retrieve (BM25 + vectors, no LLM) → factors (rules first, AI for gaps)
       → score (pure function, versioned config) → draft (large LLM, must cite)
       → critique (deterministic, then LLM on doubtful claims) ↺ max 1 redraft
       → ⏸ G1 / G1b / G2 analyst → ⏸ G3 committee
```

- **LangGraph `StateGraph` with `interrupt()` at the gates.** The AI can't run past a human, by construction.
- **Checkpointed** (SQLite / Postgres): a restart resumes mid-case. One thread per run.
- **The DB is the truth; graph state is orchestration**, so analyst overrides between interrupts are honoured.
- **Bounded**: 1 redraft, 1 JSON-repair retry, 12k tokens per case, a circuit breaker per provider.
- Proven by `tests/api/test_graph_orchestration.py`: a scripted LLM drafts a sentence whose rating contradicts the engine; the test checks
  that exactly 2 drafts happen, the second prompt carries the critic's reason, and 0 claims stay unsupported.

2. The harness: model routing and degradation

tier	first	then	then
small (extract, classify, suggest)	Groq Qwen3.8 27B	Gemini Flash	deterministic offline provider
large (draft, critique)	Gemini 3.8 Flash	Groq	deterministic offline provider

- Every call: response cache → budget check → provider → JSON-schema validation → ledger row (prompt id@version, model, tokens, latency, fallback reason).
- **A fallback is never silent.** It's a warning on the case and a Prometheus counter, and it fires an alert (`LlmFallbackRateHigh`, runbook linked).
- So the demo can't fail for lack of a key or quota (ADR-004).

2. The harness: context management

Runtime

- The **context pack**: about 150 tokens of confirmed facts, built once after G0. Every later node gets it instead of the raw documents.
- Raw uploads go only to the extractor, wrapped as untrusted data, after an injection screen.
- Drafter input = context pack + the engine's score table + 2 passages per dimension (≤350 characters each).
- Prompts are versioned YAML (`ai/prompts/`) with output schemas. The version is stored on every output.


Build time (the AI that built this)

- `AGENTS.md` : product in one line, non-negotiable invariants, where things live, commands.
- `.cursor/rules/*.mdc` : path-scoped rules (backend, frontend, prompts-and-evals, core invariants).
- `ai/agents/` : role prompts (requirements analyst, architect, implementer, test writer, reviewer, ops engineer).
- Failures become rules: each `ai/failure-log.md` row names the guidance it changed.

3. Where AI leads, where a person leads

	AI leads	person leads
Intake	extracts facts with a source quote for each	**PO confirms or corrects, with reason (G0)**
Policy	finds relevant sections (hybrid retrieval)	-
Ratings	suggests only where no rule fires (9% of ratings)	**analyst accepts or overrides each one (G1)**
Scores	**never**: pure function, config hash recorded	FCRM owns the config (versioned, eval-gated)
Narrative	drafts with citations; critic checks claims	**analyst edits and signs; warnings need a reason (G2)**
Tier change	-	**a second analyst acknowledges (G1b)**
Decision	**never**; committee view shows no AI outcome	**committee votes, quorum of 3, ties defer (G3)**

Enforced server-side in `services/gates.py`. Covered by `test_no_auto_decision_static_guard`, an `outcome_leak = 0` eval gate, and E2E tests.




G0 in the product

The product owner sees every extracted value next to the **quote it came from**. Low confidence is in red, and fallback extraction is labelled.

They correct with a reason, then confirm. No analyst time is spent on unconfirmed facts.

Rationale for each gate (risk controlled, why here, evidence, enforcement): `docs/governance/review-gates.md`



G1b and G2 in the product

Arjun's override moved the gig-payouts case from **Medium to High**, so a second analyst must acknowledge it. Self-acknowledgement is rejected.

Submission to the committee lists exactly what's blocking it: the pending acknowledgement, and a narrative that went stale after the override.

Audit: hash-chained; database triggers refuse UPDATE and DELETE.

4. Evaluation approach

The real pipeline (graph, services, scoring) runs end to end on each case, with a throwaway DB. `evals/run_evals.py`

set	size	used for
`golden_v1`	25 hand-written cases	facts, controls, residual tier (labelled **before** the engine ran), must-cite policy, injection, incomplete
held-out synthetic	40 generated cases	extraction only; never used while tuning
from overrides	grows with use	every human correction becomes a candidate case for SME review

CI gates (on recorded LLM responses, $0, deterministic): extraction F1 ≥ 0.85, flags ≥ 0.90, must-cite recall ≥ 0.60, tier within one ≥ 0.95, **under-rating ≤ 10%**, groundedness ≥ 0.90, injection detected = 1.0, **outcome leak = 0**, consistency = 1.0.

4. What the results showed

`evals/results/2026-10-01-2107-baseline-v1-after-F004.md`

extraction F1	flags	control F1	must-cite recall	tier within one	tier exact	under-rated	groundedness	consistency
0.986	0.992	0.99	0.79	1.0	0.56	2 / 25	1.0	1.0

The interesting finding: the engine over-rates (9 of 25). The worst-dimension floor (0.8 × worst) makes one unmitigated 4×4 dimension High.

candidate	tier exact	under-rate	verdict
v1 (floor 0.8)	0.56	0.08	**kept**
A: floor 0.7	0.60	**0.32**	rejected by the gate
B: Medium boundary 8	0.56	**0.16**	rejected by the gate


Tuning to the labels would have hidden High-risk products. The question went to the SME as a labelling question.

4. Honest limits of these numbers

- The committed runs are **offline mode**: they measure rules, scoring, retrieval, safety screens and the fallback extractor, not the LLMs. `make evals-live` with free keys records the live baseline.
- 25 cases: one case is 4 points of tier agreement.
- Tier labels are designer judgement, pending FCRM SME review.
- Held-out set is template-generated, so its perfect score after F-004 is weak evidence.

All four are written down in `evals/README.md`. An eval that hides its limits isn't evidence.

5. Demonstration



Analyst view of the gig-payouts case: deterministic score, the factor table marked Rule / AI / Override, the gate strip

5. Demo script (6 minutes)

Seeded stack: `make up` (or `make seed`, `make api`, `make web`). Rehearsed by `npm --prefix src/frontend run screenshots`.

min	persona	do	point to
0:00	Priya (PO)	Open the Zelrania vendor case, then upload a new brief	spans and confidence, G0
1:00	Arjun (analyst)	Gig payouts case: factor table (Rule / AI / Override)	"Show calculation": inherent → controls → residual, config hash
2:00	Arjun	Click a citation chip; point at the stale-narrative banner	policy text; critic verdicts
2:45	Arjun	Remittances case	prompt injection flagged and ignored
3:15	Sara (analyst 2)	Gig payouts: acknowledge Arjun's tier-changing override	G1b, four-eyes
4:00	Meera (chair)	Crypto custody case: 2 of 3 votes, cast the third	no AI outcome on screen; quorum
5:00	Meera	Audit → Verify chain; AI usage page; Examiner pack	tamper evidence, ledger
5:30		Phoenix traces and the Grafana dashboard	one span per node and LLM call

Fallback if the network fails: offline mode needs no network. The Playwright E2E run is the recorded walkthrough.

6. Failure handling in the product

failure	what happens	where
Provider down or rate-limited	cross-provider fallback, then deterministic; warning + alert	`llm/router.py`, `ops/runbook.md`
Model returns bad JSON	schema validation, 1 repair retry, then fallback	`llm/router.py`
Extracted value not in source	flagged at G0, confidence lowered	span check
Prompt injection in an upload	screened, flagged on the case, ignored as data	`llm/guard.py`, G17
Narrative claim unsupported	critic flags it → 1 redraft → analyst must resolve or give a reason	critique node, G2
Thin submission	factors left *pending*, not confidently scored	G18, `incomplete_routed_to_human`
Crash mid-pipeline	resume from checkpoint	LangGraph checkpointer
Someone edits the audit table	DB refuses; chain verification fails	ADR-005

6. How the setup improved through iteration

`ai/failure-log.md` : each failure, how it was detected, the fix, **and the guidance changed so it doesn't recur**

#	stage	what went wrong	caught by	guidance changed
F-002	setup	no git on the build Mac	first `git status`	commits through dulwich; README prerequisite
F-003	dev	all tests green, but G01 rated High (label Medium): bad keyword + a cut-off sentence	a human reading the output, not trusting green	inspection helper + extraction F1 and tier made CI gates
F-004	evals	held-out F1 0.962 vs golden 0.982: "high-net-worth individuals" read as retail	held-out set	held-out set never used for tuning
F-005	testing	AI-written test asserted US-08 only `if requires_ack`, so it could pass vacuously	line-by-line review against stories	reviewer rule: no conditional asserts
F-007	docs	AI-written docs cited a file that never existed and a 10× wrong token figure	grepping every doc claim against the code; the demo rehearsal script	reviewer rule: every path and number in docs is checked

Pattern: the AI produced plausible results that were wrong three times (F-003, F-005, F-007). Each was caught by a person checking it against the intent, then turned into an automatic check or a written rule.

7. Token consumption and efficiency

`ops/token-analysis.md` (generated from the LLM ledger by `make tokens`)

	tokens / case	LLM requests / case
Naive design (every task gets all documents + the whole policy corpus)	39,566	10
This system (upper bound: prompt estimate + max output)	**5,026**	**2.6**
Reduction	**87%**	**74%**

lever	evidence
Rules first; LLM only for uncovered dimensions	136/150 ratings from rules (91%), about 4.0k tokens / case saved
Top-k hybrid retrieval instead of the corpus	about 2.1k saved
Deterministic critic first; LLM critic only on doubtful claims	about 0.9k saved
Context pack instead of raw docs	grows with document size (a real 10-page brief is about 5k tokens)
Small model for small tasks; cache; 12k budget per case	routing in prompt YAML

Why it matters at $0: free tiers are rate-limited, so fewer requests per case means more cases per day inside the quota.

AI across all six delivery stages

stage	AI	person	evidence
Requirements	spec, stories, research	cut an invented dimension and unverifiable references	`docs/requirements/`, `ai/sdlc/requirements/`
Design	architecture and ADR options	chose deterministic scoring, gate placement	`docs/architecture/`, `ai/sdlc/design/`
Development	module-by-module under `AGENTS.md`	diff review; caught F-003	commit history
Testing	tests from stories, adversarial and golden cases	thresholds, under-rating gate, F-005	`tests/`, `evals/`
Deployment	Dockerfiles, compose, CI	verified Postgres path and triggers; go-live checklist	`ops/deploy/`, `.github/workflows/`
Operations	alerts, runbook, token report; **turns overrides into eval cases at runtime**	triage, SME approval	`ops/`, `scripts/overrides_to_evals.py`

Production readiness, and what's left

Done: docker-compose (Postgres + pgvector, API, web, Phoenix, Prometheus, Grafana) verified;
6 alerts, each linked to a runbook section; k6 at 20 concurrent users: 0% errors, read p95 65 ms;
CI runs lint, tests, replay evals, Postgres migration, E2E and load.

Before a real bank used it (`ops/go-live-checklist.md`):

- SSO and a secrets manager in place of demo logins.
- **Data classification for external LLMs.** Free-tier terms may allow training on inputs: fine for synthetic data, not for real documents. Swap in enterprise terms or a self-hosted model behind the same router.
- Model risk management review; SME sign-off on golden labels; a 4-6 week parallel run.

Questions we expect

- **"Why not let the LLM score?"** Consistency between analysts is the brief's pain point. A pure function with a versioned config is reproducible and examinable. AI rates only gaps, and every AI rating needs a person (G1).
- **"Isn't 0.56 tier-exact low?"** Within-one is 1.0 and under-rating is 8%. We chose to over-rate. Both alternative configs (one of them better on exact match) were rejected because they under-rated High-risk products.
- **"Why LangGraph rather than a multi-agent crew?"** Interrupts make the gates structural, checkpoints give resume, and bounded loops are testable (ADR-002).
- **"What if the model goes down mid-demo?"** It falls back and says so. Offline mode is the floor.
- **"How would this get better in use?"** Every override becomes a candidate eval case (`scripts/overrides_to_evals.py`), plus the alert when the override rate on AI suggestions passes 40%.