

[Go to articles list](#)[RSS](#)

ERD Notations in Data Modeling. Part 6

Crow's Foot Notation



by
Patrycja Dybka
Community Manager at
Vertabelo

Posted: March 31,
2016

[crow's foot](#) | [database design](#)

[database modeling](#) | [notation](#)



The most recognizable characteristic of crow's foot notation (also known as IE notation) is that it uses graphical symbols to indicate the 'many' side of the relationship. The three-pronged 'many' symbol is also how this widely-used notation style got its name. Let's see where crow's foot is placed in the history of data modeling and take a look at its symbols.

History: How Crow's Foot Notation Got Started

The beginning of crow's foot notation dates back to an article by [Gordon Everest](#) (1976, Fifth Computing Conference, IEEE). The notation naming convention was changing; in fact, it had been evolving over several years. When asked by me about the issue, Mr. Everest said:

I called it the "inverted arrow," at the time to distinguish [it] from Bachman's notation. I preferred it to the arrow because it did not imply directionality or a physical access path, and it was visually intuitive, showing manyness. Others then started referring to it as chicken feet (e.g., Carlis textbook¹). I now prefer to call it a FORK, which is short and to the point, and doesn't require the possessive crow's or the longer chicken. In my original paper, the focus was on "Basic data structures explained with a common example"² (the title, which later became chapter 4 in my McGraw Hill text, Database Management, 1986). The use of the notation was incidental though carefully chosen. I like the fork

*since it can easily be represented
in a standard character set as in:*

[X]-----<[Y]

*showing that an individual X can
relate to multiple Ys (and each Y
relates to at most one X).*

Symbols in Crow's Foot Notation


Let's now take a look at the representation of **entities** and **relationships** in crow's foot notation.

Entities

Definition

*An entity is a representation of
a class of object. It can be a
person, place, thing, etc.
Entities usually have attributes
that describe them.*


In crow's foot notation, an entity is represented by a rectangle, with its name on the top. The name is singular (entity) rather than plural (entities).



Attributes

Definition

*An attribute is a property that
describes a particular entity.*



The attribute(s) that uniquely distinguishes an instance of the entity is the **identifier**. Usually, this type of attribute is marked with an asterisk.

Relationships

Definition

*Relationships illustrate the
association between two*


entities. They are presented as a straight line. Usually, each relationship has a name, expressed as a verb, written on the relationship line. This describes what kind of relationship connects the objects.

Note that the mentioned type of relationship is binary. In the Entity-Relationship model, representing a ternary or higher order of relationship is problematic.


Cardinality

Relationships have two indicators. These are shown on both sides of the line.

The first one (often called **multiplicity**) refers to the *maximum* number of times that an instance of one entity can be associated with instances in the related entity. It can be **one** or **many**.



The second describes the *minimum* number of times one instance can be related to others. It can be **zero** or **one**, and accordingly describes the relationship as **optional** or **mandatory**.



The combination of these two indicators is always in a specific order. Placed on the outside edge of the relationship, the symbol of multiplicity comes first. The symbol indicating whether the relationship is mandatory or optional is shown after the symbol of multiplicity.

In crow's foot notation:


A multiplicity of **one** and a **mandatory relationship** is represented by a straight line perpendicular to the relationship line.

A multiplicity of **many** is represented by the three-pronged 'crow-foot' symbol.


An **optional relationship** is represented by an empty circle.

Finally, there are four possible edges to the relationship, illustrated here:

zero or many




one or many



one and only one




zero or one



Relationship degrees make them readable as :


One-to-one



One-to-many



Many-to-many



To compare ERD notations, take a look at :

Chen notation

UML notation

Barker notation

Arrow notation

IDEF1X notation

¹ John Vincent Carlis, Joseph D. Maguire (2001).
 *Mastering Data Modeling: A User-driven Approach

² "BASIC DATA STRUCTURE MODELS EXPLAINED WITH A COMMON EXAMPLE"
 Computing Systems 1976, Proceedings Fifth Texas Conference on Computing Systems, Austin, TX, 1976 October 18-19, pages 39-46. (Long Beach, CA: IEEE Computer Society Publications Office).

Like 5  Tweet



Comments Community

 Login

 Recommend 1  Share

Sort by Best



Join the discussion...

LOG IN WITH




OR SIGN UP WITH DISQUS 

Name




Museera • a year ago
I want to make ERD of Entities (Student, Faculty, Course, Depa Offered Courses) and relationship attributes (marks , grade). I don't know how to represent relationship attributes in crow foot's notation
  • Reply • Share ›



Agnieszka Kozubek Mod 
Museera • a year ago
You can see the attributes under the section "Attributes", they are listed inside the rectangle representing the entity.
  • Reply • Share ›



Museera 
Agnieszka Kozubek • a year ago
Your response is highly appreciated Agnieszka Kozubek. But I don't want to represent attributes of specific entity. Rather, I want to represent attributes that belong to two entities. E.g. marks &

5 Shares

5

grades, these
are the two
attributes that
belong to
course and
student
entities.
And I don't
know where
and how to
represent
them?

◀ ▶ ↺ ↻ 🔍

Subscribe to our newsletter

If you find this article useful, join our weekly newsletter to be notified about the latest posts.

Your email address:

Subscribe

Related articles:



Crow's Foot Notation in Vertabelo



Barker's Notation



Chen Notation



IDEF1X Notation



Arrow Notation



UML Notation

You may also like:

How Does Database Design Help
Organize Teachers, Lessons, and
Students?




Denormalization: When, Why, and How



Database Modeling Course. Part 1 –
Why Do You Need Data Modeling?



A Database Model for Simple Board
Games



19 Online Resources for Learning About
Database Design Errors



How to Store Authentication Data
in a Database. Part 1