



## Handlebars

**#Node JS Notes** 

## Template Engine



#### Template Engines In Express Framework

• A template engine helps to create the HTML file in the application using very minimal code. Template engines allow us to generate HTML dynamically by adding the variables in the runtime.



#### list of template engines for Node.js Express

- Puq
- EJS
- handlebars
- hamlet



#### Handlebars

- Handlebars.js is a templating engine similar to the ejs module in node.js, but more powerful and simple to use.
- It ensures minimum templating and is a logicless engine that keeps the view and the code separated.
- It can be used with express as the hbs module, available through npm. HandleBars can be used to render web pages to the client side from data on the server-side.

#### Method

- Main Handlebars (Default Layout)
- Default Layout & Partials (Header Footer)
- 3. Only Partials (No Default Layout)



#### Steps


```
1.) Create New Project in Express
2.) Download Express-handlebard Package
       >npm install --save express-handlebars
3.) Load Package in app.js
       const exphbs = require('express-handlebars');
4.) HandleBars Needs Following Directory Structure
       view/
                layouts/
                        main.handlebars
                                {{title}}
        index.handlebars
       about.handlebars
```



#### Layout Benefit

- Code Reuse
- Easy to Change Website Layout at anytime
- We can create master Layout







#### Install Express-handlebars

```
package.json X
package.json > {} dependencies
         "private": true,
         ▶ Debug
         "scripts": {
           "start": "node ./bin/www"
         "dependencies": {
           "cookie-parser": "~1.4.4",
           "debug": "~2.6.9",
 10
 11
           "express": "~4.16.1",
           "express-handlebars": "^5.3.3",
 12
 13
           "http-errors": "~1.6.3",
           "morgan": "~1.9.1"
 14
 15
 PROBLEMS
           OUTPUT
                    TERMINAL
                              DEBUG CONSOLE
 D:\lecture2k21\myapphbs>npm i express-handlebars --save
 up to date, audited 79 packages in 2s
 1 package is looking for funding
  run `npm fund` for details
 4 vulnerabilities (2 low, 1 moderate, 1 critical)
 To address all issues, run:
```




#### App Setup

```
Js app.js
                                          •
EXPLORER
                 Js app.js > ...
MYAPPHBS
                                      var createError = require('http-errors');
> | bin
                                      var express = require('express');
> node_modules
                                      var path = require('path');
> a public
                                      var cookieParser = require('cookie-parser');
> In routes
                                      var logger = require('morgan');
> lows
                                      const exphbs = require('express-handlebars');
  Js app.js
                                      var indexRouter = require('./routes/index');
  package-lock.json
                                      var usersRouter = require('./routes/users');
  package.json
                                10
                                      var app = express();
                                11
                                12
                                      // view engine setup
                                13
                                      app.set('views', path.join(__dirname, 'views'));
                                15
                                      app.engine('handlebars', exphbs({
                                16
                                17
                                        defaultLayout: 'main'
                                      }));
                                      app.set('view engine', 'handlebars');
                                19
                                      app.use(logger('dev'));
                                21
                                      app.use(express.json());
                                22
                                      app.use(express.urlencoded({ extended: false }));
                                23
                                      app.use(cookieParser());
                                      app.use(express.static(path.join( dirname, 'public')));
                                25
```



Akash Technolabs

#### Folder





#### Main.handlebars

```
main.handlebars X
views > layouts > ~ main.handlebars > ...
       <html>
        <body>
            <center><h1>AkashSir.com</h1></center>
   4
            <hr/>
   5
            <a href="/">Home</a> | <a href="/about">About</a>
            <hr/>
   6
                {{{body}}}
            <hr/>
   8
   9
            Website Developed by Akash Padhiyar
        </body>
  10
  11
        </html>
```



#### Handlebars

```
index.handlebars X
views > ~ index.handlebars > ...
       Welcome to {{title}}
   2
```

```
about.handlebars X
views > ~ about.handlebars > ...
        <h1>About</h1>
```



#### Route

```
Js index.js
       EXPLORER
                                                                                                                     routes > Js index.js > ...
∨ MYAPPHBS
                                                                                                                                                     var express = require('express');
      > in bin
                                                                                                                                                     var router = express.Router();
       > node_modules
       > a public
                                                                                                                                                     /* GET home page. */


✓ Image: value of the valu
                                                                                                                                                     router.get('/', function(req, res, next) {
                     Js index.js
                                                                                                                                                               res.render('index', { title: 'Express' });
                      Js users.js
                                                                                                                                                     });

✓ Image views

                                                                                                                                 8
                                                                                                                                                      router.get('/about', function(req, res, next) {
           ∨ 📻 layouts
                                                                                                                                                               res.render('about', { title: 'Express' });
                                                                                                                            10
                         main.handlebars
                                                                                                                            11
                                                                                                                                                     });
                     about.handlebars
                                                                                                                            12
                     error.handlebars
                                                                                                                            13
                                                                                                                                                     module.exports = router;
                    index.handlebars
                                                                                                                            14
                 Js app.js
                package-lock.json
                 package.json
```



#### Output





# Partials



#### **Using Shared Partials Handlebars Template**

Using partials we can call specific page code in other pages.

Syntax: {{ > filename without extension }}



#### Register Partial Folder (Optional)

```
app.engine('handlebars', exphbs({
  defaultLayout: 'main',
  extname: '.handlebars',
  layoutsDir: path.join(__dirname, 'views/layouts'),
  partialsDir : [
    // path to your partials
    path.join(__dirname, 'views/partials'),
]
}));
app.set('view engine', 'handlebars');
```

```
us app.js > ...
      var createError = require('http-errors');
      var express = require('express');
      var path = require('path');
      var cookieParser = require('cookie-parser');
      var logger = require('morgan');
      const exphbs = require('express-handlebars');
      var indexRouter = require('./routes/index');
      var usersRouter = require('./routes/users');
      var app = express();
 10
      // view engine setup
 11
      app.set('views', path.join( dirname, 'views'));
 12
 13
      app.engine('handlebars', exphbs({
 14
 15
        defaultLayout: 'main',
        extname: '.handlebars',
 16
 17
        layoutsDir: path.join(__dirname, 'views/layouts'),
        partialsDir : [
 18
 19
          // path to your partials
          path.join(__dirname, 'views/partials'),
 20
 21
 22
      }));
 23
      app.set('view engine', 'handlebars');
 24
```




#### Create Folder and Files

Create Partials Folder and Various files in Folder

```
views > partials > -- news.handlebars > ...

1     <marquee> Welcome to my Website</marquee>
2
```





#### Call News Partial in Main


```
main.handlebars X
views > layouts > ~ main.handlebars > ...
       <html>
        <body>
            <center><h1>AkashSir.com</h1></center>
            <hr/>
   4
            <a href="/">Home</a> | <a href="/about">About</a>
            <hr/>
   6
            {{> news}}
            <hr/>
   8
                {{{body}}}
            <hr/>
  10
            Website Developed by Akash Padhiyar
  11
  12
        </body>
  13
        </html>
  14
```




#### Partial in About



#### Output



#### AkashSir.com





# Use Partials only



#### Use Partials Only not Default Layout

By default handlebars calling main.handlebars file but if you don't want to use it then you can add defaultLayout: false.

```
app.engine('handlebars', exphbs({
  extname: '.handlebars',
  defaultLayout: false,
  partialsDir : [
    // path to your partials
    path.join(__dirname, 'views/partials'),
]
}));
app.set('view engine', 'handlebars');
```

```
var cookieParser = require('cookie-parser');
var logger = require('morgan');
const exphbs = require('express-handlebars');
var indexRouter = require('./routes/index');
var usersRouter = require('./routes/users');
var app = express();
// view engine setup
app.set('views', path.join( dirname, 'views'));
app.engine('handlebars', exphbs({
  extname: '.handlebars',
 defaultLayout: false,
  partialsDir : [
    // path to your partials
    path.join( dirname, 'views/partials'),
app.set('view engine', 'handlebars');
```



```
EXPLORER
                                                              about.handlebars X
∨ MYAPPHBS 🖺 📮 ひ 🗊
                       views > ~ index.handlebars > ...
                                                              views > ~ about.handlebars > ...
                          1 Welcome to {{title}}
                                                                     <h1>About</h1>
 > lin bin
                                                                     {{> sidebar}}
 > node_modules
 > e public
 > iroutes
 views

✓ a partials

     news.handlebars
     sidebar.handlebars
    about.handlebars
    error.handlebars
    index.handlebars
   Js app.js
   package-lock.json
   package.json
```





Welcome to Express

## About

## Sidebar



# Bind Data and Condition, Loops



#### **Bind Data To Template**

 Using handlebars we can even send the data to the template by just passing the data inside the render method.

```
app.get('/', (req, res) => {
   res.render('home', { msg: 'This is home page'});
});
```



#### **Display Data Conditionally**

• We can use the if-else condition in the template itself to show data conditionally.

```
>
{{#if msg}}
 {{msg}}
{{else}}
 No message was found
{{/if}}
```



#### **Display Array Data**

 Handlebars also allow us to display an array of object data into templates using each syntax.

```
{#each peoples}}{[name]}
```

## Get Exclusive Video Tutorials





www.aptutorials.com
https://www.youtube.com/user/Akashtips









## Get More Details

## www.akashsir.com



# If You Liked It! Rating Us Now




#### **Just Dial**

https://www.justdial.com/Ahmedabad/Akash-Technolabs-Navrangpura-Bus-Stop-Navrangpura/079PXX79-XX79-170615221520-S5C4 BZDET



#### Sulekha

https://www.sulekha.com/akash-technolabs-navrangpuraahmedabad-contact-address/ahmedabad





#### Connect With Me



Akash Padhiyar #AkashSir

www.akashsir.com www.akashtechnolabs.com www.akashpadhiyar.com www.aptutorials.com

#### # Social Info

- **f** Akash.padhiyar
- O Akashpadhiyar
- Akash\_padhiyar
- +91 99786-21654



#Akashpadhiyar #aptutorials