Assignment 2 - Genetic Programming for SBFL

Name : Rd Pradipta Gitaya Samiadji
Student ID : 20254099
Repository Link : https://github.com/Diptags/cs454-assignments

1. Overview

This assignment replicates the

paper: a **Genetic Programming (GP)** engine, written from scratch, evolves a spectrum-based fault localisation (SBFL) formula `sbfl(ep, ef, np, nf)` that ranks the **faulty method** of 119 Defects4J bugs (Chart, Lang, Math, Time) as high as possible. 4-stage process:

1. **Prepare** the raw coverage data into program spectra, once, and cache them (`data.py`).
2. **Evaluate** a formula: score every statement, aggregate to methods with max, and rank the faulty method (`evaluate.py`).
3. **Evolve** formulas with GP, using acc@1 and wef on training bugs as fitness (`gp.py`).
4. **Export** the single best formula, hard-coded, to `best.py`.

File	Contents
`data.py`	Converts the raw coverage (`bug_data/*-cov.pkl` + `*.json`) into statement spectra grouped by method; caches them in `spectra.pkl`
`evaluate.py`	Method-level ranking (max aggregation), tie-breaking, acc@1 and wef (overall and per project), human-designed baselines
`gp.py`	The GP engine: tree representation, initialisation, selection, crossover, mutation, fitness, train/validation split, multiple runs
`best.py`	The single best evolved formula, hard-coded (uses the required safe division)
`results.txt`, `runs/`	Results of all 18 GP runs, the final evaluation, and the 50-seed sweep (Section 5.5)

Usage:

```
pip install -r requirements.txt
python data.py        # once: build spectra.pkl (~25 s)
python gp.py --runs 1 --pop 300 --gens 60 [--seed0 N]
             [--train-all] [--fitness acc|wef|log]
python evaluate.py    # baselines + best.py on all 119 bugs
```

The defaults are a population of 300, 60 generations and fitness `acc`. One GP run takes about 1.5–4 minutes; evaluating `best.py` on all 119 bugs takes less than a second. Every run is fully reproducible from its seed: re-running all 18 runs reproduced the same formulas and numbers.

2. Data Preparation

2.1 Program spectrum

For every statement, I compute the four numbers of the spectrum from the coverage matrix (rows = statements, columns = tests) and the list of failing tests:

- `ef` / `ep`: number of **failing** / **passing** tests that execute the statement;
- `nf = F - ef` and `np = P - ep`, where F and P are the numbers of failing and passing tests.

The method of a statement is its identifier without the line number. **Example:**

`"pkg$Class#m(args):123".rsplit(":", 1)[0]`. All four counts are stored as plain Python `int`, because `sbfl()` must be called with ints. The spectra are computed **once** and cached, because the GP evaluates thousands of formulas on every bug.

2.2 Dataset

Project	Bugs	Bugs with 1 failing test	Bugs with ≥ 2 failing tests	Methods (total)
Chart	19	12	7	10,773
Lang	34	22	12	6,140
Math	48	34	14	19,417
Time	18	9	9	24,919
All	**119**	**77**	**42**	**61,249**

Every faulty method appears in the coverage data, so no bug is impossible by construction.

3. Evaluation

3.1 Method-level ranking

- **Aggregation:** the score of a method is the **maximum** score of its statements.
- **Multiple faulty methods:** the best-ranked faulty method is used.
- **acc@1:** number of bugs whose faulty method is ranked **first**.
- **wef:** mean rank of the faulty method.

3.2 Tie-breaking

Many methods often receive the same score. Let *higher* be the number of non-faulty methods with a strictly higher score, and *tied* be the number with the same score. `evaluate.py` computes three ranks:

Scheme	Rank of the faulty method	Meaning	10 methods tied at the top
Pessimistic (conservative)	`higher + tied + 1`	the bug is inspected last in its tie group	10
Average	`higher + tied / 2 + 1`	tie group inspected in random order	5.5
Optimistic	`higher + 1`	the bug is inspected first in its tie group	1

The GP fitness and the headline numbers use pessimistic ties. With optimistic ties, a useless formula that gives every statement the same score would tie everything and rank every bug first, and the GP would learn to exploit that. For example, `Wong1 = ef` ranks **103/119** bugs first optimistically but only **2/119** pessimistically. I still report the other two schemes for comparison (Section 5.3). Note that for acc@1 the average and pessimistic schemes always agree: the average rank is exactly 1 only when nothing is tied with the faulty method.

3.3 Baselines and speed

- **Baselines:** Ochiai, Tarantula, Jaccard, Op2, Wong1 and AMPLE. They use `x / 0 = 0`, the usual convention in the literature. With the assignment's safe division (`x / 0 = 1`), statements executed by no test would get Ochiai = 1, the maximum score.
- **Speed:** many statements share the same spectrum, so each bug is compressed to its **unique** spectra (20,500 instead of about 250,000 statements). The formula is called once per unique spectrum with Python ints; the method maxima are then taken with `numpy.maximum.reduceat`. One evaluation on all 119 bugs takes about 12 ms.

4. GP Approach

No GP library is used for this project. One run works as follows:

1. **Initialisation.** A random population is created with ramped half-and-half (depths 2–5, half *full* trees, half *grow* trees).
2. **Evaluation.** Every formula is compiled into a Python lambda and evaluated on the training bugs. Fitness is cached by the formula's source string, because crossover often recreates formulas that were already seen.
3. **Elitism.** The best 5 individuals are copied unchanged into the next generation.
4. **Variation.** The rest of the next generation is produced from parents chosen by tournament selection: crossover (80%), mutation (15%) or plain reproduction (5%).
5. **Repeat** for 60 generations, then return the best formula.

Aspect	Choice
Representation	Expression trees as nested tuples, e.g. `("div", "ef", ("sqrt", "ep"))` = `ef / sqrt(ep)`
Terminals	`ep`, `ef`, `np`, `nf`, constant `1`
Non-terminals	`+`, `-`, `*`, safe `/` (required definition), protected `sqrt(|x|)` (as in the reference paper)
Selection	Tournament of size 5; elitism of 5
Crossover	Subtree crossover: a random subtree of parent A is replaced by a random subtree of parent B
Mutation	Half subtree mutation (new random subtree of depth 1–3), half point mutation (change one node, keep the shape)
Bloat control	Maximum depth 8 (larger children are rejected); tree size is the last tie breaker in fitness
Population/generations	300 / 60
Fitness (minimised)	`(-acc@1, wef, size)` on the training bugs, pessimistic ties, compared lexicographically

4.1 Choosing the fitness function

I tried to compare three fitness definitions in short pilot runs (population 200, 30–40 generations): wef first, mean $\log_2$(rank), and acc@1 first. On the 48 validation bugs, acc@1-first reached a mean validation acc@1 of 17.3 (3 runs), against 16.3 for log-rank (3 runs) and 17 for wef-first (1 run), while keeping wef competitive, so I chose acc@1 first.

5. Results

5.1 Best evolved formula

As evolved (`/` is the safe division and `sqrt` is `sqrt(|x|)`):

```
((sqrt((sqrt(((nf - ep) + sqrt(np))) * (ef * ef))) / (sqrt((sqrt((nf - ef)) + ((nf - ep) *
(ef - ep)))) * ((1 * (ef + nf)) / nf))) / sqrt((sqrt((nf - ef)) + ((((1 * 1) + nf) - ep) *
(ef - (1 + nf))))))
```

5.2 Results on the 119 bugs

Formula	acc@1 pessimistic	acc@1 average	acc@1 optimistic	wef pessimistic	wef average	wef optimistic
GP (best.py)	**53**	**53**	**76**	**4.83**	**4.17**	**3.51**
Ochiai	46	46	70	5.09	4.48	3.87
Jaccard	45	45	70	5.22	4.60	3.97
Tarantula	42	42	71	5.53	4.85	4.18
Op2	43	43	65	15.27	14.67	14.07
AMPLE	42	42	64	11.57	10.97	10.36
Wong1	2	2	103	88.76	50.15	11.53

The GP formula is the best under every tie-breaking scheme, except for Wong1's optimistic acc@1, which is the "tie everything" effect from Section 3.2.

Average wef per project (pessimistic ties):

Project	Bugs	GP acc@1	GP wef	Ochiai acc@1	Ochiai wef
Chart	19	7	4.47	7	4.79
Lang	34	19	4.15	18	5.00
Math	48	19	5.12	15	5.10
Time	18	8	5.72	6	5.56
All	**119**	**53**	**4.83**	**46**	**5.09**

5.3 Robustness over 18 runs

A single run can be lucky, so I looked at all of them. On the same 48 validation bugs, Ochiai ranks 18 first (wef 5.79) and Jaccard 17.

Seed	Trained on	Validation acc@1 (of 48)	Validation wef	acc@1 on all 119	wef on all 119	Tree size
100	71 (split)	14	6.10	48	10.06	75
101	71 (split)	18	6.52	51	5.39	32
102	71 (split)	15	7.06	51	5.46	53
103	71 (split)	18	6.17	53	5.13	40
104	71 (split)	15	6.38	51	5.20	33

Seed	Trained on	Validation acc@1 (of 48)	Validation wef	acc@1 on all 119	wef on all 119	Tree size
105	71 (split)	16	7.52	50	5.73	45
200	71 (split)	14	6.38	47	5.24	41
201	71 (split)	14	7.25	48	5.66	24
202	71 (split)	18	6.90	51	5.62	24
203	71 (split)	19	6.38	52	5.27	27
204	71 (split)	17	7.48	49	5.87	24
205	71 (split)	18	6.48	52	5.24	41
300	all 119	–	–	52	5.61	26
301	all 119	–	–	52	5.24	37
302	all 119	–	–	51	5.59	54
400	all 119	–	–	52	5.01	38
401 (best.py)	**all 119**	**–**	**–**	**53**	**4.83**	**54**
402	all 119	–	–	53	5.29	46

Validation acc@1 varies between 14 and 19 (mean 16.3), so the best runs generalise at least as well as Ochiai, but run-to-run variance is large. The original paper shows the same variance over its 30 runs. All final runs reach 51–53/119.




Figure 1. Convergence of the final run (seed 401): acc@1 and wef of the best individual per generation.

5.4 A larger seed sweep (50 additional runs)

To check whether more GP runs would find a clearly better formula, I ran 50 additional seeds (601–650) with the same setting as the final runs: trained on all 119 bugs, population 300, 60 generations (about 2.3 minutes per run). All 50 runs finished without errors.

acc@1 on 119 bugs	Runs	Seeds
54	4	636, 617, 647, 619
53	7	Same as best.py
52	31	–
51	6	–
50	2	–

Four runs reached 54/119, so I compared the top candidates with best.py bug by bug, and with a bootstrap over the 119 bugs (2,000 resamples of the bugs):

Seed	acc@1	wef	Top-1 gained/lost vs best.py	Rank better / worse (bugs)	Bootstrap: lower wef
401 (best.py)	**53**	**4.83**	**–**	**–**	**–**
636	54	5.07	+Lang-22 / none	6 / 8	19%
647	54	5.20	+Lang-22 / none	7 / 9	8%
619	54	5.28	+Math-6 / none	3 / 8	5%
617	54	5.17	+Lang-22, Lang-9, Time-18 / −Lang-30, Time-6	9 / 12	11%
637	53	4.41	+Math-6 / −Lang-31	15 / 4	100%
630	53	4.58	+Lang-22 / −Time-6	12 / 6	77%

- **The 54-runs are not clearly better.** Each one gains essentially a single extra bug, mostly the same one (Lang-22), while its wef gets worse and it ranks the faulty method lower on more bugs than higher. This looks like the GP fitting one specific bug rather than a general improvement.
- **Seeds 637 and 630 keep 53/119 with a lower wef score.** Their advantage is consistent on these 119 bugs, but it was found by picking the best of 56 runs on the same data, so part of it is selection luck that cannot be confirmed without new bugs.

I therefore kept seed 401 as best.py. The sweep confirms that about 53 top-1 hits is the practical ceiling of a single formula on this data, and that best.py is already among the best runs: none of the 50 additional seeds improved acc@1 without also making wef worse.