
Solarious
ENERGY



575 Wp - 600 Wp

MONOPERC 10BB

MONO-FACIAL

30 YEARS WARRANTY FOR LINEAR PERFORMANCE*

30 YEARS

12 YEAR PRODUCT WARRANTY ON MATERIALS AND WORKMANSHIP*

12 YEARS

FEATURES:

- PID Free /Low LID Protection
- Positive Tolerance @ 0~5W
- 100% in Line Hi-Pot Testing
- M10 MONO-PERC

CERTIFICATIONS:

IEC 61730 | IEC 62804(PID) |
IEC 61701(Salt Mist) | IEC 61853 | IEC 6280

ISO 9001, ISO 14001
ISO 45001

IS 14286
IS 61730 - 1 & 2

R-71031178

Benefits of Solarious Solar Panels

- Super Performance
- Quality Materials
- Advanced Technology
  Warranty and Support

156 HALF CUT CELL MONOPERC MONO-FACIAL MODULE

TECHNICAL SPECIFICATION SLM-M10-156-XXX

ELECTRICAL SPECIFICATION (STC)

Maximum Power (Pmp)	575	580	585	590	595	600
Open Circuit Voltage (Voc)	53.25	53.30	53.35	53.40	53.45	53.50
Short Circuit Current (Isc)	13.45	13.50	13.65	13.80	13.90	13.95
Maximum Power Voltage (Vmp)	45.90	45.95	46.00	46.10	46.20	46.30
Maximum Power Current (Imp)	12.55	12.65	12.75	12.80	12.90	13.00
Module Efficiency %	20.75	20.90	21.10	21.30	21.50	21.70
Power Tolerance (Positive Only)	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W


Under Standard Test Conditions (STC) of irradiance 1000 W/m², spectrum AM 1.5 and cell temperature of 25 °C , Except Pmax
all other parameter have a tolerance of ± 3%, No Negative Power Tolerance in Nominal Power

THERMAL DATA


Temp. Cofficient Open-circuit Voltage	-0.28%/°C
Temp. Cofficient Open-circuit Current	0.05%/°C
Temp. Coefficient Rated Power	-0.35%/°C
NOCT (Normal operating cell Temperature)	45 °C ± 2°C

BACK VIEW


*Module dimensions with ± 2mm tolerance.




IV CURVE



PV CURVE



LINEAR PERFORMANCE WARRANTY



MECHNICAL SPECIFICATION

Solar Cell	MONO-PERC, 10BB, 156 (13x6x2) Half-Cut Cells
Encapsulation	Ultra-clear PID Free EVA (Ethylene-vinyl-Acetate)
Backside	UV protected reflactive backsheet
frame	Anodized Aluminium Alloy (Silver/Black)
Front glass	3.2mm, High Transmission, Low Iron, ARC Tempered Glass
Dimensions	(L) 2465 mm x (W) 1134mmx(H) 35mm
Weight	31.5Kg
J-box	Split JB IP 68 certified, 3 Diodes
Cable	Solar cable 4mm², 400mm (1000mm/1200mm on customization request)
Connectors	MC4-compatible connectors
Application Class	Class A
Electrical Safety	Class II

PERMISSIBLE OPERATING CONDITIONS


Operating Temperture Range	- 40 °C To 85 °C
Max. system Voltage	1500 V DC
Maximum Snow Load Capacity	5400PA
Maximum Wind load capacity	2400PA
Resistance against hail	Max 24mm with impact Speed of 83km/h
protection Class Against Electrical Shock	II
Maximum Reverse Current	25A

PACKING CONFIGURATION

Container Lorry	20"GP	40"HQ
Module Per Pallet	28	32
Pallet Per Container	10	20
Module Per Container	280	640

** Product Specifications are subjected to change without notice
** Warranty clause can be claimed as per Solarious Energy warranty certificate

Solarious
ENERGY



515 Wp - 555 Wp

MONOPERC 10BB

MONO-FACIAL

30 YEARS WARRANTY FOR LINEAR PERFORMANCE*

30 YEARS

12 YEAR PRODUCT WARRANTY ON MATERIALS AND WORKMANSHIP*

12 YEARS

FEATURES:

- PID Free /Low LID Protection
- Positive Tolerance @ 0~5W
- 100% in Line Hi-Pot Testing
- M10 MONO-PERC

CERTIFICATIONS:

IEC 61730 | IEC 62804(PID) |
IEC 61701(Salt Mist) | IEC 61853 | IEC 6280

ISO 9001, ISO 14001
ISO 45001

IS 14286
IS 61730 - 1 & 2

R-71031178

Benefits of Solarious Solar Panels

- Super Performance
- Quality Materials
- Advanced Technology
  Warranty and Support

144 HALF CUT CELL MONOPERC MONO-FACIAL MODULE

TECHNICAL SPECIFICATION SLM-M10-144-XXX

ELECTRICAL SPECIFICATION (STC)

Maximum Power (Pmp)	515	520	525	530	535	540	545	550	555
Open Circuit Voltage (Voc)	49.20	49.24	49.28	49.32	49.36	49.40	49.44	49.80	50.00
Short Circuit Current (Isc)	13.15	13.26	13.38	13.49	13.60	13.72	13.83	13.98	14.05
Maximum Power Voltage (Vmp)	41.72	41.76	41.80	41.84	41.88	41.92	41.96	41.95	41.99
Maximum Power Current (Imp)	12.34	12.45	12.56	12.67	12.77	12.88	12.99	13.12	13.22
Module Efficiency %	19.93	20.12	20.31	20.51	20.70	20.89	21.09	21.28	21.48
Power Tolerance (Positive Only)	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W


Under Standard Test Conditions (STC) of irradiance 1000 W/m², spectrum AM 1.5 and cell temperature of 25 °C , Except Pmax all other parameter have a tolerance of ± 3%, No Negative Power Tolerance in Nominal Power

THERMAL DATA


Temp. Cofficient Open-circuit Voltage	-0.28%/°C
Temp. Cofficient Open-circuit Current	0.05%/°C
Temp. Coefficient Rated Power	-0.35%/°C
NOCT (Normal operating cell Temperature)	45 °C ± 2°C

BACK VIEW


*Module dimensions with ± 2mm tolerance.




IV CURVE



PV CURVE



LINEAR PERFORMANCE WARRANTY



MECHNICAL SPECIFICATION

Solar Cell	MONO-PERC, 10BB, 144 Half-Cut
Encapsulation	Ultra-clear PID Free EVA (Ethylene-vinyl-Acetate)
Backside	UV protected reflactive backsheet
frame	Anodized Aluminium Alloy (Silver/Black).
Front glass	3.2mm, High Transmission, Low Iron, ARC Tempered Glass
Dimensions	(L) 2278 mm x (W) 1134mmx(H) 35mm
Weight	27.5 Kg
J-box	Split JB, IP 68 certified, 3 Diodes
Cable	Solar cable 4mm², 400mm (1000mm/1200mm on customization request)
Connectors	MC4-compatible connectors
Application Class	Class A
Electrical Safety	Class II

PERMISSIBLE OPERATING CONDITIONS


Operating Temperture Range	- 40 °C To 85 °C
Max. system Voltage	1500 V DC
Maximum Snow Load Capacity	5400PA
Maximum Wind load capacity	2400PA
Resistance against hail	Max 24mm with impact Speed of 83km/h
protection Class Against Electrical Shock	II
Maximum Reverse Current	25A

PACKING CONFIGURATION

Container Lorry	20"GP	40"HQ
Module Per Pallet	28	32
Pallet Per Container	10	20
Module Per Container	280	640

** Product Specifications are subjected to change without notice
** Warranty clause can be claimed as per Solarious Energy warranty certificate

Solarious
ENERGY



490 Wp - 510 Wp

MONOPERC 10BB

MONO-FACIAL

30 YEARS WARRANTY FOR LINEAR PERFORMANCE*

30 YEARS

12 YEAR PRODUCT WARRANTY ON MATERIALS AND WORKMANSHIP*

12 YEARS

FEATURES:

- PID Free /Low LID Protection
- Positive Tolerance @ 0~5W
- 100% in Line Hi-Pot Testing
- M10 MONO-PERC

CERTIFICATIONS:

IEC 61730 | IEC 62804(PID) |
IEC 61701(Salt Mist) | IEC 61853 | IEC 6280

ISO 9001, ISO 14001
ISO 45001

IS 14286
IS 61730 - 1 & 2

R-71031178

Benefits of Solarious Solar Panels

- Super Performance
- Quality Materials
- Advanced Technology
  Warranty and Support

132 HALF CUT CELL MONOPERC MONO-FACIAL MODULE

TECHNICAL SPECIFICATION SLM-M10-132-XXX

ELECTRICAL SPECIFICATION (STC)

Maximum Power (Pmp)	490	495	500	505	510
Open Circuit Voltage (Voc)	45.32	45.36	45.70	45.90	46.10
Short Circuit Current (Isc)	13.57	13.69	13.72	13.82	13.92
Maximum Power Voltage (Vmp)	38.46	38.50	38.55	38.58	38.62
Maximum Power Current (Imp)	12.74	12.86	12.97	13.09	13.21
Module Efficiency %	20.64	20.86	21.07	21.28	21.49
Power Tolerance (Positive Only)	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W


Under Standard Test Conditions (STC) of irradiance 1000 W/m², spectrum AM 1.5 and cell temperature of 25 °C , Except Pmax
all other parameter have a tolerance of ± 3%, No Negative Power Tolerance in Nominal Power

THERMAL DATA


Temp. Cofficient Open-circuit Voltage	-0.28%/°C
Temp. Cofficient Open-circuit Current	0.05%/°C
Temp. Coefficient Rated Power	-0.35%/°C
NOCT (Normal operating cell Temperature)	45 °C ± 2°C

BACK VIEW


*Module dimensions with ± 2mm tolerance.




IV CURVE



PV CURVE



LINEAR PERFORMANCE WARRANTY



MECHNICAL SPECIFICATION

Solar Cell	MONO-PERC, 10BB, 132 Half-Cut
Encapsulation	Ultra-clear PID Free EVA (Ethylene-vinyl-Acetate)
Backside	UV protected reflactive backsheet
frame	Anodized Aluminium Alloy (Silver/Black)
Front glass	3.2mm, High Transmission, Low Iron, ARC Tempered Glass
Dimensions	(L) 2093 mm x (W) 1134mmx(H) 35mm
Weight	26Kg
J-box	IP 68 certified, 3 Diodes
Cable	Solar cable 4mm², 400mm (1000mm/1200mm on customization request)
Connectors	MC4-compatible connectors
Application Class	Class A
Electrical Safety	Class II

PERMISSIBLE OPERATING CONDITIONS


Operating Temperture Range	- 40 °C To 85 °C
Max. system Voltage	1500 V DC
Maximum Snow Load Capacity	5400PA
Maximum Wind load capacity	2400PA
Resistance against hail	Max 24mm with impact Speed of 83km/h
protection Class Against Electrical Shock	II
Maximum Reverse Current	25A

PACKING CONFIGURATION

Container Lorry	20"GP	40"HQ
Module Per Pallet	28	32
Pallet Per Container	10	20
Module Per Container	280	640

** Product Specifications are subjected to change without notice
** Warranty clause can be claimed as per Solarious Energy warranty certificate

Solarious
ENERGY



425 Wp - 460 Wp

MONOPERC 10BB

MONO-FACIAL

30 YEARS WARRANTY FOR LINEAR PERFORMANCE*

30 YEARS

12 YEAR PRODUCT WARRANTY ON MATERIALS AND WORKMANSHIP*

12 YEARS

FEATURES:

- PID Free /Low LID Protection
- Positive Tolerance @ 0~5W
- 100% in Line Hi-Pot Testing
- M10 MONO-PERC

CERTIFICATIONS:

IEC 61730 | IEC 62804(PID) |
IEC 61701(Salt Mist) | IEC 61853 | IEC 6280

ISO 9001, ISO 14001
ISO 45001

IS 14286
IS 61730 - 1 & 2

R-71031178

Benefits of Solarious Solar Panels

- Super Performance
- Quality Materials
- Advanced Technology
  Warranty and Support

120 HALF CUT CELL MONOPERC MONO-FACIAL MODULE

TECHNICAL SPECIFICATION SLM-M10-120-XXX

ELECTRICAL SPECIFICATION (STC)

Maximum Power (Pmp)	425	430	435	440	445	450	455	460
Open Circuit Voltage (Voc)	40.54	40.06	40.8	40.41	41.2	41.4	41.6	41.8
Short Circuit Current (Isc)	13	13.27	13.34	13.41	13.49	13.6	13.69	13.78
Maximum Power Voltage (Vmp)	34.37	34.41	34.45	34.49	34.53	34.57	34.61	34.65
Maximum Power Current (Imp)	12.37	12.5	12.63	12.76	12.89	13.02	13.15	13.28
Module Efficiency %	19.64	19.87	20.1	20.34	20.57	20.8	21.03	21.26
Power Tolerance (Positive Only)	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W


Under Standard Test Conditions (STC) of irradiance 1000 W/m², spectrum AM 1.5 and cell temperature of 25 °C , Except Pmax
all other parameter have a tolerance of ± 3%, No Negative Power Tolerance in Nominal Power

THERMAL DATA


Temp. Cofficient Open-circuit Voltage	-0.28%/°C
Temp. Cofficient Open-circuit Current	0.05%/°C
Temp. Coefficient Rated Power	-0.35%/°C
NOCT (Normal operating cell Temperature)	45 °C ± 2°C

BACK VIEW


*Module dimensions with ± 2mm tolerance.




IV CURVE



PV CURVE



LINEAR PERFORMANCE WARRANTY



MECHNICAL SPECIFICATION

Solar Cell	MONO-PERC, 10BB, 120 Half-Cut
Encapsulation	Ultra-clear PID Free EVA (Ethylene-vinyl-Acetate)
Backside	UV protected reflactive backsheet
frame	Anodized Aluminium Alloy (Silver/Black)
Front glass	3.2mm, High Transmission, Low Iron, ARC Tempered Glass
Dimensions	(L) 1908 mm x (W) 1134mmx(H) 35mm
Weight	23Kg
J-box	IP 68 certified, 3 Diodes
Cable	Solar cable 4mm², 400mm (1000mm/1200mm on customization request)
Connectors	MC4-compatible connectors
Application Class	Class A
Electrical Safety	Class II

PERMISSIBLE OPERATING CONDITIONS


Operating Temperture Range	- 40 °C To 85 °C
Max. system Voltage	1500 V DC
Maximum Snow Load Capacity	5400PA
Maximum Wind load capacity	2400PA
Resistance against hail	Max 24mm with impact Speed of 83km/h
protection Class Against Electrical Shock	II
Maximum Reverse Current	25A

PACKING CONFIGURATION

Container Lorry	20"GP	40"HQ
Module Per Pallet	28	32
Pallet Per Container	10	20
Module Per Container	280	640

** Product Specifications are subjected to change without notice
** Warranty clause can be claimed as per Solarious Energy warranty certificate

Solarious
ENERGY



385 Wp - 415 Wp

MONOPERC 10BB

MONO-FACIAL

30 YEARS WARRANTY FOR LINEAR PERFORMANCE*

30 YEARS

12 YEAR PRODUCT WARRANTY ON MATERIALS AND WORKMANSHIP*

12 YEARS

FEATURES:

- PID Free /Low LID Protection
- Positive Tolerance @ 0~5W
- 100% in Line Hi-Pot Testing
- M10 MONO-PERC

CERTIFICATIONS:

IEC 61730 | IEC 62804(PID) |
IEC 61701(Salt Mist) | IEC 61853 | IEC 6280

ISO 9001, ISO 14001
ISO 45001

IS 14286
IS 61730 - 1 & 2

R-71031178

Benefits of Solarious Solar Panels

- Super Performance
- Quality Materials
- Advanced Technology
  Warranty and Support

108 HALF CUT CELL MONOPERC MONO-FACIAL MODULE

TECHNICAL SPECIFICATION SLM-M10-108-XXX

ELECTRICAL SPECIFICATION (STC)

Maximum Power (Pmp)	385	390	395	400	405	410	415
Open Circuit Voltage (Voc)	36.88	36.92	36.96	37	37.3	37.5	37.7
Short Circuit Current (Isc)	13.28	13.43	13.59	13.74	13.81	13.87	13.95
Maximum Power Voltage (Vmp)	30.88	30.92	30.96	31	31.04	31.08	31.12
Maximum Power Current (Imp)	12.47	12.61	12.76	12.9	13.04	13.19	13.34
Module Efficiency %	19.72	19.97	20.23	20.48	20.75	21	21.25
Power Tolerance (Positive Only)	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W	0 to +5W


Under Standard Test Conditions (STC) of irradiance 1000 W/m², spectrum AM 1.5 and cell temperature of 25 °C , Except Pmax
all other parameter have a tolerance of ± 3%, No Negative Power Tolerance in Nominal Power

THERMAL DATA


Temp. Cofficient Open-circuit Voltage	-0.28%/°C
Temp. Cofficient Open-circuit Current	0.05%/°C
Temp. Coefficient Rated Power	-0.35%/°C
NOCT (Normal operating cell Temperature)	45 °C ± 2°C

BACK VIEW


*Module dimensions with ± 2mm tolerance.




IV CURVE



PV CURVE



LINEAR PERFORMANCE WARRANTY



MECHNICAL SPECIFICATION

Solar Cell	MONO-PERC, 10BB, 108 Half-Cut
Encapsulation	Ultra-clear PID Free EVA (Ethylene-vinyl-Acetate)
Backside	UV protected reflactive backsheet
frame	Anodized Aluminium Alloy (Silver/Black)
Front glass	3.2mm, High Transmission, Low Iron, ARC Tempered Glass
Dimensions	(L) 1722 mm x (W) 1134mmx(H) 35mm
Weight	21.5Kg
J-box	IP 68 certified, 3 Diodes
Cable	Solar cable 4mm², 400mm, 1200mm, can be Customization option.
Connectors	MC4-compatible connectors
Application Class	Class A
Electrical Safety	Class II

PERMISSIBLE OPERATING CONDITIONS

Operating Temperture Range	- 40 °C To 85 °C
Max. system Voltage	1500 V DC
Maximum Snow Load Capacity	5400PA
Maximum Wind load capacity	2400PA
Resistance against hail	Max 24mm with impact Speed of 83km/h
protection Class Against Electrical Shock	II
Maximum Reverse Current	25A

PACKING CONFIGURATION

Container Lorry	20"GP	40"HQ
Module Per Pallet	28	32
Pallet Per Container	10	20
Module Per Container	280	640

** Product Specifications are subjected to change without notice
** Warranty clause can be claimed as per Solarious Energy warranty certificate