Logger

Library version:RENAT 0.1.8g1Library scope:test suiteNamed arguments:supported

Introduction

Provides advanced logging functions. Every <u>Logger</u> instance has one <u>VChannel</u> object and the is synchronized with the current active <u>VChannel</u>. **Notes:** log file is not updated pararelly. Anytime a terminal is switched to, it will update its log file.

Shortcuts

Log · Log All · Switch

Keywords

Keyword	Arguments	Documentation
Log	msg, with_time=False, mark=***	Inserts a message msg to the current <i>VChannel</i> log file. A default mark of *** will be added at the beginning ant the end of this message. Example:
		Logger. <u>Log</u> START TRAFFIC FROM HERE \${TRUE} Logger. <u>Log</u> START TRAFFIC FROM HERE \${False} ===
Log All	msg, with_time=False, mark=***	inserts a message msg to current all VChannel log files.
		A default mark of *** and newline will be added at the beggining and the end of this message.
		Example:
		Logger. Log All START TRAFFIC FROM HERE \${TRUE} Logger. Log All START TRAFFIC FROM HERE \${TRUE} ===
		The log file will look likes this:
		user@vmx12>
		*** 06:01PM on August 13, 2017: START TRAFFIC FROM HERE ***
		=== 06:01PM on August 13, 2017: START TRAFFIC FROM HERE ===
		configure
Switch	name	Switches the current <u>VChannel</u> instance to name is the name of the <u>VChannel</u> (usually is the node name defined in the current active local.yaml).
		Example:
		Logger. Switch vmx11

Altogether 3 keywords.

Generated by <u>Libdoc</u> on 2018-06-01 21:39:29.

