## Logger

Library version:RENAT 0.1.11Library scope:test suiteNamed arguments:supported

## Introduction

Provides advanced logging functions. Every <u>Logger</u> instance has one <u>VChannel</u> object and the is synchronized with the current active <u>VChannel</u>. **Notes:** log file is not updated pararelly. Anytime a terminal is switched to, it will update its log file.

## **Shortcuts**

Log · Log All · Switch

## Keywords

Keyword	Arguments	Documentation
Log	msg, with_time=False, mark=***	Inserts a message msg to the current <i>VChannel</i> log file. A default mark of *** will be added at the beginning ant the end of this message.  Example:  Logger. Log START TRAFFIC FROM HERE \${TRUE}
Log All	msg, with_time=False, mark=***	Logger. Log START TRAFFIC FROM HERE \${False} ===  Inserts a message msg to current all VChannel log files.  A default mark of *** and newline will be added at the beggining and the end of this message.  Example:
		Logger. Log All START TRAFFIC FROM HERE \${TRUE} Logger. Log All START TRAFFIC FROM HERE \${TRUE} ===  The log file will look likes this:
		user@vmx12>  *** 06:01PM on August 13, 2017: START TRAFFIC FROM HERE ***  === 06:01PM on August 13, 2017: START TRAFFIC FROM HERE ===  configure
Switch	name	Switches the current VChannel instance to name is the name of the VChannel (usually is the node name defined in the current active local.yaml).  Example:  Logger. Switch vmx11

Altogether 3 keywords.

Generated by <u>Libdoc</u> on 2018-12-02 19:41:46.

