vmware

Library scope: global **Named arguments:** supported

Introduction

provides function for VMware ESXI

Athough this module provides some keywords for interact with the console (WebConsole), they only suppport very primitive actions. Do not use this to accomplish complex tasks. Instead, using VChannel through a SSH/Telnet channel.

Shortcuts

Capture Mks Screenshot · Click Mks · Get Mks Ticket · Get Vm Id · Get Vm List · Get Vm Power State · Open Console · Power Off · Power On · Reset Capture Counter · Send Mks Cmd · Send Mks Key · Set Capture Format

Keywords

| Keyword | Arguments | Documentation | | | | |
|--------------------------|---|--|---|------------------|------------------------------|--|
| Capture Mks | self, filename=None, extra= | Captures the current web console to <i>filename</i> | | | | |
| Screenshot | | If <i>filename</i> is None, the captured filename will be decided by the current format with an auto-increment counter and a extra at the end. | | | | |
| | | Example: | | | | |
| | | '' | will create a file console_0000000001.png | | | |
| | | Hypervisor.Capture MKS x Screenshot | xx.png | | # will create a file xxx.png | |
| | | 77 | will create a file onsole_00000000 | 02.png | | |
| Click Mks | self, xoffset, yoffset | Click on the MKS console at xoffset, yoffset coordinate | | | | |
| | | Notes : The coordinate (0,0) is at the left corner of the console screen | | | | |
| Get Mks Ticket | self, vm_name | Returns a MSK ticket for WebConsole | | | | |
| Get Vm Id | self, vm_name | Returns a VMID of a VM | | | | |
| Get Vm List | self | Returns current VM name list of the hypervisor | | | | |
| Get Vm Power State | self, vm_name | Get vm power status | | | | |
| | | Return on of off | | | | |
| Open Console | self, vm_name, width=None, height=None | Opens a web console for a VM vm_name | | | | |
| | | Returns the <i>width</i> and <i>height</i> of the console Examples: | | | | |
| | | | · | | | |
| | | Hypervisor. <u>Set Capture Format</u> <u>Open Console</u> | console_%010 \${VM_NAME} | u e | | |
| | | Hypervisor. <u>Capture MKS Screenship</u> | | | | |
| | | Send MKS Cmd | root | | | |
| | | Send MKS Cmd | password | wait=10s | | |
| | | Send MKS Cmd | ls | | | |
| | | Hypervisor. Capture MKS Screensh | <u>ot</u> | | | |
| | | Send MKS Key | \${CTRL_L} | | | |
| | | Send MKS Cmd | whoami | | | |
| | | Hypervisor.Capture MKS Screensh | ot` | | | |
| Power Off | self, vm_name, graceful=True Shutdowns a VM | | | | | |
| | | If graceful is True, a graceful shutdown is tried before a power off. | | | | |
| | | Note: if VMware tools is not install on the VM, graceful shutdown is not available | | | | |
| Power On | self, vm_name | Power on a VM | | | | |
| Reset Capture Counter | self | | | | | |
| Send Mks Cmd | self, cmd, wait=2s | Sends command to current web console and wait for a while | | | | |
| | | By default, wait time is 2s and the the cmd | keyword will autor | naticall add a N | ewline char after sending | |
| Send Mks Key | self, key, wait=1s | Sends key strokes to current web console | | | | |
| | | Special Ctrl char could be used as \${CTRL_A} to \${CTRL_Z} | | | | |
| | | | | | | |
| | | Examples: | | | | |

| | | Send MKS Key \${CTRL_L} |
|-------------|--------------|--------------------------------------|
| Set Capture | self, format | Set console capture format |
| Format | | Initialized format is 'vmware_%010d' |

Altogether 13 keywords.
Generated by <u>Libdoc</u> on 2018-10-08 19:18:12.

