RENAT

Library version: RENAT 1.7.1

Library scope: global **Named arguments:** supported

Introduction

Document for RENAT framework

All in one pdf renat.pdf

Libraries

RENAT includes following libraries:

Common:

Common library of RENAT

VChannel:

Library controls connection to targets (servers, routers, ...)

Logger:

Library provides enhanced loggging keywords

Optical:

Library provides keywords to control L1 switches, includes mod calient mod, mod ntm mod

Router:

Library provides keywords to control routers, includes $\underline{\mathsf{mod_juniper}}$ mod , $\underline{\mathsf{mod_cisco}}$ mod and $\underline{\mathsf{mod_gr}}$ mod

Tester:

Library provieds keywors to control testers, includes mod ixnet and mod ixload

WebApp:

Common library for web application, includes 2 child libraries: Samurai and Arbor

Others

Changes:

Changes information

Choose each libraries for detail infomration and samples about keywords.

Shortcuts

Keywords

Keyword	Arguments	Documentation	
Altogether 0 keywords			٦

Altogether 0 keywords

Generated by <u>Libdoc</u> on 2018-04-12 19:20:29.



Common

Library version:RENAT 1.7.1Library scope:globalNamed arguments:supported

Introduction

Common library for RENAT

It loads config files and create necessary varibles. The file should be the 1st library included from any test case.

Table of Contents

- Configuration file
- <u>Variables</u>
- Shortcuts
- Keywords

Configuration file

Global configuration

There are 2 kinds of configuration files. The global configuration files (aka master files) include device information, authentication etc that are used for all the test cases in the suite. The local configuration file local.yaml includes information about nodes, tester ports etc. that are used in a specific test case.

At the beginning, the module makes a local copy the master files and initialize necessary variables.

The master files folder is defined by renat-master-folder in \$RENAT_PATH/config/config.yaml. Usually, users do not need to modify the master files. The most common case is when new device is deployed, the device.yaml need to be update so that device could be used in the test cases.

• device.yaml: contains global device information

```
device:
  apollo:
    type: ssh-host
    description: main server
    ip: 10.128.3.101
  artermis:
    type: ssh-host
    description: second server
    ip: 10.128.3.91
  vmx11:
    type: juniper
    description: r1
    ip: 10.128.64.11
  vmx12:
    type: juniper
    description: r2
    ip: 10.128.64.12
```

• auth.yaml: contains authentication information

```
auth:
  plain-text:
    default:
      user: user
      pass: nttXXX
    flets:
      user: user
      pass: lpcoXXXX
    arbor:
      user: admin
      pass: nttXXX
  public-key: # for Public Key authentication
    default:
      user: robot
      key: /home/user/.ssh/robot_id_rsa
    test:
      user: jenkins
      key: /var/lib/jenkins/.ssh/id_rsa
```

• template.yaml: contains devvice template information

```
access-template:
ssh-host:
access: ssh
auth: public-key
profile: default
prompt: \$
```

```
append:
    init: unalias -a
 juniper:
    access: telnet
    auth: plain-text
    profile: default
    prompt: "(#|>) "
    append: ' | no-more'
    init:
 cisco:
    access: ssh
    auth: plain-text
    profile: default
    prompt: "\@.*(#|>) "
    append:
    init:
snmp-template:
   juniper:
      mib: ./mib-Juniper.json
      community: public
      poller: renat
   cisco:
      mib: ./mib-Cisco.json
      community: public
      poller: renat
```

Local Configuration

Local configuration (aka local.yaml) was used by a test case of its sub test cases. Test cases could includes several test cases (the sub level is not limited). The local configuration is defined by local.yaml in the config folder of each test case. If a test case does not has the local.yaml in its config folder, it will use the local.yaml file in its parent test case and so on. This will help users to share the test information for related test case without having the same local.yaml for each test case (**Note:** this feature is enabled from RENAT 0.1.4). The local.yaml that is really used for the test is called active local.yaml.

When user used the wizard case.sh to create a new test case, they have the ability to crete new local.yaml or not. local.yaml could be edited and inserted new information later to hold more informations for the test case.

When a test is run, it will display its current active local.yaml

<testcase>/config/local.yaml: contains local data for a test case

```
node:
 vmx11:
    device: vmx11
   snmp_polling: yes
  vmx12:
    device: vmx11
    snmp_polling: yes
  apollo:
   device: vmx11
    snmp_polling: yes
tester:
  tester01:
    type: ixnet
    ip: 10.128.32.70
    config: vmx_20161129.ixncfg
port-mapping:
  uplink01:
    device: vmx11
    port: ge-0/0/0
  downlink01:
    device: vmx12
    port: ge-0/0/2
default:
  ignore_dead_node: yes
  terminal:
    width: 80
   height: 32
 result_folder: result
```

Variables

The module automatically create GLOBAL & LOCAL variable for other libraries. It also creates global list variables *GLOBAL,LOCAL* and *NODE* that could be accessed from Robot Framework` test cases.

The GLOBAL variable holds all information defined by the master files and LOCAL variable holds all variables defined by active local.yaml. And NODE is a list that hold all active nodes defined in the local.yaml.

Users could access to the information of a key in local.yaml by \${LOCAL['key']}, information of a node by \${LOCAL['node'][vmx11']} or simply \$NODE[vmx]. When a keyword need a list of current node, @{NODE} could be used.

Notes: By default, RENAT will stop and raise an exception if connection to a node is failed. But if ignore_dead_node is defined as yes (default) is the current active local.yaml, RENAT will omit an warning but keep running the test and remove the node from its active node list.

Shortcuts

Change Mod · Cleanup Result · Convert Html To Pdf · Count Keyword · Count Keyword Line · Count Match Regexp · Create Sequence · Csv Concat · Csv Merge · Csv Select · Diff File · Err · Error Line Should Not Be Bigger Than · Error Should Not Be Bigger Than · File Md5 · Fold Str · Follow Syslog And Trap · Get Config Path · Get File Without Error · Get Item Config Path · Get Item Name · Get Renat Path · Get Result Folder · Get Result Path · Get Test Device · Is Stable · Keyword Line Should Not Be Bigger Than · Keyword Should Not Be Bigger Than · Load Plugin · Log · Log To Console · Loop For Node Tag · Md 5 · Merge Files · Mib For Node · Node With Attr · Node With Tag · Node Without Tag · Pause · Ping Until Ok · Random Name · Random Number · Renat Version · Set Multi Item Variable · Set Result Folder · Slack · Str 2 Seq · Version

Keyword	Arguments		Docume	ntation	
Change Mod	name, mod, relative=False	Changes file mod, lik	ces Unix chmod		
		mod is a string specifying the privilege mode relative is False or True			lse or True
		Examples:			
		Common. Change Mod tmp 0775			
Cleanup Result	ignore=^(log.html output.xml report.html)\$	Cleans up the result	folder		
			rrent active folder that e time the test has sta		the ignore expression
		Note: The keyword of	only removes files but	not folders	
Convert Html To Pdf	html_file, pdf_file	Converts html file to	pdf file		
Count Keyword	keyword, *pattern_list	Count the keyword in	n files. Keyword is not	case-sensitive	
Count Keyword Line	keyword, *pattern_list	Count the number of	lines contains the key	yword	
		Notes: Keyword is matched by error ke	natched partially. For earlyword.	example, error or	errorXXX will be
Count Match Regexp	regexp, *pattern_list	Count the number of	regex found in patter	n_list	
		Examples:			
		\${err_num}= Coun	<u>it Match RegExp</u> .*erroi	r.* result/*.csv res	sult/*.txt
Create Sequence	start, end, interval, option=float	Creates a list with nu	umber from start to en	d with interval	
		Example:			
		@{list}= Create Se	<u>quence</u> 10 15 0.5		
		will create a list of [1	1.0, 11.5, 12.0, 12.5, 13	3.0, 13.5, 14.0, 14.5	5]
Csv Concat	src_pattern, dst_name, has_header=None	Concatinates CSV files vertically If the CSV files has header, set has_heades \$\text{TRUE}*{}			er, set has_header to
		Examples:			
		Commmon. <u>CSV</u> <u>Merge</u>	config/data0[3,4].csv	result/result2.csv	
		Commmon. <u>CSV</u> <u>Merge</u>	config/data0[3,4].csv	result/result2.csv	has_header=\${TRUE}
Csv Merge	src_pattern, dst_name, on_key=0, has header=None	Merges all CSV files	horizontally by on_ke	y key from src_p	pattern
	Tras_freader=Notite	on_key is the order of Default is zero.	of key column that is I	used as key whe	n merging the files.
			not None (default va me. Returns False if o	, .	
		Examples:			
		Common. <u>CSV</u> <u>Merge</u>	config/data0[3,4].csv	result/result2.csv	
		Common. <u>CSV</u> <u>Merge</u>	config/data0[3,4].csv	result/result2.csv	has_header=\${TRUE}
Csv Select	src_file, dst_file, str_row=:, str_col=:, has_header=None	Select part of the CSV file and write it to other file str_row and str_co specify necessary rows and columns. They are using the same form for Python list. I and : means all rows and columns I and : means first 2 rows and all columns I and 1,2 means all rows and 2nd and 3rd columns I o:3 and 1 means 3 rows from the 1st one(0,1,2) and second columns I o:5:2 and 1 means 3 rows(0,3,5) and second column			
				cond column	

		Notes:		
		 Rows and columns are indexed from zero When ':' is used, the string has format: <start>:<stop> or <start>:<stop>:</stop></start></stop></start> <step> For convenience, ':' means all the data, ':x' means first 'x' data</step> Examples: 		
		CSV Select result/data05.csv result/result3.csv 0,1,2 0,1 CSV Select result/data05.csv result/result4.csv : 0,1 CSV Select result/data05.csv result/result5.csv :2 : CSV Select result/data05.csv result/result6.csv 0:3 : CSV Select result/data05.csv result/result7.csv 0:5:2 :		
Diff File	path1, path2, newline=True	Shows difference between files Returns the diff result (multi lines) path1, path2 are absolute paths.		
Err	msg	Prints error msg to console		
Error Line Should Not Be Bigger Than	num, *pattern_list	Checks whether the number of lines that contains error be less than a number		
Error Should Not Be Bigger Than	num, *pattern_list	Checks whether the number of error be less than a number		
File Md5	path	Returns MD5 hash of a file		
Fold Str	ctr	path is an absolute path Foldo a string by adding Nep Width Space ober (0y200b) at 6th ober		
Follow Syslog And Trap	str pattern, log_file_name=syslog-trap.log, delay_str=1s	Folds a string by adding Non-Width-Space char (0x200b) at 6th char Pauses the execution and wait for the pattern is matched if the file <i>log_file_name</i> located in the current result folder.		
	20.5/_0.10	By default the log_file_name is ./result/syslog-trap.log which is created by <u>Follow</u> <u>Syslog and Trap</u> keyword.		
		The keyword should be in tests between Follow Syslog adn Trap Start and Follow Syslog and Trap Stop keywords.		
Get Config Path		Returns absolute path of RENAT config folder path		
Get File Without Error	file_path	Get content of the file and return null string if the file does not exist		
Get Item Config Path		Returns absolute path of current item config folder		
Get Item Name		Returns the name of the running item		
Get Renat Path		Returns the absolute path of RENAT folder		
Get Result Folder		Returns current result folder name. Default is result in current test case. Note: the keyword only returns the name of the result folder not its absolue path.		
Get Result Path		Returns absolute path of the current result folder		
Get Test Device		Return a list of all test device that is used in this test Notes: Device number could less than node number		
Is Stable	seq, threshold, percentile=90	Checks if the value sequence is stable or not		
Keyword Line Should Not Be Bigger Than	num, keyword, *pattern_list	Checks whether the number of line containing the keyword be less than a number		
Keyword Should Not Be Bigger Than	num, keyword, *pattern_list	Checks whether the number of keyword be less than a number		
Load Plugin		Load plugin in renat/plugin folder		
Log	msg, level=1	Logs msg to the current log file (not console) The msg will logged only if the level is bigger than the global level \${DEBUG} which could be defined at runtime. If \${DEBUG} is not defined, it will be considered as the default level as 1.		
		Examples:		
		Common. <u>Log</u> XXX # this always be logged		
		Common.Log AAA level=2 # this will not be logged with common run.sh		
		Common. <u>Log</u> BBB level=2 # ./run.sh -v DEBUG:2 will log the message		
		Notes: For common use level 1: is default level 2: is debug mode level 3: is very informative mode		

Log To Console	msg, level=1	Logs a message to console			
Loop For Node Tag	var, tags, *keywords	See Common. Print for more details about debug level Repeatly executes RF keyword for nodes that has tag tags			
	,	multi tags are separated by : keywords has same meaning with keywords under the Run Keywords of RobotFramework (keyword and its arguments are separated AND with the others.			
		Example:			
		Loop For Node Tag \\${node} tag1			
		Switch \\${node} AND			
		Cmd show system user AND Cmd show system uptime			
		, , ,			
		Note: \$ in variable name must be escaped			
Md 5	str	Returns MD5 hash of a string			
Merge Files	path_name, file_name	Merges all the text files defined by path_name to file_name Example: Merge Files //result/*.csv //result/test.csv			
Mib For Node	node	Returns the mib file name for this node mib file is define by mib keyword under			
		the node in local.yaml node: vmx11: device: vmx11 snmp_polling: yes mib: mib11.txt			
		Default value is defined by mib keyword from global config/snmp-template.yaml the type of the node			
		Example:			
		\${mib}= Common. <u>MIB For Node</u> vmx11			
Node With Attr	attr_name, value	Returns a list of nodes which have attribute attr_name with value value			
Node With Tag	*tag_list	Returns list of node from local.yaml that has ALL tags defined by tag_list			
		vmx11: device: vmx11 snmp_polling: yes tag: - tag1 - tag2			
		Examples:			
		\${test3}= Common. <u>Node With Tag</u> tag1 tag3			
Node Without Tag	*tag_list	Returns list of node from local.yaml that does not has ANY tags defined by tag_list			
		Tag was defined like this in local.yaml vmx11: device: vmx11 snmp_polling: yes tag: - tag1 - tag2 Examples:			
Davis	was a disease of Ob	\${test3}= Common.Node Without Tag tag3			
Pause	msg=, time_out=3h, error_on_timeout=True, default_input=	Displays the message msg and pauses the test execution and wait for user inp In case of error_on_timeout is True(default), the keyword will raise an error wher timeout occurs. Otherwise, it will continue the test.			
		Notes: If the variable \${RENAT_BATCH} was defined, the keyword will print out message and keeps running without pausing.			
		Examples:			
		Common. Pause Waiting 10s error_on_timeout=\${TRUE} default input Common. Pause Waiting 10s			
Ping Until Ok	node, wait_str=5s, extra=-c 3	Ping a node until it gets response. Then wait for more wait_str Default extra op is -c 3			

Random Name	base, a=0, b=99	Returns a random name by a base and a random number between [a,b]	
		Example:	
		\${FOLDER}= Random Name capture_%05d 0 99	
Random Number	a=0, b=99	Returns a random number between [a,b]	
Renat Version		Returns RENAT version string	
Set Multi Item Variable	*vars	Set multiple varibles to be <i>suite variable</i> at the same time Suite variables (or item variable) could be access anywhere in all the item scenario.	
Set Result Folder	folder	Sets the result folder to folder and return the old result folder. The result folder contains all output files from the test likes tester ouput, config file folder is a folder name that under current test case folder	
		The system will create a new folder if it does not exist and set its mode to 0775 Note: Result folder should be set at the begining of the test. Changing result folder only has effect on up comming connection	
Slack	msg, channel=#automation_dev, user=renat, host=127.0.0.1	Post a message to Slack	
Str 2 Seq	str_index, size	Returns a sequence from string format Samples: Str2Seq : 5 # (0,1,2,3,4) Str2Seq :2 5 # (0,1) Str2Seq 1:3 5 # (1,2) Str2Seq 0:5:2 5 # (0,2,4)	
Version		Returns the current version of RENAT	

Altogether 48 keywords.
Generated by <u>Libdoc</u> on 2018-04-12 19:20:22.



VChannel

Library version: RENAT 1.7.1
Library scope: test suite
Named arguments: supported

Introduction

A basic library that provides Terminal connection to routers/hosts

VChannel is a core RENAT library that maintains input/output to nodes with an attached virtual terminal. It encapsulates the SSH/Telnet connections behind and provides common usage of access and execute commands to the nodes. Each channel instance has its own log file and a virtual terminal.

Table of Contents

- Device, Node and Channel
- Connections
- Shortcuts
- Keywords

Device, Node and Channel

RENAT has 3 types of connection target. Device, Node and Channel.

Device

Each device stands for a real physical box that has its own IP address and is defined in the master file device.yaml . Users do not directly use device in keywords.

Node

Node is a logical instance of a device. It could stand for a logical instance of a router or just a virtual terminal to the router. Nodes were defined in local.yaml of the test case. Several nodes could point to a same device.

Channel

Each channel holds a session to a node. Each channel has its own log file and a virtual terminal. Any command used by <u>Cmd, Write</u> or <u>Read</u> will be logged to the log file. Each channel is identified by a name when it is created with <u>Connect</u> keyword and is released with <u>Close</u> keyword.

Notes: multi sessions to a same device could be done with predefined multi nodes to same device in the local.yaml file or by using multi <u>Connect</u> with different <u>name</u>.

Connections

The library provides a channel to a target node. Each channel is attached with a virtual terminal. Input and output to the node are made through this virtual terminal. This will help to provide the output looks like the output when operator is using the real terminal.

When keywords <u>Read</u>, <u>Write</u>, <u>Cmd</u> are used, if the connection is not available anymore, the system will try to reconnect to the host with the information provided in the 1st connect. It will try max_retry_for_connect times and wait for interval_between_retry seconds between retries. The values of max_retry_for_connect and interval_between_retry are defined in ./config/config.yaml

Usually when RENAT could not make the connections to the target, the system will raise an exception. But if the <code>ignore_dead_node</code> is defined as yes in the current active <code>local.yaml</code>, the system will ignore the dead node, remove it from the global variable <code>LOCAL[node]</code> and <code>NODE</code> and keep running the test.

Shortcuts

Change Log · Change Prompt · Close · Close · Close · Close · Cond · Cmd · Cmd · Connect · Connect · Close · Close · Channel · Get Channel · Get Channel · Get Channel · Connect · Connect

Keyword	Arguments	Documentation		
Change Log	log_file, mode=w	Stops current log file and create a new log file.		
		Every log from that point wil	I be saved to the new log fil	e Return old log filename
Change Prompt	str_prompt	Changes the current prompt of the channel		
		Returns previous prompt. Us command that expects to se Example:	•	pt before execute the new
		Router. Switch	vmx11	
		\${prompt}=	VChannel. Change Prompt	6
		VChannel. <u>Cmd</u>	start shell	
		VChannel. <u>Cmd</u>	Is	
		VChannel. Change Prompt	\${prompt}	

Close		Closes current connection and reset the channel name	
Close All		Closes all current sessions and flush out all log files.	
		Current node name was reset to None	
Cmd	command, prompt=, match_err=	Executes a command and wait until for the prompt.	
	(unknown command. syntax error, expecting <command/> .)	This is a blocking keyword. Execution of the test case will be postponed until the pror appears. If prompt is a null string (default), its value is defined in the ./config/template.	
		Output will be automatically logged to the channel current log file.	
		See Common for details about the config files.	
Cmd Yesno	cmd, ans=yes, question=? [yes,no]	Executes a cmd, waits for question and answers that by ans	
Connect	node, name, log_file, timeout=20m,	Connects to the node and create a VChannel instance	
	w=80, h=32, mode=w	Login information is automatically extracted from yaml configuration. By defaullt a virt terminal (vty100) with size 80x64 is attachted to this channel.	
		If a login was successful, VChannel will create a log file name log_file for the connect the current result folder of the test case. This log file will contain any command input/of executed on this channel.	
		Multi sessions to the same node could be open with different names. Use <u>Switch</u> to could the current active session by its name	
		Examples:	
		Connect vmx11 vmx11.log Connect vmx11 vmx11.log 80 64	
		See Common for more detail about the yaml config files.	
Connect All	prefix=	Connects to all nodes that are defined in active local.yaml.	
		A prefix prefix was appended to the alias name of the connection. A new log file by <alias>.log was automatiocally created.</alias>	
		See Common for more detail about active local.yaml	
Flush All			
Get Channel	name	Returns a channel by its name	
Get Channels		Returns all current vchannel instances	
Get Current Channel		Returns the current active channel	
Log	msg	Writes the log message msg to current log file of the channel	
Read	silence=False	Returns the current output of the virtual terminal and automatically logs to file.	
		In normal mode this will return the unread output only, not all the content of the scree	
Reconnect	name	Reconnects to the name node using existed information	
		The only difference is that the mode of the log file is set to `a+` by default	
Set Log Separator	sep=	Set a separator between the log of read, write or cmd keywords	
Start Screen		Starts the screen mode.	
Mode		In the screen mode, the output is just the same with the real terminal. It means that ar real-time application likes top will be captured as-is. Consecutive <u>read</u> from this VCha instance may produce redundancy ouput.	
Stop Screen		Stops the screen mode and returns to normal mode	
Mode		In screen mode, <u>Write</u> does not return any thing and no output is logged. In normal moescape sequences are not processed by the virtual terminal.	
Switch	name	Switches the current active channel to name. There only one active channel at any tir	
		Examples:	
		VChannel. Switch vmx12	
Write	str_cmd, str_wait=1s,	Sends str cmd to the target node and return after str wait time.	
	start_screen_mode=False		
		If start_screen_mode is True, the channel will be shifted to Screen Mode. Default valuescreen_mode is False.	
		In normal mode, a new line char will be added automatically to the str_cmd and the command return the output it could get at that time from the terminal and also logs that the log file.	
		In screen Mode, if it is necessary you need to add the new line char by your own and ouput is not be logged or returned from the keyword.	
		Parameters:	

str_cmd: the command
 str_wait: time to wait after apply the command
 start_screen_mode: whether start the screen mode right after writes the command
 Special input likes Ctrl-C etc. could be used with global variable \${CTRL-<char>}
 Returns the output after writing the command the the channel.
 Notes: This is a non-blocking command.
 Examples:
 VChannel. Write monitor interface traffic start_screen_mode=\${TRUE}
 VChannel. Write \${CTRL_C}
 # simulates Ctrl-C

Altogether 20 keywords.
Generated by <u>Libdoc</u> on 2018-04-12 19:20:25.



Logger

Library version:RENAT 1.7.1Library scope:test suiteNamed arguments:supported

Introduction

Provides advanced logging functions. Every <u>Logger</u> instance has one <u>VChannel</u> object and the is synchronized with the current active <u>VChannel</u>. **Notes:** log file is not updated pararelly. Anytime a terminal is switched to, it will update its log file.

Shortcuts

Log · Log All · Switch

Keywords

Keyword	Arguments	Documentation
Log	msg, with_time=False, mark=***	Inserts a message msg to the current <i>VChannel</i> log file. A default mark of *** will be added at the beginning ant the end of this message. Example:
		Logger. <u>Log</u> START TRAFFIC FROM HERE \${TRUE} Logger. <u>Log</u> START TRAFFIC FROM HERE \${False} ===
Log All	msg,	inserts a message msg to current all VChannel log files.
	with_time=False, mark=***	A default mark of *** and newline will be added at the beggining and the end of this message.
		Example:
		Logger. Log All START TRAFFIC FROM HERE \${TRUE} Logger. Log All START TRAFFIC FROM HERE \${TRUE} ===
		The log file will look likes this:
		user@vmx12>
		*** 06:01PM on August 13, 2017: START TRAFFIC FROM HERE ***
		=== 06:01PM on August 13, 2017: START TRAFFIC FROM HERE ===
		configure
Switch	name	Switches the current <u>VChannel</u> instance to name. name is the name of the <u>VChannel</u> (usually is the node name defined in the current active local.yaml).
		Example:
		Logger. Switch vmx11

Altogether 3 keywords.

Generated by <u>Libdoc</u> on 2018-04-12 19:20:23.

Q

OpticalSwitch

Library version:RENAT 1.7.1Library scope:test suiteNamed arguments:supported

Introduction

A library provides control for L1 Optical Switch

Unlike other device, there is no Switch keywork with optical switch. Usually user only need to care about the interfaces not the ports of the switches.

Shortcuts

 $\textbf{A} \texttt{d} d \cdot \textbf{C} \texttt{lear} \, \texttt{By} \, \texttt{File} \cdot \textbf{C} \texttt{lose} \, \texttt{All} \cdot \textbf{C} \texttt{onnect} \, \texttt{All} \cdot \textbf{D} \, \texttt{elete} \cdot \textbf{G} \\ \texttt{et} \, \texttt{Connection} \, \texttt{Info} \cdot \textbf{Load} \, \texttt{From} \, \texttt{File} \cdot \textbf{S} \\ \texttt{ave} \, \texttt{To} \, \texttt{File} \cdot \textbf{C} \\ \texttt{elete} \cdot \textbf{C} \\$

Keywords

Keyword	Arguments	Documentation
Add	dev1, intf1, dev2, intf2, direction=bi, force=False	Adds a connection. See details in each module help
Clear By File	file_name=, comment=#	Clears all x-connections defined in the connection file
		Default connection file is defined in optic/connection of config/local.yaml
Close All		Close all connections
Connect All		Connect to all L1 switch and read all neccesary information
Delete	dev1, intf1, dev2, intf2, direction=bi, force=False	Deletes a connection. See details in each module help
Get Connection Info	dev, intf	Returns connection information. See details in each module help.
Load From File	file_name=, force=True, comment=#	Loads the connection file and set the connections filename is the name of the connection file under the current config folder. If filename is empty, the value of optic/connection from config/local.yaml will be used. The connection file supports jinja2 template language. Besides, # is the default comment char which could be changed The format of connection file follows: - each connection is described by 1 line - source and destination are separated by `- or > , which mean `bidirection or unidirection (unidirection connects source tx to dest rx Connection file sample: - device1:port1 - device2:port2 - device1:port3 > device2:port Examples: OpticalSwitch.Load From File
Save To File	file_name	OpticalSwitch. Load From File save1.conn Saves the current connection of all devices in this test. By default, all interfaces of the devices are save. If a connection file is given, only interfaces
		specified in the connection file are saved Examples: OpticalSwitch. Save To File save1.conn

Altogether 8 keywords.
Generated by <u>Libdoc</u> on 2018-04-12 19:20:24.



calient

Library scope: global **Named arguments:** supported

Introduction

A library provides control for Calient Optical Switch

Table of Contents

- Master file
- Connection file Format
- Shortcuts
- <u>Keywords</u>

Master file

The L1 switch provides a mechanism to remotely connect device interface. Each device interface has been wired to L1 switch already. The connection was described in the master file located specific by *calient-master-path* in the configuration file *renat/config/config.yaml*.

The master file includes several Calients in each tab. The column meaning and order is trivial.

Connection file Format

Keywords Load From File, Clear By File and Save To File use the x-connection file. X-connection files are text files and have the following format:

this is the comment device1,interface1,-,device2,interface2 device1,interface1,>,device2,interface2

The separator - means a bidirection connection and > means a unidirection connection. For a unidirection connection, device1/interface1 TX will be connected to device2/interface2 RX.

Note: The separator character must be surrounded by spaces or commas.

The connection file also support jinja2 template format. After the template is evaluated, comment could be used by comment char

There is no need to specify which L1 switch for the x-connection. The system will automatically find the appropriate switch.

Shortcuts

 $\textbf{A} \, \text{dd} \cdot \textbf{D} \, \text{elete} \cdot \textbf{G} \, \text{et Connection Info}$

Keyword	Arguments	Documentation
Add	self, dev1, intf1, dev2, intf2,	Adds x-connection between dev1:intf1 and dev2:intf2
	direction=bi, force=False	direction is bi for bi-direction or uni for uni-direction. If direction is uni, the tx of dev 1:port 1 will be connected to $dev 2:port 2$.
		With force mode, existed connection that use those ports will be deleted. Without force mode, an existed connection will make the keyword fails
		Examples:
		OpticalSwitchAdd mx2008-31-33 xe-3/0/0 mx2008-31-33 xe-3/0/1 bi \${TRUE}
		Note : when force is False but the current ports is owned by the same connection endpoints, keyword will succeed.
		For a bidirection connection, 2 single uni-direction connection will be made instead of 1 bidirection connection. This will make the link could be simulated tx/rx failure later.
Delete	self, dev1, intf1, dev2, intf2, direction=bi, force=False	Deletes the connection between dev1:intf1 - dev2:intf2
	unection=bi, force=raise	Examples:
		OpticalSwitch. <u>Delete</u> mx2008-31-33 xe-3/0/1 mx2008-31-33 xe-3/0/1 uni
Get Connection Info	self, dev, intf	Returns information of the optic switch port that connected to dev:intf. The information is in jason format.
		Examples:
		OpticalSwitch. Get Connection Info mx2008-31-33 xe-3/0/1
		return information looks like below:
		result = {u'outoc': u'NOHW', u'outopwdh': u'-20.0', u'inos': u'OOS', u'outalias': u", u'inowner': u'TRANSIT', u'outopwct': u'-23.0', u'inpower': u'-3.4', u'inas': u'IS', u'outpower': u'-4.8', u'outas': u'OOS-NP', u'inopt': u'-4.8', u'outas': u'OS-NP', u'inopt': u'-4.8', u'outas': u'-4.8', u'outas': u'OS-NP', u'inopt': u'-4.8', u'outas': u'OS-NP', u'inopt': u'-4.8', u'outas':
		u'-17.0', u'inopth': u'13.0', u'incircuit': u'3.3.1>3.3.2', u'inalias': u",

u'inoc': u'NOHW', u'inoptc': u'-20.0', u'outos': u'OOS', u'port': u'3.3.1', u'outowner': u'NONE', u'outcircuit': u"}

Altogether 3 keywords.

Generated by <u>Libdoc</u> on 2018-04-12 19:20:27.



g4ntm

Library scope: global **Named arguments:** supported

Introduction

A library provides control for Telescent Network Topology Management (NTM) robot patch.

Shortcuts

Add · Delete · Get Connection Info

Keywords

Keyword	Arguments	Documentation
Add	self, dev1, intf1, dev2, intf2, direction=bi, force=False	
Delete	self, dev1, intf1, dev2, intf2, direction=bi, force=False	Deletes the connection between dev1:intf1 - dev2:intf2
Get Connection Info	self, dev, intf	Returns information about the connection by router/interface

Altogether 3 keywords.

Generated by <u>Libdoc</u> on 2018-04-12 19:20:28.



Router

Library version:RENAT 1.7.1Library scope:test suiteNamed arguments:supported

Introduction

A class provides keywords for router controll. Usual command could be executed via VChannel. This class provides the vendor independent commands

Device's type is defined in master device.yaml. The system will load appropriate modules for each device.

Details about keywords provided by modules could be found in document of each module likes:

- Juniper module
- Cisco module
- GR module

Keywords provides by above module could be executed through <u>Xrun</u> keyword or directly called from Router. Examples:

Router. Xrun	Load Config	
Router.Load Config		

Shortcuts

Cmd · Cmd And Wait For · Exec File · Follow Mib · Get Ip · Read · Snap · Snap Diff · Stop Screen Mode · Switch · Write · Xrun

Keyword	Arguments	Documentation	ocumentation					
Cmd	command=, prompt=	Runs the command command and waits until the prompt defined for this router. This keywork is identical to VChannel.Cmd						
		Examples: Router. <u>Cmd</u> set system login user testtest authentication plain- password: # wait for						
		Router. Cmd Renat2017 password: # wait password:	for					
		· ·	for default					
		The above sample creates an output likes this:						
		user@vmx11# set system login user testtest authentication plain-text-password New password:Renat2017 Retype new password:Renat2017						
		[edit]						
Cmd And Wait For	command, keyword, interval=30s, max_num=10, error_with_max_num=True	Execute a command and expect keyword occurs in the output. If not wait for interepeat the process again	erval and					
		After max_num, if error_with_max_num is True then the keyword will fail. Orther continues.	wise the tes					
Exec File	file_name, vars=, comment=#, step=False, str_error=syntax,rror	Executes commands listed in file_name Lines started with comment character is considered as comments						
		file_name is a file located inside the config folder of the test case.						
		This command file could be written in Jinja2 format. Default usable variables are LOCAL and GLOBAL which are identical to Common.LOCAL and Common.GLOBAL. More variables could be supplied to the template by vars.						
		vars has the format: var1=value1,var2=value2						
		If step is True, after very command the output is check agains an error list. And if a match is found, execution will be stopped. Error list is define by str_err, that contains multi regular expression separated by a comma. Default value of str_err is error						
		A sample for command list with Jinja2 template:						
		show interface {{ LOCAL['extra']['line1'] }} show interface {{ LOCAL['extra']['line2'] }}						
		{% for i in range(2) %} show interface et-0/0/{{ i }} {% endfor %}						
		Examples:						

		Router. <u>Exec File</u> cmd.lst
		Router. <u>Exec File</u> step=\${TRUE} str_error=syntax,error
		Note: Comment in the middle of the line is not supported For example if comment is "# "
		# this is comment line < this line will be ignored ## this is not an comment line, and will be enterd to the router cli, but the router might ignore this
Follow Mib	node_list, wait_time=10s,	Waits until all the nodes defined in node_list become stable.
	interval_time=5s, len=12, percentile=80, threshold=75, max_len=300, factor=1	Stableness is checked by SNMP polling result. The MIB list is define by mib in node section Parameter:
		 wait_time(1): the time before the evaluation starting interval_time(2): interval between SNMP polling time threshold: below this value is evaluated as stable len(3): the size of the evaluation window (number of values that are used in each valuation) percentile: real useful percentage of data (ignore top 100-percentile percent) max_len(4): maximum waiting lend for this checking
		time sequence:(1) -(2)- <(3)> poll poll <(4)>
Get Ip		Returns the IP address of current node Examples:
		\${router_ip}= Router. <u>Get IP</u>
Read		Executes command read for the current vchannel coressponded to this router
Snap	name, *cmd_list	Remembers the result of a list of command defined by cmd_list
		Use this keyword with <u>Snap Diff</u> to get the difference between the command's result. The a new snapshot will overrride the previous result.
		Each snap is identified by its name
Snap Diff	name	Executes the comman that have been executed before by name snapshot and return the difference.
		Difference is in context diff format
Stop Screen Mode		Stop the screen mode
Switch	name	Changes the current channel of this router to name
		Rerturns old node name
		Note: This is identical to VChannel.Switch
		Examples:
		Router. Switch vmx11 Router. Cmd show version
Write	cmd_str, wait_str=1s, start_screen_mode=False	Executes command write for the current vchannel coressponded to this router
Xrun	cmd, *args, **kwargs	Runs the vendor independent keywords.
		Parametes:
		cmd: a keywordargs: other argumemts
		Examples:
		Router. Xrun Flap Interface ge-0/0/0
		This keyword will then actually calling the correspond keyword for the device type.

Altogether 12 keywords. Generated by <u>Libdoc</u> on 2018-04-12 19:20:23.



cisco

Library scope:globalNamed arguments:supported

Introduction

Provides keywords for Cisco platform

Shortcuts

Get Version

Keywords

Keyword Arguments		Documentation		
Get Version	self	return router version information		

Altogether 1 keywords.

Generated by <u>Libdoc</u> on 2018-04-12 19:20:26.



gr

Library scope: global Named arguments: supported

Introduction

Provides keywords for Hitachi GR platform

Shortcuts

Get Chassis Serial · Get Version

Keywords

Keyword	Arguments	Documentation		
Get Chassis Serial self		Returns the serial number of the chassis		
Get Version	self	return router version information		

Altogether 2 keywords.
Generated by <u>Libdoc</u> on 2018-04-12 19:20:26.



juniper

Library scope: global **Named arguments:** supported

Introduction

Provides keywords for Juniper platform

Notes: Ignore the self parameters when using those keywords.

Shortcuts

Create Best Path Select Data · Disable Interface · Enable Interface · Enable Interface · Get Chassis Serial · Get Cli Mode · Get Config · Get Current Datetime · Get File · Get Intf Addr · Get Route Number · Get Version · Link Status · Load Config · Number Of Bgp Neighbor · Number Of Ospf Neighbor · Numb

Keyword	Arguments	Documentation					
Create Best	self, route_content,	Creates the matrix of best path selection					
Path Select Data	output_excel=best.xlsx	Provides the test described in smb://10.128.3.91/SharePoint01/31_VerificationRoom/31_13_ /BGP-Best-Path-Selection All-in-One _20161118 / The test uses predefined Ixia config and follows predefined steps					
Disable Interface	self, intf	Disables an interface intf					
Enable Interface	self, intf	Enables an interface intf					
Flap Interface	self, intf, time_str=10s	Simulates an interface flap for interface intf					
		Disables the interface and wait for a while before turning it up again					
Get Chassis Serial	self	Returns the serial number of the chassis					
Get Cli Mode	self	Returns current mode of the CLI.					
		Return value is config for configuration mode or command for command mode					
Get Config	self, dst_name=	Gets the current configuration file of the router to current result folder. Wait for str_timeout to finish the download, default str_timeout is 10 seconds. Increases this value if the config file is large.					
		Default dst_name is juniper.conf.gz					
Get Current Datetime	self, time_format=%H:%M:%S, delta_time=0s, dir=+, **kwargs	Returns the current date time with vendor format delta_time will be added or subtracted to current time, default is 0s					
		time_format decides the time part of the output. Example result are :					
		May 24 04:14:25 May 4 04:14:25					
		Note: The date part is padded by space, and the result is allways 15 characters					
Get File	self, src_file, dst_file=	Gets a file from router					
		 src_file is a absolute path insides the router dst_file is a file name under result folder 					
Get Intf Addr	self, intf_name, family=inet	Returns the tuple of address and netmask of an interface					
		family should be inet or inet6 If the address is not set, (",") will be returned.					
Get Route	self, table=inet.0	Returns number of active route in the table					
Number		table could be inet.0 or inet.6					
Get Version	self	Returns router version information					
Link Status	self, if_name	Returns link physical status as string (aka: "up down", "up up")					
Load Config	self, mode=set, config_file=,	Loads configuration to a router. Usable mode is set, override, merge and replace					
	confirm=0s, vars=, err_match= (syntax error)	set mode uses configuration that contains set command. Mode override, merge and replace use ordinary JunOS configuration file with appropriate mode. config_file is a configuration file inside the config folder of the current test case.					
		Config file could includes jinja2 template. The template will be evalued with <i>LOCAL</i> , <i>GLOBAL</i> and varibles defined by <i>vars</i> . The <i>vars</i> has the format: var1=value1,var2=value2					
		If the loading has no error that match the error_match, the configuration will be committed.					
		The keywordl waits for confirm seconds before rollback the committed configuration. A zero value indicates an immediatly commit					

Number Of Bgp Neighbor	self, state=Established	Returns number of BGP neighbor in state state
Number Of Ospf Neighbor	self, state=Full	Returns number of OPSF neighbors with status state
Number Of Ospf3 Neighbor	self, state=Full	Returns number of OPSFv3 neighbors with status state

Altogether 17 keywords. Generated by <u>Libdoc</u> on 2018-04-12 19:20:25.



WebApp

Library version:RENAT 1.7.1Library scope:test suiteNamed arguments:supported

Introduction

A library provides common keywords for web applications (aka Samurai, Arbor TMS)

The library utilize Selenium2Library and adds more functions to control Samurai application easily.

The WebApp uses the configuration in local.yaml in webapp section:

...
webapp:
samurai-1:
device: samurai-b
profile: samurai.profile
arbor-1:
device: arbor-sp-a
profile: samurai.profile

Selenium2Library keywords still could be used along with this library. See Selenium2Library for more details.

See Arbor, Samurai for details about keywords of each application.

Shortcuts

 $\textbf{C} \textbf{apture Screenshot} \cdot \textbf{C} \textbf{onnect All} \cdot \textbf{R} \textbf{eset Capture Counter} \cdot \textbf{Set Capture Counter} \cdot \textbf{Set Capture Format}$

Keywords

Keyword	Arguments	Documentation					
Capture	filename=None,	Captures the current screen to file					
Screenshot	extra=	Using the internal counter for filename if filename is not specified. In this case, the filename is defined by a preset format. Set Capture Format could be used to change the current format.					
		An extra information will be add to the filename	e ii extra is defined				
		Examples:					
		Samurai. <u>Capture Screenshot</u>	# samurai_000000001.png				
		Samurai. <u>Capture Screenshot</u> extra=_list	# samurai_0000000002_ <i>list</i> .png				
		Arbor. <u>Capture Screenshot</u>	# arbor_000000001.png				
		Arbor. <u>Capture Screenshot</u> extra=_xxx	# arbor_000000001_xxx.png				
		Samurai. <u>Capture Screenshot</u> file_name=1111	.png # 1111.png				
Connect All		Connects to all applications defined in local.yaml					
		The name of the connection will be the same of the webapp name					
Reset Capture Counter		Resets the counter of the screen capture					
Set Capture Counter	value=0	Sets the counter of the screen capture to value					
Set Capture	format	Sets the format for the screen capture file					
Format		The format does not include the default prefix or arbor	png The default format is <mod>_%010d. mod could be</mod>	samurai			
		See https://docs.python.org/2/library/string.html#format-specification-mini-language for more details about the format string.					
		Examples:					
		Samurai. Set Capture Format \${case}_%010d	# \${case} is a predefined variable				

Altogether 5 keywords.

Generated by <u>Libdoc</u> on 2018-04-12 19:20:28.



Samurai

Library version: RENAT 1.7.1
Library scope: test suite
Named arguments: supported

Introduction

A library provides functions to control Samurai application

The library utilize Selenium2Library and adds more functions to control Samurai application easily. Without other furthur mentions, all of the concepts of user, user group are Samurai concepts.

By default, RENAT will try to connect all Samurai nodes defined in active local.yaml at the beginning of the test and disconnect from them at the end of the test automatically. Usually user does not need to use Connect All and Close explicitly.

Currently, this module supposed that Samurai is used in Japanese locale. When Samurai module has error, it tried to make the last snapshot in result/selenium-screenshot-x.png. Checking this capture will help to understand the reason of the error.

Some keywords of Samurai is using xpath to identify elements. See Selenium2Library for more details about xpath.

See WebApp for common keywords of web applications.

Selenium2Library keywords still could be used together within this library. See Selenium2Library for more details.

Shortcuts

Add Policy · Add Policy Group · Add User · Capture Screenshot · Change Policy View Group · Click All Elements · Close · Close All · Connect · Connect All · Delete Policy · Delete Policy Group · Delete User · Edit Policy · Left Menu · Login · Logout · Make Item Map · Reset Capture Counter · Select Items In Table · Set Capture Counter · Select Items In Table · Set Capture Format · Show Policy Basic · Show Policy Mo· Show Policy Mo· Show Policy Mo· Start Mitigation · Stop Mitigation · Switch

Keyword	Arguments		Documentation						
Add Policy	**policy	Adds a new Samurai policy							
		policy is a map containing the below information to create the new policy.							
		key							
		name	name of the policy	yes	test001				
		basic alias	alias name of the policy	ycs	test001				
		basic_port_id	another alias		1031001				
		basic_facing	customer Or backbone		customer				
		basic_intf_list	list of router and interface pair, separated by comma	yes	10.128.18.31:xe-0	/0/0.1			
		basic_cidr_list	list of CIDR separate by comma						
		basic_option_filter	optinal filter						
		basic_direction	direction of the traffic (incoming or outgoing)		Incoming				
		traffic_enabled	Enable traffic monitoring or not	yes	\${True} or \${False}	3			
		detection_enabled	Enable detection or not	yes	\${True} or \${False}	3			
		mitigation_zone_name	Name of the zone for mitigation		zone001				
		mitigation_zone_prefix	Prefixes that could mitigate		1.1.1.1/32				
		mitigation_thr_bps	Upper limit (bps)		800,000,000				
		mitigation_thr_pps	Upper limit (pps)		54,000,000				
		mitigation_mo_enabled	Using Arbor TMS MO or not	yes	\${True} or \${False}				
		mitigation_device_list	Devices used for TMS, separated by comma		ArborSP-A				
		mitigation_mo_name	MO name, separated by comma OCN12(ALU)_LOOSE		OSE				
		mitigation_comm_list	commna separated peer/community list	yes	1.10(180.0.1.10)/2914:666,1.11(180.0.1.11)/2914:7				
		nw_monitor_gre1	1st GRE address for NW monitor		210.0.1.1 210.0.1.1 210.0.1.2				
		nw_monitor_gre2	2nd GRE address for NW monitor						
		nw_monitor_ce1	1st CE address for NW monitor						
		nw_monitor_ce2	2nd CE address for NW monitor		210.0.1.2				
		nw_monitor_pe1	1st PE for NW monitor (list) edge		edge01hige-MX20	dge01hige-MX2020-15(118.23.176.244)			
		nw_monitor_pe2	2nd PE for NW monitor (list)		edge01hige-MX20	020-15(118.23.176.244)			
		event_name	name of the message event to make		info1				
		event_addr	address to send the events		user@mail.com				
		view_group	user group that could view this policy, separated by comma	yes	SuperGroup,test_g	group_007			
		Example:	Example:						
		Samurai. Switch samura	ni-1						
		Samurai. <u>Add</u> name= <u>Policy</u>	\${POLICY_NAME}			basic_alias=\${POLICY_NAME}			
		basic_t	facing=customer			basic_intf_list=10.128.18.31:xe- 0/0/0.1			
		basic_c	cidr_list=1.1.1.0/24			basic_direction=incoming			
		traffic_c	enabled=\${TRUE}						
		detection	on_enabled=\${TRUE}						

				one_name=tes evice_list=Arbo		rSP-R		mitigation_zone_prefix=1.1
				evice_list=Arbo o_enabled=\${`		IOF-D		
				o_enabled=\${ o_name=N000		OOSE		
							1.11(180.0.1.11)/2914:777	
			 /ent_name		,		,	event_addr=user@mail.coi
		vi	ew_group=	SuperGroup				
Add Policy	group_name,	Add a new policy gro	oup					
Group	policy_list=*, limit_bps=4000000000, limit_pps=2700000		or this para				a separated of existed pol I policy. limit_bps and limi	-
Add User	group, **user_info	Adds user to the cur privilege and policy	rent group	user_info is a	a dictionary	contains	user information that has	following keys: name, pa
		privilege is existed	privilege th	at has been c	reated (e.g	: system_	admin.	
		noticy could be * fo	r all currer	it nolicies or a	list of polic	v names	that are binded to this use	r
					•	,a	mar are smaller to time acc	
		group is the user gr	oup. Doi(.)	means cure	iii group			
		Examples:						
		Samurai. <u>Add User</u>	OCNDDo	S	name=use	r000	password=Test1234567	8
			privilege=	system_admin	policy=*			
		Samurai. <u>Add User</u>			username:		password=Test1234567	8
			privilege=	system_admin	policy=OC	N11,OCN1	2	
Capture	filename=None, extra=	Captures the current	screen to	file				
Screenshot		_				-	. In this case, the filenam	e is defined by a pre-set f
		Set Capture Format		_				
		An extra information	will be ad	d to the filena	me if extra	is defined		
		Examples:						
		Samurai. <u>Capture S</u>	<u>Screens</u> hot		# sa	amurai 000	00000001.png	
		Samurai. <u>Capture S</u>					00000002_ <i>list</i> .png	
		Arbor. Capture Scre					000001.png	
		Arbor. Capture Screen	<u>eenshot</u>	extra=_xxx	# ar	bor_00000	000001_ <i>xxx</i> .png	
		Samurai. Capture S	<u>Screenshot</u>	file_name=11	11.png # 1	111.png		
Change Policy	name, *group_name	Changes the groups	that could	see this polic	у			
View Group		name is the policy name. group name is a list of policies						
		Example:					-	
		Samurai. <u>Change F</u>	Policy View	Group super_	admin test_	_group001		
Click All	xpath	Click all element in o	current pag	ge defined by	xpath			
Elements		Returns the number of elements that have been clicked						
Close		Closes the current a						
Close All								
		Closes all current op	- ''					
Connect	app, name	Opens a web browse	er and con	nects to applic	cation and a	assigns a	name.	
		If not defined in local	I.yaml tho	se following ke	ey will have	e defaut va	alues:	
		browser	fire	efox	optio	nal		
		login_url	/		optio	na		
		proxy:			optio	nal		
		http: 10.128.8.210:		tional				
		ssl: 10.128.8.210:8		tional		_		
		socks: 10.128.8.21			wofile	nal		
_		profile_dir		onfig/samurai.p		пап		
Connect All		Connects to all appli	cations de	fined in local.	yaml			
		The name of the cor	nnection w	ill be the same	e of the <i>wel</i>	<i>bapp</i> name	Э	
Delete Policy	*policy_names	Deletes poilcies by t	heir name	S				
_		Returned the numbe						
					tom :::!! : :			
		Notes: If the policy of	uoes not e	AISIS, INE SYS	terri Will Not	report an	y enoi.	
		Examples:						
		Samurai. <u>Delete Po</u>	test00	1 test002				
Delete Policy	*group_list	Deletes policy group	S					
Group		Returns the number	of deleted	policy groups	Example:			
		Samurai. <u>Delete Po</u>	licy Group	test group001	I test arour	0002		
	group, *user_list	Deletes user from th						
Delete Hser	group, user_list				nt araus D	sturne +	number of deleted	
Delete User		availe in the		THEADS CHIPP	nı uroub Ke	aums the	number of deleted users	
Delete User			oup. And	means care	3 -			
Delete User		group is the user group Examples:	oup. And .	means cane	3 1			
Delete User								

Edit Policy	**policy	Edits a Samurai policy
		policy contains information about the policy. See <u>Add Policy</u> for more details about policy format
Left Menu	menu	Chooses the left panel menu by its displayed name
		Return a list of 1st meaningful column Example:
		Samurai. <u>Left Menu</u> Traffic
		Samurai. Left Menu Detection
		Samurai. Left Menu
Login		Logs-in into the application
Logout		User and password is set by the template and authentication methods in the master files
Logout Make Item Map	xpath	Logs-out the current application, the browser remains
wake item wap	λραιτ	Makes a item/webelement defined <i>xpath</i> The man is a distingery from item to the WebElement Items name found by yearth are used as keys
Reset Capture		The map is a dictionary from <i>item</i> to the <i>WebElement</i> Items name found by xpath are used as keys Resets the counter of the screen capture
Counter		Tresets the counter of the screen capture
Select Items In	xpath, xpath2,	Checks items in Samurai table by xpath
Table	*item_list	xpath points to the column that used as key and xpath2 is the relative xpath contains the checkbox column.
		item_list is a list of item that need to check. Item in the list could be a regular expresion with the format reg= <regular< td=""></regular<>
		expression.
		The keyword is called with assuming that the table is already visible.
		Returns the tupple of all items and selected items
		Note: Non-width-space (\u200b) will be take care by the keyword.
		Note: if the first item_list is * then the keywork will try to click a link named .
Set Capture Counter	value=0	Sets the counter of the screen capture to value
Set Capture	format	Sets the format for the screen capture file
Format		The format does not include the default prefix .png The default format is <mod>_%010d. mod could be samurai or arbor</mod>
		See https://docs.python.org/2/library/string.html#format-specification-mini-language for more details about the format string.
		Examples:
		Samurai. Set Capture Format \${case}_%010d #\${case} is a predefined variable
Show Policy	policy_name	Makes the virtual browser show basic setting of the policy <i>name</i> .
Basic		A following Samurai. Capture Screenshot is necessary to capture the result.
Show Policy	policy_name	Make the virtual browser show the mitigation setting of a policy
Mitigation		A following Samurai. Capture Screenshot is necessary to capture the result.
Show Policy	policy_name	Make the virtual browser show the MO setting of a policy
Мо		Automatically expand the MO section of other devices if necessary.
		A following Samurai. Capture Screenshot is necessary to capture the result.
Show Policy	policy_name	Make a virtual browser show the mitigation setting of a policy
Monitor		A following Samurai. Capture Screenshot is necessary to capture the result.
Start Mitigation	policy, prefix,	Starts a mitigation with specific prefix
	comment=mitigation started by RENAT,	device is used for matching real device name configured by Samurai If force is TRUE then the keyword will fail if selected
	device=None,	device does not contain device
	force=False	Returns mitigation id and selected arbor device
		Example:
Stop Mitigation	id	\$\(\frac{1}{3}\) \\$\(\delta\) \\(\delta\) \\(\delt
Ciop minganon		Stops a mitigation by its ID
		Example:
Oital:		Samurai. Stop Mitigation 700
Switch	name	Switches the current browser to name

Altogether 29 keywords. Generated by <u>Libdoc</u> on 2018-04-12 19:20:29.



Arbor

Library version:RENAT 1.7.1Library scope:test suiteNamed arguments:supported

Introduction

A library provides functions to control Arbor application

The library utilize Selenium2Library and adds more functions to control Arbor application easily.

See WebApp for common keywords of web applications.

Selenium2Library keywords still could be used along with this library. See Selenium2Library for more details.

Shortcuts

 $\textbf{C} \ \text{apture Screenshot} \cdot \textbf{C} \ \text{lose} \cdot \textbf{C} \ \text{lose} \cdot \textbf{C} \ \text{lonect} \cdot \textbf{C} \ \text{onnect} \cdot \textbf{C} \ \text{onnect} \cdot \textbf{D} \ \text{etail} \ \text{First Mitigation} \cdot \textbf{L} \ \text{ogout} \cdot \textbf{R} \ \text{eset Capture Counter} \cdot \textbf{Set Capture Counter} \cdot \textbf{Set Capture Format} \cdot \textbf{Set Count} \cdot \textbf{Show All Mitigation} \cdot \textbf{Show Detail Mitigation} \cdot \textbf{Switch}$

Keyword	Arguments	Documentation				
Capture	filename=None,	Captures the current screen to file				
Screenshot	extra=	Using the internal counter for filename if filename is not specified. In this case, the filename is defined by a preset format. <u>Set Capture Format</u> could be used to change the current format.				
		An extra information will be add to the filename if extra is defined				
		Examples:				
		Samurai. Capture Screenshot # samurai_000000001.png				
		Samurai. Capture Screenshot extra=_list # samurai_0000000002_list.png				
		Arbor. <u>Capture Screenshot</u> # arbor_000000001.png				
		Arbor. Capture Screenshot extra=_xxx # arbor_000000001_xxx.png				
		Samurai. Capture Screenshot file_name=1111.png # 1111.png				
Close		Closes the current active browser				
Close All		Closes all current opened applications				
Connect	app, name	Opens a web browser and connects to application and assigns a name.				
		Extra information could be added to the webapp sections likes login_url, browser or profile_dir. Default values are:				
		browser firefox				
		login_url /				
		profile_dir ./config/samurai.profile				
Connect All		Connects to all applications defined in local.yaml				
		The name of the connection will be the same of the webapp name				
Detail First Mitigation		Shows details about the 1st mitigation on the list				
Login		Logged-into the Arbor application				
Logout		Logs-out the current application, the browser remains				
Reset Capture Counter		Resets the counter of the screen capture				
Set Capture Counter	value=0	Sets the counter of the screen capture to value				
Set Capture	format	Sets the format for the screen capture file				
Format		The format does not include the default prefix .png The default format is <mod>_%010d. mod could be samurai or arbor</mod>				
		See https://docs.python.org/2/library/string.html#format-specification-mini-language for more details about the format string.				
		Examples:				
		Samurai. Set Capture Format \${case}_%010d # \${case} is a predefined variable				
Set Count	counter=0	Sets current counter to counter				
Show All		Shows all mitigations				
Mitigations						
Show Detail	id					

Mitigation		Shows detail information for a mitigation
Switch	name	Switches the current browser to name

Altogether 15 keywords. Generated by <u>Libdoc</u> on 2018-04-12 19:20:29.



Tester

Library version: RENAT 1.7.1
Library scope: test suite
Named arguments: supported

Introduction

A class provides keywords for controlling testers and traffic generators.

It could load predefined traffic file, manipulate traffic items, start and stop traffic flows. It also could generate traffic reports and support QuickTest for IxNetwork.

Tester information is stored in the active local.yaml likes this:

tester:

tester01:

device: ixnet03_8009 config: vmx_20161129.ixncfg

real_port:

- description: to egde router

chassis: 10.128.32.71

card: 6 port: 11

- description: to backbone router

chassis: 10.128.32.71

card: 6

port: 9

where device is the tester defined in the master device.yaml file. If real_port does not exist, port remapping will not take place. Otherwise, port remapping will use the real_port information to reassign all existed ports and map to Ixia ports.

In this case, the order will be the order when user created the port in Ixia GUI.

Note: User can always confirm the created order by clear sorting in Ixia GUI.

Examples:

Tester. Connect All	
Tester. Switch	tester01
Tester.Load And Start Traffic	
Sleep	30s
Tester.Stop Traffic	

Time format used in this module is same with time string format of Robot Framework. For more details about this, see <u>DateTime</u> library of Robot Framework.

Note: See IxNet module, IxLoad module for details about keyword of each module.

Shortcuts

Close All · Connect · Connect All · Switch

Keywords

Keyword	Arguments	Documentation
Close All		Closes all connections
Connect	name	Connect to the tester name
Connect All		Connects to all testers
Switch	name	Switchs the current tester to name

Altogether 4 keywords.

Generated by <u>Libdoc</u> on 2018-04-12 19:20:24.



ixload

Library scope: global
Named arguments: supported

Introduction

provides functions for IxLoad

RENAT runs a virtual IxLoad client locally in the background that connects to a Windows App server. Keywords from test case will send control messages to the client, which in turn will control the test ports.

Different to IxNetwork, an IxLoad test case usually stops within predefined time before Stop Traffic was called.

Notes: Ignore the self parameters when using those keywords.

Shortcuts

 $\textbf{C} \textbf{lose} \cdot \textbf{C} \textbf{ollect} \, \textbf{Data} \cdot \textbf{G} \textbf{et} \, \textbf{Test} \, \textbf{Report} \cdot \textbf{L} \textbf{oad} \, \textbf{Config} \cdot \textbf{L} \textbf{oad} \, \textbf{Traffic} \cdot \textbf{S} \textbf{tart} \, \textbf{Traffic} \cdot \textbf{S} \textbf{top} \, \textbf{Traffic} \, \textbf{Traffi$

Keywords

ose
llect Data
t Test Report
ad Config
ad Traffic
art Traffic
op Traffic
ad Traffic art Traffic

Altogether 7 keywords.

Generated by <u>Libdoc</u> on 2018-04-12 19:20:27.

Q

ixnet

Library scope: global **Named arguments:** supported

Introduction

provides functions for IxNetwork

RENAT will connect to the App server and control the test ports. Test files and result will be insde the RENAT server.

In order to run RENAT test case with IxLoad, the TCLServer must be activated with Administrator privileges on the Ixia App server.

Notes: Ignore the self parameters when using those keywords.

Shortcuts

Add Port · Add Quicktest · Apply Traffic · Change Frame Rate · Change Frame Rate Dynamic · Change Frame Size · Collect All Data · Collect Data · Get All Test Result · Get Quicktest List · Get Quicktest Result · Get Quicktest Result · Cand Config · Load Traffic · Load Frame Rate Dynamic · Change Frame Size · Collect All Data · Collect Data · Get All Test Result · Get Quicktest List · Get Quicktest Result · Cand Config · Load Traffic · Load Frame Rate Dynamic · Cand Frame Size Result · Cand Result · Cand Config · Can

Keyword	Arguments	Documentation
Add Port	self, force=True,	Add ports using the information from active local config
	time_out=2m, learn_time=2m	 time_out is the wait time until port is connected (default is 2m) learn_time is the time waiting for arp to be learned (default is 2m)
		Sample of local config tester:
		tester: device: ixnet03_8009 config: quicktest.ixncfg real_port: - chassis: 10.128.4.41 card: 4 port: 3 ip: 10.100.11.2 mask: 24 gw: 10.100.11.1 - chassis: 10.128.4.41 card: 4
		port: 4
		ip: 10.100.14.2 mask: 24 gw: 10.100.14.1
Add Quicktest	self, name,	Create a new Quicktest with default value
	test_type=rfc2544throughput, tx_mode=interleaved, clear_all=True	Type could be one of following: rfc2544throughput, rfc2544frameLoss, rfc2544back2back. Use Tester. <u>Load Config</u> to load a customized quicktest
		When clear_all is True, any existed quicktests will be cleared.
		Transmit mode tx_mode takes following values: interleaved (default) or sequential. The mode should be identical with the transmit mod of the ports.
		Notes : The keyword does not create necessary ports. It should be used with a existed configuration by Tester. <i>Load Config</i> or Tester. <i>Add Port</i> keyword.
Apply Traffic	self	Applies the current traffic configuration
		Note: This is a blocking command
Change Frame	self, value, pattern=.*	Changes the frame rate
Rate		Parameter:
		 value: value to set. Depends on the current configuration, this could be percent line rate or bit per second etc. traffic_pattern: a regular expression to identify traffic item name, default is everything `.*
Change Frame Rate Dynamic		Changes the traffic flow rate on-fly
		No need to stop the running traffic to change the rate
		Parameter:
		value: value to set. Depend on the current configuration, this could be percent line rate or bit per second etc.
		pattern: a regular expression to identify traffic item name, default is everything .*
Change Frame	self, type, value, pattern=.*	Changes the frame size
Size		Parameter:
	T. Control of the Con	

		 value: value to set traffic_pattern: a regular expression to identify traffic item name, default is everything.*
Close	self	Disconnects the current tester client
Collect All Data	self, prefix=stat_	Deprecated. Use
Collect Data	self, view, prefix=stat_	Depricated. Use <u>Get Test Result</u>
Get All Test	self, prefix=stat_	Collects all Ixia traffic data after traffic is stopped.
Result		Results are CSV files that are stored in result folder. The prefix prefix is appended to the original view na
Get Quicktest List	self	Returns current loaded Quicktest list
Get Quicktest Result	self, test_index=-1, prefix=, enable all=True	Get the result.csv file from the latest Quicktests
nesuit	eriable_ali=True	test_index is a index of the current Quicktest1 means that last one.
Get Quicktest Result Path	self, test_index=-1	Returns the path of the newest run of a Quicktest
		test_index is a index of the current Quicktest1 means that last one.
Get Test Report	local_name=ixnet_report.pdf,	Generates and get report of the current active test in PDF format local_name: name of the report on local machine. Default is ixnet_report.pdf
Get Teet Recult	enable_all=True self, view, prefix=stat	Collects traffic data of a view and expert to a CSV file in regult folder
det rest nesuit	Sell, View, prelix=Stat_	Collects traffic data of a view and export to a CSV file in result folder
		Currently, supported views are:
		Port Statistics, Global Protocol Statistics, BGP Aggregated Statistics, BGP Aggregated State Counts, OSPF Aggregated Statistics, OSPF Aggregated State Counts, OSPFv3 Aggregated Statistics, OSPFv3 Aggregated Statistics, OSPFv3 Aggregated Statistics, Counts, L2-L3 Test Summary Statistics, Flow Statistics, Flow Detective, Data Plane Port Statistics, User Defi Statistics, Traffic Item Statistics
		Result were store as CSV files in result folder. If there is no valid data, view will be silently ignored
		The prefix prefix is appended to the view name for the CSV file.
Load And Start	self, wait_time1=10s, wait_time2=10s	Combines Load Traffic and Start Traffic to one keyword.
Load Config	self, config_name=,	loads traffic configuration, applies and start protocol if necessary.
	wait_time=2m,	The config file name was defined in the <i>'local.yaml</i> which is a Ixia Network configuration file and located
	wait_time2=2m, apply=True, protocol=True, force=True,	the config folder of the test.
	tx_mode=interleaved	The keyword remap the vports to real port when data is specified in the local configuration file. For some reasons, the txMode is cleared when remapping happens. Use tx_mode to set the TxMode of the remapports.
		Parameters:
		■ apply: applies traffic when True otherwise
		 protocol: starts all protocols when True otherwise force: force to reclaim the ports when True otherwise
		 tx_mode: sequential or interleaved(default)
		■ wait_time : wait time after applying protocols
		wait_time2: maximum wait time befor all ports become available. In
		common case, this is calculated automatically so user does not need to change this value.
		See Common for more details about the yaml configuration files.
Load Traffic	self, wait_time=2m, wait_time2=2m, apply=True, protocol=True, force=True,	
	tx_mode=interleaved	
Loss From File	self, file_name=Flow_Statistics.csv,	Returns packet loss by miliseconds and delta frame.
	tx_frame_i=3, frame_delta_i=5, time1_i=23, time2_i=24	The calculation should be performed when traffic is stopped. The calculation supposed traffic is configure frame per second
Ping	self, dst_ip, src_port_index=0,	Ping from Ixia to dst_ip
	src_intf_index=0	The keyword return the output string as it is. The return could be
		- Port <portname>: ping failed: port not assigned</portname>
		- Response received from <sourcelp>/unknown . Sequence Number <sequencenumber> - Ping request to <destinationlp>/unknown ip failed: <genericpingerror>/<error>: <genericerror>unknown reas - Error: Couldn't find any source interface for Send Ping to <destinationlp> on <portname> Id <id> - Error: Couldn't find any source IP for Send Ping to <destinationlp> on <portname> Id <id></id></portname></destinationlp></id></portname></destinationlp></genericerror></error></genericpingerror></destinationlp></sequencenumber></sourcelp>
		Parameters:
		 src_port_index: index of Ixia port (starts from 0) src_intf_index: index of interface insides the port (starts from 0)
		Examples:
		Tester. <u>Ping</u> 1.1.1.1 0 0 Tester. <u>Ping</u> 1.1.1.1
Reset Config	self	Clears current config and creates new blank config
	I .	

Set Bgp Items self, port_index, neighbor_index, cutte_range_index, is_enables Parameters: • port_index index of the port • index index of the port • index index of the port • index index of the religiblor or " • order index index of the religiblor or " • order index index of the religiblor or " • order index index of the religiblor or " • order index index of the religiblor or " • order index index of the religiblor or " • order index index of the religiblor or " • order index index of the religiblor or " • order index index of the religiblor or " • order index index of the religiblor or " • order index index of BGP learns or " index or index of BGP neighbor (index is started from zero) • vport_index is the larget yout index • order index is the larget yout index • order index is a finished. TRUE or FALSE Examples: Tester Set BGP Item 0 vport_index or enabled-signal. Tester Set BGP Ite	Set All Traffic	wait_until_finish=True self, enabled=True	Warning: it could take a long time to finish a quicktest Enables/Disables all traffic items at once	
Parameters:		Jon, Gradica-Trac	Enables/ Disables all traffic at Office	
Teater_Set BGP_bens_0 \$ \$ \$ \$ \$ \$ \$ \$ \$	Set Bgp Items	neighbor_index,	Parameters: port_index: index of the port neighbor_index: index of the neighbor or * route_range_index: index of the route range or * is_enable: \${TRUE} or \${FALSE}	
wargs contains following parameters:			Tester. Set BGP Items 0 * * \${FALSE}	
Set Capture Port self, data_mode=True, control_mode=True, control_mode=True, port_index=0 Set_index=0 Set_index=0 Capture packets for follow port port_index: is a index of current test port (start from 0) data_mode: capture data packets and save in https://disables.com/capture-controls packets and save in https://disables.com/capture-controls packets and save in https://disables.com/capture-controls packets and save in https://disables.com/capture-controls packets and data_mode only saves data packet Examples: Tester_Set_Capture Port 0 Tester_Set_Capture Por		self, *indexes, **kwargs	kwargs contains following parameters: indexes: is a list of index of BGP neighbor (index is started from zero) vport_index: is the target vport index enabled: TRUE or FALSE Examples: Tester.Set BGP Item 0 1 vport_index=0 enabled=\${FALSE}	
Parameters: • items: a list of Ixia traffic item name • enabled: False or True, the mode to set traffic item to, default is True (enabled) Note: traffic item could be specified by :: <num> format. In this case the num is the order of traffic count from zero. Returns True if all items are set coordinately or otherwise Examples: Set Traffic Item Traffic Item 1 Traffic Item 2 Set Traffic Item Traffic Item 2 Set Traffic Item Traffic Item 1 Traffic Item 2 Set Traffic Item Traffic Item 1 Traffic Item 2 Set Traffic Item Traffic Item 1 Items Set Traffic Item 2 Set Traffic Item 3 Traffic Item 4 Set Traffic Item 4 Traffic Item 5 Set Traffic Item 5 Traffic Item 6 Set Traffic Item 6 Traffic Item 7 Set Traffic Item 7 Traffic Item 8 Set Traffic Item 8 Traffic Item 9 Set Traffic Item 9 Traffic Item 1 Set Traffic Item 1 Traffic Item 1 Set Traffic Item 9 Traffic Item 1 Set Traffic Item 9 Traffic Item 1 Set Traffic Item 1 Traffic Item 1 Traffic Item 1 Traffic Item 1 Set Traffic Item 1 Traffic Item 1 Traffic Item 1 Traffic Item 1 Set Traffic Item 2 Set Traffic Item 1 Traffic Item 1 Traffic Item 2 Set Traffic Item 1 Traffic Item 1 Traffic Item 2 Set Traffic Item 2 Set Traffic Item 1 Traffic Item 1 Traffic Item 2 Set Traffic Item 1 Traffic Item 1 Traffic Item 2 Set Traffic Item 1 Traffic I</num>	•	control_mode=True,	Capture packets for follow port port_index: is a index of current test port (start from 0) data_mode: capture data packets and save in <intf>_HW.cap file control_mode: capture controls packets and save in <intf>_SW.cap file Note: control_mode saves all control packets and data_mode only saves data packets. Note: control_mode saves all control packets and data_mode only saves data packet Examples: Tester. Set Capture Port 0</intf></intf>	
The keyword return True if succeeds Start Capture Start Capture Start portocol Start Protocol Start Proto	Set Tramic item	sen, nems, kwargs	Parameters: items: a list of Ixia traffic item name enabled: False or True, the mode to set traffic item to, default is True (enabled) Note: traffic item could be specified by :: <num> format. In this case the num is the order of traffic item count from zero. Returns True if all items are set coordinately or otherwise Examples: Set Traffic Item Traffic Item 1 Traffic Item 2 Set Traffic Item @{item_list}</num>	
Start Capture Start Capture Start Protocol Start Start Protocol Start Traffic Start Start Protocol Start S				
Start Protocol self, wait_time=1m Starts all protocols and wait for wait_time Default wait_time is 1 minute. Make sure wait_time is big engouh to start all protocols. Start Traffic self, wait_time=30s Starts the current traffic settiing and wait for wait_time. Note: This is a asynchronus action. After called, the keyword finishes immediatly but it will take a before traffic starts By default the keyword will wait for 30 seconds. Stop All Protocols Stop And Save Capture self, prefix=, wait_until_finish=True, monitor_interval=5s Stop And Save Capture Captured files will be saved in current result folder with prefix appended in their names. Examples:	Start Capture	self, wait_time=30s	Start packet capture	
Note: This is a asynchronus action. After called, the keyword finishes immediatly but it will take a before traffic starts By default the keyword will wait for 30 seconds. Stop All Protocols Stop And Save Capture Stop Capture Stop Capture Stop Capture Note: This is a asynchronus action. After called, the keyword finishes immediatly but it will take a before traffic starts By default the keyword will wait for 30 seconds. Stop all running protocols Stop all running protocols Stop current capture and save the resuls to folder specified by path Captured files will be saved in current result folder with prefix appended in their names. Examples:	Start Protocol	self, wait_time=1m	Starts all protocols and wait for wait_time	
Protocols Stop And Save Capture Stop Capture Stop Capture Stop Current capture and save the resuls to folder specified by path Capture or capture and save the resuls to folder specified by path Captured files will be saved in current result folder with prefix appended in their names. Examples:	Start Traffic	self, wait_time=30s	Note: This is a asynchronus action. After called, the keyword finishes immediatly but it will take a while before traffic starts	
Stop And Save Capture Stop Current capture and save the results to folder specified by path Capture Stop Current capture and save the results to folder specified by path Captured files will be saved in current result folder with prefix appended in their names. Examples:	•	self, wait_time=30s	Stop all running protocols	
Sleep 10s	Stop And Save	wait_until_finish=True,	Captured files will be saved in current result folder with prefix appended in their names. Examples: Tester. Start Capture Sleep 10s	
Tester. Stop And Save Capture \${RESULT_FOLDER}/capture.zip Stop Quicktest self, test_index=0 Stops a running test			Lighter Ston And Save Canture SIRESHIT FOI DERVicanture zin	

Stop Traffic	self, stop_protocol=False, wait_time=10s	Stops the current traffic and wait for wait_time Parameters:
		stop_protocol: if True also stops all running protocols wait time: time to wait after apply the command
Wait Until Connected	self, timeout_str=5m	Waits until ports become enabled and connected

Altogether 36 keywords.
Generated by <u>Libdoc</u> on 2018-04-12 19:20:26.

