LDAPExplorerTool 2

(a short)user's guide

Configuration

Configuration	
	Identifier for the configuration
(mandatory)	
Server	
Server name or IP (mandatory)	Server IP adress or name (FQDN if SSL or TLS)
Server port	The port number of the server. If « use default port » is checked this value is ignored.
Server SSL port	The port number of the server for SSL connections. If « use default port » is checked this value is ignored.
Version	LDAP protocol version supported by the LDAP server.
Connection	
User DN	DN of the user for connection (ex: cn=administrator,dc=mydomain). If « Anonymous login » is checked this value is ignored.
Password	Password for the user previously configured. If « Anonymous login » is checked this value is ignored. If « Store password » is unchecked this value is ignored. Be careful, the password is stored in clear text in the registry (Windows) or in the configuration file (Linux).
Use SSL port	Connect to server using SSL on the SSL port.
Use TLS	Connect to server using TLS on the standard port.
Base DN	The root DN to display on connection. The « Guess value » action tries to get the directory's base DN.
Option	
Time limit	Timeout to set for searches.
Size limit	Maximum number of entries returned for a search.
Follow referals	
Schema DN	Dn of the schema if not the standard one.
Guess binary values	
SSL/TLS	
CA certificate	Full path to the server public certificate. This field is mandatory if you plan to use SSL or TLS.
Client Certificate	Full path to the client certificate file.
Client Key	Full path to the client key.

Usage

All actions are available on the left or right panel through contextual menus.

The left panel displays entries of the directories the right panel displays the selected entry attributes.

The data displayed are never interpreted.