

Stabilizing Grand Cooperation of Machine Scheduling Game via Setup Cost Pricing

Lindong Liu

School of Management; International Institute of Finance
University of Science and Technology of China

Co-authored with Zikang Li (PG Student, USTC)

NWPU-Online, July, 2020

Outline

- 1 Preliminaries
- 2 Motivation and Illustrative Example
- 3 Models and Analyses
- 4 Algorithms and Computations
- 5 Extension and Generalization
- 6 Conclusion

PRELIMINARIES

Cooperative Game

A **cooperative game** is defined by a pair (V, C) :

- A set $V = \{1, 2, \dots, v\}$ of players, **grand colalition**;
- A **characteristic function** $C(S)$ = the minimum total cost achieved by the cooperation of members in coalition $S \in \mathbb{S} = 2^V \setminus \{\emptyset\}$.

The game requires:

- A **cost allocation** $\alpha = [\alpha_1, \alpha_2, \dots, \alpha_v] \in \mathbb{R}^v$, where α_k = the cost allocated to each player $k \in V$.

Define $\alpha(S) = \sum_{k \in S} \alpha_k$.

A cost allocation $\alpha \in \mathbb{R}^V$ is in the **core** if it satisfies:

- **Budget Balance** Constraint: $\alpha(V) = C(V)$;
- **Coalition Stability** Constraints: $\alpha(S) \leq C(S)$ for each $S \in \mathbb{S}$.

$$\text{Core}(V, C) = \left\{ \alpha : \alpha(V) = C(V), \right. \\ \left. \alpha(S) \leq C(S), \forall S \in \mathbb{S} \setminus \{V\}, \alpha \in \mathbb{R}^V \right\}.$$

Define $\alpha(S) = \sum_{k \in S} \alpha_k$.

A cost allocation $\alpha \in \mathbb{R}^V$ is in the **core** if it satisfies:

- **Budget Balance** Constraint: $\alpha(V) = C(V)$;
- **Coalition Stability** Constraints: $\alpha(S) \leq C(S)$ for each $S \in \mathcal{S}$.

$$\text{Core}(V, C) = \left\{ \alpha : \alpha(V) = C(V), \right. \\ \left. \alpha(S) \leq C(S), \forall S \in \mathcal{S} \setminus \{V\}, \alpha \in \mathbb{R}^V \right\}.$$

However, $\text{Core}(V, c)$ can be empty.

Existing Instruments

$$\text{Core}(V, C) = \left\{ \alpha : \alpha(V) = C(V), \alpha(S) \leq C(S), \forall S \in \mathbb{S} \setminus \{V\} \right\}$$

Existing Instruments

$$\text{Core}(V, C) = \left\{ \alpha : \alpha(V) = C(V), \alpha(S) \leq C(S), \forall S \in \mathbb{S} \setminus \{V\} \right\}$$

- Subsidization: $\alpha(V) = C(V) - \theta$, ϵ -core;

Existing Instruments

$$\text{Core}(V, C) = \left\{ \alpha : \alpha(V) = C(V), \alpha(S) \leq C(S), \forall S \in \mathbb{S} \setminus \{V\} \right\}$$

- Subsidization: $\alpha(V) = C(V) - \theta$, ϵ -core;
- Penalization: $\alpha(S) \leq C(S) + z$, **least core**;

Existing Instruments

$$\text{Core}(V, C) = \left\{ \alpha : \alpha(V) = C(V), \alpha(S) \leq C(S), \forall S \in \mathbb{S} \setminus \{V\} \right\}$$

- Subsidization: $\alpha(V) = C(V) - \theta$, ϵ -core;
- Penalization: $\alpha(S) \leq C(S) + z$, **least core**;
- Simul. S & P: $\alpha(V) = C(V) - \theta$ and $\alpha(S) \leq C(S) + z$, **PSF**;

Existing Instruments

$$\text{Core}(V, C) = \left\{ \alpha : \alpha(V) = C(V), \alpha(S) \leq C(S), \forall S \in \mathbb{S} \setminus \{V\} \right\}$$


- Subsidization: $\alpha(V) = C(V) - \theta$, ϵ -core;
- Penalization: $\alpha(S) \leq C(S) + z$, **least core**;
- Simul. S & P: $\alpha(V) = C(V) - \theta$ and $\alpha(S) \leq C(S) + z$, **PSF**;
- Inv. Opt.: Changing c to d such that $\text{Core}(V, D)$ is non-empty.

ILLUSTRATIVE EXAMPLE

Example: Machine Scheduling Game (MSG)

Game of Parallel Machine Scheduling with Setup Cost:

- Grand coalition: $V = \{1, 2, 3, 4\}$;
- Processing times: $t_1 = 2$, $t_2 = 3$, $t_3 = 4$, $t_4 = 5$;
- Machine setup cost: $t_0 = 9.5$;
- $c(S)$ for $S \in \mathbb{S}$: minimizes the total completion time of jobs in S plus the machine setup cost;
- $\pi(N) = \pi(\{1, 3\}) + \pi(\{2, 4\}) = 38$ (SPT Rule).



Example: Empty Core

Coalitions	Cost
$\{1\}$	11.5
$\{2\}$	12.5
$\{3\}$	13.5
$\{4\}$	14.5
$\{1, 2\}$	16.5
$\{1, 3\}$	17.5
$\{1, 4\}$	18.5
$\{2, 3\}$	19.5
$\{2, 4\}$	20.5
$\{3, 4\}$	22.5
$\{1, 2, 3\}$	25.5
$\{1, 2, 4\}$	26.5
$\{1, 3, 4\}$	28.5
$\{2, 3, 4\}$	31.5
$\{1, 2, 3, 4\}$	38

Example: Empty Core

Coalitions	Cost
{1}	11.5
{2}	12.5
{3}	13.5
{4}	14.5
{1, 2}	16.5
{1, 3}	17.5
{1, 4}	18.5
{2, 3}	19.5
{2, 4}	20.5
{3, 4}	22.5
{1, 2, 3}	25.5
{1, 2, 4}	26.5
{1, 3, 4}	28.5
{2, 3, 4}	31.5
<u>{1, 2, 3, 4}</u>	<u>38</u>

Optimal Cost Allocation Problem

$$\begin{aligned} \max \quad & (\alpha_1 + \alpha_2 + \alpha_3 + \alpha_4) = 37.25 < 38 \\ \text{s.t.} \quad & \alpha_1 \leq 11.5, \dots, \alpha_4 \leq 14.5, \\ & \alpha_1 + \alpha_2 \leq 16.5, \dots, \alpha_3 + \alpha_4 \leq 22.5, \\ & \dots, \\ & \alpha_1 + \alpha_2 + \alpha_3 + \alpha_4 \leq 38. \end{aligned}$$

$$\alpha^* = [6; 8.75; 10.75; 11.75]$$

MODELS & ANALYSES

Problem Definition and Formulation

Definition

A cooperative TU game (V, c) is called an Identical Variable Parallel machine scheduling of Unweighted jobs (IVPU) if it satisfies the following formulations:

Definition

A cooperative TU game (V, c) is called an Identical Variable Parallel machine scheduling of Unweighted jobs (IVPU) if it satisfies the following formulations:

- **Optimality:** an initial feasible solution x^0 is optimal to $D(V)$;

Definition

A cooperative TU game (V, c) is called an Identical Variable Parallel machine scheduling of Unweighted jobs (IVPU) if it satisfies the following formulations:

- **Optimality:** an initial feasible solution x^0 is optimal to $D(V)$;
- **Consistency:** the social optimum is consistent $C(V) = D(V)$;

Problem Definition and Formulation

Definition

A cooperative TU game (V, c) is called an Identical Variable Parallel machine scheduling of Unweighted jobs (IVPU) if it satisfies the following formulations:

- **Optimality:** an initial feasible solution x^0 is optimal to $D(V)$;
- **Consistency:** the social optimum is consistent $C(V) = D(V)$;
- **Balancedness:** the updated IM game (V, D) is balanced.

Problem Definition and Formulation

Definition

A cooperative TU game (V, c) is called an Identical Variable Parallel machine scheduling of Unweighted jobs (IVPU) if it satisfies the following formulations:

- **Optimality:** an initial feasible solution x^0 is optimal to $D(V)$;
- **Consistency:** the social optimum is consistent $C(V) = D(V)$;
- **Balancedness:** the updated IM game (V, D) is balanced.

$$\min_{\delta} \left\{ f(\delta) : d \in \mathbb{O}, D(V) = C(V), dx^0 = D(V), \delta = d - c \right\},$$

where $f(\delta) = \omega \times |\delta|$ (L_1 norm); \mathbb{O} is the Balanced Cost Vector Set.

Definition

A cooperative TU game (V, c) is called an Identical Variable Parallel machine scheduling of Unweighted jobs (IVPU) if it satisfies the following formulations:

Problem Definition and Formulation

Definition

A cooperative TU game (V, c) is called an Identical Variable Parallel machine scheduling of Unweighted jobs (IVPU) if it satisfies the following formulations:

$$c(s, P) = \min \sum_{k \in V} \sum_{j \in O} c_{kj} x_{kj} + P \sum_{k \in s} x_{k1}$$

$$s.t. \quad \sum_{j \in O} x_{kj} - y_k^s = 0, \forall k \in V,$$

$$\sum_{k \in V} x_{kj} \leq m, \forall j \in O,$$

$$x_{kj} \in \{0, 1\}, \forall k \in V, \forall j \in O,$$

$$y_k^s = 1, k \in s; y_k^s = 0, k \notin s.$$

Properties

ALGORITHMS & COMPUTATIONS

... Algorithm

Computational Results

EXTENSION & GENERALIZATION

Machine Scheduling Game with Weighted Jobs

Pricing in General IM Games

CONCLUSIONS

- ★ **Cooperative Game Theory:**
 - New Instrument for Stabilization via Cost Adjustment.
- ★ **Inverse Problem:**
 - Constrained Inverse Optimization Problem.
- ★ **Models, Solution Methods and Applications:**
 - Several equivalent LP formulations;
 - Feasibility analyses & How to handle infeasibility;
 - Implementations on WMG and UFL games.

Thank you!