

The order of visiting nodes is A, C, B, D, E, G, F .

Initialization: We put A in the queue and mark it ($\text{marked}[A] = \text{true}$). Queue: [A].

Step 1 (Extract A): Extract A from the queue. We check its neighbors: C, B, D. All of them are not marked. We mark them all, set $\text{edgeTo}[C, B, D] = A$ and add them to the queue. Queue: [C, B, D].
+1

Step 2 (Extracting C): Extract C. We check the neighbors: A, B, D. All of them have already been marked and are in the queue or processed. Queue: [B, D].

Step 3 (Extracting B): Extract B. We check the neighbors: A, C, E, G. Nodes A and C are marked. Nodes E and G are new. We mark them, set $\text{edgeTo}[E, G] = B$ and add them to the queue. Queue: [D, E, G].

Step 4 (Extracting D): Extract D. We check the neighbors: C, A. Both are already marked. Queue: [E, G].

Step 5 (Extracting E): Extract E. We check the neighbors: G, F, B. Nodes G and B are marked. Node F is new. We mark it, set $\text{edgeTo}[F] = E$ and add it to the queue. Queue: [G, F].

Step 6 (Extracting G): Extract G. We check the neighbors: F, B. Both are already marked. Queue: [F].

Step 7 (Extracting F): Extract F. Its neighbors G and E are already marked. The queue is empty. The search is completed.