FOLIO

Implementation Brief for VS Code / Claude Code

Design system · Screen specs · Component library · Build order

September 2026 — Confidential

How to use this document

This brief is written for an AI coding assistant (Claude Code in VS Code) building the Folio platform from scratch. Every section is a concrete instruction set, not a description. Read the Design System section (§1–§4) first and establish all tokens and base components before building any screen. Then build screens in the order listed in §5 onward — each screen references the base components and should not require new design decisions.

Where a section says "see token X" or "use component Y", that token or component is defined earlier in this document. When you encounter an ambiguous layout choice, default to the principles in §3. When you encounter a missing piece of copy, use the voice guidelines in §4.

> ⚠️ **Do not import any component library (shadcn, MUI, Ant Design, Radix UI). Build every component from scratch using Tailwind utility classes. The design must not look like any existing component library.**
>
> *Stack: Next.js 14 (App Router), TypeScript, Tailwind CSS, Claude API (claude-sonnet-4-6), PostgreSQL via Prisma, Auth.js v5. Monorepo root is /folio.*

SECTION 1

Design Tokens

All tokens live in tailwind.config.ts under theme.extend. Never use raw hex values or arbitrary Tailwind values in component code — always reference a named token. This is enforced by the design system.

1.1 Colour palette

Folio's palette is drawn from aged paper, ink, deep library shelving, and the particular blue of early-evening reading light. It is warm but not sentimental; serious but not cold.

`ink.950`	#0D1117 — near-black; primary text, headings
`ink.800`	#1E2A35 — secondary text, icon fills
`ink.500`	#5A6A7A — tertiary text, meta labels, placeholders
`ink.200`	#C8D4DC — borders, dividers, subtle strokes
`ink.50`	#F0F4F7 — very light surfaces, hover states
`paper.50`	#FAFAF8 — page background (slightly warm white)
`paper.100`	#F4F2ED — card backgrounds, panel fills
`paper.200`	#EAE6DE — active/selected state backgrounds
`shelf.700`	#2C4A6E — primary accent; links, active nav, CTAs
`shelf.500`	#4A78A8 — lighter accent; hover on shelf.700 elements
`shelf.100`	#D6E6F5 — accent tint; selected chip backgrounds

`amber.600`	#C4760A — warning states, price alerts, reminders
`amber.100`	#FDF3DC — warning background tint
`sage.600`	#3A7A5A — success states, availability indicators
`sage.100`	#DFF0E8 — success background tint
`rose.600`	#B03050 — destructive actions, error states
`rose.100`	#F7E0E5 — error background tint

1.2 Typography

Two typefaces only. Headings and display: Lora (Google Fonts, serif). Body, UI, labels: Inter (Google Fonts, sans-serif). Load both via next/font/google in app/layout.tsx.

`font-display`	Lora — headings, book titles, pull quotes, hero text
`font-body`	Inter — all UI text, labels, buttons, body copy
`text-xs`	12px / 1.5 — metadata, timestamps, captions
`text-sm`	14px / 1.6 — secondary labels, helper text
`text-base`	16px / 1.7 — primary body copy (max 68ch line length)
`text-lg`	18px / 1.6 — lead paragraphs, card body
`text-xl`	20px / 1.5 — section subheadings, emphasis
`text-2xl`	24px / 1.4 — H3 level, card titles
`text-3xl`	30px / 1.3 — H2 level, page section headings
`text-4xl`	38px / 1.2 — H1 level, page titles
`text-5xl`	48px / 1.1 — hero headings, marketing surfaces

1.3 Spacing

Use the default Tailwind 4px base scale. Key landmark values:

`space-1`	4px
`space-2`	8px
`space-3`	12px
`space-4`	16px — standard inner padding for compact components
`space-5`	20px
`space-6`	24px — standard gap between related elements
`space-8`	32px — section padding, card padding
`space-10`	40px
`space-12`	48px — major section gaps
`space-16`	64px — page-level vertical rhythm
`space-20`	80px — hero section padding

1.4 Border radius

`rounded-sm`	4px — input fields, small chips
`rounded`	6px — buttons, small cards
`rounded-md`	8px — standard cards, panels
`rounded-lg`	12px — large cards, modals, drawers
`rounded-full`	9999px — avatars, pill badges only

⚠️ **No rounded-xl or rounded-2xl anywhere. The design is not bubbly.**

1.5 Shadows

`shadow-card`	box-shadow: 0 1px 3px rgba(13,17,23,0.08), 0 1px 2px rgba(13,17,23,0.04)
`shadow-panel`	box-shadow: 0 4px 12px rgba(13,17,23,0.10)
`shadow-modal`	box-shadow: 0 16px 48px rgba(13,17,23,0.16)
`shadow-none`	no shadow — use border instead for flat surfaces

1.6 Motion

One transition duration: 150ms ease-out for micro-interactions (button press, hover state), 250ms ease-out for panel open/close and page element reveal. No decorative animations. No scroll-triggered fade-ins.

`transition-fast`	150ms ease-out
`transition-base`	250ms ease-out

SECTION 2

Base Component Library

Build these components first in /components/ui/. All other screens compose from these. Each component spec below includes: purpose, exact class structure, variants, and states.

2.1 Button

Variants

- Primary — shelf.700 fill, white text, hover → shelf.500
- Secondary — ink.50 fill, ink.800 text, ink.200 border, hover → ink.100 fill
- Ghost — transparent fill, ink.800 text, hover → ink.50 fill
- Danger — rose.600 fill, white text, hover → rose.700
- Link — no background, no border, shelf.700 text, underline on hover

Sizes

- sm — h-8 px-3 text-sm rounded
- md — h-10 px-4 text-base rounded (default)
- lg — h-12 px-6 text-lg rounded

States

- disabled: opacity-40 cursor-not-allowed
- loading: show a 16px spinner (CSS border-animation, no library), text hidden, same width
- focus-visible: outline-2 outline-offset-2 outline-shelf-700

⚑ Buttons never have icons unless the spec explicitly calls for one. No chevrons, no arrows.

2.2 Input & Textarea

```
Base: w-full bg-paper-50 border border-ink-200 rounded-sm       px-3 py-2
text-base text-ink-950 placeholder:text-ink-500       focus:outline-none
focus:border-shelf-700 focus:ring-1 focus:ring-shelf-700       transition-
fast Error state: border-rose-600 focus:border-rose-600 focus:ring-rose-600
Disabled: bg-ink-50 text-ink-500 cursor-not-allowed
```

2.3 BookCard

The primary unit of display for a book throughout the product. Used on shelves, search results, recommendations, and lists.

Structure (horizontal, default)

```
<div class="flex gap-4 p-4 bg-paper-100 rounded-md shadow-card">   <img  /*
cover */ class="w-14 h-20 object-cover rounded flex-shrink-0 shadow-sm" />
<div class="flex flex-col gap-1 min-w-0">     <span /* title */ class="font-
display text-base font-semibold text-ink-950 truncate" />     <span /*
author */ class="text-sm text-ink-500" />     <span /* shelf/status badge */
/>   /* see §2.5 */     <div  /* meta row: year · pages · format */
class="flex gap-2 text-xs text-ink-500 mt-auto" />   </div>   <div  /*
action slot: shelf picker, quick-add, kebab */ class="ml-auto flex-shrink-0"
/> </div>
```

Variant: card-vertical (used in carousels and grid views)

```
<div class="flex flex-col gap-2 w-40">   <img class="w-40 h-56 object-cover
rounded shadow-card" />   <span /* title */ class="font-display text-sm
font-semibold text-ink-950 line-clamp-2" />   <span /* author */
class="text-xs text-ink-500" /> </div>
```

⚑ Cover images: fetch from Open Library covers API first (https://covers.openlibrary.org/b/isbn/{isbn}-M.jpg), fallback to a generated placeholder showing first letter of title in paper.200 with ink.500 text, same dimensions.

2.4 ShelfBadge

A coloured pill indicating which shelf a book is on.

```
reading_now:    bg-shelf-100 text-shelf-700   "Reading now" read:
bg-sage-100 text-sage-600     "Read" tbr:            bg-amber-100 text-
amber-600   "Want to read" owned_unread:   bg-ink-50 text-ink-500
"Owned, unread" wishlist:       bg-paper-200 text-ink-800     "Wishlist"
```

```
dnf:            bg-rose-100 text-rose-600     "Did not finish" not_for_me:
bg-ink-50 text-ink-500        "Not for me" interested:     bg-paper-200
text-ink-800     "Interested" lent_out:       bg-amber-100 text-amber-600
"Lent out"  All: text-xs font-medium px-2 py-0.5 rounded-full
```

2.5 RatingStars

Five stars, half-star precision. Filled: ink.800. Empty: ink.200. Interactive version: hover fills incrementally. Display-only version is identical but pointer-events-none. No JavaScript libraries — build with SVG stars and clip-path for half-star.

2.6 ProgressBar

Used on Reading Now cards to show reading progress.

```
<div class="h-1 bg-ink-200 rounded-full overflow-hidden">   <div class="h-
full bg-shelf-700 rounded-full transition-base"        style={{ width: `$
{pct}%` }} /> </div> <span class="text-xs text-ink-500 mt-1">{currentPage}
of {totalPages}</span>
```

2.7 Modal

Overlay: bg-ink-950/50 backdrop-blur-sm. Panel: bg-paper-50 rounded-lg shadow-modal max-w-lg w-full mx-4 p-6. Close: ghost button top-right with × character (not an icon library glyph). Animate: panel scales from 96% to 100% over 200ms on open; reverses on close.

2.8 Toast / Notification

```
Position: fixed bottom-4 right-4 z-50 Base: bg-ink-950 text-paper-50
rounded-md px-4 py-3 text-sm shadow-panel       flex items-center gap-3 max-
w-sm Success prefix: small sage.400 dot (6px circle) Error prefix: small
rose.400 dot Warning prefix: small amber.400 dot Auto-dismiss: 4 seconds.
Dismiss on click. Multiple toasts: stack vertically with 8px gap.
```

2.9 Skeleton loader

Every list/card surface has a skeleton state. Use bg-ink-200 with a shimmer animation (background-position slide, 1.5s ease-in-out infinite). Match the exact shape of the real content — same height, same border-radius.

2.10 Drawer (side panel)

Used for book detail, shelf management, chat expansion. Slides in from the right on desktop (width: 480px), full-screen on mobile. Overlay identical to Modal. Contains a sticky header (title + close button) and scrollable body.

2.11 EmptyState

```
Centre-aligned block in the content area. Icon: simple SVG illustration
(book-open or similar), 64px, ink.200 Heading: font-display text-xl text-
ink-800 Body: text-base text-ink-500 max-w-xs mx-auto Action: Primary button
below (when applicable) No border, no card — sits directly on page
background.
```

2.12 Avatar

```
Sizes: sm (24px), md (32px), lg (48px), xl (80px) Shape: rounded-full Image:
object-cover Fallback: initials (1–2 chars) in font-body font-medium,
bg generated from username hash (use one of 8 paper/shelf tones),
text-ink-800
```

SECTION 3

Layout System

3.1 App shell

The app shell is the persistent wrapper around all authenticated screens.

Desktop (≥1024px)

```
Full-height flex row. Left sidebar: w-56 bg-paper-100 border-r border-ink-
200 flex-shrink-0   → Logo at top (32px height, left-aligned, px-5 pt-5)   →
Nav items (see §3.2)   → User avatar + name at bottom (px-4 py-4) Main
content: flex-1 min-w-0 overflow-y-auto bg-paper-50   → Max content width:
max-w-4xl mx-auto px-8
```

Mobile (< 1024px)

```
Full-height flex column. Top bar: h-12 bg-paper-50 border-b border-ink-200
→ Logo centre, menu icon left, avatar icon right Content: flex-1 overflow-y-
auto Bottom nav: h-16 bg-paper-50 border-t border-ink-200   → 4 icons: Chat,
Library, Browse, Community   → Icon + label below, text-xs, active state:
shelf.700
```

3.2 Sidebar navigation

Nav items (in order)

```
Chat         — speech-bubble icon Library      — bookshelf icon Browse
— compass icon Community    — people icon ── separator ── Settings     —
gear icon (bottom, above avatar)
```

Nav item styles

```
Default: flex items-center gap-3 px-4 py-2.5 text-sm text-ink-800
font-body rounded mx-2          hover: bg-paper-200 text-ink-950 Active:
bg-shelf-100 text-shelf-700 font-medium Icon:    20px, currentColor stroke,
1.5px stroke-width          (build as inline SVG components, no icon
library)
```

3.3 Page layouts

Single-column (Chat, Settings)

```
max-w-3xl mx-auto px-4 sm:px-8 py-8
```

Two-column (Library, Browse)

```
Desktop: grid grid-cols-[240px_1fr] gap-8 Mobile:  stack, secondary column collapses to top filter bar
```

Full-width grid (Community feed)

```
max-w-5xl mx-auto px-4 sm:px-8 grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 gap-6
```

SECTION 4

Voice & Copy Guidelines

Every string in the UI — buttons, empty states, toasts, labels, AI messages — follows these rules. Do not use placeholder text like "No books found." Write like a thoughtful person who loves books and respects the reader.

Tone

- Warm and direct. Not effusive. Not corporate.
- Sentence case everywhere — never ALL CAPS labels.
- No exclamation marks in UI chrome. Reserve them for genuine moments of celebration (completing a book, hitting a reading goal).
- Books and reading are taken seriously. The product does not condescend.

Empty states — examples

```
Empty TBR:        "Nothing on your list yet. The chat can help you find what's next." Empty Read:       "You haven't logged a finished book yet. Add one and it will live here." Empty chat:       "Ask anything. Your library, recommendations, a bookshop nearby." No search result: "Nothing for that search. Try a title, author, or ISBN."
```

Toasts — examples

```
Book added:        "Added to your library." Session logged:    "36 pages logged. You're on page 214." Gift reminder set: "Reminder set for 3 weeks before Sarah's birthday." Error:             "That didn't save. Try again."
```

AI assistant persona

The AI speaks as a knowledgeable reading companion. It does not say "Great question!" It does not over-explain. It is specific, direct, and sometimes opinionated. It references the user's actual books by title. It occasionally admits uncertainty ("I'm not certain of the exact publication date — worth checking").

SECTION 5

Screen: Chat

Route: /chat (or / for authenticated users). This is the primary surface. It must load fast and feel immediately useful.

5.1 Layout

```
Full-height column: flex flex-col h-full  Header (sticky top):   h-12
border-b border-ink-200 bg-paper-50/90 backdrop-blur-sm   px-4 flex items-
center justify-between   Left: "Chat" in font-display text-lg text-ink-950
Right: Context indicator — small BookCard thumbnail of current read
(cover image only, 28px wide, rounded-sm) + "p.{page}" text-xs text-ink-500
Clicking this opens the book detail drawer.  Message list:   flex-1
overflow-y-auto px-4 py-4 space-y-4  Input area (sticky bottom):   border-t
border-ink-200 bg-paper-50 px-4 py-3   flex gap-2 items-end
```

5.2 Message bubbles

User message

```
Self-contained: max-w-[85%] ml-auto bg-shelf-700 text-white rounded-lg
rounded-br-sm px-4 py-2.5 text-base font-body
```

Assistant message

```
Self-contained: max-w-[85%] mr-auto No bubble background — sits directly on
the chat background. font-body text-base text-ink-950 leading-relaxed
Markdown rendered: **bold** → font-semibold, *italic* → italic,
lists → standard list indent  If the message contains a book recommendation:
Inline BookCard (horizontal, compact) embedded in the message flow.
Rendered below the text, not inline within it.   Max 3 cards per message. If
more, show "Show more" button.
```

5.3 Input area

```
Textarea (auto-grows, max 6 lines):   flex-1 resize-none bg-paper-100 border
border-ink-200 rounded-md   px-3 py-2 text-base focus:outline-none
focus:border-shelf-700   placeholder: "Ask anything about your books..."
Send button: Primary size-sm, disabled when empty  Suggestion chips (shown
when chat is empty):   Horizontal scroll row below the input   bg-paper-100
border border-ink-200 rounded-full px-3 py-1.5   text-sm text-ink-800
hover:bg-paper-200   Examples:     "What should I read next?"     "Log some
pages"     "Find a bookshop nearby"     "Gift ideas for Mum"     "How am I
doing this month?"
```

5.4 Chat API integration

```
POST /api/chat Body: { messages: Message[], userId: string }  Server
assembles context object before calling Claude:   - currentBook: { title,
author, currentPage, totalPages, pace }   - recentlyRead: last 10 books
(title, author, rating)   - tbrTop10: prioritised TBR list   - savedPlaces:
user's bookshops and libraries   - userContext: decrypted private context
profile (see §13)  System prompt injected server-side — user never sees it.
Stream the response: use ReadableStream, render tokens as they arrive. If
response contains ISBN references, automatically fetch and render BookCards
for those ISBNs at message end.
```

Screen: Library

Route: /library. Two-column layout. Left: shelf navigation. Right: book list for the selected shelf.

6.1 Left column — shelf navigation

```
Sticky top-0 (scrolls with page on mobile, fixed on desktop).  Section:
"Your shelves" — text-xs text-ink-500 mb-2 font-medium Each shelf item:
flex items-center justify-between px-3 py-2 rounded text-sm   hover: bg-
paper-200   active (selected): bg-shelf-100 text-shelf-700 font-medium
Left: shelf name (see §2.4 for shelf names)   Right: book count badge —
text-xs text-ink-500 bg-paper-200 px-1.5 rounded-full  Separator then: "Gift
lists"   Each contact as a shelf item — Avatar (sm) + contact name  Bottom:
"+ New shelf" ghost button, text-sm text-ink-500
```

6.2 Right column — book list

Toolbar

```
flex items-center justify-between mb-4 Left: shelf title font-display text-
2xl text-ink-950       + book count text-sm text-ink-500 ml-3 Right: view
toggle (list / grid) + sort dropdown  Sort options: Recently added, Title A–
Z, Author A–Z,               Date read (finished shelf only), Rating,
Progress Sort dropdown: bg-paper-50 border border-ink-200 rounded text-sm
px-2 py-1.5
```

Book list (default view)

```
space-y-2 Each item: BookCard horizontal (§2.3)  For "Reading Now" cards,
add below the meta row:   ProgressBar (§2.6)   "Log pages" ghost button —
text-sm, opens inline log form  Inline page log form (expands below the
card):   "I read from page ___ to page ___"   Two number inputs (w-20),
sentence around them   "Log" primary button sm + "Cancel" ghost button sm
```

Empty shelf

```
EmptyState component (§2.11) Different copy per shelf:   TBR empty: "Nothing
on your list yet. The chat can help you find what's next."   Read empty:
"You haven't logged a finished book yet."   etc.
```

6.3 Book detail drawer

Opens from clicking any BookCard. Drawer from right (§2.10).

Drawer contents (top to bottom)

```
1. Cover image — centered, 120px wide, shadow-card 2. Title — font-display
text-2xl text-ink-950 3. Author(s) — text-base text-ink-500 (clickable →
author page) 4. ShelfBadge + shelf picker dropdown 5. RatingStars
(interactive) 6. ProgressBar (if reading_now) 7. Tabs: Details | Notes |
Sessions | Editions  Tab: Details   Published, pages, language, genres (as
chips)   Series indicator if applicable: "Book 2 of The Southern Reach
Trilogy"   GET THIS BOOK panel (see §6.4)  Tab: Notes   Textarea: private
notes. Auto-saves on blur.   Below: "Reading journal" — chronological list
of session notes          Each entry: date, pages read, optional note text
"+ Add note to this session" inline textarea  Tab: Sessions   Table: Date |
Start page | End page | Pages | Duration (if logged)   Total at bottom: X
sessions · Y pages · Z days  Tab: Editions   List editions: Format,
Publisher, Year, Translator (if applicable)   "This edition" marker on owned
copy   "Find another edition" → opens search
```

6.4 GET THIS BOOK panel

Used in the book detail drawer and on book pages. Shows all acquisition options.

```
Heading: "Get this book" text-sm font-medium text-ink-500 mb-2  Sections (only show if data available):  Borrow   → "[Library name] — available" (sage.600) / "not available" (ink.500)   → "Request from network" link  Buy nearby   → "[Shop name] — X miles" (link, opens map)  Buy new   → Bookshop.org | Publisher | Amazon (three inline links, text-sm)  Buy secondhand   → AbeBooks | World of Books (inline links)  Digital   → Internet Archive (free borrow if available, shows "Free")   → Project Gutenberg (if out of copyright, shows "Free")   → Kindle / Kobo links Listen   → Libro.fm | Audible | LibriVox (if out of copyright)  Each section is a flex-col gap-1 block. Section headings: text-xs text-ink-500 uppercase tracking-wide Links: text-sm text-shelf-700 hover:underline Availability indicators: text-xs text-sage-600 or text-ink-500
```

6.5 Add book flow

Triggered by "+ Add book" button in toolbar. Opens a modal (§2.7).

```
Step 1: Search   Input with placeholder "Title, author, or ISBN"   Live search against Open Library API as user types (debounce 300ms)   Results: BookCard vertical thumbnails, 4 per row   OR: "Scan barcode" button (mobile only) → camera ISBN scan  Step 2: Confirm & shelve   Selected book shown large (cover + metadata)   Shelf picker: radio group of shelf names Edition selector: dropdown of known editions (format, year, publisher) "Add to library" primary button  After add: toast "Added to [shelf name]." + drawer opens to new book.
```

SECTION 7

Screen: Gift Lists

Route: /library/gifts. Accessible from the Library left column. Shows all gift contacts and their lists.

7.1 Contact list view

```
Grid: grid-cols-2 sm:grid-cols-3 lg:grid-cols-4 gap-4  Each contact card: bg-paper-100 rounded-md p-4 shadow-card hover:shadow-panel cursor-pointer Avatar (xl) centered   Name: font-display text-base text-ink-950 text-center mt-2   Next occasion: text-xs text-ink-500 text-center     If within 30 days: text-amber-600 + small dot indicator   Book count: text-xs text-ink-500 text-center  "+ Add person" card: same size, dashed border border-ink-200,   centred "+" icon + "Add someone" text-sm text-ink-500
```

7.2 Contact detail view

Clicking a contact opens their gift list. Same two-column layout as Library.

```
Left column:   Contact avatar (xl) + name (font-display text-2xl)   Taste notes (editable textarea, text-sm text-ink-800)   Upcoming occasions list (date + label, editable)   "Ask AI to expand this list" primary button "Share this list" ghost button (generates shareable link)  Right column: Toolbar: "Gift ideas for [Name]" + "Find nice editions" button   Book list:
```

```
BookCard horizontal     Each card has right-side: Priority badge (Perfect
fit / Might like / Wildcard)                                  "Claimed" toggle
(checkbox style)                                Remove button (×)  Claimed
state: book card opacity-60, strikethrough on title,                "Claimed
by [name]" text-xs text-sage-600
```

7.3 Birthday reminder banner

```
When a contact's occasion is within 21 days: Show a banner at top of
/library/gifts (and in Chat as a message)  Banner:   bg-amber-100 border
border-amber-600/20 rounded-md p-4   flex items-start gap-3   Left: small
gift icon SVG, text-amber-600, 20px   Text: "[Name]'s birthday is in X
days." font-medium text-ink-950         "Here are 3 books from their list
under £[budget]:" text-sm text-ink-800   Below: 3 BookCard horizontal
(compact) with Buy link prominent   Dismiss: × button top-right, ghost,
remembers dismissal for that occasion
```

SECTION 8

Screen: Reading Diary

Route: /library/diary. Accessible from Library left column. Shows reading history, stats, and journal entries.

8.1 Stats header

```
bg-paper-100 rounded-md p-6 mb-6 shadow-card  Top row: 4 stat blocks in a
grid   Each block: number (font-display text-3xl text-ink-950) + label
(text-sm text-ink-500)   Stats: Pages this year | Books finished | Current
streak | Avg session  Below: thin ProgressBar showing year progress (books
read vs goal)   Only if user has set a yearly goal.   Label: "X of Y books
this year" text-sm text-ink-500  No gamification elements. No trophy icons.
No streak fire emoji.
```

8.2 Reading timeline

```
Chronological list, grouped by month.  Month header: text-sm font-medium
text-ink-500 mb-3 (e.g. "September 2026")  Session entry:   flex items-start
gap-3 py-3 border-b border-ink-200   Left: date column (text-xs text-ink-
500, w-16, flex-shrink-0)   Cover thumbnail (32px wide, rounded-sm)   Text
block:     Title text-sm font-medium text-ink-950     "X pages (p.Y → p.Z)"
text-sm text-ink-500     Duration if logged: "55 min" text-xs text-ink-500
Journal note if present: italic text-sm text-ink-800 mt-1
```

8.3 Finished book entries

```
When a book is marked as finished, appears in timeline as a distinct entry:
bg-sage-100 rounded-md p-3 (not a row — stands out)   "Finished: [Title]"
font-display text-base text-ink-950   Date, total pages, total days, rating
if given   Review link: "Write a review" text-sm text-shelf-700
```

SECTION 9

Screen: Browse

Route: /browse. Discovery hub: reading paths, bookshops, staff picks, new releases from followed authors, community-curated lists.

9.1 Layout

```
Single column, sections stacked vertically. Each section: mb-12 Section header: flex justify-between items-baseline mb-4   Left: section title font-display text-2xl text-ink-950   Right: "See all" text-sm text-shelf-700 link
```

9.2 Sections (in order)

Continue reading

```
Only shown if user has a current book. Full-width card: bg-paper-100 rounded-md p-5 shadow-card   Horizontal: cover (80px) | book info + progress | "Log pages" button
```

New from authors you've read

```
Horizontal scroll of BookCard vertical (§2.3) Author badge below card: small Avatar + author name text-xs Overflow: scroll-snap-x mandatory, hidden scrollbar,           arrow buttons at edges on desktop (ghost, ink.200 bg on hover)
```

Reading paths

```
Grid: grid-cols-1 sm:grid-cols-2 gap-4  ReadingPathCard:   bg-paper-100 rounded-md p-4 shadow-card   Title: font-display text-lg text-ink-950   Description: text-sm text-ink-500 line-clamp-2   Footer: "X books" text-xs text-ink-500 + creator Avatar + name text-xs   Cover collage: 3 small book covers overlapping, top-right corner
```

Nearby bookshops

```
Only shown if location permission granted. Horizontal scroll of BookshopCard:   bg-paper-100 rounded-md p-4 shadow-card w-48 flex-shrink-0   Name: text-sm font-medium text-ink-950   Type badge: text-xs text-ink-500 (Independent / Secondhand / Antiquarian)   Distance: text-xs text-ink-500   "Save" ghost button sm
```

From the community

```
Grid: grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 gap-4 CommunityCard: review excerpt, avatar + name, book cover thumbnail See §11 for full Community card spec.
```

SECTION 10

Screen: Book Page

Route: /book/[workId]. Public page for a specific work. SEO-optimised (SSR).

10.1 Header

```
Two-column: left 200px (cover), right flex-1  Cover: 200px wide, rounded-md, shadow-panel Right column (top to bottom):   Title: font-display text-4xl text-ink-950   Author(s): text-xl text-ink-500 (links to author page)  Series indicator (if applicable): text-sm text-shelf-700   Genre chips: text-xs bg-paper-200 text-ink-800 rounded-full px-2 py-0.5   Meta row: Year · Pages · Original language · text-sm text-ink-500   RatingStars + community rating text-sm text-ink-500 ("4.1 · 312 ratings")   Add to library button: Primary lg   GET THIS BOOK panel (§6.4)
```

10.2 Body tabs

```
Tabs: About | Editions & Translations | Reviews | Discussion | Reading Paths  Tab bar: border-b border-ink-200, each tab text-sm px-4 py-2 Active tab: border-b-2 border-shelf-700 text-shelf-700 font-medium  Tab: About   Description (up to 4 paragraphs, "Show more" collapse)   Awards (if any): list with year   Adaptations: films, TV, audiobooks   Wikipedia link: text-sm text-shelf-700  Tab: Editions & Translations   Grouped by language, then by translator   Each edition row: Publisher | Year | Format | Translator | ISBN | "Add to library"   Translator name is a link → translator profile page  Tab: Reviews   Community reviews sorted by Most liked   Each: Avatar + name, RatingStars, date, review text (collapsed to 4 lines, expand)   "Write a review" button (if in library)  Tab: Discussion   Forum threads for this book   Two sections: No spoilers | Spoilers (collapsed by default)  Tab: Reading Paths   ReadingPathCards (§9.2) that include this book
```

SECTION 11

Screen: Community

Route: /community. Logged-out public feed and logged-in personalised feed.

11.1 Feed

```
max-w-2xl mx-auto — narrower than Browse, more like a reading feed.  FeedCard variants:  Review card:   bg-paper-50 border border-ink-200 rounded-md p-4 mb-3   Header: Avatar sm + name text-sm font-medium + "reviewed" text-sm text-ink-500           + book cover thumbnail 36px + title text-sm text-shelf-700   RatingStars (display)   Review excerpt: text-base text-ink-950 line-clamp-4   Footer: Like count | Comment count | Share button           All text-xs text-ink-500  Finished book card (milestone): Same frame, different content:   "[Name] finished [Title]"   Pages + days taken text-sm text-ink-500   Quote (if user chose to share one): italic text-base text-ink-950  Blog post card:   Cover image (if post has one): full-width, max-h-48, object-cover, rounded-t-md   Title: font-display text-xl text-ink-950   Excerpt: text-base text-ink-500 line-clamp-2   Author + date + read time text-xs text-ink-500
```

11.2 Book clubs

Route: /community/clubs. Grid of BookClubCards.

```
BookClubCard:   bg-paper-100 rounded-md p-4 shadow-card   Name: font-display text-lg   Current read: BookCard horizontal compact   Members: row of Avatar sm overlapping (max 5, "+X more")   "Join" or "Request to join" primary button sm   Privacy badge: "Open" / "Private" text-xs text-ink-500
```

SECTION 12

Screen: Profile

Route: /profile/[username]. Public-facing reading identity.

```
Header:   Avatar xl centered (desktop: left-aligned)   Display name: font-display text-3xl text-ink-950   Username: text-sm text-ink-500   Bio: text-base text-ink-800 max-w-xl   Stats row: X books | X reviews | Following X | X followers              text-sm text-ink-500, numbers font-medium text-ink-950   Follow button (if not own profile): Primary  Tabs: Shelves | Reviews | Reading paths | Blog | Shop  Tab: Shelves   Shows public shelves only   Horizontal scroll per shelf (BookCard vertical)  Tab: Reviews   Chronological list of public reviews  Tab: Shop (if user has enabled it)   Curated lists with Buy links   Text: "Books I recommend"
```

SECTION 13

Screen: Private Context Profile

Route: /settings/context. Not linked from public navigation — only accessible from Settings. This is the most sensitive screen in the product.

13.1 Page design

```
max-w-2xl mx-auto px-4 py-8  Page header:   Title: font-display text-3xl   "Your reading context"   Subtext: text-base text-ink-500 max-w-prose   "This is private. Only you and the Folio AI can read it.",     "It shapes recommendations silently — you'll never need to repeat yourself."   Privacy badge: bg-sage-100 text-sage-600 rounded px-3 py-1.5 text-sm     "Encrypted · Not used for advertising · Delete anytime"
```

13.2 Sections

Life right now

```
Label: "Is there anything going on in your life the AI should be aware of?"   text-base text-ink-800  Below: freeform textarea, 5 rows, placeholder:   "Anything at all — a bereavement, something you'd rather not read about right now, a difficult period. You don't need to be specific."  This maps to: life_context in the schema.
```

Your days

```
Label: "When do you usually read?" Multi-select chips: Morning commute | Lunch | Evenings | Weekends | Before bed   | Whenever I can These are chips with toggle behaviour.  Below: "How much time do you usually have?" — radio row:   Under 30 min | 30–60 min | 1–2 hours | As long as I like
```

Reading diary (private)

```
A simple chronological journal. Not connected to reading sessions — this is personal writing.  "+ New entry" button → expands inline textarea with today's date as label Entries displayed: date (text-xs text-ink-500) + text (text-base text-ink-800) Edit: click to expand back to textarea Delete: × per entry (with confirmation: "Delete this entry?")  Important: entries are encrypted at rest. Add a subtle visual cue:   Small lock icon (16px, ink.200) beside the "Reading diary" section heading.
```

Save behaviour

```
Auto-save on blur for all fields. Toast on save: "Saved." (no detail) No explicit save button needed.  Delete all button: bottom of page, rose.600 ghost, "Delete my context profile" Confirmation modal: "This will clear everything. The AI will start fresh.                    Your reading library is not affected." "Delete" button danger variant | "Keep it" ghost button
```

SECTION 14

Screen: Settings

Route: /settings. Standard settings layout — left nav + right panel.

```
Settings sections (left nav):   Account | Reading context | Notifications | Privacy | Connections |   Reading goal | Import & export | Danger zone Connections sub-page:   Connected accounts: TikTok, Instagram, YouTube, Reddit, Bluesky   Each: logo (SVG) + platform name + "Connected as @handle" / "Connect" button   Library connections: Goodreads (import), Kindle (sync), Audible (sync)   Location: "Allow location access" toggle — used for bookshop discovery  Reading goal sub-page:   "Books this year:" number input   Toggle: "Show progress in Diary"  Import & export:   "Import from Goodreads" — file upload (.csv), progress bar during import   "Export my library" — download as CSV or JSON   "Import from LibraryThing" — file upload
```

SECTION 15

Database & API Setup

15.1 Prisma schema (key models)

```
// prisma/schema.prisma  model Work {   id              String       @id @default(cuid())   title           String   openLibraryId   String?   @unique   wikidataId      String?   originalLang    String   @default("en")   description     String?   genres          String[]   themes   String[]   embedding       Float[]      // pgvector   translations   Translation[]   authors         AuthorWork[] }  model Translation {   id   String     @id @default(cuid())   workId      String   language    String   translators Contributor[] @relation("TranslatorRelation")   editions   Edition[]   work        Work       @relation(fields: [workId], references: [id]) }  model Edition {   id            String      @id @default(cuid())   translationId String?   workId        String   publisher     String?   year
```

```
Int?   isbn13        String?     @unique   format        String      //
hardback|paperback|ebook|audiobook   coverUrl      String?   pageCount
Int?   userBooks     UserBook[] }  model UserBook {   id          String
@id @default(cuid())   userId      String   editionId   String   shelf
String   priority    Int      @default(0)   dateAdded   DateTime
@default(now())   dateStarted DateTime?   dateFinished DateTime?   rating
Float?   privateNotes String?   sessions    ReadingSession[]   user
User     @relation(fields: [userId], references: [id])   edition     Edition
@relation(fields: [editionId], references: [id]) }  model ReadingSession {
id          String   @id @default(cuid())   userBookId  String   date
DateTime @default(now())   pageStart   Int   pageEnd     Int   timeStart
DateTime?   timeEnd     DateTime?   note        String?   userBook
UserBook @relation(fields: [userBookId], references: [id]) }  model
GiftContact {   id          String   @id @default(cuid())   userId
String   name        String   birthday    DateTime?   tasteNotes  String?
giftItems   GiftItem[] }  model GiftItem {   id          String      @id
@default(cuid())   contactId   String   editionId   String   priority
String      // perfect|might_like|wildcard   claimedBy   String?   note
String? }  model UserContextProfile {   id              String   @id
@default(cuid())   userId          String   @unique   lifeContext     Bytes?
// AES-256-GCM encrypted   lifeStructure   Bytes?   tasteProfile    Bytes?
biography       Bytes?   updatedAt       DateTime @updatedAt }  model
ContextDiaryEntry {   id          String   @id @default(cuid())   userId
String   content     Bytes    // AES-256-GCM encrypted   createdAt
DateTime @default(now()) }
```

15.2 Key API routes

```
POST   /api/chat                  — streaming AI chat POST   /api/chat/log-
session      — parse + log reading session from chat message  GET
/api/books/search          — search Open Library + local DB GET
/api/books/[isbn]          — fetch full book metadata by ISBN POST
/api/library/add           — add book to user library PATCH
/api/library/[userBookId]  — update shelf, rating, notes POST
/api/library/session       — log a reading session directly  GET
/api/gifts/contacts        — list gift contacts POST   /api/gifts/contacts
— create contact GET    /api/gifts/[contactId]     — contact + their gift
list POST   /api/gifts/[contactId]/ai  — AI expand gift list  GET
/api/places/nearby         — bookshops near coords GET
/api/availability/[isbn]   — library + retail availability  GET
/api/context               — decrypt + return user context (session-gated)
PATCH  /api/context              — update context (encrypts before save)
POST   /api/context/diary        — add diary entry (encrypts before save)
DELETE /api/context              — wipe all context  POST
/api/import/goodreads      — parse Goodreads CSV, queue import job GET
/api/import/status/[jobId] — poll import progress
```

15.3 Environment variables

```
DATABASE_URL= NEXTAUTH_SECRET= NEXTAUTH_URL=  ANTHROPIC_API_KEY=
OPEN_LIBRARY_BASE=https://openlibrary.org GOOGLE_PLACES_API_KEY=
WORLDCAT_API_KEY=  BOOKSHOP_ORG_AFFILIATE_ID= AMAZON_ASSOCIATE_TAG=
ABEBOOKS_AFFILIATE_KEY=  CONTEXT_ENCRYPTION_SALT=   # server-side salt for
key derivation  AWS_S3_BUCKET= AWS_REGION=eu-west-2 AWS_ACCESS_KEY_ID=
AWS_SECRET_ACCESS_KEY=
```

SECTION 16

Build Order

Follow this sequence. Do not build a later phase until the earlier phase works end-to-end. Each phase ends with a testable product.

Phase 1 — Foundation (build this first)

- Project scaffold: Next.js 14 App Router, TypeScript, Tailwind with token config
- Prisma schema + migrations for: Work, Translation, Edition, UserBook, ReadingSession, User
- Auth.js: email/password sign-up and login
- App shell: sidebar + bottom nav, responsive
- All base components (§2): Button, Input, BookCard, ShelfBadge, Modal, Toast, Skeleton, EmptyState
- Library screen: default shelves, book add (ISBN lookup), shelf management
- Chat screen: basic message UI, Claude API streaming integration, library context injection
- Goodreads CSV import

End of Phase 1: a user can sign up, import their Goodreads library, view their shelves, and chat with an AI that knows their books.

Phase 2 — Core features

- Reading session logging (via chat NLP + direct UI)
- Reading diary screen with stats
- Translation and edition hierarchy in UI
- Book detail drawer with all tabs
- GET THIS BOOK panel with Bookshop.org + library availability
- Browse screen: Continue reading, New from authors, Reading paths
- Book page (public, SSR)

End of Phase 2: the product is meaningfully better than Goodreads.

Phase 3 — Gift & social

- Gift contacts and gift lists
- Birthday reminder banner and notifications
- AI gift list expansion (POST /api/gifts/[contactId]/ai)
- Public profiles
- Reviews and community feed
- Book clubs (create, join, discussion)
- Reading challenges

Phase 4 — Creator & social media

- Blog editor (TipTap) and public blog

- Video upload and per-book attachment
- Social media cross-posting (TikTok, Instagram, YouTube)
- Shareable asset generation (book cards, quote cards)
- Personalised shop pages

Phase 5 — Context & marketplace

- Private context profile screen (§13) with encryption
- Context injection into chat AI (life context, diary)
- Reading Life marketplace (MVP: Reading Objects + Books)
- Sensory reading kit generation
- Reading afternoon planning (weather + places + pace synthesis)
- Nearby bookshops screen
- Nice editions finder

End of implementation brief.