

NumPy Joining Array

Joining NumPy Arrays

Joining means putting contents of two or more arrays in a single array.

In SQL we join tables based on a key, whereas in NumPy we join arrays by axes.

We pass a sequence of arrays that we want to join to the `concatenate()` function, along with the axis. If axis is not explicitly passed, it is taken as 0.

Example

Join two arrays

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
arr = np.concatenate((arr1, arr2))
print(arr)
```

Example

Join two 2-D arrays along rows (axis=1):

```
import numpy as np
arr1 = np.array([[1, 2], [3, 4]])
arr2 = np.array([[5, 6], [7, 8]])
arr = np.concatenate((arr1, arr2), axis=1)
print(arr)
```

Joining Arrays Using Stack Functions

Stacking is same as concatenation, the only difference is that stacking is done along a new axis.

We can concatenate two 1-D arrays along the second axis which would result in putting them one over the other, ie. stacking.

We pass a sequence of arrays that we want to join to the `stack()` method along with the axis. If axis is not explicitly passed it is taken as 0.

Example

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
arr = np.stack((arr1, arr2), axis=1)
print(arr)
```

Stacking Along Rows

NumPy provides a helper function: `hstack()` to stack along rows.

Example

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
arr = np.hstack((arr1, arr2))
print(arr)
```

Stacking Along Columns

NumPy provides a helper function: `vstack()` to stack along columns.

Example

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
arr = np.vstack((arr1, arr2))
print(arr)
```

Stacking Along Height (depth)

NumPy provides a helper function: `dstack()` to stack along height, which is the same as depth.

Example

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
arr = np.dstack((arr1, arr2))
print(arr)
```

NumPy Splitting Array

Splitting NumPy Arrays

Splitting is reverse operation of Joining.

Joining merges multiple arrays into one and Splitting breaks one array into multiple.

We use `array_split()` for splitting arrays, we pass it the array we want to split and the number of splits.

Example

Split the array in 3 parts:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5, 6])
newarr = np.array_split(arr, 3)
print(newarr)
```

Note: The return value is a list containing three arrays.

If the array has less elements than required, it will adjust from the end accordingly.

Example

Split the array in 4 parts:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5, 6])
newarr = np.array_split(arr, 4)
print(newarr)
```

Note: We also have the method `split()` available but it will not adjust the elements when elements are less in source array for splitting like in example above, `array_split()` worked properly but `split()` would fail.

Split Into Arrays

The return value of the `array_split()` method is an array containing each of the split as an array.

If you split an array into 3 arrays, you can access them from the result just like any array element:

Example

Access the splitted arrays:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5, 6])
newarr = np.array_split(arr, 3)
print(newarr[0])
print(newarr[1])
print(newarr[2])
```

Splitting 2-D Arrays

Use the same syntax when splitting 2-D arrays.

Use the `array_split()` method, pass in the array you want to split and the number of splits you want to do.

Example

Split the 2-D array into three 2-D arrays.

```
import numpy as np
arr = np.array([[1, 2], [3, 4], [5, 6], [7, 8], [9, 10], [11, 12]])
newarr = np.array_split(arr, 3)
print(newarr)
```

The example above returns three 2-D arrays.

Let's look at another example, this time each element in the 2-D arrays contains 3 elements.

Example

Split the 2-D array into three 2-D arrays.

```
import numpy as np
arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15], [16, 17, 18]])
newarr = np.array_split(arr, 3)
print(newarr)
```

The example above returns three 2-D arrays.

In addition, you can specify which axis you want to do the split around.

The example below also returns three 2-D arrays, but they are split along the row (`axis=1`).

Example

Split the 2-D array into three 2-D arrays along rows.

```
import numpy as np
arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15], [16, 17, 18]])
```

```
newarr = np.array_split(arr, 3, axis=1)

print(newarr)
```

An alternate solution is using `hsplit()` opposite of `hstack()`

Example

Use the `hsplit()` method to split the 2-D array into three 2-D arrays along rows.

```
import numpy as np
arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15], [16, 17, 18]])
newarr = np.hsplit(arr, 3)
print(newarr)
```

Note: Similar alternates to `vstack()` and `dstack()` are available as `vsplit()` and `dsplit()`.