

## Event and Listener (Java Event Handling)

Changing the state of an object is known as an event. For example, click on button, dragging mouse etc. The java.awt.event package provides many event classes and Listener interfaces for event handling.

### Java Event classes and Listener interfaces

Event Classes	Listener Interfaces
ActionEvent	ActionListener
MouseEvent	MouseListener and MouseMotionListener
MouseWheelEvent	MouseWheelListener
KeyEvent	KeyListener
ItemEvent	ItemListener
TextEvent	TextListener
AdjustmentEvent	AdjustmentListener
WindowEvent	WindowListener
ComponentEvent	ComponentListener
ContainerEvent	ContainerListener
FocusEvent	FocusListener

### Steps to perform Event Handling

Following steps are required to perform event handling:

- Register the component with the Listener

### Registration Methods

For registering the component with the Listener, many classes provide the registration methods. For example:

### Button

- `public void addActionListener(ActionListener a){}`

### **MenuItem**

- `public void addActionListener(ActionListener a){}`

### **TextField**

- `public void addActionListener(ActionListener a){}`
- `public void addTextListener(TextListener a){}`

### **TextArea**

- `public void addTextListener(TextListener a){}`

### **Checkbox**

- `public void addItemListener(ItemListener a){}`

### **Choice**

- `public void addItemListener(ItemListener a){}`

### **List**

- `public void addActionListener(ActionListener a){}`
  - `public void addItemListener(ItemListener a){}`
1. Anonymous class

### **Java event handling by implementing ActionListener**

```
import java.awt.*;
import java.awt.event.*;
class AEvent extends Frame implements ActionListener
{
    TextField tf;
    AEvent()
    {
        tf=new TextField();
        tf.setBounds(60,50,170,20);
        Button b=new Button("click me");
```

```
b.setBounds(100,120,80,30);
b.addActionListener(this);//passing current instance
add(b);add(tf);
setSize(300,300);
setLayout(null);
setVisible(true);
}
public void actionPerformed(ActionEvent e)
{
tf.setText("Welcome");
}
public static void main(String args[])
{
new AEvent();
}
}
```

**public void setBounds(int xaxis, int yaxis, int width, int height);** have been used in the above example that sets the position of the component it may be button, textfield etc.