ASSIGNMENT 1

Dishank Jain AI20BTECH11011

Download all python codes from

https://github.com/Dishank422/EE3900/blob/main/ Gate-Assignment1/codes

and latex-tikz codes from

https://github.com/Dishank422/EE3900/blob/main/ Gate-Assignment1/latex code.tex

1 EC 2019 Q.33

Let the state-space representation on an LTI system be $\dot{x}(t) = Ax(t) + Bu(t)$, y(t) = Cx(t) + du(t) where A,B,C are matrices, d is a scalar, u(t) is the input to the system, and y(t) is its output. Let $B = \begin{pmatrix} 0 & 0 & 1 \end{pmatrix}$ and d = 0. Which one of the following options for A and C will ensure that the transfer function of this LTI system is

$$H(s) = \frac{1}{s^3 + 3s^2 + 2s + 1}$$
 (1.0.1)

(A)
$$A = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -1 & -2 & -3 \end{pmatrix}$$
 and $C = \begin{pmatrix} 1 & 0 & 0 \end{pmatrix}$
(B) $A = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -3 & -2 & -1 \end{pmatrix}$ and $C = \begin{pmatrix} 1 & 0 & 0 \end{pmatrix}$
(C) $A = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -1 & -2 & -3 \end{pmatrix}$ and $C = \begin{pmatrix} 0 & 0 & 1 \end{pmatrix}$
(D) $A = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -3 & -2 & -1 \end{pmatrix}$ and $C = \begin{pmatrix} 0 & 0 & 1 \end{pmatrix}$

(B)
$$A = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -3 & -2 & -1 \end{pmatrix}$$
 and $C = \begin{pmatrix} 1 & 0 & 0 \end{pmatrix}$

(C)
$$A = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -1 & -2 & -3 \end{pmatrix}$$
 and $C = \begin{pmatrix} 0 & 0 & 1 \end{pmatrix}$

(D)
$$A = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -3 & -2 & -1 \end{pmatrix}$$
 and $C = \begin{pmatrix} 0 & 0 & 1 \end{pmatrix}$

2 Solution

We are given

$$\begin{pmatrix} \dot{x}(t) \\ y(t) \end{pmatrix} = \begin{pmatrix} A & B \\ C & d \end{pmatrix} \begin{pmatrix} x(t) \\ u(t) \end{pmatrix}$$
 (2.0.1)

Taking Laplace transform on both sides,

$$\begin{pmatrix} sX(s) \\ Y(s) \end{pmatrix} = \begin{pmatrix} A & B \\ C & d \end{pmatrix} \begin{pmatrix} X(s) \\ U(s) \end{pmatrix}$$
 (2.0.2)

$$\implies sX(s) = AX(s) + BU(s) \tag{2.0.3}$$

$$\implies X(s) = (sI - A)^{-1}BU(s) \tag{2.0.4}$$

$$\implies Y(s) = CX(s) + dU(s)$$
 (2.0.5)

$$= C(sI - A)^{-1}BU(s) + dU(s)$$
 (2.0.6)

By definition,

$$Y(s) = H(s)U(s) \tag{2.0.7}$$

$$\implies H(s) = C(sI - A)^{-1}B + d$$
 (2.0.8)

$$=\frac{1}{s^3+3s^2+2s+1}\tag{2.0.9}$$

$$\implies C(sI - A)^{-1}B + d = \frac{1}{s^3 + 3s^2 + 2s + 1}$$
(2.0.10)

Now we cross verify the options with eq 2.0.10. Using the codes from codes/codes.py,

(A)

$$C(sI - A)^{-1}B + d = \frac{1}{s^3 + 3s^2 + 2s + 1}$$
 (2.0.11)

(B)

$$C(sI - A)^{-1}B + d = \frac{1}{s^3 + 1s^2 + 2s + 3}$$
 (2.0.12)

(C)

$$C(sI - A)^{-1}B + d = \frac{s^2}{s^3 + 3s^2 + 2s + 1}$$
 (2.0.13)

(D)

$$C(sI - A)^{-1}B + d = \frac{s^2}{s^3 + 1s^2 + 2s + 3}$$
 (2.0.14)

Hence only option A is the correct option.