JAVASCRIPT

- ✓ JavaScript is the **Programming Language** for the Web.
- ✓ JavaScript can **calculate**, **manipulate** and **validate** data.
- ✓ JavaScript is a **client-side scripting** language

JavaScript Display Possibilities

Writing into an HTML element, using **innerHTML**.

Writing into the HTML output using **document.write().** → should only be used for testing

Writing into an alert box, using **window.alert().**

Writing into the browser console, using **console.log().**

❖ Using External Javascript

```
<head>
        <title></title>
        <script type="text/javascript" src=""></script>
</head>
```

JavaScript Comments

Single line comments start with //

Multi-line comments start with /* and end with */

Variable in JavaScript

- ✓ **Var**
  - ✓ **Example : var x, y, hello;** **(Do not using Space and numeric values starting)**
- ✓ **Let**

Let → Do not Declare again **only assign second time**

```
let hello =" hello";
let hello ="divine"

document.write(hello);
```

```
let hello =" hello";
hello ="divine"
document.write(hello);
```

- ✓ **Const (constant variables)**

Do not Declare again **only assign second time**

```
const hello =" hello";
hello ="divine"
document.write(hello);
```

JavaScript Datatype

```
var x = "Divine institute";  ------------------- String
var x = 25; ----------------------------------- Number
var x = true  --------------------------------- Boolean
var x = ["html", "css", "js"] ------------------ Array
var x = {first:"divine", last:"institute"}  --- object
var x = null  --------------------------------- null;
var x = undefined----------------------------- undefined
```

document.write (typeof); → Indefine
In JavaScript Array, object and null values same define → object

Arithmetic Operators

Operator	Description
+	Addition
-	Subtraction
*	Multiplication
**	Exponentiation (ES2016)
/	Division
%	Modulus (Remainder)
++	Increment
--	Decrement

```
var a,b,c;
a = 10;
b = 20;
c = a+b;
document.write(c);
```

```
var a,b,c;
a = 5;
b = 3;
a++;
document.write(a+b);
```

```
var a,b,c;
a = 5;
b = 3;
a--;
document.write(a+b);
```

Assignment

Operator	Example	Same As
=	x = y	x = y
+=	x += y	x = x + y
-=	x -= y	x = x - y
*=	x *= y	x = x * y
/=	x /= y	x = x / y
%=	x %= y	x = x % y

```
<script>
    var a = 20;
    var b = 50;
    a -= b;
    document.write(a);
</script>
```

divine institute - 8866790979

Comparison Operators

Operator	Description	Example
`==`	**Equal to:** `true` if the operands are equal	`5==5; //true`
`!=`	**Not equal to:** `true` if the operands are not equal	`5!=5; //false`
`===`	**Strict equal to:** `true` if the operands are equal and of the same type	`5===‘5’; //false`
`!==`	**Strict not equal to:** `true` if the operands are equal but of different type or not equal at all	`5!==‘5’; //true`
`>`	**Greater than:** `true` if the left operand is greater than the right operand	`3>2; //true`
`>=`	**Greater than or equal to:** `true` if the left operand is greater than or equal to the right operand	`3>=3; //true`
`<`	**Less than:** `true` if the left operand is less than the right operand	`3<2; //false`
`<=`	**Less than or equal to:** `true` if the left operand is less than or equal to the right operand	`2<=2; //true`

```
<script type="text/javascript">
    var a,b,c;
    a = 10;
    b = "10";
    console.log(a===b);
</script>
```

Console Log

```
<script>
    console.time("Test");
    console.log(['2','7','7']);
    console.log("jagdish");
    console.error('Hello');
    console.warn('warning');
    console.timeEnd("Test");
    console.clear();
</script>
```

Logical Operators

```
&&   Logical AND x && y
||   Logical OR  x || y
!    Logical not !(x==y)
```

```
var age = 20;

if(age >= 20 && age <= 26){
    console.log("Welcome to our family");
}
```

```
var a = 8;
var b = 28;

if(a >= 20 || b <= 26){
    console.log ("Welcome to Divine");
}
```

```
var a = 18;
console.log(!(a>=10));
```

If- else

if (*condition1*) {
  // *block of code to be executed if condition1 is true*
} else if (*condition2*) {
  // *block of code to be executed if the condition1 is false and condition2 is true*
} else {
  // *block of code to be executed if the condition1 is false and condition2 is false*
}

```
var per = 100;

if( per >= 80 && per <= 100){
    document.write('A');
}else if(per >= 60 && per <=80){
    document.write('B');
}else if(per >= 40 && per <=60){
    document.write("C");
}else if(per< 35){
    document.write("d");
}
else{
    document.write("Enter valid data");
}
```

JavaScript Conditional Ternary Operator

```
var a = 200;
var b;
(a == 290)? b="true" : b ="false";
document.write(b);
```

Switch Case

```
var months = 3;

switch(months){
    case 0: //case:1 case: 2  Using Multipal Case
        document.write("January");
     // document.write("dacember"); Also Use Multipal Statement
    break;

    case 1: // case (months>= 30 && months <= 40):
        document.write("February");
    break;

    case 2:
        document.write("March");
    break;

    case 3:
        document.write("April");
    break;

    default:
        document.write("Choose valid days");
}
```

Alert Box

```
// alert("Hello, Divine");
var a = 20;
var b = 30;
if(a>b){
    alert("A is big" + a);
}else{
    alert("B is big " + b);
}
```

Confirm Box

```
<script type="text/javascript">

    a = confirm("Do u like pizza?");
    if(a){
        alert("true");
    }else{
        alert("false");
    }

</script>
```

Prompt Box

```
var name = prompt("What is your name");
// alert(name);
document.write("My name is " + name + ".");
```

Functions

reuse the same code again and again.

```
function hello(){
    document.write('divine institute');
}
hello();
// hello();
// hello(); Use multiple time
// hello();
```

Functions with Parameters

```
function hello(a,b){

  document.write(a*b);
}
hello(9,8);

function divine(fname = "jagdish", lname= "shingala"){
  document.write("Hello " + fname + " " + lname+ "<br>");

}
divine("jagdish", "shingala");
```

divine institute - 8866027278

Functions with Return Value

create function with returning value and use that value on another function.

```
function sum(eng,maths,sci){

    var total = eng+maths+sci;
    return total;

}
    var sum = sum(80,89,50);
    document.write(sum);
```

Global & Local Variable

```
var a = "divine";  // Global Variable

function hello(){
    var a = "divine"; // local variable
    document.write(a + "<br>");
}
hello();
document.write(a);
```

Events

mouse events, keyboard events and window events
window event only work on body tag

- Click (onclick)
- Double Click (ondblclick)
- Right Click (oncontextmenu)
- Mouse Hover (onmouseenter)
- Mouse Out (onmouseout)
- Mouse Down (onmousedown)
- Key Press (onkeypress)
- Key Up (onkeyup)
- Load (onload)
- Unload (onunload)
- Resize (onresize)
- Scroll (onscroll)

```
<script type="text/javascript">

    function divine(){
        alert("Hello, Sachin");
    }

</script>
```

```
<button onclick="divine();">Click Me</button>
```

```
<body onscroll="divine();">
<button onunlode="divine();">Click Me</button>
```

While Loop

```
<script type="text/javascript">

        var a=1;
        document.write("<ol>");
        while(a<=100){
            document.write("<li> hello</li>");
            a++;
        }
        document.write("</ol>");

</script>
```

Do-While Loop

```
var a = 1;
do{
document.write("hello divine<br>");
a++;
}while(a<10)
```

divine institute - 8866790979

For Loop

Initialization Condition Increment / Decrement

```
for(var a = 1; a <= 10; a++){
  document.write("Yahoo Baba");
}
```

```
for(var a=1; a<=10; a++){
    document.write("Hello divine<br> " + a);
}
```

For Loop - Break & Continue Statement

```
for(var a=1; a<=10; a++){
    if(a == 4){
        document.write(a + " Hi<br>");
        // continue;
        break;
    }

    document.write(a + " Divine<br>");
}
```



```
for(var a=1; a<=100; a++){
    if(a % 2 == 1){
        document.write(a + "<br>");
    }
}
```

Array

var a = 10;

var a = 10,20,30; → Error

var a = "10,20,30"; → String

var a = [10,20,30];

```
<script type="text/javascript">
    var array = [10,20,30,40,50];
    // var sum = 0;
    // document.write("<ul>")

    for(var a=0; a<=4; a++){
    document.write("<li>" + array[a] + "</li>");
    // sum = sum + array[a];
}
    // document.write("</ul>");
    // document.write(sum);
</script>
```

Modify & Delete Array

```
var array = ["jagdish","27","Iphone"];
document.write(array + "<br>");

array[1] = "30";

document.write(array);

delete array[2];

document.write(array);
```

divine institute - 8866790979

Sort Reverse Array

```
var a = ["Jagdish", "reena", "Ankit", "Jinal"];
document.write(a + "<br>");
a.sort();
document.write(a + "<br>");
a.reverse();
document.write(a + "<br>");
```

Array Pop & Push

Pop → **Delete last** value and Push → **Add last** values

```
var a = ["Jagdish", "reena", "Ankit", "Jinal"];
document.write(a + "<br>");
a.pop();
document.write(a + "<br>");
a.push("divine");
document.write(a + "<br>");
```

Shift & Unshift

Shift → **Delete first** value and Unshift → **Add first** values

```
var a = ["Jagdish", "reena", "Ankit", "Jinal"];
document.write(a + "<br>");
a.shift();
document.write(a + "<br>");
a.unshift("divine");
document.write(a + "<br>");
```

divine institute - 8866790979

Array Concat & Join

Concat → **Join String or Array**

```
var a = ["Jagdish", "Jay", "Deep"];
var b = ["Ankit"];
var c = ["divine"];
var d = a.concat(b,c);
document.write(d);
```

Join → **Marge values and add Special characters**

```
var e = a.join(" * ");
document.write(e + "<br>");
```

Array Slice & Splice

Slice → **Join String or Array**

slice(start , end)

```
var a = ["Jagdish", "Jay", "Deep", "divine", "institiute"];
document.write(a + "<br>");
var b = a.slice(1,4);  // a.slice(2); --> After 2 all
document.write(b);
```

Splice → **Marge values and add Special characters**

splice(index , howmany , “new value”
Delete

```
var a = ["Jagdish", "Jay", "Deep", "divine", "institiute"];
document.write(a + "<br>");
a.splice(3,2,"hello", "hi");
document.write(a + "<br>");
```

isArray Slice & Splice

isArray →Check Values array or not

```
var a = ["Divine"];
// var a = 40;

if(Array.isArray(a)){
    document.write("This is a Array");
}else{
    document.write("Not Array");
}
// var b = Array.isArray(a);
// document.write(b);
```

Array indexOf & lastIndexOf

indexOf →Check values index

indexOf("Search item" , Start)

```
var a = ["jagdish", "jay", "deep", "divine", "deep"];
var b = a.indexOf("deep",3);
document.write(b);
```

If We have a not find Any values values is : **-1**

lastIndexOf →Stating Last

```
var c = a.lastIndexOf("deep");
document.write(c + "<br><br>");
```

2

4

includes Array

includes →Check values In array have or have not

```
<script type="text/javascript">

    var a = ["jagdish", "jay", "deep", "divine", "deep"];
    document.write(a + "<br><br>");

    var b = a.includes("institute");
    document.write(b);


</script>
```

jagdish,jay,deep,divine,deep

false

Some & Every Methods

Some → Check values 18- or not

```
var age = [10,20,50,30];
document.write(age + "<br>");

var b = age.some(checkage);
document.write(b + "<br>");

function checkage(age){
    return age >= 18;
}
```

Every → Check values 18+ or not

```
var age = [60,20,50,30];
document.write(age + "<br>");

var b = age.every(checkage);
document.write(b + "<br>");

function checkage(age){
    return age >= 18;
}
```

60,20,50,30
true

Array find & findIndex

find → find first vales of condition

```
var age = [10,13,50,60];
document.write(age + "<br>")

var b = age.find(checkvalues)
document.write(b);

function checkvalues(ages){
    return ages >= 18;
}
```

```
10,13,50,60
50
```

findindex→ find first value index of conition

```
var age = [10,13,50,60];
document.write(age + "<br>")

var b = age.findIndex(checkvalues)
document.write(b);

function checkvalues(ages){
    return ages >= 18;
}
```

```
10,13,50,60
2
```

Array find & findIndex

find → find first vales of condition

```
var age = [10,13,50,60];
document.write(age + "<br>")

var b = age.find(checkvalues)
document.write(b);

function checkvalues(ages){
    return ages >= 18;
}
```

```
10,13,50,60
50
```

findindex→ find first value index of conition

```
var age = [10,13,50,60];
document.write(age + "<br>")

var b = age.findIndex(checkvalues)
document.write(b);

function checkvalues(ages){
    return ages >= 18;
}
```

```
10,13,50,60
2
```

Array Filter

Array Filter →Filter as per condition and create new array

```
var age = [10,100,50,6,60];
document.write(age + "<br>")

var b = age.filter(checkvalues)
document.write(b);

function checkvalues(ages){
    return ages >= 18;
}
```

10,100,50,6,60
100,50,60

toString, valueOf & fill Methods

toString →Array convert in to string Do not Apply any array method

```
var a = ["hello", "jagdish", "Hi"];
a.toString();
document.write(a);
```

valueOf →Return array values

```
var a = ["hello", "jagdish", "Hi"];
a.valueOf();
document.write(a);
```

fill →Return Static Value of Array

```
var a = ["hello", "jagdish", "Hi"];
a.fill("jagdish11");
document.write(a);
```

Foreach Loop → Run Values

```
var a = ["divine", "institute", "hello"];

a.forEach(function(value,index){
    document.write(index + " : " + value + "<br>");
});
```

JavaScript Objects

```
var a =  {
    fname : 'divine',
    lname : 'institute',
    age : 20,
    email : 'info@divine-institute.in',
    website : 'divine-institute.in',
    courses : ['web', 'Graphics', 'digital', 'marketing'],
    salary : function(){
        return 25000;
    },

}

console.log(a);
document.write(a.email + "<br>");
document.write(a.courses[2]);
document.write(a.salary());
```

For in Loop

GET Object values For In loop

```
var obj = {

    fname : 'Divine',
    sur_name : 'Institute',
    age : 26,
    email : 'divineinstitute.info'
}

for(var value in obj){
    document.write(obj[value] + "<br>");
}
```

Array Map

Creating Calculator and Create new Array

```
var array = [20,30,40,50];
document.write(array + "<br>");

var b = array.map(test);
document.write(b + "<br>");

function test(values){
    return values*10;
}
```

20,30,40,50
200,300,400,500

JavaScript String Methods

- length
- toLowerCase()
- toUpperCase()
- includes()
- startsWith()
- endsWith()
- search()
- match()
- indexOf()
- lastIndexOf()
- replace()
- trim()
- charAt()
- charCodeAt()
- fromCharCode()
- concat()
- split()
- repeat()
- slice()
- substr()
- substring()
- toString()
- valueOf()

```
var str = "Hello Javascript";

var divine = str.includes("Hello");
document.write(divine);
```

```
var str = "Hello Javascript Good Morning";

var divine = str.search("Good");
document.write(divine);
```

```
var str = "Hello Javascript";

var divine = str.length;
document.write(divine);
```

```
var str = "Hello Javascript";

var divine = str.toUpperCase();
document.write(divine);
```

```
var str = "Hello Javascript Good Morning";

var divine = str.endsWith("Hello");
document.write(divine);
```

JavaScript String Methods

- length
- toLowerCase()
- toUpperCase()
- includes()
- startsWith()
- endsWith()
- search()
- match()
- indexOf()
- lastIndexOf()
- replace()
- trim()
- charAt()
- charCodeAt()
- fromCharCode()
- concat()
- split()
- repeat()
- slice()
- substr()
- substring()
- toString()
- valueOf()

```
var str = "Hello Javascript Good Morning
    Hello";

var divine = str.indexOf("Good");
document.write(divine);
```

Find Array Position…

```
var str = "Hello Javascript, Good Morning Divine";

var a = str.charAt(1);
document.write(a);
```

Return Character in String

```
var str = "Hello Javascript Good Morning Hello";

// var divine = str.replace("Javascript", "PHP");
var divine = str.replace(/Hello/g, "Hi");

document.write(divine);
```

```
var str = "    Hello Javascript Good Morning Divine    ";

var a = str.trim();
alert(a);
```

Extra Space Remove Right and left sides

JavaScript String Methods

- length
- toLowerCase()
- toUpperCase()
- includes()
- startsWith()
- endsWith()
- search()
- match()
- indexOf()
- lastIndexOf()
- replace()
- trim()
- charAt()
- charCodeAt()
- fromCharCode()
- concat()
- split()
- repeat()
- slice()
- substr()
- substring()
- toString()
- valueOf()

```
var str = "Hello Javascript, Good Morning Divine";

var a = str.charCodeAt(1);
document.write(a);
```

Return Charcode..

```
var str = "Hello Javascript Good Morning
    Hello";

var divine = str.match(/Hello/g);
document.write(divine);
```

Find multiple time and Return Array

```
var str = "Hello Javascript Good Morning Hello";

// var divine = str.replace("Javascript", "PHP");
var divine = str.replace(/Hello/g, "Hi");

document.write(divine);
```

```
var str = "    Hello Javascript Good Morning Divine    ";

var a = str.trim();
alert(a);
```

Extra Space Remove Right and left sides

JavaScript String Methods

- length
- toLowerCase()
- toUpperCase()
- includes()
- startsWith()
- endsWith()
- search()
- match()
- indexOf()
- lastIndexOf()
- replace()
- trim()
- charAt()
- charCodeAt()
- fromCharCode()
- concat()
- split()
- repeat()
- slice()
- substr()
- substring()
- toString()
- valueOf()

```
var a = String.fromCharCode(89);
document.write(a);
```

```
var a = "divine";
var b = " Institute Nikol";

var c = a.concat(b);
document.write(c);
```

```
var a = "Divine Institute bapunagar Nikol";
var c = a.split("i");
document.write(c);
```

D,v,ne Inst,tute bapunagar N,kol

```
var a = "Divine Institute bapunagar Nikol";
var c = a.repeat(3);
document.write(c);
```

```
var a = "Divine Institute bapunagar Nikol";
var c = a.slice(3,10); //Start from 3 and 10
document.write(c);
```

Take word Or Characters

JavaScript String Methods

- length
- toLowerCase()
- toUpperCase()
- includes()
- startsWith()
- endsWith()
- search()
- match()
- indexOf()
- lastIndexOf()
- replace()
- trim()
- charAt()
- charCodeAt()
- fromCharCode()
- concat()
- split()
- repeat()
- slice()
- substr()
- substring()
- toString()
- valueOf()

```
var a = 50;
var b = a.toString(); //num convert to string
document.write(b);
```

```
var a = "divine Institiute";
var b = a.valueOf();
document.write(b);
```

Output Get String

```
var a = "Diwali holi";
// var c = a.slice(3,5); //after 3 and  to 5 //output al
// var d = a.substr(1,7);  // after 1 , 7 charater Return
var d = a.substring(1,4);  // going to 4 but 4 not print
document.write(d);
// document.write(c);
```

JavaScript String Methods

- length
- toLowerCase()
- toUpperCase()
- includes()
- startsWith()
- endsWith()
- search()
- match()
- indexOf()
- lastIndexOf()
- replace()
- trim()
- charAt()
- charCodeAt()
- fromCharCode()
- concat()
- split()
- repeat()
- slice()
- substr()
- substring()
- toString()
- valueOf()

```
var a = 50;
var b = a.toString(); //num convert to string
document.write(b);
```

```
var a = "divine Institiute";
var b = a.valueOf();
document.write(b);
```

Output Get String

```
var a = "Diwali holi";
// var c = a.slice(3,5); //after 3 and  to 5 //output al
// var d = a.substr(1,7);  // after 1 , 7 charater Return
var d = a.substring(1,4);  // going to 4 but 4 not print
document.write(d);
// document.write(c);
```

JavaScript Number Method

```
var a ="90";
var num = Number(a); //Covert String Into Number
document.write(num + 80);
```

```
var a ="90.06";
var num = parseFloat(a); //Covert Decimal to number
document.write(num);
```

```
var a = 50.7687;
var num = a.toFixed(3); //after point fix value
document.write(num);
```

```
var a ="90.06";
var num = parseInt(a); //Covert Decimal to number
document.write(num);
```

```
var a = Infinity;  //Infinity
var num = isFinite(a); //check value FInite or not
document.write(num);
```

- number()
- parseInt()
- parseFloat()
- isFinite()
- isInteger()
- toFixed(x)
- toPrecision(x)

```
var a = 50.7;
var num = Number.isInteger(a);
document.write(num);
```

```
var a = 50.7687;
var num = a.toPrecision(3); //total values Return
document.write(num); // output 50.7
```

Math Method In Javascript

```
var a = Math.ceil(5.99); // upper value
var b = Math.floor(6.44); // Down Value
document.write(b);
```

```
var a = Math.sqrt(225); // Square Root
var b = Math.cbrt(125); // Cubic Root
document.write(b);
```

```
var a = Math.round(5.34); // IF value above 5..
var b = Math.trunc(6.44); // Return of interger value
document.write(b);
```

```
var a = Math.max(10,5,6,4,8,90,2); // IF value above 5..
var b = Math.min(5,7,12,16,70,90); // Return of interger value
document.write(a);
```

```
var a = Math.pow(6,3); // 6*6*6
// var b = Math.random(); // Random values generat
var b = Math.floor(Math.random() * 10) + 1;
var c = Math.PI;
document.write(c);
```

JavaScript **Date Methods**

- toDateString()
- getDate()
- getFullYear()
- getMonth()
- getDay()
- getHours()
- getMinutes()
- getSeconds()
- getMilliseconds()
- setDate()
- setFullYear()
- setHours()
- setMilliseconds()
- setMinutes()
- setMonth()
- setSeconds()

```
var now = new Date();
document.write(now);
```

```
var now = new Date();
now.setDate(23); //set past date
document.write(now);
```

```
var now = new Date();
//document.write(now.getDate());
//document.write(now.getFullYear());
document.write(now.getSeconds());  //get Seconds..
```

JavaScript DOM

Three way to Use Dom Target

1)Id → document.getElementById(id)
2)Class Name → document.getElementsByClassName(name)
3) Tag Name → document.getElementsByTagName(name)

- document
- document.all
- document.documentElement
- document.head
- document.title
- document.body
- document.images
- document.anchors
- document.links
- document.forms
- document.doctype
- document.URL
- document.baseURI
- document.domain

JavaScript DOM

```
var element;
element = document.all;
console.log(element);
```

```
var element;
// element = document.head;
//element = document.body;
element = document.title;
console.log(element);
```

```
        var element;
        // element = document.head;
        //element = document.body;
        element = document.getElementsByClassName('h2');
        console.log(element);

    </script>
</head>
<body>

    <h1>Hello, Divine</h1>
    <h2 class="h2">Institute</h2>
    <img class="h2" src="" alt="">
```

```
var element;
// element = document.head;
//element = document.body;
element = document.getElementsByTagName('h1');
console.log(element);
```

JavaScript DOM Get Method

- innerText
- innerHTML
- getAttribute
- getAttributeNode
- Attributes

```
//  var a = document.getElementById("hello").innerText; //Get text inside Id..
    var a = document.getElementById("hello").innerHTML; //Get html Inside Id..

    console.log(a);
```

```
<div id="hello" class="abcd">
```

```
var a = document.getElementById("hello").getAttribute("class");
```

```
<div id="hello" class="abcd" style="border: 1px solid red;">
```

```
var a = document.getElementById("hello").getAttributeNode("style"); //getAttributeNode Also
use for values

console.log(a);
```

JavaScript DOM Get Method

```
var a = document.getElementById("hello").attributes; //get all details Inside ID
```

```
▼ NamedNodeMap
  ▶ 0: id
  ▶ 1: class
  ▶ 2: style
    length: 3
  ▶ class: class
  ▶ id: id
  ▶ style: style
  ▶ __proto__: NamedNodeMap
```

JavaScript DOM SET Method

```
// var a = document.getElementById('h1').innerHTML = "<h3>jagdish</h3>";
var a = document.getElementById('h1').innerText = "<h3>jagdish</h3>";
```

```
// var a = document.getElementById('h1').innerHTML = "<h3>jagdish</h3>";
var a = document.getElementById('h1').setAttribute("class", "divine");
```

JavaScript querySelector & querySelectorAll

```
<ul id="list">
    <li>Web Design</li>
    <li>Graphics Design</li>
    <li>Digital Marketing</li>
    <li>Web Development</li>
</ul>
<script type="text/javascript">
    var a = document.querySelector('#list'); // Also use class
    console.log(a);
</script>
```

```
<p class="p">HEllo<p>
<p class="p">Divine</p>
<p class="p">Web</p>
<script type="text/javascript">
    var a = document.querySelectorAll('.p')[2].innerHTML; // Also use class and Tagname
    console.log(a);
</script>

/body>
/html>
```



JavaScript Style Selector

```
<p id="hello" class="p" style="border: 2px solid red">HEllo<p>
<p class="p">Divine</p>
<p class="p">Web</p>

<script type="text/javascript">
    document.querySelector("#hello").style.backgroundColor="cyan"; // setcolor
    var a = document.querySelector('#hello').style.border;
    console.log(a);
</script>
```

```
    <style type="text/css">
        .p{
            color: red;
        }
    </style>
</head>
<body>

    <p id="hello">HEllo<p>
    <p class="p">Divine</p>
    <p class="p">Web</p>

    <script type="text/javascript">
        document.querySelector("#hello").className = "p abcd";
        var a = document.querySelector('#hello').style.border;
        console.log(a);
    </script>
```