

Introduction

Organizor is the backend API for managing tenant environments. It keeps tenant records in a central catalog database and provisions a separate PostgreSQL database for each tenant.

The current implementation focuses on tenant lifecycle operations:

- creating tenant catalog records;
- onboarding tenants by creating a tenant database and applying migrations through internal operations;
- resolving tenant context for tenant-scoped requests;
- upgrading tenant databases by running migrations;
- soft-deleting tenants before hard deletion;
- exposing health checks, OpenAPI JSON, and Scalar endpoint exploration in development.

Main Concepts

CONCEPT	DESCRIPTION
Tenant	A customer or isolated workspace tracked by <code>Id</code> , <code>Name</code> , <code>Slug</code> , <code>DatabaseName</code> , lifecycle status, and deletion metadata.
Catalog database	Central PostgreSQL database that stores all tenant records.
Tenant database	PostgreSQL database named from the tenant slug, currently using the <code>organizor_tenant_{slug}</code> convention.
Tenant resolution	Middleware step that reads <code>X-Tenant-Slug</code> , loads the tenant, and stores the current tenant in <code>ITenantContext</code> .
Provisioning workflow	Infrastructure workflow that creates the tenant database and applies tenant migrations.

Project Layout

PROJECT	RESPONSIBILITY
<code>Code7Dev.Organizor.Api</code>	ASP.NET Core host, controllers, DTOs, mappers, middleware, OpenAPI/Scalar, health checks, CORS, and logging setup.
<code>Code7Dev.Organizor.Application</code>	Tenant service contracts, tenant models, onboarding, lifecycle, upgrade, and catalog-facing application logic.
<code>Code7Dev.Organizor.Domain</code>	Tenant entity and <code>TenantStatus</code> enum.
<code>Code7Dev.Organizor.Infrastructure</code>	EF Core contexts, repository implementation, PostgreSQL connection string building, database creation/deletion, migration, and tenant context storage.

Documentation Boundaries

The documentation is split into two intentionally different areas:

AREA	PURPOSE
Conceptual docs	Explain behavior, workflows, configuration, security, local development, operations, and integration decisions.
Generated API reference	Lists C# namespaces, classes, interfaces, methods, and signatures generated from source.

Do not use the generated reference to explain workflows or product behavior. Keep that content in the conceptual articles so it stays readable and can include context, examples, and operational guidance.



Getting Started

For the full local topology, expected ports, startup order, and verification checklist, use [Local Development](#). This page keeps the shorter first-run flow.

Prerequisites

- .NET SDK 10.
- PostgreSQL available to the API.
- Keycloak available to the API. The repository includes a development Keycloak compose file.
- A catalog database connection string named `Catalog`.
- PostgreSQL server settings under the `Postgres` configuration section for tenant database creation and resolution.
- Keycloak bearer-token settings under the `Keycloak` configuration section.
- DocFX installed as a .NET tool when building documentation locally.

Install DocFX if the `docfx` command is not available:

```
dotnet tool install -g docfx
```

Start the development Keycloak instance:

```
docker compose up -d
```

The compose file starts Keycloak at `https://localhost:8443`. Generate and trust the local certificate first if `keycloak/certs/keycloak.p12` does not exist. Configure the `organizer-dev` realm, clients, roles, and users as described in [Keycloak Setup](#).

Run the API

From the repository root:

```
dotnet run --project .\Code7Dev.Organizor.Api\Code7Dev.Organizor.Api.csproj
```

Development launch profiles expose:

PROFILE	URL
http	http://localhost:5100
https	https://localhost:7184 and http://localhost:5100

On startup the API:

- 1. configures Serilog;
- 2. registers catalog and tenant database services;
- 3. registers application and infrastructure services;
- 4. seeds or migrates the catalog database;
- 5. maps controllers, health checks, OpenAPI, and Scalar in development.

Development Endpoints

ENDPOINT	PURPOSE
/health	ASP.NET Core health checks.
/openapi/v1.json	OpenAPI document, available in development.
/scalar	Interactive OpenAPI/Scalar endpoint explorer, available in development.

Example tenant catalog request:

```
$token = "<organizer-admin JWT>"
```

```
Invoke-RestMethod `
-Method Post `
-Uri "http://localhost:5100/api/v1/tenants" `
-Headers @{ Authorization = "Bearer $token" } `
-ContentType "application/json" `
-Body '{"name":"Acme","slug":"acme"}'
```

`POST /api/v1/tenants` creates a catalog record only and requires an `organizer-admin` token. Use `POST /api/admin/tenants/onboard` when you also need tenant database and Keycloak provisioning.

Run the Portal UI

From the repository root:

```
dotnet run --project
.\Code7Dev.Organizer.Portal.Ui\Code7Dev.Organizer.Portal.Ui.csproj --
launch-profile https
```

The HTTPS profile exposes the portal at `https://localhost:7025`. The portal is configured to:

- authenticate against `https://localhost:8443/realms/organizer-dev`;
- use the `organizer-ui` Keycloak client;
- receive login callbacks at `https://localhost:7025/authentication/login-callback`;
- call the API at `https://localhost:7184`.

Build the Documentation

From the repository root:

```
docfx .\docs\docfx.json
```

DocFX writes the generated site to `docs/_site` and generated C# type-reference metadata to `docs/api`. Both folders are ignored by git and can be rebuilt.


Local Development

This page is the canonical reference for running Organizer locally. Use it to confirm the expected ports, startup order, and how the Blazor portal, Keycloak, API, and databases fit together.

NOTE

Keep this page as the source of truth for local ports and startup order. Link here from other articles instead of duplicating endpoint tables.

Local Topology



Ports And URLs

COMPONENT	URL	NOTES
Portal UI	https://localhost:7025	Blazor WebAssembly HTTPS launch profile
Portal UI HTTP	http://localhost:5080	Development fallback profile. Prefer HTTP! for auth testing.

COMPONENT	URL	NOTES
Organizor API	<code>https://localhost:7184</code>	API HTTPS launch profile used by the portal.
Organizor API HTTP	<code>http://localhost:5100</code>	Useful for direct local API calls without the portal.
Keycloak	<code>https://localhost:8443</code>	Docker Compose service with local HTTPS certificate.
Keycloak realm issuer	<code>https://localhost:8443/realms/organizor-dev</code>	Must match API <code>Keycloak:Authority</code>
Keycloak token endpoint	<code>https://localhost:8443/realms/organizor-dev/protocol/openid-connect/token</code>	Used for manual token testing.

Required Local Configuration

The API needs:

- a `ConnectionStrings:Catalog` connection string;
- `Postgres` settings for tenant database creation and resolution;
- `Keycloak:Authority` set to `https://localhost:8443/realms/organizor-dev`;
- `Keycloak:BaseUrl` set to `https://localhost:8443`;
- `Keycloak:Realm` set to `organizor-dev`;
- `Keycloak:AdminClientId` set to `organizor-api`;
- `Keycloak:AdminClientSecret` from the Keycloak `organizor-api` client.

⚠ WARNING

The API authority must match the token issuer exactly. A token issued by `https://localhost:8443/realms/organizor-dev` will not validate against any

different scheme, host, port, or realm.

The portal is currently configured to:

- use Keycloak authority `https://localhost:8443/realms/organizer-dev`;
- use Keycloak client ID `organizer-ui`;
- redirect login callbacks to `https://localhost:7025/authentication/login-callback`;
- call the API at `https://localhost:7184`.

Startup Order

1. Generate or verify the Keycloak HTTPS certificate at `keycloak/certs/keycloak.p12`.
2. Start Keycloak with Docker Compose.
3. Confirm the `organizer-dev` realm, clients, roles, groups, and users exist.
4. Start the API with the HTTPS launch profile.
5. Start the portal with the HTTPS launch profile.
6. Sign in through the portal and verify the API accepts the issued token.

Commands

Start Keycloak:

```
docker compose up -d
```

Run the API:

```
dotnet run --project .\Code7Dev.Organizer.Api\Code7Dev.Organizer.Api.csproj  
--launch-profile https
```

Run the portal:

```
dotnet run --project
.\Code7Dev.Organizor.Portal.Ui\Code7Dev.Organizor.Portal.Ui.csproj --
launch-profile https
```

Build the documentation:

```
docfx .\docs\docfx.json
```

Keycloak Client Requirements

The `organizor-ui` client must allow the portal origin:

SETTING	VALUE
Valid redirect URI	<code>https://localhost:7025/*</code>
Login callback	<code>https://localhost:7025/authentication/login-callback</code>
Web origin	<code>https://localhost:7025</code>

The `organizor-api` client is used for API service-account operations during tenant onboarding and hard deletion. Its client secret must be available to the API through configuration or user secrets.

PRODUCTION CHECKLIST

Do not copy local wildcard origins, local certificates, or development secrets into deployed environments. Production should use real HTTPS certificates, explicit origins, and managed secret storage.

Verification Checklist

Use this checklist when local authentication or API calls fail:

- Keycloak opens at `https://localhost:8443` without a certificate warning.
- The API `Keycloak:Authority` exactly matches `https://localhost:8443/realms/organizor-dev`.
- The portal login callback is allowed by the `organizor-ui` client.
- The portal calls `https://localhost:7184`, not the API HTTP endpoint.
- The API HTTPS profile is running before logging in through the portal.
- The signed-in user has the expected realm roles and tenant groups.

Related Guides

- [Keycloak HTTPS Setup](#) explains certificate generation and browser trust.
- [Keycloak Setup](#) explains realm, client, role, group, and claim mapper configuration.
- [Configuration](#) documents API configuration sections.
- [Portal UI Overview](#) documents the Blazor portal responsibilities and integration points.

Portal UI Overview

The Portal UI is the front-end application of the Organizer platform. It provides the user-facing interface for authentication, tenant selection, navigation, and all customer-side functionality.

This document gives a high-level overview of the Portal UI architecture, its responsibilities, and how it integrates with the backend services.

Purpose of the Portal UI

- Provide a clean and intuitive interface for end-users.
 - Handle authentication and session management via Keycloak.
 - Communicate with the Organizer API using secure access tokens.
 - Render tenant-specific data and enforce authorization rules.
 - Serve as the entry point for all customer-facing features.
-

Technology Stack

- **Blazor WebAssembly** for client-side rendering.
 - **.NET 10** for the portal runtime and API integration.
 - **Keycloak** for authentication (OIDC + PKCE).
 - **Component-based architecture** for maintainability.
-

High-Level Structure

The Portal UI is organized into:

- **Pages** — top-level routes (e.g., `/dashboard`, `/profile`)
- **Components** — reusable UI building blocks
- **Services** — API clients, auth handlers, state management
- **Layouts** — shared UI shells (navigation, headers, footers)
- **wwwroot** — static assets

Authentication Flow

The Portal UI uses:

- OIDC Authorization Code Flow with PKCE
- Keycloak as the identity provider
- Access tokens for API calls
- Refresh tokens handled by Keycloak session

Current local configuration:

SETTING	VALUE
Portal origin	<code>https://localhost:7025</code>
Keycloak authority	<code>https://localhost:8443/realms/organizer-dev</code>
Keycloak client	<code>organizer-ui</code>
Login callback	<code>https://localhost:7025/authentication/login-callback</code>
Logout callback	<code>https://localhost:7025/</code>

See:

Authentication Flow → `authentication-flow.md`

API Integration

The Portal UI communicates with the Organizer API using:

- Typed `HttpClient` instances
- `AuthorizationMessageHandler`
- Automatic token injection
- Tenant-aware endpoints

The local portal API client targets `https://localhost:7184` and attaches tokens issued by the `organizer-dev` realm.

See:

API Integration → `api-integration.md`

Summary

The Portal UI is a modular, secure, and scalable front-end built on Blazor WebAssembly. It integrates tightly with Keycloak for authentication and the Organizer API for data access, providing a seamless experience for end-users.

Authentication Flow — High-Level

The Portal UI uses Keycloak to authenticate users and determine what they are allowed to do. The process follows the standard OpenID Connect Authorization Code Flow with PKCE.

What Happens During Login

1. The user clicks **Login**.
2. The Portal redirects the user to Keycloak at `https://localhost:8443/realms/organizor-dev`.
3. Keycloak handles the login form and verifies credentials.
4. After successful login, Keycloak sends the user back to `https://localhost:7025/authentication/login-callback`.
5. The Portal receives a secure token and uses it for API requests.

Why Keycloak

- Centralized user management
- Role-based access control
- Secure token handling
- Standard OIDC protocol support

What Developers Need to Know

- The Portal never handles passwords directly.
- Tokens are automatically attached to API requests.
- Protected pages require the user to be authenticated.
- Keycloak configuration determines what each user can access.
- The `organizor-ui` Keycloak client must allow `https://localhost:7025/*` as a redirect URI and `https://localhost:7025` as a web origin.

Portal UI Structure — High-Level

The Portal UI is organized into a small set of logical building blocks that keep the application clean and maintainable.

Main Building Blocks

Pages

Screens the user can navigate to, such as:

- Login
- Dashboard
- Not Found

Components

Reusable UI elements that appear across multiple pages.

Layouts

Define the overall structure of the application, including navigation and shared UI elements.

Services

Handle communication with the API and manage authentication state.

Why This Structure

- Easy to extend with new features
- Clear separation between UI, logic, and layout
- Reusable components reduce duplication
- Predictable folder structure for developers

API Integration — High-Level

The Portal UI communicates with the Organizer API to perform all business operations. Every action — from loading data to updating records — goes through the API.

How Communication Works

- The Portal uses `HttpClient` to send requests.
- A secure access token is automatically added to each request.
- The API validates the token before processing the request.

Local development configuration:

SETTING	VALUE
Portal origin	<code>https://localhost:7025</code>
API base URL	<code>https://localhost:7184</code>
Authorized URL	<code>https://localhost:7184</code>
Token issuer	<code>https://localhost:8443/realms/organizer-dev</code>

What Developers Should Know

- API calls are centralized through a configured `HttpClient`.
- Authentication is handled automatically.
- Errors from the API surface in the UI through standard Blazor patterns.
- If the API authority and portal token issuer differ by scheme, host, or port, API requests will fail with `401 Unauthorized`.


Why This Matters

This approach ensures:

- Consistent security across the platform
- A clean separation between UI and backend logic
- The ability to scale or replace parts of the system independently

Architecture

Organizor follows a layered structure around tenant management.



API Layer

The API project owns transport concerns:

- controller routes for public tenant catalog operations and internal tenant operations;
- request and response DTOs;
- mapping between API DTOs and application models;
- correlation ID, exception handling, and tenant resolution middleware;
- Serilog request logging;
- CORS, health checks, OpenAPI, and Scalar setup.

The startup flow in `Program.cs` composes the application by registering catalog persistence, tenant persistence, application services, infrastructure services, and API services.

Application Layer

The application project owns use cases and contracts. It defines interfaces for repository access, tenant database management, migration, provisioning, onboarding, upgrades, and lifecycle operations.

Current services:

SERVICE	RESPONSIBILITY
TenantService	Creates catalog tenant records and reads tenants by slug or as a list.
TenantOnboardingService	Creates a catalog tenant, runs provisioning, and marks the tenant active or failed.
TenantLifecycleService	Soft-deletes tenants and hard-deletes already soft-deleted tenants.
TenantUpgradeService	Runs migrations for an existing tenant database.

Domain Layer

The domain project currently contains the tenant entity and status enum. A tenant stores identity, slug, database name, creation date, lifecycle status, provisioning failure reason, and deletion metadata.

Infrastructure Layer

The infrastructure project owns external resources:


- `CatalogDbContext` stores tenant records.
- `OrganizorDbContext` connects to the current tenant database after tenant resolution.
- `TenantRepository` implements catalog tenant persistence.
- `ConnectionStringBuilder` builds PostgreSQL connection strings from configuration.
- `TenantDatabaseManager` creates and drops tenant databases.
- `TenantMigrator` applies EF Core migrations to tenant databases.
- `TenantProvisioningWorkflow` creates a tenant database and applies migrations during onboarding.

- `TenantJobScheduler` schedules tenant-scoped Quartz jobs from catalog tenant records.
- `TenantAwareJobFactory` creates Quartz jobs through dependency injection.
- `SyncTenantJob` runs recurring tenant synchronization work with `ITenantContext` populated from Quartz job data.

Background Jobs

Quartz is registered by the API layer and backed by persistent PostgreSQL storage in the catalog database. On startup, the application schedules a recurring synchronization job for each catalog tenant. Each job carries the tenant ID and slug in Quartz job data, then sets the tenant context before running tenant database work.

Request Pipeline



Tenancy

Organizor uses catalog-driven, database-per-tenant tenancy.

Tenant Catalog

The catalog database stores tenant metadata through `CatalogDbContext`. Each tenant includes:

- `Id` ;
- `Name` ;
- `Slug` ;
- `DatabaseName` ;
- `CreatedAt` ;
- `Status` ;
- `FailureReason` ;
- soft-delete metadata.

The database name convention is `organizor_tenant_{slug}`. Slugs are normalized to lowercase before they are stored or used for lookups.

Normal catalog reads exclude soft-deleted tenants. Repository methods can include soft-deleted records when an internal operation explicitly asks for them.

Tenant Statuses

STATUS	MEANING
Pending	Tenant exists in the catalog but provisioning is not complete.
Active	Tenant provisioning completed successfully.
Upgrading	Reserved for upgrade lifecycle state.

STATUS	MEANING
Failed	Provisioning failed or an unexpected onboarding error occurred.
Deleted	Tenant has been soft-deleted.

Tenant Resolution

`TenantResolutionMiddleware` resolves tenant context for tenant-scoped routes.

It skips platform endpoints such as:

- `/api/admin`;
- `/api/v1/tenants`;
- `/health`;
- `/scalar`;
- `/openapi`;
- root and common static paths.

For tenant-scoped requests, clients must send:

```
X-Tenant-Slug: acme
```


The middleware loads the tenant from the catalog and stores `TenantInfo` in `ITenantContext`. If the header is missing, the response is `400 Bad Request`. If the slug does not match a catalog tenant, the response is `404 Not Found`.


Tenant Database Resolution

`OrganizorDbContext` uses a fallback in-memory database when no tenant has been resolved. This supports startup, Scalar, migrations, and design-time tooling.

When a tenant is resolved, `PerTenantDbResolver` loads the catalog tenant, builds a PostgreSQL connection string for that tenant database, and `OrganizerDbContext` uses that database.

Tenant Onboarding Flow





not create Keycloak groups or a tenant database.

Hard deletion is intentionally guarded: the tenant must be soft-deleted before `TenantLifecycleService` runs the hard-delete workflow. That workflow removes the Keycloak tenant group and default admin user, drops the tenant database, and removes the catalog record.

Public API Behavior

The public API currently exposes tenant catalog endpoints. These endpoints are platform/catalog routes, so tenant resolution does not require `X-Tenant-Slug` for them. They are still authenticated:

- `POST /api/v1/tenants` requires `organizer-admin`.
- `GET /api/v1/tenants` and `GET /api/v1/tenants/{slug}` require `organizer-admin`, `tenant-admin`, or `tenant-user`.

Tenant-scoped application endpoints should include the `X-Tenant-Slug` header unless the path is explicitly skipped by tenant resolution.

Internal tenant administration endpoints are documented separately in [Internal Operations](#).

Tenant Catalog

Create Tenant

```
POST /api/v1/tenants
Authorization: Bearer <organizer-admin-token>
Content-Type: application/json

{
  "name": "Acme",
  "slug": "acme"
}
```

Creates a catalog tenant record with `Pending` status and returns tenant metadata. This route does not provision Keycloak groups, a default tenant admin, or a tenant database. Use `POST /api/admin/tenants/onboard` for the full onboarding workflow.

Example response:

```
{
  "id": "11111111-1111-1111-1111-111111111111",
  "name": "Acme",
  "slug": "acme",
  "databaseName": "organizer_tenant_acme",
  "createdAt": "2026-05-15T10:00:00Z"
}
```

Possible responses:

STATUS	MEANING
200 OK	Tenant catalog record was created.
401 Unauthorized	Missing or invalid bearer token.
403 Forbidden	Token does not satisfy the <code>organizer-admin</code> role policy.
409 Conflict	Duplicate tenant slug.
500 Internal Server Error	Unexpected server error. See Errors and Observability .

Get Tenant By Slug

```
GET /api/v1/tenants/acme
Authorization: Bearer <token>
```

Returns a tenant by slug, or `404 Not Found` when no tenant exists. Soft-deleted tenants are excluded.

List Tenants

```
GET /api/v1/tenants
Authorization: Bearer <token>
```

Returns all catalog tenants visible through the tenant repository. Soft-deleted tenants are excluded.

Platform Endpoints

ENDPOINT	PURPOSE
<code>/health</code>	Public health check endpoint.
<code>/openapi/v1.json</code>	OpenAPI document in development.
<code>/scalar</code>	Interactive OpenAPI/Scalar endpoint explorer in development.

OpenAPI And Scalar

When the API runs in development:

- OpenAPI JSON is available at `/openapi/v1.json`.
- Scalar is available at `/scalar`.

Use this article for behavior: routes, authorization expectations, tenant headers, response shapes, and operational meaning. Use the generated API reference only for C# type signatures.

Database Provisioning

Organizor uses one catalog database and one PostgreSQL database per tenant.

Catalog Database

`CatalogDbContext` stores tenant records in the `tenants` table.

Important constraints:

FIELD	CONSTRAINT
<code>Name</code>	Required, max length 200.
<code>Slug</code>	Required, max length 100, unique index.
<code>DatabaseName</code>	Required, max length 200.
<code>IsDeleted</code>	Required, defaults to <code>false</code> .
<code>DeletionReason</code>	Optional, max length 500.

On startup, the API checks whether the catalog database exists, creates it when needed, and applies catalog migrations.

The full tenant onboarding workflow is documented in [Internal Operations](#). Database provisioning is one part of that workflow; Keycloak tenant access is provisioned before the tenant database is created.

Tenant Database Naming

Tenant databases use:

```
organizer_tenant_{slug}
```

Example:

```
organizer_tenant_acme
```

Slugs are normalized to lowercase before tenant records are written.

PostgreSQL Requirements

The configured PostgreSQL user must be able to:

- connect to the admin `postgres` database;
- create tenant databases;
- drop tenant databases during hard deletion;
- create extensions in tenant databases.

Tenant database creation currently uses:

```
CREATE DATABASE "{databaseName}" OWNER = postgres ENCODING = 'UTF8';
```

Each tenant database is initialized with:

```
CREATE EXTENSION IF NOT EXISTS "pgcrypto";  
CREATE EXTENSION IF NOT EXISTS "citext";
```

Hard deletion uses:

```
DROP DATABASE IF EXISTS "{databaseName}" WITH (FORCE);
```

Migration Flow

`TenantMigrator` builds a tenant-specific connection string, checks pending migrations on `OrganizorDbContext`, applies them, and returns:

FIELD	MEANING
<code>Database</code>	Tenant database name.
<code>Success</code>	Whether migrations completed.
<code>AppliedMigrations</code>	Count of migrations pending before execution.
<code>Duration</code>	Migration runtime.
<code>Error</code>	Error message when migration fails.

Onboarding and Cleanup

During `POST /api/admin/tenants/onboard`, the database steps are:

1. create the tenant database named `organizor_tenant_{slug}`;
2. initialize required PostgreSQL extensions;
3. apply pending `OrganizorDbContext` migrations;
4. return success so the tenant can be marked `Active`.

If the migration result fails or onboarding throws unexpectedly, the catalog tenant is marked `Failed`.

During hard deletion, the tenant must already be soft-deleted. The hard-delete workflow drops the tenant database with `DROP DATABASE IF EXISTS ... WITH`

(FORCE) after Keycloak cleanup and then removes the catalog record.

Keycloak Setup

This document describes the Keycloak configuration for the Organizer development environment. It includes realm setup, API/UI clients, tenant groups, claim mapping, user/role setup, and the admin-client permissions used by tenant onboarding.

The local Keycloak container is expected to run over HTTPS at

`https://localhost:8443`. See [Keycloak HTTPS Setup](#) before configuring clients.

Realm Setup

- Open Keycloak Admin Console.
- Realm dropdown -> **Create Realm**.
- Name: `organizer-dev`.
- Save.

API Client (`organizer-api`)

Settings:

- Client type: OpenID Connect
- Client ID: `organizer-api`
- Name: Organizer API

Required values:

- Client authentication: **ON**
- Authorization: OFF
- Standard flow: OFF
- Direct access grants: **ON**
- Implicit flow: OFF
- Service accounts roles: **ON**

Credentials:

- Open the **Credentials** tab.

- Copy the **Client Secret**.
- Store it in development tooling that requests tokens.

The API currently validates bearer tokens only; it does not read the client secret from application configuration. The client secret is only needed by tooling or services that request tokens with the `client_credentials` flow.

The infrastructure Keycloak admin client also uses this client secret during tenant onboarding. Configure these application settings from the same Keycloak client:

```
{
  "Keycloak": {
    "Authority": "https://localhost:8443/realms/organizer-dev",
    "BaseUrl": "https://localhost:8443",
    "Realm": "organizer-dev",
    "AdminClientId": "organizer-api",
    "AdminClientSecret": "<client-secret>"
  }
}
```

For tenant onboarding and hard deletion, the `organizer-api` service account must be allowed to use the Keycloak Admin REST API. Assign the required `realm-management` client roles for:

- reading groups and users;
- creating and deleting tenant groups;
- assigning realm roles to groups;
- creating the default tenant admin user;
- resetting the default tenant admin password;
- adding users to groups;
- deleting the default tenant admin user during hard deletion.

UI Client (`organizer-ui`)

Settings:

- Client type: OpenID Connect

- Client ID: `organizor-ui`
- Name: Organizor UI

Required values:

- Client authentication: OFF
- Authorization: OFF
- Standard flow: **ON**
- Direct access grants: OFF
- Implicit flow: OFF
- Service accounts roles: OFF

Development redirect URIs:

- `https://localhost:7025/*`
- `https://localhost:7025/authentication/login-callback`
- `http://localhost:5080/*`

Web origins:

- `https://localhost:7025`
- `http://localhost:5080`

Use `*` only for quick local testing. Explicit origins are preferable because they catch redirect and CORS mistakes earlier.

Tenant Groups

Tenant onboarding creates the group structure automatically when `POST /api/admin/tenants/onboard` is used. Manual setup is only needed for bootstrap or testing.

Group structure:

- `/tenants`
- `/tenants/acme`
- `/tenants/acme/users`
- `/tenants/acme/admins`

Each tenant has:

- `/users` group
- `/admins` group

On onboarding, Organizer assigns:

- `tenant-admin` to `/tenants/{slug}/admins`;
- `tenant-user` to `/tenants/{slug}/users`.

It also creates a default tenant admin user:

- Username: `{slug}-admin`
- Email: `{slug}-admin@organizer.local`
- Temporary password: `ChangeMe123!`
- Group: `/tenants/{slug}/admins`

During hard deletion, Organizer removes the tenant group `/tenants/{slug}` and deletes the default `{slug}-admin` user when it exists.

Tenant Membership Claim Mapper

Location:

- Clients -> `organizer-api`
- Client scopes -> `organizer-api-dedicated`
- Mappers -> Create

Values:

- Name: `tenant-membership`
- Mapper type: **Group Membership**
- Token Claim Name: `tenant`
- Full group path: **ON**
- Add to ID token: ON
- Add to access token: ON
- Add to userinfo: ON

User Setup

Create these realm roles before assigning users:

- `organizor-admin`
- `tenant-admin`
- `tenant-user`

Platform admin:

- Username: `admin@organizor.dev`
- Password: `Admin123!`
- Assign realm role: `organizor-admin`
- No tenant groups assigned

Tenant admin:

- Username: `admin@acme.dev`
- Password: `Admin123!`
- Assign realm role: `tenant-admin`
- Assign group: `/tenants/acme/admins`

Tenant user:

- Username: `user@acme.dev`
- Password: `Admin123!`
- Assign realm role: `tenant-user`
- Assign group: `/tenants/acme/users`

Token Testing

Token endpoint:

- `https://localhost:8443/realms/organizor-dev/protocol/openid-connect/token`


Expected role claim examples:

```
{
  "realm_access": {
    "roles": ["organizer-admin"]
  },
  "resource_access": {
    "organizer-api": {
      "roles": ["tenant-user"]
    }
  }
}
```

Example tenant claim:

```
"tenant": ["/tenants/acme/admins"]
```

Keycloak Architecture Diagram



Keycloak HTTPS Setup

The development Keycloak container runs over HTTPS at `https://localhost:8443`. The Blazor WebAssembly portal uses this endpoint for OIDC Authorization Code Flow with PKCE, and the API uses the same realm issuer when validating bearer tokens.

Why HTTPS Is Required

- The portal runs as a browser application and should not mix HTTPS portal/API calls with HTTP identity-provider redirects.
- OIDC redirect URIs must match the portal origin exactly.
- Keycloak 24 runs with explicit hostname and HTTPS configuration when started in production mode.
- Local HTTPS keeps browser, API, and identity-provider behavior closer to production.

Certificate

The compose file mounts a PKCS#12 certificate from:

```
keycloak/certs/keycloak.p12
```

Generate a trusted local certificate with `mkcert`:

```
mkcert -install  
mkcert -pkcs12 -p12-file .\keycloak\certs\keycloak.p12 localhost
```

`mkcert` PKCS#12 files use the password `changeit`, which matches the Docker Compose configuration.

Keep generated certificates out of source control. If the certificate is missing or not trusted, Keycloak may fail to start or the browser may reject the login page.

Docker Compose

The Keycloak service uses production mode with an HTTPS keystore:

```
keycloak:
  image: quay.io/keycloak/keycloak:24.0
  command:
    - start
    - --hostname=localhost
    - --https-port=8443
    - --https-key-store-file=/opt/keycloak/conf/keycloak.p12
    - --https-key-store-password=changeit
  volumes:
    - ./keycloak/certs/keycloak.p12:/opt/keycloak/conf/keycloak.p12
  ports:
    - "8443:8443"
```

Start or restart Keycloak from the repository root:

```
docker compose down
docker compose up -d
```

Open the admin console at:

```
https://localhost:8443
```

Development admin credentials are configured in `docker-compose.yml`:


```
admin / admin
```

Browser Trust

Chrome and Edge normally trust the `mkcert` root certificate through the Windows certificate store after `mkcert -install`.

If Edge still reports `ERR_CERT_AUTHORITY_INVALID`, import the mkcert root certificate manually into Trusted Root Certification Authorities:

```
%LOCALAPPDATA%\mkcert\rootCA.pem
```

Then restart the browser.

Expected Local Endpoints

COMPONENT	URL
Keycloak	<code>https://localhost:8443</code>
Keycloak realm issuer	<code>https://localhost:8443/realms/organizor-dev</code>
Portal UI	<code>https://localhost:7025</code>
API HTTPS profile	<code>https://localhost:7184</code>

The portal and API must both use the HTTPS Keycloak authority. Tokens issued by `https://localhost:8443/realms/organizor-dev` will not validate against an API configured for the old HTTP Keycloak endpoint.

Troubleshooting

SYMPTOM	LIKELY CAUSE	FIX
Keycloak does not start	Missing <code>keycloak/certs/keycloak.p12</code>	Generate the certificate with <code>mkcert</code>
Browser rejects Keycloak	<code>mkcert</code> root CA is not trusted	Run <code>mkcert -install</code> or import the manually.
Portal login redirects fail	Keycloak client redirect URI does not include <code>https://localhost:7025/*</code>	Update the <code>organizer-ui</code> client redirect URIs.
API returns 401 for portal tokens	API <code>Keycloak:Authority</code> still points to HTTP	Set authority to <code>https://localhost:8443/realms/organizer-dev</code> .

API Authentication

Overview

This document explains how the Organizer API authenticates requests using Keycloak-issued JWT tokens.

JWT Validation

The API validates tokens using the Keycloak realm:

- Authority: `https://localhost:8443/realms/organizer-dev`
- Audience validation: disabled for the current development setup
- Token type: Bearer

The authentication middleware:

- validates the token signature;
- validates the issuer;
- validates token expiration;
- populates `HttpContext.User`.

Audience validation is intentionally disabled in code while the Keycloak client and token shape are still being finalized. Once the API has a stable audience claim, enable audience validation and document the expected value here.

Authentication Flow

1. Frontend logs in via Keycloak.
2. Keycloak issues a JWT.
3. Frontend sends `Authorization: Bearer <token>`.
4. Frontend also sends `X-Tenant-Slug: acme` for tenant-scoped routes.
5. API validates the JWT.
6. `[Authorize]` attributes enforce authentication where applied.

Service Accounts

The `organizer-api` client can use the `client_credentials` flow for internal API-to-API communication. Service account tokens are identified by the `client_id` claim:

```
"client_id": "organizer-api"
```

Service accounts bypass tenant access checks.

WhoAmI Endpoint

Example response:

```
{
  "user": "admin@acme.dev",
  "tenant": null,
  "tenantClaims": [
    "/tenants/acme/admins"
  ],
  "roles": [
    "tenant-admin",
    "tenant-user"
  ],
  "claims": [
    { "type": "sub", "value": "..." },
    { "type": "tenant", "value": "/tenants/acme/admins" },
    { "type": "role", "value": "tenant-admin" }
  ]
}
```

Error Codes

- 401 Unauthorized -> Missing or invalid token.
- 403 Forbidden -> Token is valid, but the user is not allowed.
- 400 Bad Request -> Missing or invalid tenant header on tenant-scoped routes.

Test Request

GET https://localhost:7184/api/auth/whoami

Authorization: Bearer <token>

Role-Based Authorization

Overview

The API authorizes requests with ASP.NET Core policies backed by Keycloak roles. Authentication validates the JWT first, tenant access middleware enforces tenant membership next, and endpoint authorization policies run after that.

Roles

ROLE	PURPOSE
<code>organizer-admin</code>	Platform administrator. Can manage tenants and call admin operations.
<code>tenant-admin</code>	Tenant administrator. Can use tenant-aware application endpoints and tenant catalog reads.
<code>tenant-user</code>	Tenant member. Can use shared tenant-aware application endpoints and tenant catalog reads.

JWT Role Sources

The API maps these Keycloak claim shapes to ASP.NET Core role claims:

```
{
  "realm_access": {
    "roles": ["organizer-admin"]
  },
  "resource_access": {
    "organizer-api": {
      "roles": ["tenant-user"]
    }
  }
}
```

```
}  
}
```

Only client roles under `resource_access.organizor-api.roles` are promoted. Roles for other clients, such as `account`, are ignored for API authorization.

Policies

POLICY	ACCEPTED ROLES
<code>RequireOrganizorAdminRole</code>	<code>organizor-admin</code>
<code>RequireTenantUserRole</code>	<code>organizor-admin</code> , <code>tenant-admin</code> , <code>tenant-user</code>
<code>RequireTenantAdminRole</code>	<code>organizor-admin</code> , <code>tenant-admin</code>

Use policies for new endpoints unless the endpoint is intentionally authentication-only.

```
[Authorize(Policy = AuthorizationPolicies.RequireOrganizorAdminRole)]
```

Current Endpoint Enforcement

ENDPOINT AREA	POLICY
<code>/api/admin/tenants/*</code>	<code>RequireOrganizorAdminRole</code>
<code>POST /api/v1/tenants</code>	<code>RequireOrganizorAdminRole</code>
<code>GET /api/v1/tenants</code>	<code>RequireTenantUserRole</code>
<code>GET /api/v1/tenants/{slug}</code>	<code>RequireTenantUserRole</code>

ENDPOINT AREA	POLICY
GET /api/auth/whoami	authenticated user only

Tenant Interaction

Role checks do not replace tenant checks. For tenant-scoped routes, a user must pass both:

- Tenant authorization in `TenantAccessMiddleware`.
- Endpoint role or policy authorization in ASP.NET Core.

This means a `tenant-user` token for `acme` is still denied when it sends `X-Tenant-Slug: contoso`.

Assigning Roles in Keycloak

Realm roles are assigned from the user details screen:

1. Open Keycloak Admin Console.
2. Select the `organizer-dev` realm.
3. Open Users and select the user.
4. Open Role mapping.
5. Assign one of `organizer-admin`, `tenant-admin`, or `tenant-user`.

Client roles can also be assigned under the `organizer-api` client. If client roles are used, verify they appear in `resource_access.organizer-api.roles`.

Test Matrix

SCENARIO	EXPECTED
<code>organizer-admin</code> calls <code>/api/admin/tenants</code>	Allowed

SCENARIO	EXPECTED
tenant-user calls /api/admin/tenants	403 Forbidden
tenant-admin calls GET /api/v1/tenants	Allowed
tenant-user calls GET /api/v1/tenants	Allowed
Token has no Organizer role and calls protected endpoint	403 Forbidden
Valid role with wrong tenant slug on tenant-scoped route	403 Forbidden

Tenant Authorization

Overview

Tenant-scoped API routes require both a valid JWT and an `X-Tenant-Slug` header. The API resolves the header to a catalog tenant, validates that the JWT is allowed to use that tenant, then lets controller authorization policies run.

Tenant Resolution

Tenant-scoped routes must include:

```
X-Tenant-Slug: acme
```

The tenant resolution middleware skips platform and infrastructure routes, including:

- `/api/admin`
- `/api/v1/tenants`
- `/api/auth`
- `/health`
- `/openapi`
- `/scalar`
- `/favicon`
- `/robots`

Resolution steps:

1. Middleware reads `X-Tenant-Slug`.
2. Middleware looks up the tenant in the catalog database.
3. Middleware sets `tenantContext.Current`.
4. Middleware logs tenant metadata.

JWT Tenant Claim

Tenant membership is represented by one or more `tenant` claims. The middleware accepts either direct slugs or Keycloak-style paths:

```
{  
  "tenant": ["/tenants/acme/admins", "/tenants/contoso/users"]  
}
```


The slug is extracted from the segment after `/tenants/`. For `/tenants/acme/admins`, the effective tenant slug is `acme`.

Enforcement Rules

For tenant-scoped routes:

- Missing or invalid `Authorization` returns `401 Unauthorized` when the endpoint requires `[Authorize]`.
- Missing `X-Tenant-Slug` returns `400 Bad Request`.
- Unknown `X-Tenant-Slug` returns `404 Not Found`.
- A JWT with tenant claims must include the same slug as `X-Tenant-Slug`.
- A JWT tenant/header mismatch returns `403 Forbidden`.
- A JWT without tenant claims is treated as a platform superadmin token and bypasses tenant membership checks.
- The `organizer-api` service account, identified by `client_id = organizer-api`, bypasses tenant membership checks.
- Matching tenant JWTs are still checked through `ITenantAccessService.UserHasAccessAsync(userId, tenantId)`.
- If `ITenantAccessService` denies access, the API returns `403 Forbidden`.

Middleware Chain



HTTP Test Matrix

SCENARIO	AUTHORIZATION	X-TENANT-SLUG	EXPECTED
Tenant token for <code>acme</code> calls <code>acme</code>	tenant JWT	<code>acme</code>	Allowed if <code>ITenantAccessService</code> allows

SCENARIO	AUTHORIZATION	X-TENANT-SLUG	EXPECTED
Tenant token for <code>acme</code> calls <code>contoso</code>	tenant JWT	<code>contoso</code>	403 Forbidden
Superadmin token has no tenant claim	superadmin JWT	any valid slug	Allowed
Service account token	<code>client_id = organizer-api</code>	any valid slug	Allowed
Missing tenant header on tenant route	valid JWT	omitted	400 Bad Request
Unknown tenant header on tenant route	valid JWT	unknown slug	404 Not Found
Missing token on authorized route	omitted	valid slug	401 Unauthorized
<code>ITenantAccessService</code> denies matching user	tenant JWT	matching slug	403 Forbidden

Sample Requests

Tenant-scoped request:

```
GET http://localhost:5100/api/some-tenant-scoped-route
Authorization: Bearer <tenant-token>
X-Tenant-Slug: acme
Accept: application/json
```

Cross-tenant denial:

```
GET http://localhost:5100/api/some-tenant-scoped-route
Authorization: Bearer <token-with-tenant-acme>
X-Tenant-Slug: contoso
Accept: application/json
```

Superadmin bypass:

```
GET http://localhost:5100/api/some-tenant-scoped-route
Authorization: Bearer <token-without-tenant-claim>
X-Tenant-Slug: acme
Accept: application/json
```

Configuration

Organizor reads standard ASP.NET Core configuration from `appsettings.json`, environment-specific files, user secrets, and environment variables.

Catalog Connection String

`CatalogDbContext` expects a connection string named `Catalog`.

Example shape:

```
{
  "ConnectionStrings": {
    "Catalog":
      "Host=localhost;Port=5432;Database=organizor_catalog;Username=postgres;Password=postgres"
  }
}
```

Tenant PostgreSQL Settings

`ConnectionStringBuilder` builds tenant and admin connection strings from the `Postgres` section.

```
{
  "Postgres": {
    "Host": "localhost",
    "Port": "5432",
    "User": "postgres",
    "Password": "postgres"
  }
}
```

The admin connection uses the `postgres` database. Tenant connections use the tenant database name stored in the catalog.

Keycloak

The API requires Keycloak settings for two separate concerns:

- JWT validation uses `Keycloak:Authority`.
- Tenant onboarding uses the Keycloak admin client settings to create tenant groups, assign roles, and create the default tenant admin user.

Example development shape:

```
{
  "Keycloak": {
    "Authority": "https://localhost:8443/realms/organizer-dev",
    "BaseUrl": "https://localhost:8443",
    "Realm": "organizer-dev",
    "AdminClientId": "organizer-api",
    "AdminClientSecret": "<client-secret>"
  }
}
```

`Authority` must match the token issuer exactly. The local Keycloak container runs at `https://localhost:8443`, so tokens from the Blazor portal will have issuer `https://localhost:8443/realms/organizer-dev`.

Store client secrets in user secrets, environment variables, or deployment secrets rather than committing them to source.

Portal UI

The Blazor WebAssembly portal uses Keycloak for OIDC login and calls the API with bearer tokens.

Current local development endpoints:

SETTING	VALUE
Portal URL	<code>https://localhost:7025</code>
Keycloak authority	<code>https://localhost:8443/realms/organizer-dev</code>
Keycloak client ID	<code>organizer-ui</code>
Login callback	<code>https://localhost:7025/authentication/login-callback</code>
API base URL	<code>https://localhost:7184</code>

These values must stay aligned with the `organizer-ui` client redirect URIs and web origins in Keycloak.

Quartz

Quartz uses the `Catalog` connection string for its persistent store. The same catalog database stores tenant records and Quartz scheduler tables.

The API registration configures:

- PostgreSQL-backed Quartz persistence;
- Newtonsoft JSON serialization for persisted job data;
- clustering support;
- hosted service startup for Quartz background processing.

Tenant job scheduling is not enabled on application startup yet. `TenantJobScheduler` is available for future real tenant jobs, but the startup scheduling block is currently commented out until those jobs exist.

Logging

Serilog is configured in `appsettings.json`.

Current sinks:

- console;
- rolling file logs under `logs/log-.txt`.

Log output includes tenant and request correlation properties when available:

- `Id`;
- `Slug`;
- `DatabaseName`;
- `CorrelationId`.

CORS

The API selects a CORS policy by environment:

- `DevCors` in development allows any origin, header, and method.
- `ProdCors` outside development must be configured with explicit allowed origins before browser clients can call the API.

The current production policy has no origins configured. Treat that as a deployment checklist item, not a complete production setting.

OpenAPI and Scalar

OpenAPI and Scalar endpoints are mapped only in development. This keeps the production surface smaller while retaining local API exploration during development.

Localization

Organizor provides multilingual support for error responses using a simple, predictable, API-friendly localization pipeline.

Supported Languages

Organizor currently supports:

- `en` - English (fallback)
- `nl` - Dutch

Additional languages can be added by creating new resource files in the `Code7Dev.Organizor.Api/Resources` folder.

How Localization Works

Localization is driven by the standard `Accept-Language` HTTP header.

Example:

```
Accept-Language: nl
```

The API resolves the culture for the request and uses it to translate error messages. If a translation is missing, the system falls back to English (`en`).

Key Principles

- Application services return error codes only, such as `TENANT_NOT_FOUND`.
- The API middleware maps those codes to localized resource strings.
- No hardcoded user-facing messages exist in the domain or application layers.
- Localization is deterministic and client-controlled.

Culture Resolution

Organizor uses the following resolution order:

- `Accept-Language` header.
- Fallback to English (`en`).

This keeps behavior predictable and client-controlled.

Error Code Translation

Each error code corresponds to a resource key.

Examples:

- `TENANT_NOT_FOUND`
- `TENANT_ALREADY_EXISTS`
- `UNEXPECTED_ERROR`

These keys exist in:

- `Code7Dev.Organizor.Api/Resources/Shared.en.resx`
- `Code7Dev.Organizor.Api/Resources/Shared.nl.resx`

The middleware retrieves the localized string and injects it into the RFC 7807 problem response.

Example Request and Response

Request:

```
GET /api/v1/tenants/unknown
Authorization: Bearer <token>
Accept-Language: nl
```

Response:

```
{
  "type": "https://httpstatuses.com/404",
  "title": "Tenant niet gevonden",
  "status": 404,
  "error": "TENANT_NOT_FOUND",
  "correlationId": "abc123"
}
```

The error code remains stable and language-independent. The title is localized based on the request culture.

Adding New Translations

To add a new language:

1. Create a new `.resx` file, for example `Shared.fr.resx`.
2. Add the same error keys as in the English file.
3. Provide translated values.
4. Register the culture in `AddApiLocalization`.
5. Restart the API.

Errors and Observability

Correlation IDs

Every request passes through `CorrelationIdMiddleware`.

Clients can provide a correlation ID:

```
X-Correlation-ID: request-123
```

If the header is missing, the API generates a GUID. The final value is returned in the response header:

```
X-Correlation-ID: 2ad71e7a-13cb-4ef8-a4c7-f3a37ad9dc71
```

The same value is pushed into Serilog context as `CorrelationId`.

Error Shape

Unhandled exceptions are returned as RFC 7807-style problem details:

```
{
  "type": "https://httpstatuses.com/500",
  "title": "An unexpected error occurred.",
  "status": 500,
  "detail": "Exception message",
  "instance": "/api/v1/tenants",
  "correlationId": "2ad71e7a-13cb-4ef8-a4c7-f3a37ad9dc71"
}
```

The response content type is:

```
application/problem+json
```

NOTE

The current middleware includes exception messages in `detail`. Treat that as useful during development, but review it before exposing production environments.

Tenant Resolution Errors

Tenant-scoped requests require:

```
X-Tenant-Slug: acme
```

Missing tenant slug returns `400 Bad Request` with a plain text response. Unknown tenant slug returns `404 Not Found` with a plain text response.

Log Context

Serilog output is configured to include:

PROPERTY

```
CorrelationId
```

```
Id
```

```
Slug
```

```
DatabaseName
```

SOURCE

Request header or generated GUID.

Resolved tenant ID.

Resolved tenant slug.

Tenant database selection when available.

PROPERTY`SourceContext`**SOURCE**

Logger source in file logs.

Internal Operations

This page documents internal routes and workflows for developers and operators.

Onboard Tenant

```
POST /api/admin/tenants/onboard
Authorization: Bearer <organizor-admin-token>
Content-Type: application/json

{
  "name": "Acme",
  "slug": "acme"
}
```

The onboarding flow:

1. normalizes the slug to lowercase;
2. creates a catalog tenant with `Pending` status;
3. provisions Keycloak tenant groups under `/tenants/{slug}`;
4. assigns `tenant-admin` to `/tenants/{slug}/admins` and `tenant-user` to `/tenants/{slug}/users`;
5. creates a default tenant admin user named `{slug}-admin` with a temporary password of `ChangeMe123!`;
6. creates the tenant database using `organizor_tenant_{slug}`;
7. initializes PostgreSQL extensions;
8. applies tenant migrations;
9. marks the tenant `Active` on success or `Failed` on provisioning failure.

Example response:

```
{
  "id": "11111111-1111-1111-1111-111111111111",
  "name": "Acme",
```

```
"slug": "acme",  
"databaseName": "organizer_tenant_acme"  
}
```

Upgrade Tenant

```
POST /api/admin/tenants/{id}/upgrade  
Authorization: Bearer <organizer-admin-token>
```

Runs pending migrations for the tenant database.

Example response:

```
{  
  "database": "organizer_tenant_acme",  
  "success": true,  
  "appliedMigrations": 2,  
  "duration": "00:00:01.2340000",  
  "error": null  
}
```

Soft Delete Tenant

```
DELETE /api/admin/tenants/{id}  
Authorization: Bearer <organizer-admin-token>  
Content-Type: application/json
```

```
{  
  "reason": "Customer cancellation"  
}
```

Soft deletion marks the tenant as deleted, stores deletion metadata, and sets status to `Deleted`. The tenant database is not dropped.

Hard Delete Tenant

```
POST /api/admin/tenants/{id}/hard-delete
Authorization: Bearer <organizer-admin-token>
```

Hard deletion requires the tenant to already be soft-deleted. It:

1. deletes the default Keycloak admin user named `{slug}-admin` when it exists;
2. deletes the Keycloak tenant group `/tenants/{slug}` when it exists;
3. drops the tenant database;
4. removes the catalog record.

Keycloak cleanup tolerates missing groups or users so a partially-provisioned tenant can still be cleaned up.

Scheduled Tenant Jobs

Organizer is wired for Quartz recurring background work, but tenant job scheduling is not currently enabled on startup. `Program.cs` contains a commented-out scheduling block for future use.

The scheduler:

1. loads all tenants from the catalog database;
2. creates a durable `SyncTenantJob` with job key `sync-{tenantId}` in the `tenant-jobs` group;
3. stores `TenantId` and `TenantSlug` in the Quartz job data map;
4. creates a trigger named `sync-{tenantId}-trigger` in the `tenant-triggers` group;
5. schedules the job when it is new, or replaces and reschedules it when it already exists.

Current trigger cadence:

```
0/10 * * * * ?
```

That Quartz cron expression would run the tenant synchronization job every 10 seconds when scheduling is enabled.

`SyncTenantJob` reads the tenant data from the job data map, sets `ITenantContext`, and then runs tenant-scoped work through `OrganizorDbContext`. The current implementation logs execution and contains placeholder synchronization work.

Quartz persistence is stored in the catalog database and uses the PostgreSQL tables added by the `AddQuartzTables` migration. The API configures Quartz with the `Catalog` connection string, JSON serialization, and clustering enabled.

Documentation Deployment

The repository contains a GitHub Actions workflow at `.github/workflows/docfx-deploy.yml`.

On pushes to `master`, it:

1. checks out this repository;
2. installs DocFX;
3. builds `docs/docfx.json`;
4. checks out the public documentation repository;
5. copies `docs/_site` into that repository;
6. commits and pushes the generated documentation.

The workflow uses the `DOCS_DEPLOY_KEY` secret to push to the public docs repository.

Sitemap and Crawlers

DocFX generates `docs/_site/sitemap.xml` from the `build.sitemap.baseUrl` value in `docs/docfx.json`.

The documentation source includes `robots.txt`, which is copied into the generated site and points crawlers to the sitemap.