Use case	Registration	
Release (id)	UC1, v0.1, 19/04/2026	
Context of Use	User authentication and account management.	
Scope	Let an anonymous user create a new account.	
Level	Primary task	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to create an account
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be logged out.	
Minimal Guarantees	No duplicated or unsecure account is created.	
Success Guarantees	The anonymous user successfully created an account and is logged in.	
Trigger	The anonymous user selects “register”.	
Description	**Step**	**Action**
	1	The anonymous user selects the functionality “register”.
	2	The system asks the user to insert username and email.
	3	The user inserts the required data.
	4	The system checks whether an account with at least one between username and email already exists.
	5	The system asks the user to insert the password twice.
	6	The user inserts the required data.

	7	The system checks whether the password satisfies the security requirements and if the two passwords coincide.
	8	The system asks the user's consent for personal data processing.
	9	The anonymous user accepts the personal data processing.
	10	The system saves the data in the account archive.
	11	The system notifies the user of successful registration with an email.
	12	The system switches to the authenticated user functionalities.
Extension	**Step**	**Other action**
	4a	Invalid username or email: UC1.1
	7a	Invalid password: UC1.2
Technology & data Variations	None	

Alternative flow	Registration: Invalid username or email	
Release (id)	UC1.1, v0.2, 25/04/2026	
Context of Use	User authentication and account management.	
Scope	The system alerts the anonymous user that they have inserted an invalid username or email.	
Level	Subfunction	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to create an account
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted an already existing username or email.	
Minimal Guarantees	No duplicated account is created.	
Success Guarantees	None	
Trigger	UC1	
Description	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid username or email.
	2	The sequence of events starts at step 2 of the main flow (UC1).
Technology & data Variations	None	

Alternative flow	Registration: Invalid password	
Release (id)	UC1.2, v0.2, 25/04/2026	
Context of Use	User authentication and account management.	
Scope	The system alerts the anonymous user that they have inserted an invalid password.	
Level	Subfunction	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to create an account
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted a password that does not satisfy the security requirements or the two passwords do not coincide.	
Minimal Guarantees	No unsecure account is created.	
Success Guarantees	None	
Trigger	UC1	
Description (Main Success Scenario)	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid password, specifying the problem.
	2	The sequence of events starts at step 5 of the main flow (UC1).
Technology & data Variations	None	

Use case	Account deletion	
Release (id)	UC2, v0.1, 19/04/2026	
Context of Use	Account management.	
Scope	Let an authenticated user delete her account.	
Level	Primary task	
Primary actor	Passenger or train company	
Stakeholder & interest	**Stakeholder**	**Interest**
	Passenger	Wants to delete her account
	Train company	Wants to delete its account
	System	Managse the user interface, the database and their interactions
Preconditions	The user must be logged in.	
Minimal Guarantees	None	
Success Guarantees	The user successfully deleted her account and is logged out.	
Trigger	The user selects “delete account”.	
Description	**Step**	**Action**
	1	The anonymous user selects the functionality “delete account”.
	2	The system removes the data in the account archive.
	3	The system notifies the user of successful deletion with an email.
	4	The system switches to the unauthenticated user functionalities.
Extension	**Step**	**Other action**
	-	-

Technology & data Variations	None

Use case	Account data view	
Release (id)	UC3, v0.2, 25/04/2026	
Context of Use	Account management.	
Scope	Let an authenticated user view her account's data.	
Level	Primary task	
Primary actor	Authenticated user (passenger, train company or network manager)	
Stakeholder & interest	**Stakeholder**	**Interest**
	Authenticated user	Wants to view her account's data
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be logged in.	
Minimal Guarantees	None	
Success Guarantees	The user successfully views her account's data.	
Trigger	The anonymous user selects "view account's data".	
Description	**Step**	**Action**
	1	The anonymous user selects the functionality "view account's data".
	2	The system shows the data saved in the account archive, that is username and email.
Extension	**Step**	**Other action**
	-	-
Technology & data Variations	None	

Use case	Account data change	
Release (id)	UC4, v0.2, 25/04/2026	
Context of Use	Account management.	
Scope	Let an authenticated user change her account's data.	
Level	Primary task	
Primary actor	Authenticated user (passenger, train company or network manager)	
Stakeholder & interest	**Stakeholder**	**Interest**
	Authenticated user	Wants to change her account's data
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be logged in.	
Minimal Guarantees	No duplicated or unsecure account is created with a modification.	
Success Guarantees	The authenticated user successfully changed her account's data.	
Trigger	The authenticated user selects "change data".	
Description	**Step**	**Action**
	1	The authenticated user selects the functionality "change data".
	2	The system asks the user which data to modify.
	3	If the user selects username
	3.1	The system asks the user to insert the new username.
	3.2	The user inserts the new username.
	3.3	The system checks whether an account with the same username already exists.

	4	If the user selects email
	4.1	The system asks the user to insert the new email.
	4.2	The user inserts the new email.
	4.3	The system checks whether an account with the same email already exists.
	5	If the user selects password
	5.1	The system asks the user to insert the password twice.
	5.2	The user inserts the required data.
	5.3	The system checks whether the password satisfies the security requirements and if the two passwords coincide.
	6	The system saves the data in the account archive.
	7	The system notifies the user of successful data change with an email.
Extension	**Step**	**Other action**
	3.3a	Invalid username or email: UC4.1
	4.3a	Invalid email: UC4.2
	5.3a	Invalid password: UC4.3
Technology & data Variations	None	

Alternative flow	Account data change: Invalid username	
Release (id)	UC4.1, v0.2, 25/04/2026	
Context of Use	Account management.	
Scope	The system alerts the authenticated user that they have inserted an invalid username.	
Level	Subfunction	
Primary actor	Authenticated user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Authenticated user	Wants to change username
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted an already existing username.	
Minimal Guarantees	No duplicated account is created.	
Success Guarantees	None	
Trigger	UC4	
Description	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid username.
	2	The sequence of events starts at step 3.1 of the main flow (UC4).
Technology & data Variations	None	

Alternative flow	Account data change: Invalid email	
Release (id)	UC4.2, v0.2, 25/04/2026	
Context of Use	Account management.	
Scope	The system alerts the authenticated user that they have inserted an invalid email.	
Level	Subfunction	
Primary actor	Authenticated user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Authenticated user	Wants to change email
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted an already existing email.	
Minimal Guarantees	No duplicated account is created.	
Success Guarantees	None	
Trigger	UC4	
Description	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid email.
	2	The sequence of events starts at step 4.1 of the main flow (UC4).
Technology & data Variations	None	

Alternative flow	Registration: Invalid password	
Release (id)	UC4.3, v0.2, 25/04/2026	
Context of Use	Account management.	
Scope	The system alerts the authenticated user that they have inserted an invalid password.	
Level	Subfunction	
Primary actor	Authenticated user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Authenticated user	Wants to change password
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted a password that does not satisfy the security requirements or the two passwords do not coincide.	
Minimal Guarantees	No unsecure account is created.	
Success Guarantees	None	
Trigger	UC4	
Description (Main Success Scenario)	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid password, specifying the problem.
	2	The sequence of events starts at step 5.1 of the main flow (UC4).
Technology & data Variations	None	

Use case	Reset password	
Release (id)	UC5, v0.1, 25/04/2026	
Context of Use	Account management.	
Scope	Let an anonymous user reset the password.	
Level	Primary task	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to reset the password
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be logged out.	
Minimal Guarantees	No unsecure account is created with a modification. No user can change the password of another user.	
Success Guarantees	The anonymous user successfully changed the password.	
Trigger	The anonymous user selects “forgot password”.	
Description	**Step**	**Action**
	1	The anonymous user selects the functionality “forgot password”.
	2	The system asks the user to insert the email associated to her account.
	3	The user inserts the email.
	4	The system checks if the email is associated to an existing account.
	5	The system creates a random identifier.
	6	The system sends the identifier to the email.
	7	The system asks the user to insert the identifier it sent.

	8	The user inserts the identifier.
	9	The system checks whether the identifier is correct.
	10	The system asks the user to insert the password twice.
	11	The user inserts the required data.
	12	The system checks whether the password satisfies the security requirements and if the two passwords coincide.
	13	The system saves the data in the account archive.
	14	The system notifies the user of successful password change with an email.
Extension	**Step**	**Other action**
	4a	Invalid email: UC5.1
	9a	Invalid identifier: UC5.2
	12a	Invalid password: UC5.3
Technology & data Variations	None	

Alternative flow	Reset password: Invalid email	
Release (id)	UC5.1, v0.1, 25/04/2026	
Context of Use	Account management.	
Scope	The system alerts the authenticated user that they have inserted an invalid email.	
Level	Subfunction	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to reset password
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted an email that does not correspond to any existing account.	
Minimal Guarantees	None	
Success Guarantees	None	
Trigger	UC5	
Description	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid email.
	2	The sequence of events starts at step 2 of the main flow (UC5).
Technology & data Variations	None	

Alternative flow	Reset password: Invalid identifier	
Release (id)	UC5.2, v0.1, 25/04/2026	
Context of Use	Account management.	
Scope	The system alerts the authenticated user that they have inserted an invalid identifier.	
Level	Subfunction	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to reset password
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted an identifier that does not correspond to the one created by the system.	
Minimal Guarantees	None	
Success Guarantees	None	
Trigger	UC5	
Description	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid identifier.
	2	The sequence of events starts at step 9 of the main flow (UC5).
Technology & data Variations	None	

Alternative flow	Reset: Invalid password	
Release (id)	UC5.3, v0.1, 25/04/2026	
Context of Use	Account management.	
Scope	The system alerts the anonymous user that they have inserted an invalid password.	
Level	Subfunction	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to reset password
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted a password that does not satisfy the security requirements or the two passwords do not coincide.	
Minimal Guarantees	No unsecure password is created.	
Success Guarantees	None	
Trigger	UC5	
Description (Main Success Scenario)	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid password, specifying the problem.
	2	The sequence of events starts at step 12 of the main flow (UC5).
Technology & data Variations	None	

Use case	Login	
Release (id)	UC6, v0.1, 20/04/2026	
Context of Use	User authentication.	
Scope	Let an anonymous user login.	
Level	Primary task	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to login
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be logged out.	
Minimal Guarantees	No user login in an account they have no authorization for.	
Success Guarantees	The anonymous user is logged in her account.	
Trigger	The anonymous user selects “login”.	
Description	**Step**	**Action**
	1	The anonymous user selects the functionality “login”.
	2	The system asks the user to insert username and password.
	3	The user inserts the required data.
	4	The system checks whether both the username and password correspond to an existing account.
	5	The system switches to the authenticated user functionalities.
Extension	**Step**	**Other action**
	4a	Invalid username or password: UC5.1

Technology & data Variations	None

Alternative flow	Login: Invalid username or password	
Release (id)	UC6.1, v0.2, 25/04/2026	
Context of Use	User authentication.	
Scope	The system alerts the anonymous user that they have inserted an invalid username or password.	
Level	Subfunction	
Primary actor	Anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user	Wants to login
	System	Manages the user interface, the database and their interactions
Preconditions	The user inserted a pair of username and password that does not correspond to any existing account	
Minimal Guarantees	No user login in an account they have no authorization for.	
Success Guarantees	None	
Trigger	UC5	
Description (Main Success Scenario)	**Step**	**Action**
	1	The system alerts the user that has inserted an invalid username or password, specifying the problem.
	2	The sequence of events starts at step 2 of the main flow (UC5).
Technology & data Variations	None	

Use case	Logout	
Release (id)	UC7, v0.1, 20/04/2026	
Context of Use	User authentication.	
Scope	Let an authenticated user logout.	
Level	Primary task	
Primary actor	Authenticated user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Authenticated user	Wants to logout
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be logged in.	
Minimal Guarantees	None	
Success Guarantees	The authenticated user is logged out.	
Trigger	The anonymous user selects “logout”.	
Description	**Step**	**Action**
	1	The anonymous user selects the functionality “logout”.
	5	The system switches to the anonymous user functionalities.
Extension	**Step**	**Other action**
	-	None
Technology & data Variations	None	

Use case	Ticket display	
Release (id)	UC8, v0.1, 21/04/2026	
Context of Use	Ticketing management.	
Scope	Let a user view the details of a ticket.	
Level	Primary task	
Primary actor	Authenticated user (passenger, train company or network manager) or anonymous user	
Stakeholder & interest	**Stakeholder**	**Interest**
	Authenticated user	Wants to view tickets' details
	Anonymous user	Wants to view tickets' details
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be in an interface where a ticket is displayed. Magari da ultra-specificare gli include Arrivi da: path, train, station	
Minimal Guarantees	None	
Success Guarantees	The user is in an interface displaying the ticket's details.	
Trigger	The user selects "view tickets' details".	
Description	**Step**	**Action**
	1	The authenticated user selects the functionality "view tickets' details".
	2	The system displays the ticket's details.
Extension	**Step**	**Other action**
	-	None
Technology & data Variations	None	

Use case	Ticket purchase	
Release (id)	UC9, v0.2, 25/04/2026	
Context of Use	Ticketing management.	
Scope	Enable a passenger to purchase a ticket.	
Level	Primary task	
Primary actor	Passenger	
Stakeholder & interest	**Stakeholder**	**Interest**
	Passenger	Wants to buy a ticket
	Payment gateway	Manages transaction
	System	Manages the user interface, the database and their interactions
Preconditions	The passenger must be logged in. The passenger must be in an interface displaying the ticket's details.	
Minimal Guarantees	The passenger who cannot pay does not purchase any ticket.	
Success Guarantees	The passenger successfully purchased a ticket.	
Trigger	The passenger selects "Buy ticket".	
Description	**Step**	**Action**
	1	The passenger selects the functionality "Buy ticket".
	2	The system sends a transaction request to the payment gateway.
	3	The payment gateway manages the transaction.
	4	The payment gateway sends the transaction's status to the system.
	5	If the transaction is not successful

	5.1	The system alerts the passenger about the failed transaction.
	6	Otherwise
	6.1	The system alerts the passenger about the completed transaction.
	6.2	The system notifies the passenger of successful purchase with an email.
	6.3	The system saves the ticket in the account archive.
Extension	**Step**	**Other action**
	-	None
Technology & data Variations	None	

Use case	Ticket cancellation	
Release (id)	UC10, v0.1, 21/04/2026	
Context of Use	Ticketing management.	
Scope	Enable a passenger to cancel a purchased ticket.	
Level	Primary task	
Primary actor	Passenger	
Stakeholder & interest	**Stakeholder**	**Interest**
	Passenger	Wants to buy a ticket
	Payment gateway	Manages transaction
	System	Manages the user interface, the database and their interactions
Preconditions	The passenger must be logged in. The passenger must be in an interface displaying the ticket's details. The passenger must have already purchased the ticket.	
Minimal Guarantees	The passenger does not cancel any ticket they have not purchased.	
Success Guarantees	The passenger successfully cancelled a purchased ticket.	
Trigger	The passenger selects "Cancel ticket".	
Description	**Step**	**Action**
	1	The passenger selects the functionality "Cancel ticket".
	2	The system sends a transaction request to the payment gateway.
	3	The payment gateway manages the transaction.
	4	The payment gateway sends the transaction's status to the system.
	5	If the transaction is not successful

	5.1	The system alerts the passenger about the failed transaction.
	6	Otherwise
	6.1	The system alerts the passenger about the completed transaction.
	6.2	The system notifies the passenger of successful purchase with an email.
	6.3	The system saves the ticket's cancellation information in the account archive.
Extension	**Step**	**Other action**
	-	None
Technology & data Variations	None	

Use case	Ticket history	
Release (id)	UC11, v0.1, 21/04/2026	
Context of Use	Ticketing management.	
Scope	Enable a passenger to view her tickets' history, both purchased and cancelled.	
Level	Primary task	
Primary actor	Passenger	
Stakeholder & interest	**Stakeholder**	**Interest**
	Passenger	Wants to view tickets' history
	System	Manages the user interface, the database and their interactions
Preconditions	The passenger must be logged in.	
Minimal Guarantees	None	
Success Guarantees	The passenger successfully view tickets' history.	
Trigger	The passenger selects "Tickets' history".	
Description	**Step**	**Action**
	1	The passenger selects the functionality "Tickets' history".
	2	The system shows the list of tickets purchased and cancelled by that passenger.
Extension	**Step**	**Other action**
	-	None
Technology & data Variations	None	

Use case	Find Path	
Release (id)	UC12, v0.1, 25/04/2026	
Context of Use	Path finding	
Scope	Let an anonymous user or passenger find a path between two stations	
Level	Primary task	
Primary actor	Anonymous user OR Passenger	
Stakeholder & interest	**Stakeholder**	**Interest**
	Anonymous user or Passenger	Find a path
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be either logged out or logged in as a Passenger	
Minimal Guarantees	No impossible path is proposed	
Success Guarantees	The user has a suitable path and can directly select other operations for it.	
Trigger	The user selects “find a path”.	
Description	**Step**	**Action**
	1	The user selects the functionality “find a path”.
	2	The system asks the user to insert a Departing and Arriving station
	3	The user inserts all the requested data.
	4	The system ask the user an Departure or Arrival time
	5	The user provides any of the requested data, possibly confirming zero

	6	The system checks whether at least one path along the mesh between the two stations exists
	7	The system computes whether one or the intersection of multiple service lines (referred to as candidate paths) connects the stations
	8	The system filters out all candidate paths that do not respect Departure and Arrival times, if provided
	9	The system presents the user an option to change path-sorting algorithm from a default option
	10	The system uses the path-sorting algorithm to provide the top-ranking paths computed at step 8
	11	The user selects one path
	12	The system presents to the user all path-specific actions regarding that path (UC 12.1)
Extension	**Step**	**Other action**
	3a	If the user does not insert sufficient data (leaves arrival or departure station blank), display “no arrival/departure station” error and return to step 2
	5a	If the user inserts zero data, default to “Departure” as current time, proceed normally
	6a	If no path is found, produce “Stations disconnected” error and return to step 2
	7a	If no candidate paths are found, produce “No path available” error and return to step 2
	8a	If no candidate paths remain after the filter, display “Too strict Arrival/Departure” error and return to step 4
	9-10a	If the user changes sorting algorithm, the newly selected one is used to repeat from step 8

	9-10b	If two or more paths score equally in selected sorting algorithm, use all other sorting algorithms in a pre-determined order as tie-breakers, and failing that, assign order among them randomly. Proceed as normal
Technology & data Variations	If user is not a logged-in Passenger, ticket actions for the path are displayed but marked as unavailable	

Use case	Purchase Tickets in path	
Release (id)	UC12.1, v0.1, 28/04/2026	
Context of Use	Path finding, Ticket Purchase	
Scope	Let a Passenger directly purchase tickets involved in path	
Level	Subfunction	
Primary actor	Passenger	
Stakeholder & interest	**Stakeholder**	**Interest**
	Passenger	Purchase tickets
	Payment Gateway	Process transaction
	System	Manages the user interface, the database and their interactions
Preconditions	The user must be either logged in as a Passenger	
Minimal Guarantees	No unnecessary tickets are proposed	
Success Guarantees	The user purchased each ticket	
Trigger	The user selects “Tickets” at step 13 of UC12	
Description	**Step**	**Action**
	1	The Passenger selects “Tickets”
	2	The system computes the cheapest set of tickets that cover transit in all trains of the path for the duration of the path itself
	3	All tickets already owned by the passenger are marked as “Owned” on the list.
	4	The system provides such list to the user, along with the option to include(“UC8 Ticket Display”) for each. If all tickets are marked as “Owned”, jump to step 6

	5	Upon UC8 completion (both with purchase or not) in step 4, return to step 3.
	6	The system displays a “All tickets owned!” message Return to UC12 Step 3, marking “Tickets” option as complete
Extension	**Step**	**Other action**
	2a	If no set of tickets exist, produce “Ticketing Impossible” error, return to UC12 step 13, marking “Tickets” option as error
	4a	If a well-formed UC8 option for a ticket cannot be made, and it is not already marked “Owned”, provide “Invalid Ticket” error and mark that option as error. Continue normally
Technology & data Variations	None	

Use case	View Info	
Release (id)	UC13, v0.1, 28/04/2026	
Context of Use	Info Display	
Scope	Let any user view information of trains and stations	
Level	Subfunction	
Primary actor	User	
Stakeholder & interest	**Stakeholder**	**Interest**
	User	View detailed information
	System	Manages the user interface, the database and their interactions
Preconditions	None	
Minimal Guarantees	None	
Success Guarantees	The user views the train service's or station's data	
Trigger	The user selects an abbreviated form of station or train service information	
Description	**Step**	**Action**
	1	The Passenger selects the abbreaviated information
	2A	The system displays the station's details
	3A	The system displays an abbreviated form of train information for all trains passing through the station
	4A	If the user is a Passenger, the system also computes and displays options for tickets departing from the station
	2B	The system displays the train's details

	3B	The system displays an abbreviated form of station information for all stations the train passes through
	4B	If the user is a Passenger, it displays options for tickets for the train
	5	The user may select any abbreviated information to expand into another UC13 View Information
	6	Passengers may select displayed tickets to expand into U8 Ticket Display
Extension	**Step**	**Other action**
		None
Technology & data Variations	If a the information belongs to a station, the path A is chosen. Otherwise, if the information belongs to a train service, path B is chosen.	

Use case	Search Info	
Release (id)	UC14, v0.1, 28/04/2026	
Context of Use	Info Display	
Scope	Let any user find station by name or Train service by ID	
Level	Primary Task	
Primary actor	User	
Stakeholder & interest	**Stakeholder**	**Interest**
	User	Find information by query
	System	Manages the user interface, the database and their interactions
Preconditions	None	
Minimal Guarantees	None	
Success Guarantees	The User is given a list of matching results, or is warned that there are no matches otherwise	
Trigger	User selects “Search”	
	Step	**Action**
	1	The user selects “Search”
	2	The system asks the user Station name or train ID for the query
	3	The user provides a string
	4	The system matches that string agains all known names of stations and train service IDs
	5	For all matching stations/trains, a reduced set of their information is prepared and appended to a return list
	6	The system provides the user the return list

	7	The user may select the abbrevited information to expand to a full UC13 Info View
Extension	**Step**	**Other action**
	4a	If no name matches the string, produce “No match” error and return to step 2
Technology & data Variations	None	

Use case	Show Map	
Release (id)	UC15, v0.1, 28/04/2026	
Context of Use	Info Display	
Scope	Let any user see the stations and their connections	
Level	Primary Task	
Primary actor	User	
Stakeholder & interest	**Stakeholder**	**Interest**
	User	See topology
	System	Manages the user interface, the database and their interactions
Preconditions	None	
Minimal Guarantees	None	
Success Guarantees	The User is able to see stations distributed according to the topology of the network, and select one to expand into UC13	
Trigger	User selects “Show Map”	
Description	**Step**	**Action**
	1	The user selects “Show Map”
	2	The system displays the topological map
	3	If the user selects a station, initiate UC13 for that station
Extension	**Step**	**Other action**
	4a	If no identifier matches the string, produce “No match” error and return to step 2
Technology & data Variations	None	

Use case	**Insert Station Data**	
Release (id)	UC17, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the System provide a standardised way to insert a Station's data	
Level	Subfunction	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to insert Station's Data
	System	Manages the user interface, the database and their interactions
Preconditions	None	
Minimal Guarantees	No invalid Station is returned to the calling subsystem	
Success Guarantees	A valid Station is returned to the calling subsystem	
Trigger	Another subsystem includes this use case	
Description	**Step**	**Action**

	1	The system asks the user to insert:
		• The Station's name
		• The Station's coordinates
		• The Station's platforms, including:
		  ○ their locally unique identifier
		  ▪ e.g. "1" or "1-East"

	2	The user inserts the requested data.
	3	The user submits the data
	4	The created station is returned to the calling subsystem
Extensions	**Step**	**Alternate Action**

	3a	If any of the following checks fail:
		• The Station's name must be unique
		  ○ Also amongst Junction Names
		• All platforms identifiers must be unique
		  ○ Within a single station

	3a.1	Display an error

	3a.2	Return to step 1
Technology & data Variations	If a base Station is provided by the calling subsystem • fields should be pre-populated with the base Station's data	

Use case	**Insert Junction Data**	
Release (id)	UC18, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the System provide a standardised way to insert a Junction's data	
Level	Subfunction	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to insert Junction's Data
	System	Manages the user interface, the database and their interactions
Preconditions	None	
Minimal Guarantees	No invalid Junction is returned to the calling subsystem	
Success Guarantees	A valid Junction is returned to the calling subsystem	
Trigger	Another subsystem includes this use case	
Description	**Step**	**Action**
	1	The system asks the user to insert: • The Junction's name • The Junction's Coordinates
	2	The user inserts the requested data.
	3	The user submits the data
	4	The Junction is returned to the calling subsystem
Extensions	**Step**	**Alternate action**
	3a	If any of the following are false: • The Junction's name must be unique ○ Also amongst Station Names
	3a.1	Display an error
	3a.2	Go to step 1
Technology & data Variations	If a base Junction is provided by the calling subsystem • Fields should be pre-populated with the base Junction's data.	

Use case	**Insert Line Data**	
Release (id)	UC19, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the System provide a standardised way to insert a Line's data	
Level	Subfunction	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to insert Line's Data
	System	Manages the user interface, the database and their interactions
Preconditions	None	
Minimal Guarantees	No invalid Line is returned to the calling subsystem	
Success Guarantees	A valid Line is returned to the calling subsystem	
Trigger	Another subsystem includes this use case	
Description	**Step**	**Action**
	1	The system asks the user to insert: • The Line's origin Junction / Station • The Line's destination Junction / Station • The Line's number of tracks • The Line's length • The Line's maximum speed
	2	The user inserts the requested data.
	3	The user submits the data
	4	The system returns the Line to the calling subsystem
Extensions	**Step**	**Other Action**
	3a	If any of the following conditions fail: • The Line's origin must exist • The Line's destination must exist
	3a.1	Display an error
	3a.2	Go to step 1
Technology & data	If a base Line is provided by the calling subsystem,	

Variations	• Fields should be pre-populated.	
Use case	**Create Station**	
Release (id)	UC20, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager create a Station	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to create a Station
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	No invalid Station is registered	
Success Guarantees	A Station is registered	
Trigger	The Network Manager selects “Register a station”.	
Description	**Step**	**Action**
	1	The Network Manager selects “Register a station”.
	2	Include(Insert Station Data)
	3	The system registers the Station.
Extensions	**Step**	**Other Action**
	-	None
Technology & data Variations	None	

Use case	**Create Junction**	
Release (id)	UC21, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager create a Junction	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to create a Junction
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	No invalid Junction is registered	
Success Guarantees	A Junction is registered	
Trigger	The Network Manager selects ”Register a junction”.	
Description	**Step**	**Action**
	1	The Network Manager selects ”Register a junction”.
	2	Include(Insert Junction Data)
	3	The system registers the Junction.
Extensions	**Step**	**Other Action**
	-	None
Technology & data Variations	None	

Use case	**Create Line**	
Release (id)	UC22, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager create Lines	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to create a Line
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	No invalid Line is registered	
Success Guarantees	A Line is registered	
Trigger	The Network Manager selects “Register a line”.	
Description	**Step**	**Action**
	1	The Network Manager selects “Register a line”.
	2	Include(Insert Line Data)
	3	The system registers the Line.
Extensions	**Step**	**Other Action**
	-	None
Technology & data Variations	None	

Use case	**Edit Station**	
Release (id)	UC23, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager edit a Station	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to edit a Station
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	No service information is invalidated	
Success Guarantees	The selected Station is edited	
Trigger	The Network Manager selects “Edit station”.	
Description	**Step**	**Action**
	1	The Network Manager selects “Edit station”.
	2	Include(Insert Station Data) and provide the selected Station as a base.
	3	The system edits the Station with the data provided by step 2.
Extensions	**Step**	**Other Action**
	3a	If the platforms were modified and a service stops at a platform that was removed
	3a.1	Display an error to the user.
	3a.2	End
Technology & data Variations	None	

Use case	**Edit Junction**	
Release (id)	UC24, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager edit a Junction	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to edit a Junction
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	None	
Success Guarantees	The selected Junction is edited	
Trigger	The Network Manager selects “Edit junction”.	
Description	**Step**	**Action**
	1	The Network Manager selects “Edit junction”.
	2	Include(Insert Junction Data) and provide the selected Junction as a base
	3	The system edits the Junction with the data provided by step 1
Extensions	**Step**	**Other Action**
	-	None
Technology & data Variations	None	

Use case	**Edit Line**	
Release (id)	UC25, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager edit a Line	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to edit a Line
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	No service information is invalidated	
Success Guarantees	The selected Line is edited	
Trigger	The Network Manager selects “Edit line”.	
Description	**Step**	**Action**
	1	The Network Manager selects “Edit line”.
	2	Include(Insert Line Data) and provide the selected Line as a base
	3	The system edits the Line with the data provided by step 1
Extensions	**Step**	**Other Action**
	3a	If the line’s destination or origin are modified and a service uses the line
	3a.1	Display an error to the user.
	3a.2	End
Technology & data Variations	None	

Use case	**Delete Station**	
Release (id)	UC26, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager delete a station	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to delete a station
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	No service information is invalidated	
Success Guarantees	A station and it's connected lines (if any) are deleted	
Trigger	The Network Manager select "Delete station".	
Description	**Step**	**Action**
	1	The Network Manager select "Delete station".
	2	The system checks if any Service is using this station
	3	The system checks If any Line connects to this station
	4	The station is deleted
Extensions	**Step**	**Other Action**
	2a	If any service is scheduled to use this station
	2a.1	Then display an error informing the user that the station cannot be deleted as it is in use
	2a.2	End
	3a	If any line is connected to the station

	3a.1	Then display a warning that informs the user of the lines that will subsequently be deleted and allows them to continue or abort the deletion.
	3a.2	If the user selects abort
	3a.2.1	End
	3a.3	Otherwise
	3a.3.1	Foreach connected line
	3a.3.1.1	Cascade Include(Delete Line)
Technology & data Variations	None	

Use case	**Delete Junction**	
Release (id)	UC27, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager Delete a junction	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to delete a junction
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	No service information is invalidated	
Success Guarantees	A junction and it's connected lines (if any) are deleted	
Trigger	The Network Manager selects "delete junction".	
Description	**Step**	**Action**
	1	The Network Manager selects "delete junction".
	2	The system checks if any Service is using this junction
	3	The system checks if any Line connects to this junction
	4	The junction is deleted
Extensions	**Step**	**Other Action**
	2a	If any service is scheduled to use the junction
	2a.1	Then display a warning that informs the user of the impacted service(s), allowing them to choose to continue or abort the deletion.
	2a.2.1	If they chose to continue, End
	2a.2.2	Else Go to step 3
	3a	If any line is connected to the junction
	3a.1	Then display a warning that informs the user of the lines that will subsequently be deleted and allows them to choose to continue or abort the deletion.
	3a.2	If the selects abort
	3a.2.1	End

	3a.3	Otherwise
	3a.3.1	Foreach connected line
	3a.3.1.1	Cascade Include (Delete Line)
Technology & data Variations	None	

Use case	**Delete Line**	
Release (id)	UC28, v0.3, 26/04/2026	
Context of Use	Network Management	
Scope	Let the network manager delete a line	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Network Manager	Wants to delete a Line
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated	
Minimal Guarantees	No service information is invalidated	
Success Guarantees	A valid Line is deleted	
Trigger	The Network Manager selects “delete line”.	
Description	**Step**	**Action**
	1	The Network Manager selects “delete line”.
	2	The system checks if any Service is scheduled to use the Line
	3	The line is deleted
Extensions	**Step**	**Other Action**
	2a	If any service is scheduled to use the line
	2a.1	Then display a warning that informs the user of the impacted service(s), allowing them to choose to continue or abort the deletion.
	2a.2	If they chose to continue
	2a.2.1	Go to step 3
	2a.2.2	Else, End
Technology & data Variations	None	

Use case	**Defining a Train Type**	
Release (id)	UC29, v0.3, 30/04/2026	
Context of Use	Service Management	
Scope	Let a Train Company register one of their trains for use in services	
Level	Primary task	
Primary actor	Train Company	
Stakeholder & interest	**Stakeholder**	**Interest**
	Train Company	Wants to register one of their trains
	System	Manages the user interface, the database and their interactions
Preconditions	The Train Company is authenticated	
Minimal Guarantees	No duplicated train identifier is registered	
Success Guarantees	A train type is registered	
Trigger	The Train Company initiates the creation of a Train Type.	
Description	**Step**	**Action**
	1	The Train Company initiates the creation of a Train Type.

	2	The system asks the user to insert:
		• The Train Type's identifier
		• The Train Type's max speed
		• The Train Type's type (Cargo / Passenger)
		• If Passenger
		  ○ The Train Type's seated Capacity
		  ○ The Train Type's standing Capacity

	3	The user submits the requested data.
	4	The train is registered.
Extensions	**Step**	**Other Action**
	3a	If the Train Type identifier is not unique
	3a.1	Then display an error informing the user.
	3a.2	Return to step 2
Technology & data Variations	None	

Use case	**Registering a Service Type**	
Release (id)	UC30, v0.4, 03/05/2026	
Context of Use	Service Management	
Scope	Let a Train Company register a service type	
Level	Primary task	
Primary actor	Train Company	
Stakeholder & interest	**Stakeholder**	**Interest**
	Train Company	Wants to register a service Type
	System	Manages the user interface, the database and their interactions
Preconditions	The Train Company is authenticated	
Minimal Guarantees	No duplicated commercial name is registered	
Success Guarantees	A service is registered	
Trigger	The Train Company initiates the creation of a Service Type.	
Description	**Step**	**Action**
	1	The Train Company initiates the creation of a Service Type
	2	The system shows a list of registered Train Types.
	3	The system asks the user to select an existing or create a new Train Type.
	4	The user selects the Train Type.
	5	The system asks the user to insert: • This Service Type's type (Passenger / Cargo) • The service's commercial name ○ e.g. "Regionale" / "Frecciarossa" • The service's price / km
	6	The user submits the requested data.
	7	The service type is registered.
Extensions	**Step**	**Other Action**
	4a	If the user decides to create a new Train Type
	4a.1	Then (Defining a Train Type).
	4a.2	Select the newly created Train Type.
	6a	If the service's commercial name is not unique

	6a.1	Then display an error informing the user.
	6a.2	Return to step 4
Technology & data Variations	None	

Use case	**Service Request Creation**	
Release (id)	UC31, v0.1, 03/05/2026	
Context of Use	Service Management	
Scope	Let a Train Company create a service request	
Level	Primary task	
Primary actor	Train Company	
Stakeholder & interest	**Stakeholder**	**Interest**
	Train Company	Wants to create a service request
	System	Manages the user interface, the database and their interactions
Preconditions	The Train Company is authenticated	
Minimal Guarantees	No invalid service is created	
Success Guarantees	A service is created	
Trigger	The Train Company initiates the creation of a Service Request.	
Description	**Step**	**Action**
	1	The Train Company initiates the creation of a Service Request.
	2	The system shows a list of registered Service Types.
	3	The system asks the user to select an existing or create a new Service Type.
	4	The user selects the Service Type.

	5	The system asks the user to insert:
		• A list of destinations as:
		  ○ Stations for the service to stop at / go via
		  ○ Junctions for the service to go via
		• The time taken between destinations
		• A list of Dispatch Times (Applies to the first station in the list):
		  ○ A time in terms of `hh:mm`
		  ○ Train number
		  ○ On what days of the week the dispatch time is used

	6	The user submits the requested data.
	7	The service request is created.
Extensions	**Step**	**Other Action**
	4a	If the user decides to create a new Service Type
	4a.1	Then (Defining a Train Type)
	4a.2	Select the newly created Train Type.
	6a.1	If any of the following are true: • The user did not insert at least 2 stations in the destinations list • The first element of the destinations list is not a station • Any train number inserted is not unique across all services
	6a.1.1	Display an error
	6a.1.2	Go to step 4
Technology & data Variations	None	

Use case	**Service Request Review**	
Release (id)	UC32, v0.1, 03/05/2026	
Context of Use	Service Management	
Scope	Let the Network Manager review a service request	
Level	Primary task	
Primary actor	Network Manager	
Stakeholder & interest	**Stakeholder**	**Interest**
	Train Company	Wants to review a service request
	System	Manages the user interface, the database and their interactions
Preconditions	The Network Manager is authenticated. There is a Service Request not yet reviewed.	
Minimal Guarantees	An invalid service request is denied.	
Success Guarantees	A service is approved, with possible amendment.	
Trigger	The Network Management initiates the review of a Service Request.	
Description	**Step**	**Action**
	1	The Train Company initiates the review of a Service Request.
	2	The system shows a list of registered Service Requests.
	3	The system asks the user to select a Service Request.
	4	The user selects a Service Request.
	5	The system performs automated service integrity checks.
	6	The system shows the results of the integrity checks.
	7	The system asks the user to select an operation between deny, amend and approve.
	8	If the user selects “deny”
	8.1	The system deletes the service request.
	9	If the user selects “amend”
	9.2	The system shows data specified at UC31[step5].
	9.3	The network manager inserts changes.
	9.4	Go to step 5
	10.1	If the user selects “approve”
	10.2	The system saves the service as effective.

	11	The system notifies the Train Company that requested the service.
Extensions	**Step**	**Other Action**
	9.3a.1	If any of the following are true: • The user did not insert at least 2 stations in the destinations list • The first element of the destinations list is not a station Any train number inserted is not unique across all services
	9.3a.1.1	Display an error
	9.3a.1.2	Go to step 9.2
Technology & data Variations	None	