

```
DKMS make.log for evdi-5.2.14 for kernel 5.4.0-70-generic (x86_64)
vie abr  2 11:06:21 CST 2021
make KBUILD_VERBOSE=1 SUBDIRS=/var/lib/dkms/evdi/5.2.14/build SRCROOT=/var/lib/dkms/
evdi/5.2.14/build CONFIG_MODULE_SIG= -C /lib/modules/5.4.0-70-generic/build modules
make[1]: se entra en el directorio '/usr/src/linux-headers-5.4.0-70-generic'
make -f ./scripts/Makefile.build obj=arch/x86/entry/syscalls all
make -f ./scripts/Makefile.build obj=scripts/basic
set -e; mkdir -p include/config/; trap "rm -f include/config/.kernel.release.tmp"
EXIT; { echo "5.4.94$(sh ./scripts/setlocalversion .)"; } > include/
config/.kernel.release.tmp; if [ ! -r include/config/kernel.release ] || ! cmp -s
include/config/kernel.release include/config/.kernel.release.tmp; then : ' UPD
include/config/kernel.release'; mv -f include/config/.kernel.release.tmp include/
config/kernel.release; fi
make -f ./scripts/Makefile.asm-generic obj=arch/x86/include/generated/uapi/asm \
generic=include/uapi/asm-generic
set -e; mkdir -p include/generated/uapi/linux/; trap "rm -f include/generated/uapi/
linux/.version.h.tmp" EXIT; { echo \#define LINUX_VERSION_CODE 328798; echo
'\#define KERNEL_VERSION(a,b,c) (((a) << 16) + ((b) << 8) + (c))'; } > include/
generated/uapi/linux/.version.h.tmp; if [ ! -r include/generated/uapi/linux/
version.h ] || ! cmp -s include/generated/uapi/linux/version.h include/generated/uapi/
linux/.version.h.tmp; then : ' UPD include/generated/uapi/linux/version.h'; mv -
f include/generated/uapi/linux/.version.h.tmp include/generated/uapi/linux/version.h;
fi
make -f ./scripts/Makefile.modbuiltin obj=init
warning: Cannot use CONFIG_STACK_VALIDATION=y, please install libelf-dev, libelf-
devel or elfutils-libelf-devel
make -f ./scripts/Makefile.modbuiltin obj=usr
make -f ./scripts/Makefile.modbuiltin obj=arch/x86
make -f ./scripts/Makefile.modbuiltin obj=kernel
rm -f include/linux/version.h
make -f ./scripts/Makefile.modbuiltin obj=certs
make -f ./scripts/Makefile.modbuiltin obj=mm
rm -f .tmp_quiet_recordmcount
make -f ./scripts/Makefile.modbuiltin obj=fs
(for m in ; do echo $m; done; \
cat /dev/null ) > init/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > usr/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=ipc
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/crypto
make -f ./scripts/Makefile.modbuiltin obj=security
(for m in ; do echo $m; done; \
cat /dev/null ) > certs/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/entry
make -f ./scripts/Makefile.modbuiltin obj=fs/configfs
(for m in mm/zpool.ko mm/zbud.ko mm/zsmalloc.ko; do echo $m; done; \
cat /dev/null ) > mm/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > ipc/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/crypto
make -f ./scripts/Makefile.modbuiltin obj=security/apparmor
make -f ./scripts/Makefile.modbuiltin obj=kernel/bpf
make -f ./scripts/Makefile.modbuiltin obj=kernel/cgroup
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/entry/vdso
make -f ./scripts/Makefile.modbuiltin obj=kernel/debug
(for m in fs/configfs/configfs.ko; do echo $m; done; \
cat /dev/null ) > fs/configfs/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/cgroup/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=kernel/dma
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/crypto/modules.builtin
```

```
make -f ./scripts/Makefile.modbuiltin obj=crypto
(for m in ; do echo $m; done; \
cat /dev/null ) > security/apparmor/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/bpf/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=security/integrity
make -f ./scripts/Makefile.modbuiltin obj=fs/debugfs
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/events
make -f ./scripts/Makefile.modbuiltin obj=kernel/debug/kdb
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/dma/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=kernel/events
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/events/amd
make -f ./scripts/Makefile.modbuiltin obj=security/integrity/evm
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/debugfs/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/events/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/devpts
make -f ./scripts/Makefile.modbuiltin obj=security/integrity/ima
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/debug/kdb/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null kernel/debug/kdb/modules.builtin) > kernel/debug/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=kernel/irq
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/events/amd/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > security/integrity/evm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/events/intel
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/devpts/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=kernel/livepatch
make -f ./scripts/Makefile.modbuiltin obj=fs/ecryptfs
(for m in ; do echo $m; done; \
cat /dev/null ) > security/integrity/ima/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/irq/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null security/integrity/evm/modules.builtin security/integrity/ima/
modules.builtin) > security/integrity/modules.builtin
(for m in arch/x86/crypto/crc32c-intel.ko; do echo $m; done; \
cat /dev/null ) > arch/x86/crypto/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/efivarfs
make -f ./scripts/Makefile.modbuiltin obj=security/keys
make -f ./scripts/Makefile.modbuiltin obj=security/lockdown
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/livepatch/modules.builtin
(for m in fs/ecryptfs/ecryptfs.ko; do echo $m; done; \
cat /dev/null ) > fs/ecryptfs/modules.builtin
(for m in arch/x86/events/intel/intel-uncore.ko; do echo $m; done; \
cat /dev/null ) > arch/x86/events/intel/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=kernel/locking
make -f ./scripts/Makefile.modbuiltin obj=kernel/power
(for m in ; do echo $m; done; \
cat /dev/null arch/x86/events/amd/modules.builtin arch/x86/events/intel/
modules.builtin) > arch/x86/events/modules.builtin
(for m in fs/efivarfs/efivarfs.ko; do echo $m; done; \
cat /dev/null ) > fs/efivarfs/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=security/keys/encrypted-keys
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/entry/vsyscall
make -f ./scripts/Makefile.modbuiltin obj=fs/exportfs
```

```
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/entry/vdso/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/locking/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > security/lockdown/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=crypto/asymmetric_keys
make -f ./scripts/Makefile.modbuiltin obj=fs/ext4
make -f ./scripts/Makefile.modbuiltin obj=fs/fat
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/ia32
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/power/modules.builtin
(for m in security/keys/encrypted-keys/encrypted-keys.ko; do echo $m; done; \
cat /dev/null ) > security/keys/encrypted-keys/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=kernel/printk
(for m in security/keys/trusted.ko; do echo $m; done; \
cat /dev/null security/keys/encrypted-keys/modules.builtin) > security/keys/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/entry/vsyscall/modules.builtin
(for m in fs/exportfs/exportfs.ko; do echo $m; done; \
cat /dev/null ) > fs/exportfs/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null arch/x86/entry/vdso/modules.builtin arch/x86/entry/vsyscall/
modules.builtin) > arch/x86/entry/modules.builtin
(for m in fs/fat/fat.ko fs/fat/vfat.ko; do echo $m; done; \
cat /dev/null ) > fs/fat/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=security/safesetid
(for m in crypto/asymmetric_keys/public_key.ko crypto/asymmetric_keys/
x509_key_parser.ko crypto/asymmetric_keys/pkcs7_message.ko; do echo $m; done; \
cat /dev/null ) > crypto/asymmetric_keys/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel
make -f ./scripts/Makefile.modbuiltin obj=block
make -f ./scripts/Makefile.modbuiltin obj=drivers
(for m in fs/ext4/ext4.ko; do echo $m; done; \
cat /dev/null ) > fs/ext4/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > kernel/printk/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/ia32/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/fuse
(for m in crypto/crypto.ko crypto/crypto_algapi.ko crypto/aead.ko crypto/
crypto_blkcipher.ko crypto/seqiv.ko crypto/crypto_hash.ko crypto/akcipher.ko crypto/
kpp.ko crypto/dh_generic.ko crypto/rsa_generic.ko crypto/crypto_acompress.ko crypto/
cryptomgr.ko crypto/hmac.ko crypto/crypto_null.ko crypto/md5.ko crypto/
sha1_generic.ko crypto/sha256_generic.ko crypto/sha512_generic.ko crypto/gf128mul.ko
crypto/ecb.ko crypto/cbc.ko crypto/cts.ko crypto/xts.ko crypto/ctr.ko crypto/gcm.ko
crypto/aes_generic.ko crypto/deflate.ko crypto/crc32c_generic.ko crypto/
crct10dif_common.ko crypto/crct10dif_generic.ko crypto/lzo.ko crypto/lzo-rle.ko
crypto/rng.ko crypto/drbg.ko crypto/jitterentropy_rng.ko crypto/ghash-generic.ko; do
echo $m; done; \
cat /dev/null crypto/asymmetric_keys/modules.builtin) > crypto/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=kernel/rcu
make -f ./scripts/Makefile.modbuiltin obj=fs/hugetlbfs
make -f ./scripts/Makefile.modbuiltin obj=kernel/sched
(for m in ; do echo $m; done; \
cat /dev/null ) > security/safesetid/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/acpi
make -f ./scripts/Makefile.modbuiltin obj=block/partitions
make -f ./scripts/Makefile.modbuiltin obj=drivers/acpi
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/hugetlbfs/modules.builtin
```

```
(for m in fs/fuse/fuse.ko; do echo $m; done;    \  
cat /dev/null ) > fs/fuse/modules.builtin  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > kernel/rcu/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/apic  
make -f ./scripts/Makefile.modbuiltin obj=security/selinux  
make -f ./scripts/Makefile.modbuiltin obj=sound  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > kernel/sched/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=kernel/time  
make -f ./scripts/Makefile.modbuiltin obj=fs/iomap  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > arch/x86/kernel/acpi/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=drivers/acpi/acpica  
make -f ./scripts/Makefile.modbuiltin obj=ubuntu  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > arch/x86/kernel/apic/modules.builtin  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > block/partitions/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/cpu  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > sound/modules.builtin  
(for m in block/mq-deadline.ko; do echo $m; done;    \  
cat /dev/null block/partitions/modules.builtin) > block/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=fs/jbd2  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > kernel/time/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=kernel/trace  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > fs/iomap/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/mm  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > security/selinux/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=security/smack  
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/net  
make -f ./scripts/Makefile.modbuiltin obj=ubuntu/xr-usb-serial  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > drivers/acpi/acpica/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=drivers/acpi/apei  
(for m in fs/jbd2/jbd2.ko; do echo $m; done;    \  
cat /dev/null ) > fs/jbd2/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=fs/kernfs  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > kernel/trace/modules.builtin  
(for m in ; do echo $m; done;    \  
cat /dev/null kernel/bpf/modules.builtin kernel/cgroup/modules.builtin kernel/debug/  
modules.builtin kernel/dma/modules.builtin kernel/events/modules.builtin kernel/irq/  
modules.builtin kernel/livepatch/modules.builtin kernel/locking/modules.builtin  
kernel/power/modules.builtin kernel/printk/modules.builtin kernel/rcu/modules.builtin  
kernel/sched/modules.builtin kernel/time/modules.builtin kernel/trace/  
modules.builtin) > kernel/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=fs/nfs_common  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > arch/x86/net/modules.builtin  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > security/smack/modules.builtin  
make -f ./scripts/Makefile.modbuiltin obj=fs/nls  
make -f ./scripts/Makefile.modbuiltin obj=security/tomoyo  
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/cpu/mce  
(for m in ; do echo $m; done;    \  
cat /dev/null ) > ubuntu/xr-usb-serial/modules.builtin  
(for m in ; do echo $m; done;    \  

```

```
cat /dev/null ) > drivers/acpi/apei/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ubuntu/xr-usb-serial/modules.builtin) > ubuntu/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/acpi/dptf
make -f ./scripts/Makefile.modbuiltin obj=security/yama
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/kernfs/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/fpu
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/mm/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/nfs_common/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/kernel/cpu/mce/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/kprobes
(for m in fs/nls/nls_base.ko fs/nls/nls_cp437.ko; do echo $m; done; \
cat /dev/null ) > fs/nls/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/cpu/microcode
make -f ./scripts/Makefile.modbuiltin obj=samples
(for m in ; do echo $m; done; \
cat /dev/null ) > security/tomoyo/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/acpi/dptf/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform
make -f ./scripts/Makefile.modbuiltin obj=fs/notify
(for m in ; do echo $m; done; \
cat /dev/null ) > security/yama/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/acpi/hmat
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/kernel/fpu/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/pvh
(for m in ; do echo $m; done; \
cat /dev/null security/apparmor/modules.builtin security/integrity/modules.builtin
security/keys/modules.builtin security/lockdown/modules.builtin security/safesetid/
modules.builtin security/selinux/modules.builtin security/smack/modules.builtin
security/tomoyo/modules.builtin security/yama/modules.builtin) > security/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/purgatory
make -f ./scripts/Makefile.modbuiltin obj=samples/vfio-mdev
(for m in ; do echo $m; done; \
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/kernel/kprobes/modules.builtin
cat /dev/null ) > arch/x86/kernel/cpu/microcode/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/realmode
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/cpu/mtrr
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/atom
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/pvh/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/notify/dnotify
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/acpi/hmat/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/notify/fanotify
(for m in drivers/acpi/ac.ko drivers/acpi/button.ko drivers/acpi/fan.ko drivers/acpi/
processor.ko drivers/acpi/thermal.ko drivers/acpi/battery.ko drivers/acpi/hed.ko
drivers/acpi/acpi_dbg.ko; do echo $m; done; \
cat /dev/null drivers/acpi/acpica/modules.builtin drivers/acpi/apei/modules.builtin
drivers/acpi/dptf/modules.builtin drivers/acpi/hmat/modules.builtin) > drivers/acpi/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > samples/vfio-mdev/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/purgatory/modules.builtin
```

```
make -f ./scripts/Makefile.modbuiltin obj=drivers/amba
(for m in ; do echo $m; done; \
cat /dev/null samples/vfio-mdev/modules.builtin) > samples/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/realmode/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/kernel/cpu/mtrr/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/ce4100
make -f ./scripts/Makefile.modbuiltin obj=fs/notify/inotify
make -f ./scripts/Makefile.modbuiltin obj=fs/proc
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/kernel/cpu/resctrl
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/atom/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/pstore
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/notify/dnotify/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/notify/fanotify/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/amba/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/quota
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/xen
make -f ./scripts/Makefile.modbuiltin obj=drivers/android
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/notify/inotify/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/ce4100/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/proc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null fs/notify/dnotify/modules.builtin fs/notify/fanotify/modules.builtin fs/
notify/inotify/modules.builtin) > fs/notify/modules.builtin
(for m in fs/pstore/pstore.ko; do echo $m; done; \
cat /dev/null ) > fs/pstore/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/ata
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/kernel/cpu/resctrl/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/efi
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/geode
make -f ./scripts/Makefile.modbuiltin obj=fs/ramfs
(for m in ; do echo $m; done; \
cat /dev/null arch/x86/kernel/cpu/mce/modules.builtin arch/x86/kernel/cpu/microcode/
modules.builtin arch/x86/kernel/cpu/mtrr/modules.builtin arch/x86/kernel/cpu/resctrl/
modules.builtin) > arch/x86/kernel/cpu/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/quota/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null arch/x86/kernel/acpi/modules.builtin arch/x86/kernel/apic/
modules.builtin arch/x86/kernel/cpu/modules.builtin arch/x86/kernel/fpu/
modules.builtin arch/x86/kernel/kprobes/modules.builtin) > arch/x86/kernel/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/auxdisplay
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/android/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/goldfish
(for m in drivers/ata/libata.ko drivers/ata/ata_piix.ko drivers/ata/pata_sis.ko
drivers/ata/ata_generic.ko; do echo $m; done; \
cat /dev/null ) > drivers/ata/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/intel
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/intel-mid
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/efi/modules.builtin
```

```
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/geode/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/pci
make -f ./scripts/Makefile.modbuiltin obj=drivers/base
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/auxdisplay/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/ramfs/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/power
make -f ./scripts/Makefile.modbuiltin obj=fs/squashfs
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/xen/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/intel-mid/modules.builtin
(for m in arch/x86/platform/intel/iosf_mbi.ko; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/intel/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/goldfish/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/sysfs
make -f ./scripts/Makefile.modbuiltin obj=drivers/block
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/intel-quark
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/iris
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/pci/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/base/firmware_loader
(for m in drivers/block/loop.ko drivers/block/xen-blkfront.ko; do echo $m;
done; \
cat /dev/null ) > drivers/block/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/bus
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/olpc
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/intel-quark/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/iris/modules.builtin
(for m in fs/squashfs/squashfs.ko; do echo $m; done; \
cat /dev/null ) > fs/squashfs/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=fs/tracefs
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/sysfs/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/base/power
make -f ./scripts/Makefile.modbuiltin obj=fs/unicode
make -f ./scripts/Makefile.modbuiltin obj=drivers/base/firmware_loader/builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/bus/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/scx200
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/olpc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/power/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/sfi
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/tracefs/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/video
make -f ./scripts/Makefile.modbuiltin obj=drivers/cdrom
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/base/power/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/char
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/unicode/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/ts5500
make -f ./scripts/Makefile.modbuiltin obj=fs/verity
(for m in ; do echo $m; done; \
```

```
cat /dev/null ) > drivers/base/firmware_loader/builtin/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/scx200/modules.builtin
(for m in drivers/base/firmware_loader/firmware_class.ko; do echo $m; done; \
cat /dev/null drivers/base/firmware_loader/builtin/modules.builtin) > drivers/base/
firmware_loader/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/char/ipmi
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/sfi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/base/regmap
(for m in arch/x86/video/fbdev.ko; do echo $m; done; \
cat /dev/null ) > arch/x86/video/modules.builtin
(for m in drivers/cdrom/cdrom.ko; do echo $m; done; \
cat /dev/null ) > drivers/cdrom/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/char/agp
make -f ./scripts/Makefile.modbuiltin obj=drivers/base/test
(for m in ; do echo $m; done; \
cat /dev/null ) > fs/verity/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/platform/uv
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/ts5500/modules.builtin
(for m in fs/binfmt_script.ko fs/mbcache.ko; do echo $m; done; \
cat /dev/null fs/configfs/modules.builtin fs/crypto/modules.builtin fs/debugfs/
modules.builtin fs/devpts/modules.builtin fs/ecryptfs/modules.builtin fs/efivarfs/
modules.builtin fs/exportfs/modules.builtin fs/ext4/modules.builtin fs/fat/
modules.builtin fs/fuse/modules.builtin fs/hugetlbfs/modules.builtin fs/iomap/
modules.builtin fs/jbd2/modules.builtin fs/kernfs/modules.builtin fs/nfs_common/
modules.builtin fs/nls/modules.builtin fs/notify/modules.builtin fs/proc/
modules.builtin fs/pstore/modules.builtin fs/quota/modules.builtin fs/ramfs/
modules.builtin fs/squashfs/modules.builtin fs/sysfs/modules.builtin fs/tracefs/
modules.builtin fs/unicode/modules.builtin fs/verity/modules.builtin) > fs/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/char/hw_random
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/oprofile
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/base/test/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/char/ipmi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/actions
(for m in drivers/base/regmap/regmap-i2c.ko drivers/base/regmap/regmap-spi.ko drivers/
base/regmap/regmap-mmio.ko; do echo $m; done; \
cat /dev/null ) > drivers/base/regmap/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/analogbits
make -f ./scripts/Makefile.modbuiltin obj=drivers/clocksource
(for m in drivers/char/agp/agpgart.ko drivers/char/agp/amd64-agp.ko drivers/char/agp/
intel-agp.ko drivers/char/agp/intel-gtt.ko drivers/char/agp/via-agp.ko; do echo $m;
done; \
cat /dev/null ) > drivers/char/agp/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/base/firmware_loader/modules.builtin drivers/base/power/
modules.builtin drivers/base/regmap/modules.builtin drivers/base/test/
modules.builtin) > drivers/base/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net
make -f ./scripts/Makefile.modbuiltin obj=drivers/char/tpm
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/platform/uv/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null arch/x86/platform/atom/modules.builtin arch/x86/platform/ce4100/
modules.builtin arch/x86/platform/efi/modules.builtin arch/x86/platform/geode/
modules.builtin arch/x86/platform/goldfish/modules.builtin arch/x86/platform/intel/
modules.builtin arch/x86/platform/intel-mid/modules.builtin arch/x86/platform/intel-
```

```
quark/modules.builtin arch/x86/platform/iris/modules.builtin arch/x86/platform/olpc/
modules.builtin arch/x86/platform/scx200/modules.builtin arch/x86/platform/sfi/
modules.builtin arch/x86/platform/ts5500/modules.builtin arch/x86/platform/uv/
modules.builtin) > arch/x86/platform/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clocksource/modules.builtin
(for m in drivers/char/hw_random/rng-core.ko; do echo $m; done; \
cat /dev/null ) > drivers/char/hw_random/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/bcm
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/imgtec
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/oprofile/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null arch/x86/crypto/modules.builtin arch/x86/entry/modules.builtin arch/x86/
events/modules.builtin arch/x86/ia32/modules.builtin arch/x86/kernel/modules.builtin
arch/x86/mm/modules.builtin arch/x86/net/modules.builtin arch/x86/platform/
modules.builtin arch/x86/platform/pvh/modules.builtin arch/x86/purgatory/
modules.builtin arch/x86/realmode/modules.builtin arch/x86/xen/modules.builtin) >
arch/x86/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/actions/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/analogbits/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/imx
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/ingenic
make -f ./scripts/Makefile.modbuiltin obj=drivers/connector
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/mediatek
make -f ./scripts/Makefile.modbuiltin obj=net/802
(for m in drivers/char/tpm/tpm.ko drivers/char/tpm/tpm_tis_core.ko drivers/char/tpm/
tpm_tis.ko drivers/char/tpm/tpm_crb.ko; do echo $m; done; \
cat /dev/null ) > drivers/char/tpm/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/bcm/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/imgtec/modules.builtin
(for m in drivers/char/ttyprintk.ko drivers/char/virtio_console.ko; do echo $m;
done; \
cat /dev/null drivers/char/agp/modules.builtin drivers/char/hw_random/modules.builtin
drivers/char/tpm/modules.builtin) > drivers/char/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/mediatek/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/imx/modules.builtin
(for m in drivers/connector/cn.ko; do echo $m; done; \
cat /dev/null ) > drivers/connector/modules.builtin
(for m in net/802/fddi.ko; do echo $m; done; \
cat /dev/null ) > net/802/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/ingenic/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/mvebu
make -f ./scripts/Makefile.modbuiltin obj=lib
make -f ./scripts/Makefile.modbuiltin obj=drivers/cpufreq
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/lib
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/renesas
make -f ./scripts/Makefile.modbuiltin obj=drivers/cpuidle
make -f ./scripts/Makefile.modbuiltin obj=net/8021q
make -f ./scripts/Makefile.modbuiltin obj=drivers/crypto
(for m in ; do echo $m; done; \
cat /dev/null ) > net/8021q/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/mvebu/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/bpf
```

```
(for m in drivers/cpufreq/cpufreq_performance.ko drivers/cpufreq/cpufreq_powersave.ko
drivers/cpufreq/cpufreq_userspace.ko drivers/cpufreq/cpufreq_ondemand.ko drivers/
cpufreq/cpufreq_conservative.ko drivers/cpufreq/acpi-cpufreq.ko drivers/cpufreq/
powernow-k8.ko drivers/cpufreq/pcc-cpufreq.ko drivers/cpufreq/speedstep-centrino.ko;
do echo $m; done; \
cat /dev/null ) > drivers/cpufreq/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/crypto/ccp
make -f ./scripts/Makefile.modbuiltin obj=drivers/cpuidle/governors
make -f ./scripts/Makefile.modbuiltin obj=drivers/crypto/hisilicon
make -f ./scripts/Makefile.modbuiltin obj=virt
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/renesas/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/ti
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/crypto/ccp/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > arch/x86/lib/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/clk/x86
(for m in ; do echo $m; done; \
cat /dev/null ) > net/bpf/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/bpfilter
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/cpuidle/governors/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/crypto/hisilicon/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/dax
(for m in ; do echo $m; done; \
cat /dev/null drivers/cpuidle/governors/modules.builtin) > drivers/cpuidle/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/crypto/ccp/modules.builtin drivers/crypto/hisilicon/
modules.builtin) > drivers/crypto/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=virt/lib
make -f ./scripts/Makefile.modbuiltin obj=drivers/devfreq
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/ti/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=arch/x86/tools relocs
make -f ./scripts/Makefile.modbuiltin obj=net/core
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/clk/x86/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > net/bpfilter/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/clk/actions/modules.builtin drivers/clk/analogbits/
modules.builtin drivers/clk/bcm/modules.builtin drivers/clk/imgtec/modules.builtin
drivers/clk/imx/modules.builtin drivers/clk/ingenic/modules.builtin drivers/clk/
mediatek/modules.builtin drivers/clk/mvebu/modules.builtin drivers/clk/renesas/
modules.builtin drivers/clk/ti/modules.builtin drivers/clk/x86/modules.builtin) >
drivers/clk/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=lib/crypto
make -f ./scripts/Makefile.modbuiltin obj=lib/dim
(for m in virt/lib/irqbypass.ko; do echo $m; done; \
cat /dev/null ) > virt/lib/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=lib/fonts
make -f ./scripts/Makefile.modbuiltin obj=drivers/dax/pmem
(for m in ; do echo $m; done; \
cat /dev/null virt/lib/modules.builtin) > virt/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/devfreq/event
make[2]: *** No hay ninguna regla para construir el objetivo 'arch/x86/tools/
relocs_32.c', necesario para 'arch/x86/tools/relocs_32.o'. Alto.
arch/x86/Makefile:232: fallo en las instrucciones para el objetivo 'archscripts'
make[1]: *** [archscripts] Error 2
```

```
make -f ./scripts/Makefile.modbuiltin obj=net/dcb
make[1]: *** Se espera a que terminen otras tareas....
make -f ./scripts/Makefile.modbuiltin obj=net/dns_resolver
(for m in net/core/drop_monitor.ko; do echo $m; done; \
cat /dev/null ) > net/core/modules.builtin
(for m in lib/crypto/libaes.ko lib/crypto/libsha256.ko; do echo $m; done; \
cat /dev/null ) > lib/crypto/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > lib/dm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=lib/lz4
make -f ./scripts/Makefile.modbuiltin obj=drivers/dma
make -f ./scripts/Makefile.modbuiltin obj=lib/lzo
(for m in lib/fonts/font.ko; do echo $m; done; \
cat /dev/null ) > lib/fonts/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/dax/pmем/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/ethernet
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/devfreq/event/modules.builtin
(for m in drivers/dax/dax.ko; do echo $m; done; \
cat /dev/null drivers/dax/pmем/modules.builtin) > drivers/dax/modules.builtin
(for m in drivers/devfreq/governor_simpleondemand.ko drivers/devfreq/
governor_performance.ko drivers/devfreq/governor_powersave.ko drivers/devfreq/
governor_userspace.ko drivers/devfreq/governor_passive.ko; do echo $m; done; \
cat /dev/null drivers/devfreq/event/modules.builtin) > drivers/devfreq/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > net/dcb/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/ipv4
(for m in net/dns_resolver/dns_resolver.ko; do echo $m; done; \
cat /dev/null ) > net/dns_resolver/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/ipv6
make -f ./scripts/Makefile.modbuiltin obj=drivers/dma-buf
(for m in lib/lz4/lz4_decompress.ko; do echo $m; done; \
cat /dev/null ) > lib/lz4/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/edac
make -f ./scripts/Makefile.modbuiltin obj=drivers/eisa
make -f ./scripts/Makefile.modbuiltin obj=drivers/dma/mediatek
(for m in lib/lzo/lzo_compress.ko lib/lzo/lzo_decompress.ko; do echo $m; done; \
cat /dev/null ) > lib/lzo/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > net/ethernet/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=lib/math
make -f ./scripts/Makefile.modbuiltin obj=net/ipv4/bpfilter
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/dma-buf/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/ipv4/netfilter
make -f ./scripts/Makefile.modbuiltin obj=net/ipv6/netfilter
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/eisa/modules.builtin
(for m in ; do echo $m; done; \
make -f ./scripts/Makefile.modbuiltin obj=net/l3mdev
cat /dev/null ) > drivers/dma/mediatek/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/dma/qcom
(for m in drivers/edac/edac_core.ko; do echo $m; done; \
cat /dev/null ) > drivers/edac/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > net/ipv4/netfilter/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/extcon
(for m in ; do echo $m; done; \
cat /dev/null ) > net/ipv4/bpfilter/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/mpfs
(for m in ; do echo $m; done; \
```

```
cat /dev/null ) > lib/math/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/ncsi
(for m in net/ipv4/tcp_cubic.ko; do echo $m; done; \
cat /dev/null net/ipv4/bpfilter/modules.builtin net/ipv4/netfilter/modules.builtin) >
net/ipv4/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=lib/mpi
(for m in ; do echo $m; done; \
cat /dev/null ) > net/ipv6/netfilter/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > net/l3mdev/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/dma/qcom/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/firewire
(for m in net/ipv6/ipv6.ko net/ipv6/inet6_hashtables.ko; do echo $m; done; \
cat /dev/null net/ipv6/netfilter/modules.builtin) > net/ipv6/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/dma/ti
(for m in ; do echo $m; done; \
cat /dev/null ) > net/mps/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware
(for m in drivers/extcon/extcon-core.ko; do echo $m; done; \
cat /dev/null ) > drivers/extcon/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpio
make -f ./scripts/Makefile.modbuiltin obj=drivers/dma/xilinx
make -f ./scripts/Makefile.modbuiltin obj=net/netfilter
(for m in ; do echo $m; done; \
cat /dev/null ) > net/ncsi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/netlabel
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/dma/ti/modules.builtin
(for m in lib/mpi/mpi.ko; do echo $m; done; \
cat /dev/null ) > lib/mpi/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/firewire/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu
make -f ./scripts/Makefile.modbuiltin obj=net/netlink
make -f ./scripts/Makefile.modbuiltin obj=lib/xz
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/dma/xilinx/modules.builtin
(for m in drivers/gpio/gpio-lynxpoint.ko drivers/gpio/gpio-xilinx.ko; do echo $m;
done; \
cat /dev/null ) > drivers/gpio/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=lib/zlib_deflate
(for m in ; do echo $m; done; \
cat /dev/null drivers/dma/mediatek/modules.builtin drivers/dma/qcom/modules.builtin
drivers/dma/ti/modules.builtin drivers/dma/xilinx/modules.builtin) > drivers/dma/
modules.builtin
(for m in net/netlabel/netlabel_calipso.ko; do echo $m; done; \
cat /dev/null ) > net/netlabel/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/packet
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware/broadcom
make -f ./scripts/Makefile.modbuiltin obj=lib/zlib_inflate
(for m in ; do echo $m; done; \
cat /dev/null ) > net/netfilter/modules.builtin
(for m in lib/xz/xz_dec.ko; do echo $m; done; \
cat /dev/null ) > lib/xz/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware/efi
(for m in ; do echo $m; done; \
cat /dev/null ) > net/netlink/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=lib/zstd
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/vga
(for m in lib/zlib_deflate/zlib_deflate.ko; do echo $m; done; \
```

```
cat /dev/null ) > lib/zlib_deflate/modules.builtin
(for m in net/packet/af_packet.ko; do echo $m; done; \
cat /dev/null ) > net/packet/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/firmware/broadcom/modules.builtin
(for m in lib/zlib_inflate/zlib_inflate.ko; do echo $m; done; \
cat /dev/null ) > lib/zlib_inflate/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/rfkill
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware/efi/libstub
make -f ./scripts/Makefile.modbuiltin obj=net/sched
make -f ./scripts/Makefile.modbuiltin obj=net/strparser
make -f ./scripts/Makefile.modbuiltin obj=drivers/hwmon
(for m in lib/zstd/zstd_decompress.ko; do echo $m; done; \
cat /dev/null ) > lib/zstd/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/arm
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/vga/modules.builtin
(for m in lib/bitrev.ko lib/crc-ccitt.ko lib/crc16.ko lib/crc-t10dif.ko lib/crc32.ko
lib/xxhash.ko lib/digsig.ko lib/asnl_decoder.ko lib/oid_registry.ko lib/
ucs2_string.ko; do echo $m; done; \
cat /dev/null lib/crypto/modules.builtin lib/dim/modules.builtin lib/fonts/
modules.builtin lib/lz4/modules.builtin lib/lzo/modules.builtin lib/math/
modules.builtin lib/mpi/modules.builtin lib/xz/modules.builtin lib/zlib_deflate/
modules.builtin lib/zlib_inflate/modules.builtin lib/zstd/modules.builtin) > lib/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/bridge
make -f ./scripts/Makefile.modbuiltin obj=net/switchdev
(for m in ; do echo $m; done; \
cat /dev/null ) > net/sched/modules.builtin
(for m in net/rfkill/rfkill.ko; do echo $m; done; \
cat /dev/null ) > net/rfkill/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/hisilicon
(for m in ; do echo $m; done; \
cat /dev/null ) > net/strparser/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/i2c
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware/imx
(for m in drivers/hwmon/hwmon.ko; do echo $m; done; \
cat /dev/null ) > drivers/hwmon/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/arm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/bridge/synopsys
(for m in ; do echo $m; done; \
cat /dev/null ) > net/switchdev/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware/meson
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware/psci
make -f ./scripts/Makefile.modbuiltin obj=net/unix
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/hisilicon/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/i2c/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=net/wireless
make -f ./scripts/Makefile.modbuiltin obj=drivers/hwspinlock
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/firmware/imx/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/hwtracing/intel_th
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/bridge/synopsys/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/gpu/drm/bridge/synopsys/modules.builtin) > drivers/gpu/drm/
bridge/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/firmware/psci/modules.builtin
```

```
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/firmware/meson/modules.builtin
(for m in net/unix/unix.ko; do echo $m; done; \
cat /dev/null ) > net/unix/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/omapdrm
make -f ./scripts/Makefile.modbuiltin obj=drivers/i2c
make -f ./scripts/Makefile.modbuiltin obj=drivers/i3c
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/hwspinlock/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > net/wireless/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/idle
make -f ./scripts/Makefile.modbuiltin obj=drivers/input
make -f ./scripts/Makefile.modbuiltin obj=net/xdp
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/hwtracing/intel_th/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/omapdrm/displays
make -f ./scripts/Makefile.modbuiltin obj=drivers/i2c/algos
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/i3c/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/omapdrm/dss
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware/tegra
make -f ./scripts/Makefile.modbuiltin obj=drivers/input/joystick
(for m in ; do echo $m; done; \
cat /dev/null ) > net/xdp/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/idle/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/omapdrm/displays/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/firmware/xilinx
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/panel
make -f ./scripts/Makefile.modbuiltin obj=net/xfrm
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/firmware/tegra/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/input/keyboard
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/i2c/algos/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/omapdrm/dss/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/i2c/busses
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/input/joystick/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/input/misc
(for m in ; do echo $m; done; \
cat /dev/null drivers/gpu/drm/omapdrm/displays/modules.builtin drivers/gpu/drm/
omapdrm/dss/modules.builtin) > drivers/gpu/drm/omapdrm/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/firmware/xilinx/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > net/xfrm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/input/mouse
make -f ./scripts/Makefile.modbuiltin obj=drivers/input/serio
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/panel/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null net/802/modules.builtin net/8021q/modules.builtin net/bpf/
modules.builtin net/bpfilter/modules.builtin net/core/modules.builtin net/dcb/
modules.builtin net/dns_resolver/modules.builtin net/ethernet/modules.builtin net/
ipv4/modules.builtin net/ipv6/modules.builtin net/l3mdev/modules.builtin net/mpfs/
modules.builtin net/ncsi/modules.builtin net/netfilter/modules.builtin net/netlabel/
modules.builtin net/netlink/modules.builtin net/packet/modules.builtin net/rfkill/
modules.builtin net/sched/modules.builtin net/strparser/modules.builtin net/switchdev/
```

```
modules.builtin net/unix/modules.builtin net/wireless/modules.builtin net/xdp/
modules.builtin net/xfrm/modules.builtin) > net/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/rcar-du
(for m in drivers/i2c/busses/i2c-designware-core.ko drivers/i2c/busses/i2c-designware-
platform.ko; do echo $m; done; \
cat /dev/null ) > drivers/i2c/busses/modules.builtin
(for m in drivers/input/keyboard/atkbd.ko; do echo $m; done; \
cat /dev/null ) > drivers/input/keyboard/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/tilcdc
make -f ./scripts/Makefile.modbuiltin obj=drivers/iommu
make -f ./scripts/Makefile.modbuiltin obj=drivers/i2c/muxes
(for m in drivers/input/misc/uinput.ko; do echo $m; done; \
cat /dev/null ) > drivers/input/misc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/firmware/efi/libstub/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/irqchip
(for m in drivers/firmware/efi/efivars.ko; do echo $m; done; \
cat /dev/null drivers/firmware/efi/libstub/modules.builtin) > drivers/firmware/efi/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/input/mouse/modules.builtin
(for m in drivers/input/serio/serio.ko drivers/input/serio/i8042.ko drivers/input/
serio/libps2.ko; do echo $m; done; \
cat /dev/null ) > drivers/input/serio/modules.builtin
(for m in drivers/iommu/iova.ko; do echo $m; done; \
cat /dev/null ) > drivers/iommu/modules.builtin
(for m in drivers/firmware/edd.ko; do echo $m; done; \
cat /dev/null drivers/firmware/broadcom/modules.builtin drivers/firmware/efi/
modules.builtin drivers/firmware/imx/modules.builtin drivers/firmware/meson/
modules.builtin drivers/firmware/psci/modules.builtin drivers/firmware/tegra/
modules.builtin drivers/firmware/xilinx/modules.builtin) > drivers/firmware/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/input/tablet
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/rcar-du/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/tiny
make -f ./scripts/Makefile.modbuiltin obj=drivers/gpu/drm/xen
make -f ./scripts/Makefile.modbuiltin obj=drivers/input/touchscreen
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/i2c/muxes/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/tilcdc/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/isdn
(for m in drivers/i2c/i2c-core.ko drivers/i2c/i2c-dev.ko; do echo $m; done; \
cat /dev/null drivers/i2c/algos/modules.builtin drivers/i2c/busses/modules.builtin
drivers/i2c/muxes/modules.builtin) > drivers/i2c/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/leds
make -f ./scripts/Makefile.modbuiltin obj=drivers/lightnvm
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/irqchip/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/macintosh
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/xen/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/input/tablet/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/gpu/drm/tiny/modules.builtin
(for m in drivers/input/touchscreen/of_touchscreen.ko drivers/input/touchscreen/
elants_i2c.ko; do echo $m; done; \
cat /dev/null ) > drivers/input/touchscreen/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/mailbox
make -f ./scripts/Makefile.modbuiltin obj=drivers/md
```

```
(for m in drivers/gpu/drm/drm_panel_orientation_quirks.ko; do echo $m; done; \
cat /dev/null drivers/gpu/drm/arm/modules.builtin drivers/gpu/drm/bridge/
modules.builtin drivers/gpu/drm/hisilicon/modules.builtin drivers/gpu/drm/i2c/
modules.builtin drivers/gpu/drm/omapdrm/modules.builtin drivers/gpu/drm/panel/
modules.builtin drivers/gpu/drm/rcar-du/modules.builtin drivers/gpu/drm/tilcdc/
modules.builtin drivers/gpu/drm/tiny/modules.builtin drivers/gpu/drm/xen/
modules.builtin) > drivers/gpu/drm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/isdn/hardware
(for m in drivers/input/input-core.ko drivers/input/mousedev.ko drivers/input/
evdev.ko; do echo $m; done; \
cat /dev/null drivers/input/joystick/modules.builtin drivers/input/keyboard/
modules.builtin drivers/input/misc/modules.builtin drivers/input/mouse/
modules.builtin drivers/input/tablet/modules.builtin drivers/input/touchscreen/
modules.builtin) > drivers/input/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/leds/trigger
make -f ./scripts/Makefile.modbuiltin obj=drivers/media
(for m in ; do echo $m; done; \
cat /dev/null drivers/gpu/drm/modules.builtin drivers/gpu/vga/modules.builtin) >
drivers/gpu/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/lightnvm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/memory
make -f ./scripts/Makefile.modbuiltin obj=drivers/message
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/mailbox/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/macintosh/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/mfd
make -f ./scripts/Makefile.modbuiltin obj=drivers/misc
(for m in drivers/md/md-mod.ko drivers/md/dm-mod.ko; do echo $m; done; \
cat /dev/null ) > drivers/md/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/mmc
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/isdn/hardware/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/cec
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/leds/trigger/modules.builtin
(for m in drivers/leds/led-class.ko; do echo $m; done; \
cat /dev/null drivers/leds/trigger/modules.builtin) > drivers/leds/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/isdn/hardware/modules.builtin) > drivers/isdn/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/memory/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net
make -f ./scripts/Makefile.modbuiltin obj=drivers/nfc
make -f ./scripts/Makefile.modbuiltin obj=drivers/nvdim
make -f ./scripts/Makefile.modbuiltin obj=drivers/message/fusion
(for m in drivers/mfd/tps65912-core.ko drivers/mfd/tps65912-i2c.ko drivers/mfd/
tps65912-spi.ko drivers/mfd/mfd-core.ko drivers/mfd/da9063.ko drivers/mfd/max14577.ko
drivers/mfd/max77693.ko drivers/mfd/sec-core.ko drivers/mfd/sec-irq.ko; do echo $m;
done; \
cat /dev/null ) > drivers/mfd/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/misc/cardreader
make -f ./scripts/Makefile.modbuiltin obj=drivers/mmc/core
(for m in drivers/media/cec/cec.ko; do echo $m; done; \
cat /dev/null ) > drivers/media/cec/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/common
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/dsa
make -f ./scripts/Makefile.modbuiltin obj=drivers/mmc/host
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/nfc/modules.builtin
(for m in drivers/nvdim/libnvdim.ko drivers/nvdim/nd_e820.ko; do echo $m;
```

```
done; \
cat /dev/null ) > drivers/nvdim/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/misc/cb710
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/firewire
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/message/fusion/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/misc/cardreader/modules.builtin
(for m in drivers/mmc/core/mmc_core.ko; do echo $m; done; \
cat /dev/null ) > drivers/mmc/core/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/message/fusion/modules.builtin) > drivers/message/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/i2c
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/common/b2c2
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/common/saa7146
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/misc/cb710/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/misc/eeprom
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/mmc/host/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/dsa/b53
(for m in ; do echo $m; done; \
cat /dev/null drivers/mmc/core/modules.builtin drivers/mmc/host/modules.builtin) >
drivers/mmc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/firewire/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/misc/lis3lv02d
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/common/siano
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/common/b2c2/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/i2c/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/nvme
make -f ./scripts/Makefile.modbuiltin obj=drivers/nvmem
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/common/saa7146/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/3com
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/dsa/b53/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/misc/eeprom/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/opp
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/dsa/microchip
make -f ./scripts/Makefile.modbuiltin obj=drivers/pci
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/misc/lis3lv02d/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/misc/mic
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/common/siano/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/nvmem/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/common/v4l2-tpg
make -f ./scripts/Makefile.modbuiltin obj=drivers/misc/ti-st
make -f ./scripts/Makefile.modbuiltin obj=drivers/nvme/host
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/3com/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/8390
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/opp/modules.builtin
(for m in ; do echo $m; done; \
```

```
cat /dev/null ) > drivers/net/dsa/microchip/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/adaptec
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/dsa/mv88e6xxx
make -f ./scripts/Makefile.modbuiltin obj=drivers/pci/controller
make -f ./scripts/Makefile.modbuiltin obj=drivers/misc/mic/bus
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/common/v4l2-tpg/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/common/videobuf2
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/misc/ti-st/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pci/endpoint
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/8390/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/nvme/host/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/dsa/mv88e6xxx/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/adaptec/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/nvme/target
make -f ./scripts/Makefile.modbuiltin obj=drivers/perf
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/dsa/sja1105
make -f ./scripts/Makefile.modbuiltin obj=drivers/pci/controller/dwc
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/agere
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/misc/mic/bus/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/common/videobuf2/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/misc/mic/bus/modules.builtin) > drivers/misc/mic/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/media/common/b2c2/modules.builtin drivers/media/common/saa7146/
modules.builtin drivers/media/common/siano/modules.builtin drivers/media/common/v4l2-
tpg/modules.builtin drivers/media/common/videobuf2/modules.builtin) > drivers/media/
common/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/misc/cardreader/modules.builtin drivers/misc/cb710/
modules.builtin drivers/misc/eeprom/modules.builtin drivers/misc/lis3lv02d/
modules.builtin drivers/misc/mic/modules.builtin drivers/misc/ti-st/modules.builtin)
> drivers/misc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/nvme/target/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/mmc
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci
(for m in ; do echo $m; done; \
cat /dev/null drivers/nvme/host/modules.builtin drivers/nvme/target/modules.builtin)
> drivers/nvme/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pci/endpoint/functions
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/alacritech
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pci/controller/dwc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/perf/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/agere/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pci/hotplug
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform
(for m in ; do echo $m; done; \
cat /dev/null drivers/pci/controller/dwc/modules.builtin) > drivers/pci/controller/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/dsa/sja1105/modules.builtin
```

```
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/rc
(for m in ; do echo $m; done; \
cat /dev/null drivers/net/dsa/b53/modules.builtin drivers/net/dsa/microchip/
modules.builtin drivers/net/dsa/mv88e6xxx/modules.builtin drivers/net/dsa/sjall105/
modules.builtin) > drivers/net/dsa/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pci/pcie
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pci/endpoint/functions/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/mmc/siano
(for m in ; do echo $m; done; \
cat /dev/null drivers/pci/endpoint/functions/modules.builtin) > drivers/pci/endpoint/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/b2c2
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/alacritech/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/cadence
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pci/hotplug/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/alteon
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/cros-ec-cec
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/mmc/siano/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/rc/keymaps
(for m in ; do echo $m; done; \
cat /dev/null drivers/media/mmc/siano/modules.builtin) > drivers/media/mmc/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pci/pcie/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/davinci
make -f ./scripts/Makefile.modbuiltin obj=drivers/pci/switch
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/pci/b2c2/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/platform/cadence/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/broadcom
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/amazon
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/ddbridge
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/alteon/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/platform/cros-ec-cec/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/cadence
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/amd
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/rc/keymaps/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/amazon/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/media/rc/keymaps/modules.builtin) > drivers/media/rc/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/platform/davinci/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/dm1105
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/meson
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/intel
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pci/switch/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/pci/controller/modules.builtin drivers/pci/endpoint/
modules.builtin drivers/pci/hotplug/modules.builtin drivers/pci/pcie/modules.builtin
drivers/pci/switch/modules.builtin) > drivers/pci/modules.builtin
```

```
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/phy/broadcom/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/freescale
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/media/pci/ddbridge/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/mantis
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/net/ethernet/amd/modules.builtin
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/phy/cadence/modules.builtin
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/media/platform/meson/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/aquantia
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/netup_unidvb
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/media/pci/dm1105/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/omap
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/stm32
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/intel/ipu3
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/actions
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/phy/freescale/modules.builtin
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/media/pci/mantis/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/hisilicon
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/sunxi
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/net/ethernet/aquantia/modules.builtin
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/media/platform/omap/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/arc
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/media/pci/netup_unidvb/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/lantiq
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/media/pci/intel/ipu3/modules.builtin
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/media/platform/stm32/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/marvell
(for m in ; do echo $m; done;  \
cat /dev/null drivers/media/pci/intel/ipu3/modules.builtin) > drivers/media/pci/intel/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/motorola
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/pinctrl/actions/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/bcm
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/ngene
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/phy/hisilicon/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/sunxi/sun4i-csi
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/platform/sunxi/sun6i-csi
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/net/ethernet/arc/modules.builtin
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/phy/lantiq/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/atheros
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/fddi
(for m in ; do echo $m; done;  \
cat /dev/null ) > drivers/phy/marvell/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/cirrus
(for m in ; do echo $m; done;  \
```

```
cat /dev/null ) > drivers/phy/motorola/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pinctrl/bcm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/mscc
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/qualcomm
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/pci/ngene/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/pluto2
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/platform/sunxi/sun4i-csi/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/platform/sunxi/sun6i-csi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/pt1
(for m in ; do echo $m; done; \
cat /dev/null drivers/media/platform/sunxi/sun4i-csi/modules.builtin drivers/media/
platform/sunxi/sun6i-csi/modules.builtin) > drivers/media/platform/sunxi/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/atheros/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/fddi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/aurora
(for m in ; do echo $m; done; \
cat /dev/null drivers/media/platform/cadence/modules.builtin drivers/media/platform/
cros-ec-cec/modules.builtin drivers/media/platform/davinci/modules.builtin drivers/
media/platform/meson/modules.builtin drivers/media/platform/omap/modules.builtin
drivers/media/platform/stm32/modules.builtin drivers/media/platform/sunxi/
modules.builtin) > drivers/media/platform/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/freescale
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pinctrl/cirrus/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/phy/qualcomm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/pt3
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/phy/mscc/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/platform
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/intel
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/ralink
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/pci/pt1/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/pci/pluto2/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/mediatek
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/hamradio
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/aurora/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pinctrl/freescale/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/broadcom
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/pci/pt3/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/phy
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/saa7146
make -f ./scripts/Makefile.modbuiltin obj=drivers/platform/chrome
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/phy/ralink/modules.builtin
(for m in drivers/pinctrl/intel/pinctrl-cherryview.ko; do echo $m; done; \
cat /dev/null ) > drivers/pinctrl/intel/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/samsung
make -f ./scripts/Makefile.modbuiltin obj=drivers/platform/mellanox
(for m in ; do echo $m; done; \
```

```
cat /dev/null ) > drivers/pinctrl/mediatek/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/hamradio/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/mvebu
make -f ./scripts/Makefile.modbuiltin obj=drivers/platform/x86
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/broadcom/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/platform/chrome/modules.builtin
(for m in drivers/net/phy/libphy.ko drivers/net/phy/fixed_phy.ko; do echo $m;
done; \
cat /dev/null ) > drivers/net/phy/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/brocade
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/smipcie
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/pci/saa7146/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/pci/ttpci
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/nomadik
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/phy/samsung/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/platform/mellanox/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/socionext
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pinctrl/mvebu/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ppp
(for m in drivers/platform/x86/intel_pmc_core.ko drivers/platform/x86/
intel_pmc_core_pltdrv.ko; do echo $m; done; \
cat /dev/null ) > drivers/platform/x86/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pnp
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/pci/ttpci/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/platform/chrome/modules.builtin drivers/platform/mellanox/
modules.builtin drivers/platform/x86/modules.builtin) > drivers/platform/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/brocade/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/power
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cadence
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/spi
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/pci/smipcie/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/media/pci/b2c2/modules.builtin drivers/media/pci/ddbridge/
modules.builtin drivers/media/pci/dm1105/modules.builtin drivers/media/pci/intel/
modules.builtin drivers/media/pci/mantis/modules.builtin drivers/media/pci/
netup_unidvb/modules.builtin drivers/media/pci/ngene/modules.builtin drivers/media/
pci/pluto2/modules.builtin drivers/media/pci/pt1/modules.builtin drivers/media/pci/
pt3/modules.builtin drivers/media/pci/saa7146/modules.builtin drivers/media/pci/
smipcie/modules.builtin drivers/media/pci/ttpci/modules.builtin) > drivers/media/pci/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pinctrl/nomadik/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/tuners
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/phy/socionext/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/sprd
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/st
(for m in drivers/net/ppp/ppp_generic.ko; do echo $m; done; \
cat /dev/null ) > drivers/net/ppp/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pnp/pnpacpi
```

```
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/slip
make -f ./scripts/Makefile.modbuiltin obj=drivers/power/avs
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/cadence/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/spi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cavium
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/chelsio
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/tuners/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pinctrl/sprd/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pinctrl/ti
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/phy/st/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pnp/pnpacpi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/phy/ti
(for m in ; do echo $m; done; \
cat /dev/null drivers/pnp/pnpacpi/modules.builtin) > drivers/pnp/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cirrus
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/power/avs/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/power/reset
(for m in drivers/net/slip/slhc.ko; do echo $m; done; \
cat /dev/null ) > drivers/net/slip/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/chelsio/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cavium/common
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cisco
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/b2c2
make -f ./scripts/Makefile.modbuiltin obj=drivers/powercap
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pinctrl/ti/modules.builtin
(for m in drivers/pinctrl/pinctrl-amd.ko; do echo $m; done; \
cat /dev/null drivers/pinctrl/actions/modules.builtin drivers/pinctrl/bcm/
modules.builtin drivers/pinctrl/cirrus/modules.builtin drivers/pinctrl/freescale/
modules.builtin drivers/pinctrl/intel/modules.builtin drivers/pinctrl/mediatek/
modules.builtin drivers/pinctrl/mvebu/modules.builtin drivers/pinctrl/nomadik/
modules.builtin drivers/pinctrl/sprd/modules.builtin drivers/pinctrl/ti/
modules.builtin) > drivers/pinctrl/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/phy/ti/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wan
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/cirrus/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/phy/broadcom/modules.builtin drivers/phy/cadence/
modules.builtin drivers/phy/freescale/modules.builtin drivers/phy/hisilicon/
modules.builtin drivers/phy/lantiq/modules.builtin drivers/phy/marvell/
modules.builtin drivers/phy/motorola/modules.builtin drivers/phy/mscc/modules.builtin
drivers/phy/qualcomm/modules.builtin drivers/phy/ralink/modules.builtin drivers/phy/
samsung/modules.builtin drivers/phy/socionext/modules.builtin drivers/phy/st/
modules.builtin drivers/phy/ti/modules.builtin) > drivers/phy/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/power/reset/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/cisco/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/power/supply
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cavium/liquidio
(for m in ; do echo $m; done; \
```

```
cat /dev/null ) > drivers/net/ethernet/cavium/common/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cortina
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/dvb-usb
make -f ./scripts/Makefile.modbuiltin obj=drivers/pps
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/usb/b2c2/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/powercap/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/ptp
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cavium/octeon
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wan/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/cavium/thunder
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/power/supply/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/cavium/liquidio/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/usb/dvb-usb/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/cortina/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pps/clients
(for m in ; do echo $m; done; \
cat /dev/null drivers/power/avs/modules.builtin drivers/power/reset/modules.builtin
drivers/power/supply/modules.builtin) > drivers/power/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pps/generators
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/dvb-usb-v2
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/s2255
(for m in drivers/ptp/ptp.ko; do echo $m; done; \
cat /dev/null ) > drivers/ptp/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/cavium/octeon/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/siano
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/cavium/thunder/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/dec
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/usb/dvb-usb-v2/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pps/generators/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/pwm
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/pps/clients/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/net/ethernet/cavium/common/modules.builtin drivers/net/ethernet/
cavium/liquidio/modules.builtin drivers/net/ethernet/cavium/octeon/modules.builtin
drivers/net/ethernet/cavium/thunder/modules.builtin) > drivers/net/ethernet/cavium/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/stkwebcam
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/usb/s2255/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/admtek
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/ath
(for m in drivers/pps/pps_core.ko; do echo $m; done; \
cat /dev/null drivers/pps/clients/modules.builtin drivers/pps/generators/
modules.builtin) > drivers/pps/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/dec/tulip
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/usb/siano/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/atmel
(for m in ; do echo $m; done; \
```

```
cat /dev/null ) > drivers/media/usb/stkwebcam/modules.builtin
(for m in drivers/pwm/pwm-lpss.ko drivers/pwm/pwm-lpss-pci.ko drivers/pwm/pwm-lpss-
platform.ko; do echo $m; done; \
cat /dev/null ) > drivers/pwm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/broadcom
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/ttusb-budget
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/admtek/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/cisco
make -f ./scripts/Makefile.modbuiltin obj=drivers/rapidio
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/dec/tulip/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/ath/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/dlink
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/intel
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/cisco/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/atmel/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/broadcom/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/ras
make -f ./scripts/Makefile.modbuiltin obj=drivers/rapidio/devices
(for m in ; do echo $m; done; \
cat /dev/null drivers/net/ethernet/dec/tulip/modules.builtin) > drivers/net/ethernet/
dec/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/regulator
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/intersil
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/usb/ttusb-budget/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/dlink/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/emulex
make -f ./scripts/Makefile.modbuiltin obj=drivers/remoteproc
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/ttusb-dec
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/intel/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/media/usb/zr364xx
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/rapidio/devices/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/ras/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/regulator/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/rapidio/switches
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/ezchip
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/fujitsu
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/intersil/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/marvell
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/emulex/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/remoteproc/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/mediatek
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/google
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/usb/ttusb-dec/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/media/usb/zr364xx/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/quantenna
```

```
(for m in ; do echo $m; done; \
cat /dev/null drivers/media/usb/b2c2/modules.builtin drivers/media/usb/dvb-usb/
modules.builtin drivers/media/usb/dvb-usb-v2/modules.builtin drivers/media/usb/s2255/
modules.builtin drivers/media/usb/siano/modules.builtin drivers/media/usb/stkwebcam/
modules.builtin drivers/media/usb/ttusb-budget/modules.builtin drivers/media/usb/
ttusb-dec/modules.builtin drivers/media/usb/zr364xx/modules.builtin) > drivers/media/
usb/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/fujitsu/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/ezchip/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/rapidio/switches/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/media/cec/modules.builtin drivers/media/common/modules.builtin
drivers/media/firewire/modules.builtin drivers/media/i2c/modules.builtin drivers/
media/mmc/modules.builtin drivers/media/pci/modules.builtin drivers/media/platform/
modules.builtin drivers/media/rc/modules.builtin drivers/media/spi/modules.builtin
drivers/media/tuners/modules.builtin drivers/media/usb/modules.builtin) > drivers/
media/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/reset
make -f ./scripts/Makefile.modbuiltin obj=drivers/rtc
(for m in drivers/rapidio/rapidio.ko; do echo $m; done; \
cat /dev/null drivers/rapidio/devices/modules.builtin drivers/rapidio/switches/
modules.builtin) > drivers/rapidio/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/marvell/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/scsi
make -f ./scripts/Makefile.modbuiltin obj=drivers/sfi
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/mediatek/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/hp
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/google/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/spi
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/quantenna/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/ralink
make -f ./scripts/Makefile.modbuiltin obj=drivers/scsi/device_handler
make -f ./scripts/Makefile.modbuiltin obj=drivers/reset/hisilicon
(for m in drivers/rtc/rtc-cmos.ko; do echo $m; done; \
cat /dev/null ) > drivers/rtc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/sfi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/amlogic
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/hp/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/realtek
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/bcm
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/huawei
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/ralink/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/spi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/i825xx
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/rsi
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/scsi/device_handler/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/bcm/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/scsi/megaraid
```

```
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/reset/hisilicon/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/st
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/amlogic/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/reset/hisilicon/modules.builtin) > drivers/reset/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/fsl
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/mediatek
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/huawei/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/qcom
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/i825xx/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/realtek/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/intel
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/rsi/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/marvell
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/mellanox
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/scsi/megaraid/modules.builtin
(for m in drivers/scsi/scsi_mod.ko drivers/scsi/sd_mod.ko drivers/scsi/sr_mod.ko
drivers/scsi/sg.ko; do echo $m; done; \
cat /dev/null drivers/scsi/device_handler/modules.builtin drivers/scsi/megaraid/
modules.builtin) > drivers/scsi/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/st/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/mediatek/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/ti
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/fsl/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/wireless/zydas
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/qcom/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/intel/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/thermal
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/mellanox/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/renesas
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/micrel
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/marvell/octeontx2
make -f ./scripts/Makefile.modbuiltin obj=drivers/tty
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/ti/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging/android
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/wireless/zydas/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging/kpc2000
(for m in ; do echo $m; done; \
cat /dev/null drivers/net/wireless/admtek/modules.builtin drivers/net/wireless/ath/
modules.builtin drivers/net/wireless/atmel/modules.builtin drivers/net/wireless/
broadcom/modules.builtin drivers/net/wireless/cisco/modules.builtin drivers/net/
wireless/intel/modules.builtin drivers/net/wireless/intersil/modules.builtin drivers/
net/wireless/marvell/modules.builtin drivers/net/wireless/mediatek/modules.builtin
drivers/net/wireless/quantenna/modules.builtin drivers/net/wireless/ralink/
modules.builtin drivers/net/wireless/realtek/modules.builtin drivers/net/wireless/rsi/
modules.builtin drivers/net/wireless/st/modules.builtin drivers/net/wireless/ti/
```

```
modules.builtin drivers/net/wireless/zydas/modules.builtin) > drivers/net/wireless/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/thermal/broadcom
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging/media
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/micrel/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/tty/hvc
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/renesas/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/marvell/octeontx2/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging/android/ion
(for m in ; do echo $m; done; \
cat /dev/null drivers/net/ethernet/marvell/octeontx2/modules.builtin) > drivers/net/
ethernet/marvell/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/tty/ipwireless
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/sunxi
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging/kpc2000/kpc2000
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/microchip
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/staging/media/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/thermal/broadcom/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/tty/hvc/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/tty/serdev
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/staging/android/ion/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/thermal/intel
make -f ./scripts/Makefile.modbuiltin obj=drivers/thermal/samsung
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/sunxi/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/staging/android/ion/modules.builtin) > drivers/staging/android/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/microchip/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/ti
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/mscc
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/staging/kpc2000/kpc2000/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/tty/ipwireless/modules.builtin
(for m in drivers/tty/serdev/serdev.ko; do echo $m; done; \
cat /dev/null ) > drivers/tty/serdev/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/staging/kpc2000/kpc2000/modules.builtin) > drivers/staging/
kpc2000/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/thermal/st
make -f ./scripts/Makefile.modbuiltin obj=drivers/tty/serial
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging/unisys
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/thermal/intel/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/thermal/samsung/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb/common
make -f ./scripts/Makefile.modbuiltin obj=drivers/tty/vt
make -f ./scripts/Makefile.modbuiltin obj=drivers/vfio
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/ti/modules.builtin
(for m in ; do echo $m; done; \
```

```
cat /dev/null ) > drivers/net/ethernet/mscc/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/myricom
make -f ./scripts/Makefile.modbuiltin obj=drivers/soc/xilinx
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/thermal/st/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/thermal/tegra
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/staging/unisys/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/tty/serial/8250
make -f ./scripts/Makefile.modbuiltin obj=drivers/vfio/pci
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging/vme
(for m in drivers/usb/common/usb-common.ko; do echo $m; done; \
cat /dev/null ) > drivers/usb/common/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/tty/vt/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb/core
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb/dwc2
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/myricom/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/natsemi
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/soc/xilinx/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/soc/amlogic/modules.builtin drivers/soc/bcm/modules.builtin
drivers/soc/fsl/modules.builtin drivers/soc/mediatek/modules.builtin drivers/soc/qcom/
modules.builtin drivers/soc/renesas/modules.builtin drivers/soc/sunxi/modules.builtin
drivers/soc/ti/modules.builtin drivers/soc/xilinx/modules.builtin) > drivers/soc/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/thermal/tegra/modules.builtin
(for m in drivers/vfio/pci/vfio-pci.ko; do echo $m; done; \
cat /dev/null ) > drivers/vfio/pci/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/staging/vme/devices
(for m in drivers/tty/serial/8250/8250.ko drivers/tty/serial/8250/8250_base.ko
drivers/tty/serial/8250/8250_pci.ko; do echo $m; done; \
cat /dev/null ) > drivers/tty/serial/8250/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/thermal/broadcom/modules.builtin drivers/thermal/intel/
modules.builtin drivers/thermal/samsung/modules.builtin drivers/thermal/st/
modules.builtin drivers/thermal/tegra/modules.builtin) > drivers/thermal/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/video
(for m in drivers/vfio/vfio.ko drivers/vfio/vfio_virqfd.ko drivers/vfio/
vfio_iommu_type1.ko; do echo $m; done; \
cat /dev/null drivers/vfio/pci/modules.builtin) > drivers/vfio/modules.builtin
(for m in drivers/tty/serial/serial_core.ko drivers/tty/serial/max310x.ko drivers/tty/
serial/sccnxp.ko drivers/tty/serial/serial_mctrl_gpio.ko drivers/tty/serial/
kgdboc.ko; do echo $m; done; \
cat /dev/null drivers/tty/serial/8250/modules.builtin) > drivers/tty/serial/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb/early
(for m in drivers/usb/core/usbcore.ko; do echo $m; done; \
cat /dev/null ) > drivers/usb/core/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/tty/hvc/modules.builtin drivers/tty/ipwireless/modules.builtin
drivers/tty/serdev/modules.builtin drivers/tty/serial/modules.builtin drivers/tty/vt/
modules.builtin) > drivers/tty/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb/host
make -f ./scripts/Makefile.modbuiltin obj=drivers/virt
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb/misc
(for m in drivers/usb/dwc2/dwc2.ko; do echo $m; done; \
cat /dev/null ) > drivers/usb/dwc2/modules.builtin
```

```
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/natsemi/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/staging/vme/devices/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/neterion
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/netronome
(for m in ; do echo $m; done; \
cat /dev/null drivers/staging/vme/devices/modules.builtin) > drivers/staging/vme/
modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/video/backlight
(for m in ; do echo $m; done; \
cat /dev/null drivers/staging/android/modules.builtin drivers/staging/kpc2000/
modules.builtin drivers/staging/media/modules.builtin drivers/staging/unisys/
modules.builtin drivers/staging/vme/modules.builtin) > drivers/staging/modules.builtin
(for m in drivers/usb/host/ehci-hcd.ko drivers/usb/host/ehci-pci.ko drivers/usb/host/
ehci-platform.ko drivers/usb/host/ohci-hcd.ko drivers/usb/host/ohci-pci.ko drivers/
usb/host/ohci-platform.ko drivers/usb/host/uhci-hcd.ko drivers/usb/host/xhci-hcd.ko
drivers/usb/host/xhci-pci.ko; do echo $m; done; \
cat /dev/null ) > drivers/usb/host/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/video/console
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/usb/early/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/video/fbdev
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/usb/misc/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/virt/vboxguest
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/ni
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/neterion/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb/phy
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/nvidia
(for m in drivers/video/backlight/backlight.ko; do echo $m; done; \
cat /dev/null ) > drivers/video/backlight/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/video/console/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/oki-semi
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/netronome/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/usb/storage
make -f ./scripts/Makefile.modbuiltin obj=drivers/virtio
make -f ./scripts/Makefile.modbuiltin obj=drivers/video/fbdev/core
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/virt/vboxguest/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/virt/vboxguest/modules.builtin) > drivers/virt/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/ni/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/video/fbdev/omap2
make -f ./scripts/Makefile.modbuiltin obj=drivers/vme
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/usb/phy/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/nvidia/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/watchdog
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/packetengines
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/oki-semi/modules.builtin
(for m in drivers/virtio/virtio.ko drivers/virtio/virtio_ring.ko drivers/virtio/
virtio_mmio.ko drivers/virtio/virtio_pci.ko drivers/virtio/virtio_balloon.ko; do echo
$m; done; \
cat /dev/null ) > drivers/virtio/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/xen
```

```
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/pensando
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/usb/storage/modules.builtin
(for m in drivers/video/fbdev/core/fb.ko drivers/video/fbdev/core/cfbfillrect.ko
drivers/video/fbdev/core/cfbcopyarea.ko drivers/video/fbdev/core/cfbimgblt.ko; do
echo $m; done; \
cat /dev/null ) > drivers/video/fbdev/core/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/qlogic
(for m in ; do echo $m; done; \
cat /dev/null drivers/usb/common/modules.builtin drivers/usb/core/modules.builtin
drivers/usb/dwc2/modules.builtin drivers/usb/early/modules.builtin drivers/usb/host/
modules.builtin drivers/usb/misc/modules.builtin drivers/usb/phy/modules.builtin
drivers/usb/storage/modules.builtin) > drivers/usb/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/video/fbdev/omap2/omapfb
make -f ./scripts/Makefile.modbuiltin obj=drivers/vme/boards
make -f ./scripts/Makefile.modbuiltin obj=drivers/vme/bridges
(for m in drivers/watchdog/watchdog.ko drivers/watchdog/pretimeout_noop.ko; do echo
$m; done; \
cat /dev/null ) > drivers/watchdog/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/packetengines/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/qualcomm
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/pensando/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/rdc
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/realtek
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/qlogic/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/renesas
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/vme/boards/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/rocker
make -f ./scripts/Makefile.modbuiltin obj=drivers/video/fbdev/omap2/omapfb/displays
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/vme/bridges/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/vme/boards/modules.builtin drivers/vme/bridges/modules.builtin)
> drivers/vme/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/qualcomm/emacs
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/rdc/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/samsung
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/realtek/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/xen/events
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/seeq
make -f ./scripts/Makefile.modbuiltin obj=drivers/video/fbdev/omap2/omapfb/dss
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/video/fbdev/omap2/omapfb/displays/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/renesas/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/xen/xenbus
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/rocker/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/sfc
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/silan
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/qualcomm/emacs/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/xen/events/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/video/fbdev/omap2/omapfb/dss/modules.builtin
```

```
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/samsung/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/net/ethernet/qualcomm/emacs/modules.builtin) > drivers/net/
ethernet/qualcomm/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/video/fbdev/omap2/omapfb/displays/modules.builtin drivers/video/
fbdev/omap2/omapfb/dss/modules.builtin) > drivers/video/fbdev/omap2/omapfb/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/seeq/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/video/fbdev/omap2/omapfb/modules.builtin) > drivers/video/fbdev/
omap2/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/sis
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/smsc
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/socionext
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/sfc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/silan/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/stmicro
(for m in ; do echo $m; done; \
cat /dev/null drivers/video/fbdev/core/modules.builtin drivers/video/fbdev/omap2/
modules.builtin) > drivers/video/fbdev/modules.builtin
(for m in drivers/xen/xenbus/xenbus_probe_frontend.ko; do echo $m; done; \
cat /dev/null ) > drivers/xen/xenbus/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/video/backlight/modules.builtin drivers/video/console/
modules.builtin drivers/video/fbdev/modules.builtin) > drivers/video/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/sun
(for m in drivers/xen/xen-acpi-processor.ko; do echo $m; done; \
cat /dev/null drivers/xen/events/modules.builtin drivers/xen/xenbus/modules.builtin)
> drivers/xen/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/smsc/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/sis/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/synopsys
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/tehuti
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/ti
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/via
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/wiznet
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/stmicro/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/xilinx
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/socionext/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/sun/modules.builtin
make -f ./scripts/Makefile.modbuiltin obj=drivers/net/ethernet/xircom
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/synopsys/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/ti/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/via/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/wiznet/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/tehuti/modules.builtin
(for m in ; do echo $m; done; \
```

```
cat /dev/null ) > drivers/net/ethernet/xilinx/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null ) > drivers/net/ethernet/xircom/modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/net/ethernet/3com/modules.builtin drivers/net/ethernet/8390/
modules.builtin drivers/net/ethernet/adaptec/modules.builtin drivers/net/ethernet/
agere/modules.builtin drivers/net/ethernet/alacritech/modules.builtin drivers/net/
ethernet/alteon/modules.builtin drivers/net/ethernet/amazon/modules.builtin drivers/
net/ethernet/amd/modules.builtin drivers/net/ethernet/aquantia/modules.builtin
drivers/net/ethernet/arc/modules.builtin drivers/net/ethernet/atheros/modules.builtin
drivers/net/ethernet/aurora/modules.builtin drivers/net/ethernet/broadcom/
modules.builtin drivers/net/ethernet/brocade/modules.builtin drivers/net/ethernet/
cadence/modules.builtin drivers/net/ethernet/cavium/modules.builtin drivers/net/
ethernet/chelsio/modules.builtin drivers/net/ethernet/cirrus/modules.builtin drivers/
net/ethernet/cisco/modules.builtin drivers/net/ethernet/cortina/modules.builtin
drivers/net/ethernet/dec/modules.builtin drivers/net/ethernet/dlink/modules.builtin
drivers/net/ethernet/emulex/modules.builtin drivers/net/ethernet/ezchip/
modules.builtin drivers/net/ethernet/fujitsu/modules.builtin drivers/net/ethernet/
google/modules.builtin drivers/net/ethernet/hp/modules.builtin drivers/net/ethernet/
huawei/modules.builtin drivers/net/ethernet/i825xx/modules.builtin drivers/net/
ethernet/intel/modules.builtin drivers/net/ethernet/marvell/modules.builtin drivers/
net/ethernet/mellanox/modules.builtin drivers/net/ethernet/micrel/modules.builtin
drivers/net/ethernet/microchip/modules.builtin drivers/net/ethernet/mscc/
modules.builtin drivers/net/ethernet/myricom/modules.builtin drivers/net/ethernet/
natsemi/modules.builtin drivers/net/ethernet/neterion/modules.builtin drivers/net/
ethernet/netronome/modules.builtin drivers/net/ethernet/ni/modules.builtin drivers/
net/ethernet/nvidia/modules.builtin drivers/net/ethernet/oki-semi/modules.builtin
drivers/net/ethernet/packetengines/modules.builtin drivers/net/ethernet/pensando/
modules.builtin drivers/net/ethernet/qlogic/modules.builtin drivers/net/ethernet/
qualcomm/modules.builtin drivers/net/ethernet/rdc/modules.builtin drivers/net/
ethernet/realtek/modules.builtin drivers/net/ethernet/renesas/modules.builtin drivers/
net/ethernet/rocker/modules.builtin drivers/net/ethernet/samsung/modules.builtin
drivers/net/ethernet/seq/modules.builtin drivers/net/ethernet/sfc/modules.builtin
drivers/net/ethernet/silan/modules.builtin drivers/net/ethernet/sis/modules.builtin
drivers/net/ethernet/smc/modules.builtin drivers/net/ethernet/socionext/
modules.builtin drivers/net/ethernet/stmicro/modules.builtin drivers/net/ethernet/sun/
modules.builtin drivers/net/ethernet/synopsys/modules.builtin drivers/net/ethernet/
tehuti/modules.builtin drivers/net/ethernet/ti/modules.builtin drivers/net/ethernet/
via/modules.builtin drivers/net/ethernet/wiznet/modules.builtin drivers/net/ethernet/
xilinx/modules.builtin drivers/net/ethernet/xircom/modules.builtin) > drivers/net/
ethernet/modules.builtin
(for m in drivers/net/tun.ko drivers/net/xen-netfront.ko; do echo $m; done; \
cat /dev/null drivers/net/dsa/modules.builtin drivers/net/ethernet/modules.builtin
drivers/net/fddi/modules.builtin drivers/net/hamradio/modules.builtin drivers/net/phy/
modules.builtin drivers/net/ppp/modules.builtin drivers/net/slip/modules.builtin
drivers/net/wan/modules.builtin drivers/net/wireless/modules.builtin) > drivers/net/
modules.builtin
(for m in ; do echo $m; done; \
cat /dev/null drivers/acpi/modules.builtin drivers/amba/modules.builtin drivers/
android/modules.builtin drivers/ata/modules.builtin drivers/auxdisplay/
modules.builtin drivers/base/modules.builtin drivers/block/modules.builtin drivers/
bus/modules.builtin drivers/cdrom/modules.builtin drivers/char/modules.builtin
drivers/char/ipmi/modules.builtin drivers/clk/modules.builtin drivers/clocksource/
modules.builtin drivers/connector/modules.builtin drivers/cpufreq/modules.builtin
drivers/cpuidle/modules.builtin drivers/crypto/modules.builtin drivers/dax/
modules.builtin drivers/devfreq/modules.builtin drivers/dma/modules.builtin drivers/
dma-buf/modules.builtin drivers/edac/modules.builtin drivers/eisa/modules.builtin
drivers/extcon/modules.builtin drivers/firewire/modules.builtin drivers/firmware/
modules.builtin drivers/gpio/modules.builtin drivers/gpu/modules.builtin drivers/
hwmmon/modules.builtin drivers/hwspinlock/modules.builtin drivers/hwtracing/intel_th/
modules.builtin drivers/i2c/modules.builtin drivers/i3c/modules.builtin drivers/idle/
modules.builtin drivers/input/modules.builtin drivers/input/serio/modules.builtin
```

```
drivers/iommu/modules.builtin drivers/irqchip/modules.builtin drivers/isdn/
modules.builtin drivers/leds/modules.builtin drivers/lightnvm/modules.builtin drivers/
macintosh/modules.builtin drivers/mailbox/modules.builtin drivers/md/modules.builtin
drivers/media/modules.builtin drivers/memory/modules.builtin drivers/message/
modules.builtin drivers/mfd/modules.builtin drivers/misc/modules.builtin drivers/mmc/
modules.builtin drivers/net/modules.builtin drivers/nfc/modules.builtin drivers/
nvdimm/modules.builtin drivers/nvme/modules.builtin drivers/nvmem/modules.builtin
drivers/opp/modules.builtin drivers/pci/modules.builtin drivers/perf/modules.builtin
drivers/phy/modules.builtin drivers/pinctrl/modules.builtin drivers/platform/
modules.builtin drivers/pnp/modules.builtin drivers/power/modules.builtin drivers/
powercap/modules.builtin drivers/pps/modules.builtin drivers/ptp/modules.builtin
drivers/pwm/modules.builtin drivers/rapidio/modules.builtin drivers/ras/
modules.builtin drivers/regulator/modules.builtin drivers/remoteproc/modules.builtin
drivers/reset/modules.builtin drivers/rtc/modules.builtin drivers/scsi/
modules.builtin drivers/sfi/modules.builtin drivers/soc/modules.builtin drivers/spi/
modules.builtin drivers/staging/modules.builtin drivers/thermal/modules.builtin
drivers/tty/modules.builtin drivers/usb/modules.builtin drivers/vfio/modules.builtin
drivers/video/modules.builtin drivers/virt/modules.builtin drivers/virtio/
modules.builtin drivers/vme/modules.builtin drivers/watchdog/modules.builtin drivers/
xen/modules.builtin) > drivers/modules.builtin
make[1]: se sale del directorio '/usr/src/linux-headers-5.4.0-70-generic'
Makefile:22: fallo en las instrucciones para el objetivo 'all'
make: *** [all] Error 2
```