

Distance Sampling Simulations


Overview

- Why simulate?
- How it works
- Automated survey design
 - Coverage probability
 - Which design?
 - Design trade-offs
- Defining the population
 - Population description
 - Detectability
- Example Simulations



Why Simulate?

- Surveys expensive, simulations cheap!
- Test different survey designs
- Test survey protocols
- Investigate analysis properties
- Investigate violation of assumptions

How it works



How it works



Assess:

- Bias
- Precision
- CI coverage

Across different
designs/scenarios


Automated Survey Design

- Generate random sets of transects according to an algorithm
- Assess design properties
- Generate multiple transect sets for simulations



Automated Survey Design

- Coverage Probability
 - Uniform coverage probability, $\pi = 1/3$
 - Uniform coverage probability, $\pi = 1/3$
 - Uneven coverage for any given realisation



Which Design?

- **Uniformity** of coverage probability
- **Even-ness** of coverage within any given realisation
- **Overlap** of samplers
- **Cost** of travel between samplers
- **Efficiency** when density varies within the region

Design Trade-Offs

Diagram illustrating Design Trade-Offs for a Survey Region.

The diagram shows two scenarios of a Survey Region (blue area) within a Convex hull (green wavy line) and a Minimum bounding rectangle (black rectangle).

Left scenario: The Survey Region is relatively compact. The Convex hull is small, and the Minimum bounding rectangle is also small.

Right scenario: The Survey Region is more elongated. The Convex hull is larger, and the Minimum bounding rectangle is also larger.

Labels:

- Survey Region
- Convex hull
- Minimum bounding rectangle

Population Definition

- True population size?
- Occur as individuals or clusters?
- Covariates which will affect detectability?
- How is the population distributed within the study region?
 - Ideally have a previously fitted density surface Otherwise test over a range of plausible distributions

Detectability

- Distance needs:
 - shape and scale parameters on the natural scale
 - covariate parameters on the log scale

Detectability

- Golftees project

$\exp(0.268179) = 1.307581$


Detection Fx/Globus/Parameter Estimates	(MCDS)																																								
<pre> Status = 150.0000 # samples = 9168 # observations = 142 </pre>																																									
Name: $\text{BALT}(\text{miles})$ $\text{res} = \text{Exp}(\text{log}(\text{m}^2/\text{m}^2))$ $\mu = \text{All}() \quad \text{Exp}(\text{Estimate}) = 0.0013131$ Parameter A1() is the intercept of the sample parameter. Parameter A1() is the coefficient of factor GOLFTEE SIZE. Parameter A1() is the coefficient of log of factor GOLFTEE SIZE.	<p>Natural scale</p> <p>Log scale</p>																																								
<table border="1"> <thead> <tr> <th>Parameter</th> <th>Point Estimate</th> <th>Standard Error</th> <th>Percent Conf. of the Mean</th> <th>95 Percent Confidence Interval</th> </tr> </thead> <tbody> <tr> <td>A1</td> <td>-0.0013131</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> </tr> <tr> <td>A2</td> <td>-0.0024654</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> </tr> <tr> <td>A3</td> <td>-0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> </tr> <tr> <td>F001</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> </tr> <tr> <td>F002</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> </tr> <tr> <td>F003</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> </tr> <tr> <td>RM</td> <td>0.7500000</td> <td>0.0000000</td> <td>0.0000000</td> <td>0.0000000</td> </tr> </tbody> </table>	Parameter	Point Estimate	Standard Error	Percent Conf. of the Mean	95 Percent Confidence Interval	A1	-0.0013131	0.0000000	0.0000000	0.0000000	A2	-0.0024654	0.0000000	0.0000000	0.0000000	A3	-0.0000000	0.0000000	0.0000000	0.0000000	F001	0.0000000	0.0000000	0.0000000	0.0000000	F002	0.0000000	0.0000000	0.0000000	0.0000000	F003	0.0000000	0.0000000	0.0000000	0.0000000	RM	0.7500000	0.0000000	0.0000000	0.0000000	
Parameter	Point Estimate	Standard Error	Percent Conf. of the Mean	95 Percent Confidence Interval																																					
A1	-0.0013131	0.0000000	0.0000000	0.0000000																																					
A2	-0.0024654	0.0000000	0.0000000	0.0000000																																					
A3	-0.0000000	0.0000000	0.0000000	0.0000000																																					
F001	0.0000000	0.0000000	0.0000000	0.0000000																																					
F002	0.0000000	0.0000000	0.0000000	0.0000000																																					
F003	0.0000000	0.0000000	0.0000000	0.0000000																																					
RM	0.7500000	0.0000000	0.0000000	0.0000000																																					

$\exp(0.268179) = 1.307581$


Detection Fx/Summary	(MRDS)
Summary Fx of object Number of observations: 142 Distance range: 0 - 4 AIC: 420.972	
Detection Function: H1-normal key function Sample size parameter: Sample size parameter: (Estimate) = 0.0013131 (Standard Error) = 0.0000000 (t-stat) = 0.0013131 / 0.0000000 p-value = 0.9999999	
Estimate SE CV average p = 0.0000000 0.0000000 0.0000000 in covered region 0.0000000 0.0000000 0.0000000	

Detectability

- In simulation:



Detectability



Analysis

- Data Filter** must specify a right truncation distance
- Model Definition** must be either MRDS or MA
 - MRDS – for fitting a specific model
 - MA – for model selection (Note: MA model definitions require the creation of analyses)

Any questions so far...


Example Simulations

- To bin or not to bin?
- Testing pooling robustness in relation to truncation distance.
- Comparison of subjective and random designs.

To Bin or Not to Bin?

Simulation:

- Generated 999 datasets
- Added multiplicative measurement error
 - Distance = True Distance * R
 - $R = (U + 0.5)$, where $U \sim \text{Beta}(\theta, \theta)^1$
 - No error, ~15% CV ($\theta = 5$), ~30% CV ($\theta = 1$)
- Analysed them in difference ways
 - Exact distances, 5 Equal bins, 5 Unequal bins, 3 Equal bins
- Model selection on minimum AIC
 - Half-normal v Hazard rate




¹Marques T. (2004) Predicting and correcting bias caused by measurement error in line transect sampling using multiplicative error models *Biometrics* 60:757–763

To Bin or Not to Bin Results

	Exact Distances	5 Equal Bins	5 Unequal Bins	3 Equal Bins
No Error	-1.16% bias 210 SE	-1.11% bias 217 SE	-0.16% bias 221 SE	-0.19% bias 255 SE
15% CV	0.48% bias 214 SE	0.5% bias 221 SE	1.36% bias 221 SE	1.72% bias 264 SE
30% CV	6.66% bias 237 SE	6.61% bias 250 SE	7.43% bias 262 SE	8.20% bias 338 SE

Pooling Robustness and Truncation

- DSsim vignette




- Rectangular study region
- Systematic parallel transects with a spacing of 1000m

Pooling Robustness and Truncation

- DSsim vignette


Density Surface with Example Population



- Uniform density surface
- Population size of 200
- 50% male, 50% female

Pooling Robustness and Truncation

- DSsim vignette



- Half-normal shape for detectability
- Scale parameter of 120 for the females
- Scale parameter of ~540 for the males

Pooling Robustness and Truncation

- DSsim vignette

```
# Create the covariate parameter list
cov.params <- list()
# Note the covariate parameters are supplied on the log scale
cov.params$sex = data.frame(level = c("female", "male"),
                             param = c(0, 1.5))


detect.cov <- make.detectability(key.function = "hn",
                                scale.param = 120,
                                cov.param = cov.params,
                                truncation = 1000)
```

$\exp(\log(120)+1.5) = 537.8$

- Half-normal shape for detectability
- Scale parameter of 120 for the females
- Scale parameter of ~540 for the males

Pooling Robustness and Truncation

- DSsim vignette



Histogram of data from covariate simulation with manually selected candidate truncation distances.


- Two types of analyses:
 - hn v hr
 - hn ~ sex
- Selection criteria: AIC

Pooling Robustness and Truncation


- Results HN v HR:

Truncation	mean n	mean \hat{N}	mean se	$SD(\hat{N})$	%Bias	RMSE	% CI Coverage
200	66	197	34.27	34.05	-1.32	34.13	97.5
400	102	190	31.06	34.79	-5.13	36.25	87.9
600	128	190	34.04	35.27	-5.24	36.77	81.9
800	144	190	34.31	36.61	-5.10	37.99	77.1
1000	154	184	30.93	39.49	-7.76	42.42	68.1


Example Simulation



Subjective survey design



Random Designs




Coverage probability

Systematic Parallel Design



Equal Spaced Zigzag Design



Simulation

- Generates a realisation of the population based on a fixed N of 1500
- Generates a realisation of the design
 - Different each time for the random designs
 - The same each time for the subjective design
- Simulates the detection process
- Analyses the results
 - Half-normal
 - Hazard-rate
- Repeats a number of times

Practical

- Now attempt the DSSim practical:
 - *R* version – subjective design and parallel v zig zag
 - Distance version – parallel v zig zag only
- You will need the library *shapefiles*.