

An Extension of PlusCal for Modeling Distributed Algorithms

Heba Alkayed, Horatiu Cirstea, Stephan Merz

University of Lorraine, CNRS, Inria, Nancy, France

September 10, 2020

Introduction

Formal methods for distributed algorithms

- ▶ Algorithms modeled using TLA^+ can be formally verified using the TLA^+ Toolbox
- ▶ PlusCal algorithms have a more familiar syntax and can be translated to TLA^+

Distributed PlusCal Algorithms

- ▶ An extension of PlusCal offering constructs for modeling distributed algorithms
- ▶ Can be translated into a TLA+ specification
- ▶ Introduces
 - ▶ Sub-processes
 - ▶ Communication channels

General Structure of an algorithm

```
(* --algorithm <algorithm name>
(* Declaration section *)
variables <variable declarations>
channels <channel declarations>
fifos <fifo declarations>
(* ... *)
(* Processes section *)
process (<name> [=|\in] <Expr>))
    variables <variable declarations>
    <subprocesses>
*)
```

Communication Channels

- ▶ Classified by the way they handle the addition and removal of messages
 - ▶ Unordered channels
 - ▶ FIFO channels
- ▶ Supported operators
 - ▶ `send(ch, el)`
 - ▶ `receive(ch, var)`
 - ▶ `broadcast(ch, [x \in S \mapsto e(x)])`
 - ▶ `multicast(ch, [x \in S \mapsto e(x)])`
 - ▶ `clear(ch)`

Sub-Processes

- ▶ Enables the process to execute multiple tasks in parallel.
- ▶ Each sub-process consists of labeled statements.
- ▶ The special variable *pc* was modified to have the following definition

$$pc = [self \in ProcSet \mapsto [self \in IdSet \mapsto \langle "lbl", \dots \rangle]]$$

where *ProcSet* is a set that contains all the process identifiers, and the labels that appear in the sequence are the entry point actions for each sub-process.

Distributed PlusCal Example

```
process(n \in Nodes)
  variables clock = 0, req = [n \in Nodes |-> 0],
           ack = {}, sndr, msg;
  { /* thread executing the main algorithm
ncs: while (TRUE) {
  skip; /* non-critical section
try:  clock := clock + 1; req[self] := clock; ack :=
      {self};
      multicast(network, [self, nd \in Nodes |->
Request(clock)]);
enter: await (ack = Nodes /\ \A n \in Nodes \ {self} :
beats(self, n));
cs:    skip; /* critical section
exit:  clock := clock + 1;
      multicast(network, [self, n \in Nodes \ {self} |->
Release(clock)]);
  } /* end while
}
```

Translation to TLA+

```
exit:
  clock := clock + 1;
  multicast(network, [self, n \in Nodes \ {self} |->
    Release(clock)]);
```

```
exit(self) ==
  /\ pc[self] [1] = "exit"
  /\ clock' = [clock EXCEPT ![self] = clock[self] + 1]
  /\ network' = [<<slf, n>> \in DOMAIN network |->
    IF
      slf = self /\ n \in Nodes \ { self }
    THEN
      Append(network[slf, n], Release(clock'[self]))
    ELSE
      network[slf, n]]
    /\ pc' = [pc EXCEPT ![self][1] = "ncs"]
    /\ UNCHANGED << req, ack, sndr, msg >>
```


Contributions and future work

Contributions

- ▶ An extension of PlusCal called Distributed PlusCal
- ▶ Distributed PlusCal offers constructs that are designed for modeling distributed algorithms
- ▶ A backward compatible translator that translates from Distributed PlusCal and PlusCal to TLA+

Future Work

In the future we aim to introduce more types of communication channels and channel operators, and we're working on supporting PlusCals p-syntax as well.